

CHIEF, A&MMS B3001
V.A. Medical Cente
RECEIVING WHSE BLD
2002 HOLCOMBE BLVD
HOUSTON, TX 77030-

PO# 580-B30013

Configuration - Included

Item Part Number -

Qty

- SonoSite EDGE

installation can be purchased separately as needed. Available for US locations only.

SonoSite EDGE high-resolution, all-digital, 8.5-pound (3.85 kg) ultrasound system with 12.1in. LED display. This product is designed with SonoSite's proprietary Chip Fusion Technology that integrates digital signal processing and multiple system functions into a custom application-specific integrated circuit (ASIC) microchip. As a result complex system functions that typically require several large circuit boards can be accomplished using a small chip in a compact space. SonoSite EDGE high-resolution, all-digital, 8.5-pound (3.85 kg) ultrasound system with 12.1in. LED display. This product is designed with SonoSite's proprietary Chip Fusion Technology that integrates digital signal processing and multiple system functions into a custom application-specific integrated circuit (ASIC).

The purchase of the EDGE visualization tool includes the following software technologies:

- 2D grayscale with SonoMB Multi Beam Technology
- Auto Gain with SonoADAPT Tissue Optimization Technology
- M-Mode
- Clips Storage
- Application specific calculation packages

The EDGE combines the high performance of cart-based systems with the speed,

flexibility and durability of hand-carried ultrasound. 8 GB of on-board Flash memory will retain enough data for over 40 standard exams (or 2,400 seconds of clips, 1,200 still frames and 40 report pages) even after power is turned off. The system supports USB media playback, and

connectivity is accomplished through one of two USB slots on the system, which allow for direct sharing of images (JPEG) and Clips (MPEG4) to a PC or Mac. Additional connectivity is achieved via the EDGE Mini-Dock, to meet your specific needs. The system supports a HIPAA compliance tool set for the protection of sensitive information and PC direct connectivity capability (through USB Memory Stick or via SiteLink and USB Cable ordered separately). EDGE's reliability and durability are backed by a five-year standard warranty, which is included in the price of the system. Software upgrades to the main system and transducer databases are accomplished through one of two USB ports on the system. Also includes battery, ultrasound gel, and user guide on a CD (Printed user guides also available as a purchasable option). Additional features available to add to the Edge system include: SonoMBe, PW Doppler, TDI PW, CW Doppler, DICOM, Worksheets, and a full array of multi-frequency, broadband transducers. Included with the purchase of your SonoSite EDGE, you will receive the system battery, ultrasound gel, a user guide CD.

- Color Application Software Package Edge

This package provides the following capabilities for the transducers that support these features:

- Tissue Harmonic Imaging (THI), a capability in which the system transmits at one frequency and receives at a higher harmonic frequency to reduce noise and clutter and improve resolution.
- SonoHD Imaging Technology, technology which significantly reduces speckle noise while enhancing tissue margins, thereby dramatically improving contrast and structural resolution.
- Velocity color flow imaging provides the clinician with the color sensitivity to perform color Doppler examinations with all transducers during a clinical procedure.
- PW Doppler is available on all transducers.
- CW Doppler is a quantitative assessment of blood flow with Duplex imaging for higher flow velocities.

- MSK Worksheets

Worksheets specific to the Musculoskeletal clinician that includes Shoulder, knee, Elbow, Hand/Wrist, Ankle/Foot, and Hip worksheets

- SonoMBe, EDGE

Proprietary software that enhances the systems ability to aid needle

- C60X / 5-2 MHz Transducer Biopsy Compatible

C60x / 5-2 MHz multi-frequency, broadband, 60 mm curved array transducer for general purpose, abdominal, obstetric, gynecology, and nerve exams. Supports 2D with SonoMB Multi Beam Technology and Auto Gain capabilities, SonoHD Imaging Technology, Tissue Harmonic Imaging, M-mode, Color Power Doppler, Velocity Color Flow Doppler and Pulsed Wave Doppler. Biopsy guide available. 1-meter drop-test durability.

- L25X / 13-6 MHz Transducer Transverse Biopsy Compatible

L25x / 13-6 MHz multi-frequency, broadband, 25 mm linear array transducer for nerve, vascular, venous, ophthalmic, musculoskeletal, and superficial exams. Supports 2D with SonoMB Multi Beam Technology and Auto Gain capabilities, SonoHD Imaging Technology, M-mode, Color Power Doppler, Velocity Color Flow Doppler and Pulsed Wave Doppler. Transverse biopsy guide available. 1-meter drop-test durability.

Item Part Number -

- HFL50x / 15-6 MHZ Transducer Biopsy Compatible 1

HFL50x / 15-6 MHz multi-frequency, broadband, 50mm linear array transducer for small parts, breast, musculoskeletal and nerve. Supports 2D with SonoMB, Sono UltraRes Technology, Multi Beam Technology and Auto Gain capabilities, SonoHD Imaging Technology, M-mode, Color Power Doppler, Velocity Color Flow Doppler and Pulsed Wave Doppler. Biopsy guide available. Maximum depth is 6 cm.

- EDGE Stand 1

Ergonomic stand and mobile work platform for the EDGE system and transducers. Complete with power supply and mini-dock and accessory basket. OEM peripherals include: B/W or color printer. Unable to use together

- Triple Transducer Connect (TTC) w/ quick disconnect 1

Three-transducer module for mobile docking system that allows connection of up to three transducers simultaneously while the system is docked in the Stand

- User Guide EDGE 1

EDGE Ultrasound System User Guide,

- Service Manual, Edge 1

EDGE Ultrasound System Service
- Service Manual, Edge 1

EDGE Ultrasound System Service
- 135-YR-WARRANTY - 60 MONTHS - STANDARD COVERAGE 1

60 MONTHS - STANDARD COVERAGE