```
V.A. Medical Center
JERRY L PETTIS
VETERANS HOSPITAL
11201 BENTON ST
LOMA LINDA, CA 92357
```

PO# 605-B30008

QTY	DESCRIPTION
1	GOVT LOGIQ e BT12 with 5 year warranty (Made in USA (Research Park), includes DVD-RW, AC/DC, Battery pack)

GOVT LOGIQ e BT12 Compact digital ultrasound console. Scanning modes include: B-mode, M-mode, color flow, pulsed wave Doppler and continuous wave Doppler (CWD purchased separately).

Special features include: Automatic Image Optimization (for B-mode, color and PW Doppler), raw data processing, on-board patient data management and image archiving via system hard disk, integrated report package with template designer, battery pack, DVD-RW and two USB ports. Comprehensive software applications including annotation and measurement/calculation packages. Ergonomic features include the built in carrying handle, 15 inch flexible LCD with wide viewing angle, intuitive keyboard and user programmable presets. Available Options: Easy3D, LOGIQview, CW Doppler, Tissue Doppler Imaging, Stress Echo, TEE support, Anatomical M-Mode, Color M-Mode, CrossXBeam, B-Steer+, Auto IMT, eSmart Trainer, Patient Follow up tool, Flow QA, DICOM, wireless LAN, carrying case, and touch screen kit etc.

Various types of carts are available for LOGIQ e, including simple isolation cart and customizable advanced docking cart. USA version includes; DVD-RW, AC/DC, Battery pack, Manuals, 5 year standard warranty and one day of On-site Applications Training. Additional On-site Applications Training days are available for purchase.

QTY	DESCRIPTION
1	LOGIQ e DICOM Software Option

DICOM option can be used through LAN, and provides print, store, multi-frame, modality worklist, verify, MPPS (Modality Performed Procedure Step), and storage commitment functionality.

QTY	DESCRIPTION
1	Advanced Imaging Pack

Cross Beam Imaging - H41842LC

B-Steer + = H48012LF

Logiqview = H41642LK

Easy 3D = H41642LH

QTY	DESCRIPTION
1	Basic User manual and Release Notes (hardcopy) English

Basic User manual and Release Notes (hardcopy) English

QTY	DESCRIPTION
1	12L-RS Linear Array Transducer

QTY	DESCRIPTION
	Multi-Frequency transducer with bandwith between 5 and 13 MHz.
	Applications include: Small Parts, Peripherals, Vascular, Pediatric and Orthopedic Applications. FOV 38.4mm.
1	Docking Cart Power Cable for USA
	Docking Cart Power Cable.
1	Isolation cart 110V
	LOGIQ e and Vivid e Isolation cart with ergonomic features including: Transformer, probe and gel holders, shelf for DVD-R, shelf for B&W printer and clipboard holder.