

WHSE/RECEIVING B30011
V.A. Medical Center
3350 LA JOLLA VILLAGE DR
SAN DIEGO, CA 92161

PO# 664-B30011

Line #	Description	Qty
1	iU22 Vision 2012 Intelligent Design Ergonomics: Unique human-centered design for comfort and convenience Fully articulating flicker-free 20-inch wide format high resolution flat panel TFT/S-IPS display with nearly infinite positioning adjustments Fully articulating control panel, including height, swivel, and slide Easy access transducer connectors and integrated cable storage Digitally enhanced 8 speaker high-fidelity stereo audio Integrated footrest Integrated storage shelves 4 wheel swivel and swivel/brake lock control Architecture xSTREAM system architecture with capability of processing multiple data streams simultaneously built for 2D, 3D, 4D, MPR Next generation digital broadband acoustic beamforming, built for latest pulse shaping and coding techniques Up to 57,000 total digital channels High-bit, low noise, digital circuitry achieves system dynamic range up to 180dB for improved 2D performance and increased Doppler sensitivity New Adaptive Broadband flow imaging automatically adjusts bandwidth for optimal flow sensitivity and resolution Next Generation SonoCT Real-Time Compounding, with Widescreen capability and up to 9 beam-steered lines of sight XRES Adaptive Image Processing for noise and artifact reduction to improve tissue conspicuity Fully independent, multiple mode Triplex operation Transducers Supports new Explora family of transducers that feature: Ergonomic designs with lightweight flexible cables New low-loss technology for better penetration with fewer artifacts Breakthrough frequency bandwidths and array configurations Intelligent Control Interface High-resolution interactive graphical color touch panel with adjustment for various ambient light conditions Easy access primary controls with tri-state backlighting and multi-function controls Control panel operation of on-board peripheral devices Pull out alphanumeric keyboard for manual data entry User interface configurable for languages Automation iSCAN intelligent one-button optimization in 2D and Doppler modes iFOCUS intelligent focusing capability for one-button optimization of focal range size and position iOPTIMIZE intelligent optimization technologies for one-button approach to instantly adapt	1

performance for different patient sizes, flow states and clinical requirements
High-Q Automatic Doppler Analysis
Intelligent Tissue Specific Imaging
Application-specific and user definable Quicktext Automatic Annotation
QuickSAVE User Defined Programs (up to 45 per transducer)

Data

On-board workstation-class data management with thumbnail previews and storage of images, loops, and reports
Retrospective and prospective clip capture to internal drive or removable media
Integrated DVD/CD burning capability for storage of DICOM images or export in JPEG and .avi for PC compatibility
DICOM 3.0 Print and Store capability to internal drive or DVD/CD

Other Core Features

SmartExam system-guided protocols with new features that include exam record and automatic mode switching to greatly improve workflow efficiencies
Color Power Angio
Tissue Harmonics and Pulse Inversion Harmonic Imaging
Basic 3D Imaging capability with MPR visualization feature
2D, M-Mode, Pulsed, High PRF, Color Flow Doppler
Duplex CW Doppler
ECG capability
Cineloop Image, M-mode and Doppler Review
High Definition Write Zoom and Read Zoom with pan features
Chroma Imaging
Measurement tools including: distance, depth, area, and circumference
Volume Flow Measurements
Ability to send X,Y & Z volume MPR's to most PACS.

2 Efficiency Package 2012 1

Panoramic

Real-time extended field-of-view composite imaging acquired in fundamental or SonoCT mode

Netlink DICOM 3.0

DICOM 3.0 compliant with support for the following functions: performed procedure step, storage commit, modality worklist, vascular structured reporting, OB structured reporting, GYN structured reporting, and cardiac structured reporting.

Auto Doppler

Auto Doppler provides: auto placement of color flow box and steering angles in relation to vascular structures; auto sample volume placement in the area of greatest flow velocity and Auto angle correction. Auto Doppler works on all linear transducers.

3 Radiology Pkg 1

Includes the following:

- Abdominal Clinical Option
 - Gynecology Clinical Option
 - Vascular Clinical Option
 - Pediatric Clinical Option
 - Small Parts Clinical Option
 - Musculoskeletal Clinical Option
-

- Obstetrical Clinical Option
- Contrast Clinical Option
- Urology Clinical Option
- TCD Clinical Option
- Interventional Clinical Option
- Tissue Doppler Imaging (TDI)

4 Intima Media Thickness (IMT) Quantification 1

Provides automated measurements of intima media thickness in carotids and other superficial vessels. Eliminates the laborious process of manually positioning cursors minimizing the time needed to complete an IMT study.

PC Requirements for IMT ROI Parametric and Strain Plug-ins

- Windows 2000/XP PRO Operating System
- 800 MHz Processor Speed
- 512 MB RAM
- 1024 x 768 Color Resolution (24 bit color)
- 24x CD-ROM drive
- 5.25" MOD drive (if transferring 2D files from SONOS to QLAB)
- 3.5" MOD drive (if transferring 2D files from HDI to QLAB)

5 Region of Interest (ROI) Quantification 1

Designed to increase the consistency and reliability of acoustic measurements while reducing the effort required to successfully carry out ROI analysis for contrast imaging tissue analysis and color Doppler.

PC Requirements for IMT ROI Parametric and Strain Plug-ins

- Windows 2000/XP PRO Operating System
- 800 MHz Processor Speed
- 512 MB RAM
- 1024 x 768 Color Resolution (24 bit color)
- 24x CD-ROM drive
- 5.25" MOD drive (if transferring 2D files from SONOS to QLAB)
- 3.5" MOD drive (if transferring 2D files from HDI to QLAB)

6 S5-1 Purewave Broadband Phased Array Transducer 1

Sector array transducer with 5 to 1 MHz extended operating frequency range for adult cardiology adult abdominal vascular, adult renal and TCD applications

7 L9-3 Broadband Linear Array transducer 1

Linear Array transducer with 9 to 3 MHz extended operating frequency range for cerebrovascular and peripheral vascular applications, to include deep venous imaging. Provides unprecedented clinical performance for demanding vascular exams.

8 L12-5 50mm Broadband Linear Array transducer 1

Fine pitch, 256 element, high resolution linear array transducer with 12 to 5 MHz extended operating frequency range for high resolution superficial applications, including small parts, breast, vascular and musculoskeletal imaging.

9 L15-7io Intraoperative Broadband Linear Array 1

Compact high resolution linear array transducer with 15 to 7 MHz extended operating frequency range for intraoperative vascular imaging. Also supports high-resolution superficial venous and arterial studies.

For iU22 and HD11 XE: Also validated for musculoskeletal applications.
(Requires Explora connector on HD11 XE system)

For iE33: Compact high resolution linear array transducer with 15 to 7 MHz extended operating frequency range for intraoperative vascular imaging and high resolution superficial applications, including real-time review of repairs before closure in cardiac and vascular surgeries, graft harvest investigations prior to bypass, dialysis graft evaluations and superficial venous and arterial studies

10 L17-5 Broadband Linear Array transducer 1

Ultra-fine pitch, 288 element, high resolution linear array transducer with 17 to 5 MHz extended operating frequency range for high resolution superficial applications, including small parts, breast, superficial vascular and musculoskeletal imaging.

11 C5-1 Broadband Curved Array Transducer 1

PureWave curved array transducer with 5 to 1 MHz extended operating frequency range. Must be at Vision 2008 or must purchase Vision 2010 or higher software upgrade.

iU22 customers:

C5-1 PureWave Curved Array for high performance OB/GYN, Abdominal and Interventional applications. Now, one transducer provides exceptional clinical performance for a wide range of patient types including obese and technically challenging patients.

iE33 customers:

For general purpose adult abdominal vascular and OB fetal echo applications.

12 English Manual 1

Operation Manual

13 Internal Color Printer 1

Small Color Printer

14 English Manual 1

Operation Manual

15 QLAB 9.0 NA GI/ Shs Bun 1

This QLAB package is only provided if purchased in conjunction with an ultrasound system that includes a QLAB Plug-In. This encompasses QLAB Core Module, Intima Media Thickness (IMT) Quantification Plug-in, Region of Interest (ROI) Quantification Plug-in, Cardiac Parametric (PQ) Quantification Plug-in, Strain (SQ) Quantification Plug-in, Cardiac 2D Quantification (2DQ) Plug-in, Cardiac 3D Quantification (3DQ), Cardiac 3DQ Advanced Plug-in, Mitral Valve Quantification (MVQ) Plug-in, GI 3D Quantification (GI 3DQ) Plug-in Elastography Analysis (EA) plug-in and CMQ (Cardiac Motion /Mechanics Quantification Plug-in).

Includes QLAB Core Module, Intima Media Thickness (IMT) Quantification Plug-in, Region of Interest (ROI) Quantification Plug-in, Cardiac Parametric (PQ) Quantification Plug-in, Strain (SQ) Quantification Plug-in, Cardiac 2D Quantification (2DQ) Plug-in, Cardiac 3D Quantification (3DQ), Cardiac 3DQ Advanced Plug-in, Mitral Valve Quantification (MVQ) Plug-in, GI 3D Quantification (GI 3DQ) Plug-in, MicroVascular Imaging (MVI) plug-in, Elastography Quantification (EQ) plug-in and CMQ (Cardiac Motion /Mechanics Quantification Plug-in).

QLAB Core Module

QLAB is designed for ultrasound clinicians who require sophisticated analysis of image data acquired on Philips ultrasound systems.

A large number of Plug-ins is available, offering a variety of powerful 2D/3D advanced quantitative capabilities.

All Plug-ins require the QLAB Core Module.

QLAB core module provides 2D viewer by default.

The 3D Viewer comes with the 3D plug-ins when ordered.

QLAB Core Module functions include review, deletion and quantification of Philips iE33, iU22, CX50, HD15, HD11, HD7, SONOS, HDI and EnVisor C.0 image files;

PC Graphic image/movie files creation in BMP, TIFF, JPEG and AVI;

Ability to remove patient information from QLAB all screens and prior exporting new PC files;

Export of quantification data into Excel-compatible spreadsheet formats;

Built-in on-line help in multiple languages.

Ultrasound data can be sent to QLAB via DICOM network connection, MOD/CD/DVD media or USB Flash Drive/Self-powered MiniDisk devices.

Intima Media Thickness (IMT) Quantification Plug-In

Provides automated measurements of intima media thickness in carotids and other superficial vessels;

Eliminates the laborious process of manually positioning cursors, minimizing the time needed to complete an IMT study.

Compatible with Philips iE33, iU22, HD15, HD11, HD7, EnVisor C.0, SONOS and HDI systems.

Region of Interest (ROI) Quantification Plug-in

On compatible files calculates Color Mean and Standard Deviation, Echo mean and Standard Deviation, VI, FI, VFI. Enables user to apply motion compensation algorithm. Provides basic trending capabilities (off cart only).

Compatible with Philips iE33, iU22, CX50, HD15, HD11, HD7, EnVisor C.0, SONOS and HDI systems.

Cardiac Parametric Quantification (PQ) Plug-In

Allows advanced review and analysis of contrast intensities within the heart;

Provides color-coded representation of contrast intensity and replenishment rate based on either Log or linear scaling.

Compatible with iE33, SONOS and HDI systems.

Strain Quantification (SQ) Plug-in

Used in the evaluation of regional myocardial function; assessment of synchronicity and guidance during bi-ventricular pacing procedure;

Measures the myocardial velocity TDI data set and derives the displacement, strain and strain rate along user-defined M-Lines.

Compatible with iE33, iU22, CX50, HD15, HD11, SONOS and HDI systems.

2D Quantification (2DQ) Plug-in

Display of 2D ultrasound images;

Semi-automated border detection for cardiac chambers and vessel cavities;

Computes Areas, Volumes and advanced parameters for LV systolic and diastolic function including, LV Ejection Fraction (EF) and Fractional Area Change (FAC);

The Peak Ejection Rate (PER), Peak Rapid Filling Rate (PRFR) and Atrial Filling Fraction (AFF) are also reported;

Color Kinesis (CK) tool for provides color-coded visualization of global and regional wall motion;

TMAD allows visualization and quantification of Atrio-Ventricular Annulus planes Motion in order to assess cardiac global function in fast and reproducible way to facilitate trending report.

Compatible with Philips iE33, iU22, CX50, HD15 and HD11 systems.

Cardiac 3D Quantification (3DQ) Plug-in

Provides easy access to Live 3D, 3D Zoom, Full Volume and 3D Color data sets from the iE33, iU22 and SONOS 7500 Live 3D systems;

Offers viewing, cropping, slicing and quantification including distance measurements, area, Bi-plane LV Volume, Ejection Fraction (EF) and LV Mass calculations;

3DQ also provides Multiplanar Reconstruction (MPR) views for unlimited anatomical planes from 3D volume and new 3D iSlice generation.

Compatible with Philips iE33, iU22 and SONOS7500 systems.

Advanced 3D Quantification (3DQA) Plug-in

Extends the diagnostic power of Live 3D Echo by providing the first semi-automated, on-cart and off-cart analysis of true LV volumes—using all the voxels to generate a full 3D endocardial border; Cardiac 3D Quantification Advanced (3DQ Advanced) revolutionizes echo quantification and extends the diagnostic power of Live 3D echo by providing the first semi-automated, on-cart and off-cart analysis of true LV volumes—using all the voxels to generate a full 3D endocardial border. This is a true 3D border with higher accuracy and less dependency on LV shape assumptions than conventional methods, which rely on sparse view analysis.

3DQ Advanced waveform display provides accurate data for assessing global function based on LV volume, ejection fraction and stroke volume. Additionally, 3DQ Advanced allows simultaneous display of 17 regional waveforms, enabling temporal comparisons between segments.

MultiPlanar Reconstruction (MPR) views provides unlimited anatomical planes from 3D volume;

New iSlice generation run in the 3D viewer and is compatible with all Philips Live 3D dataset including color data, provides highly flexible short and long

axis slicing tool and display up to 4x4 equally spaced MPR views to facilitate LV function visualization assessment;

Measurements of LV endocardial Volumes, Stroke Volume (SV) and true 3D ejection fraction (EF) using a semi-automated border detection in 3D space;

Computes global and regional LV volumes based on ACC 17 segments model;

Displays global LV volume waveform and provides selective display of 17 regional volume waveforms;

Offers timing assessment for each 17 minimal regional volumes and determine a synchronicity index for all volume segments or a user-selectable group of volume segments;

Provides comprehensive report with summary of synchronicity indexes and displays regional Timing and Radial Excursion Parametric Images in Bull's eye representation.

iCrop capabilities with the 3D volumes.

Mitral Valve Quantification (MVQ) Plug-in

The Mitral Valve Quantification plug-in (MVQ) adds precise 2D and 3D quantification of the mitral valve anatomy and associated structures based on data acquired with Philips Live 3D Echo and

the X7-2t transesophageal transducer;

Based on the precise Live 3D TEE information, the MVQ plug-in provides a clinical decision support tool to improve diagnostic confidence, surgical planning, communication between clinicians and for the patient, and follow-up care.

Compatible with the Philips iE33 system and Live3D TEE Transducer.

GI 3DQ Plug-In

Review and display 3D data sets from the Philips iU22, iE33 and HD11 systems;

Includes MPR (Multiplanar Reconstruction) capability;

Can display as 1-up (full volume), 4-up (volume/MPR), or Direct iSlice display);

Also provides MPR rotation, basic crosshair control, rotation and movement; crosshair and MPR border graphics controls, pan and zoom controls, and export of BMP, JPEG, TIFF and AVI files;

Rotation speed control, Elevation resize for freehand volumes, Linear Measurements, Ellipse

Measurements, Stacked Contour Measurements, Region of Interest (ROI) Analysis;

Works with Matrix and Mechanical Volume Transducers.

MicroVascular Imaging (MVI) Plug-in

MVI uses specially designed post-processing software to map contrast agent progression. This software plug-in measures changes in the image from frame to frame, suppressing background tissue signals and capturing additional contrast data. The additional data obtained using MVI dramatically enhances vessel conspicuity.

Elastography Quantification (EQ) Plug-in

Perform parametric imaging and strain ratio analysis. Parametric imaging calculates relative strain with respect to a user defined reference region. Strain ratio allows calculation of relative strain of two regions of interest over time.

Cardiac Motion/Mechanics Quantification Plug-in

Based on 2D speckle tracking technology, CMQ provides a method for assessing global and regional cardiac function. It offers a suite of measurements and parametric displays to analyze trans-myocardial mechanics without Tissue Doppler imaging angle dependency limitations. Using the 17-segment ASE left ventricular model, CMQ provides additional information for many clinical applications such as ventricular wall motion and mechanical synchrony assessments.

Compatible with the Philips iE33, iU22, CX50, HD15 systems files.

PC requirements for all QLAB plug-ins:

- Processor: Intel Core 2/Xeon, AMD Athlon 64/Opteron or greater
- Operating System:
 - Windows XP Pro Service Pack 3, 32-bit
 - Windows 2003 Server, 32-bit
 - Windows 2008 Server R2, 32-bit
 - Windows Vista, 32-bit
 - Windows 7, 32-bit or 64-bit
- Memory: 2 GB RAM
- Graphics Card: 32 64 MB or greater with H/W accelerated OpenGL support and Pixel Shader 3.0 (Intel video cards may work but are not supported)
- Hard Drive: 80 GB HD with 7200 RPM
- Monitor: Minimum 1024 x 768 resolution (SVGA) and capable of 24-bit or 32-bit color display
- Media:

iU22 & iE33 Ultrasound Systems

Course Number: US2787

Class Length: 3.5 days (excludes Saturdays, Sundays, and Philips holidays)

Delivery Method: Instructor-led

Modality: Ultrasound, General

Location: Philips Healthcare Academy, Best

Accreditation: Certified

Audience: Biomedical engineers, Hospital engineers

DESCRIPTION:

This course provides an introduction to supporting the iU22 and iE33 Imaging Systems. Students receive fundamental applications training required to understand some clinical uses of these systems. They learn how to image phantoms in order to assess system performance and how to minimally operate the system to better understand the needs of the Sonographer.

This course focuses upon equipment operation, maintenance, DICOM configuration and minor repair. Board level theory and system diagnostics are studied to facilitate repair. Hands-on labs train the student to verify proper equipment operation and learn diagnostic troubleshooting techniques. Philips support philosophy is explained to facilitate working successfully with our support professionals.

For course enrolment and course dates:

Please contact your local Philips representative.

COURSE-WARE:

Student Manual

All course materials are on CSIP level 1.

PREREQUISITES:

- . Basic analog and digital electronics knowledge
- . Ultrasound and Transducer knowledge

COURSE AIMS:

Upon completion of this course it is expected that the student will be capable of partnering with our service professionals to meet the servicing needs of the customer.

He/she will be able to:

- . Recognize (and scan phantoms) with standard views.
- . Minimally operate the Ultrasound Systems.
- . Isolate and repair minor system failures.
- . Run full system diagnostics (Normal User)

KEY TOPICS:

- . System mechanics
- . User presets backup and restore
- . Dicom setup

* PHILIPS PROPRIETARY MATERIALS SUCH AS DIAGNOSTIC SOFTWARE AND SERVICE DOCUMENTATION ARE NOT INCLUDED IN THE TRAINING AND WILL NOT BE AVAILABLE FOR USE OUTSIDE OF THE TRAINING ENVIRONMENT. THE TRAINEE MUST RETURN ALL PROPRIETARY MATERIALS RECEIVED DURING THE TRAINING AT THE END OF THE TRAINING. CUSTOMER ACKNOWLEDGES AND AGREES THAT NEITHER CUSTOMER NOR TRAINEE WILL RECEIVE A LICENSE TO SUCH PROPRIETARY MATERIALS AND THAT THE
