





LOUVER TYPE	SIZE
	6'-6" X 6'-6"
	6'-6" X 6'-6"

1. DEMOLISH EXTERIOR WALL AND EXISTING LOUVER FOR ACCESS TO MECHANICAL ROOM. DEMOLISH FROM FINISH FLOOR LEVEL TO BOTTOM OF STRUCTURE ABOVE. PROVIDE CLEAN CUTS TO MATCH UP TO NEW WALL AND LOUVER CONSTRUCTION.
2. CONSTRUCT NEW EXTERIOR WALL AND INSTALL NEW LOUVERS TO MATCH EXISTING CONDITIONS.
3. CONSTRUCT NEW EXTERIOR WALL TO MATCH EXISTING CONDITIONS.
4. UPON DEMOLITION OF EXTERIOR WALL INDICATED, INSTALL 16 GAUGE METAL STUDS PER SPECIFICATION SECTION 05 40 00, 16" O.C. COORDINATE FOR OPENINGS REQUIRED FOR TEMPORARY EQUIPMENT. SECURELY ATTACH 5/8" FIRE-TREATED EXTERIOR GRADE PLYWOOD TO EXTERIOR FACE OF STUDS TO PROTECT AREA OF WORK UNTIL PERMANENT EXTERIOR WALL CONSTRUCTION IS READY TO BEGIN.

REFER TO DRAWING GI102 FOR PHASING

REFER TO DRAWING GI001 FOR COORDINATION DRAWINGS NOTE.



**Harrell,
Saltrick &
Hopper**

Recommended Approvals:	
1. MEDICAL DIRECTOR	6. OPERATIONS SERVICE LINE MANAGER
2. ASSOCIATE DIRECTOR	7. INFECTION CONTROL MANAGER
3. CHIEF OF STAFF	8. SAFETY MANAGER
4. ASSOC. DIRECTOR	9. GENERAL ENGINEER
5. SERVICE LINE MGRS.	10. COR

FINAL BID DOCUMENTS

Drawn

Number	AutoCAD File Name
--------	-------------------

r	AutoCAD File Name
---	-------------------

DRAWING No.
AS201

DRAWING No.
AS201

