

FISSURED Panels/
DOWN DX/DXL Suspension System

Features and Benefits

- Economical, all-purpose ceiling pattern available in various panel sizes.
- Optional FIRECODE® product designed to meet life-safety codes.

Applications

- Administrative offices
- Corridors
- Mass merchandisers
- Convenience stores

Substrate

- Water-felted mineral fiber

See LEED report tool at usgdesignstudio.com for detailed sustainability information.




















Medium-Textured Panel

To order samples, go to usg.com



Flat White
050

UL Classified												
Edge	Panel Size	Class ²	Item No.	NRC	CAC Min.	LR ³	Color	Grid Options	VOC Emissions	Recycled Content ¹	Panel Cost	
												
FISSURED™ Panels	SQ 	2'x2'x5/8"	Class A	560	.55	33	.81	White	A, B, C	Low	24-28%	\$
		2'x2'x5/8"		585	.55	35	.81	White	A	Low	41-49%	\$
		2'x4'x5/8"	Class A	562	.55	35	.81	White	A, B	Low	24-28%	\$
		2'x4'x5/8"		586	.55	35	.81	White	A	Low	41-49%	\$
	SLT 	2'x2'x5/8"	Class A	506	.55	33	.81	White	D	Low	24-29%	\$
		2'x4'x5/8"	Class A	507	.55	35	.81	White	D	Low	24-29%	\$
Legend  Low Emissions (VOC) Low-emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on the CHPS database for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on usg.com.  FIRECODE®												
Grid Profile Options	A DX®/DXL™	B DXW™	C⁴ CENTRICITEE™ DXT™	D DX/DXL								
												
Physical Data/ Footnotes <div><div>Product literature Data sheet: SC1815 ASTM E1264 classification Type III, Form 2, Pattern CD ASTM E84 surface burning characteristics Class A Flame spread: 25 Smoke developed: 50 Weight 0.61–1.2 lbs./sq. ft. (Class A) 1.14–1.22 lbs./sq. ft. (FIRECODE)</div><div>Thermal resistance R-1.4 (Class A) R-1.6 (FIRECODE) Maximum backloading See USG 30-Year Limited Warranty Commercial Applications SC2102. Maintenance Can be cleaned easily with a soft brush or vacuum.</div><div>Notes 1. For details, see LEED report tool at usgdesignstudio.com. 2. Fire-rated items: see UL design details. 3. LR values are shown as averages. 4. Maximum 2'x2' with SQ edge panels.</div></div>												