

Item No.	QTY	DESCRIPTION
1	1	<p>GOVT LOGIQ e BT12 with 5 year warranty (Made in USA (Research Park), includes DVD-RW, AC/DC, Battery pack)</p> <p>GOVT LOGIQ e BT12 Compact digital ultrasound console. Scanning modes include: B-mode, M-mode, color flow, pulsed wave Doppler and continuous wave Doppler (CWD purchased separately). Special features include: Automatic Image Optimization (for B-mode, color and PW Doppler), raw data processing, on-board patient data management and image archiving via system hard disk, integrated report package with template designer, battery pack, DVD-RW and two USB ports.</p> <p>Comprehensive software applications including annotation and measurement/calculation packages. Ergonomic features include the built in carrying handle, 15 inch flexible LCD with wide viewing angle, intuitive keyboard and user programmable presets. Options: Easy3D, LOGIQview, CW Doppler, Tissue Doppler Imaging, Stress Echo, TEE support, Anatomical M-Mode, Color M-Mode, CrossXBeam, B-Steer+, Auto IMT, eSmart Trainer, Patient Follow up tool, Flow QA, DICOM, wireless LAN, carrying case, and touch screen kit etc.</p> <p>Various types of carts are available for LOGIQ e, including simple isolation cart and customizable advanced docking cart. USA version includes; DVD-RW, AC/DC, Battery pack, Manuals, 5 year standard warranty and one day of On-site Applications Training. Additional On-site Applications Training days are available for purchase.</p>
2	1	<p>Advanced Plus Image Pack</p> <p>Cross Beam Imaging - H41842LC</p> <p>B-Steer + = H48012LF</p> <p>Logiqview = H41642LK</p> <p>Easy 3D = H41642LH</p> <p>DICOM = H41652LP</p>
3	1	<p>Basic User manual and Release Notes (hardcopy) English</p> <p>Basic User manual and Release Notes (hardcopy) English</p>
4	1	<p>4C-RS Convex Transducer</p> <p>Multi-Frequency transducer with bandwidth between 1.5 and 4.6</p>

Item No. QTY		DESCRIPTION
		MHz. Applications include: Abdomen, OB GYN, Urology and Vascular Applications.
5	1	<p>9L-RS Linear Array Transducer</p> <p>Wide band multi-frequency transducer with bandwidth between 3.0 and 10.0 MHz. Applications include: Vascular, breast, thyroid, musculoskeletal and other small parts.</p>
6	1	<p>4C Biopsy Guide Multi-Angle Starter Kit</p> <p>Non-sterile 4C, 4C-A, 4C-D, 4C-RS, 5CS multi-angle bracket (4, 6, 10cm) with sterile Ultra-Pro II needle guide and 14 x 91.5 cm (5.5 x 36) CIV-Flex cover (3D) (5)</p>
7	1	<p>9L Biopsy Kit</p> <p>Multi-angle, reusable biopsy kit for 9L transducer.</p>
8	1	<p>DVDRW FOR TWINIEUR)</p> <p>DVDRW FOR TWINIEUR)</p>
9	1	<p>Docking Cart Power Cable for USA</p> <p>Docking Cart Power Cable.</p>
10	1	<p>Tall Docking Cart, with 3 port, Speaker, 110V</p> <p>Tall Docking Cart, with 3 port, Speaker, 110V</p>
11	1	<p>Footswitch with 3 programmable pedal.</p> <p>Foot Switch (MKF 2- MED GP26)with 3 programmable pedal.</p>
	1	Non Products
12	1	H48292LB Touch Screen Kit