

VAMC MINNEAPOLIS, MN
PO# 618-B39053

Item	Qty
z.one ultra sp Convertible Ultrasound System	1
<p>The z.one ultra sp Convertible Ultrasound system with Advanced Hardware includes the SmartCart sp with ZONARE's exclusive sp user interface and powered by the removable Scan Engine with Advanced Hardware.</p> <p>Scan Engine with Advanced Hardware:</p> <ul style="list-style-type: none"> • Cold Boot-up time < 30 sec • Dramatically improved processing power • Multifunction USB port, Wireless ready, Digital video • B, CD, PDI, M, PW, and Tissue Harmonic imaging • Auto Opt with ZST- Instantly equalizes tissue gain and brightness. ZST automatically compensates for differences in sound speed propagation from patient echo information. • OB, Gyn, Abdominal & Vascular calculations packages • Rechargeable Battery • 2 GB Internal Drive • System software • Touch screen stylus • User's manual, & quick start guide <p>SmartCart sp:</p> <ul style="list-style-type: none"> • 19" color high resolution LCD display mounted on articulating arm • FOCUS™ User Interface • Organic LED display for customizable image mode menus • Nitrogen Gas Shock enabled full height-adjustable user interface • Multiple USB connections • Industry's only HDMI/DVI digital video output • Shock resistant and dual rubber tread wheels with 4-wheel swivel • DVD/HD are included • Customized, durable baskets to carry supplies <p>Both the Scan Engine and SmartCart sp come with a one year warranty (parts, labor, technical support & software upgrades).</p>	
Multi-Transducer Port (MTP)	1
<p>The Multi-Transducer Port (MTP), available for the z.one ultra system and z.one ultra sp ,</p>	

	enables clinicians to easily choose between 3 transducers that are connected simultaneously. Requires Minimum Software Version 3.5			
	Battery Pack for z.one ultra/ z.one ultra sp	1		
	Battery Pack for ZS3,z.one ultra, and z.one ultra sp (SmartCart/SmartCart sp) for up to 2 hours of scanning time.			
	DICOM Networking for SuperCart/SmartCart	1		
	Print, Store and Modality Worklist. DICOM Structured Reporting supported.			
	AC Power Adapter - Scan Engine w/Adv Hdw	1		
	AC Power Adapter for Scan Engine with Advanced Hardware.			
	L8-3 Linear Array Transducer	1		
	L8-3 Linear Array Transducer (8-3 MHz) Primary Applications: Peripheral Vascular. The transducer offers ten frequencies including three frequencies for 2D and M-Mode, two for Tissue Harmonics, one for Compound Harmonics, and two each for Color/Power and PW Doppler.			
	L14-5sp Special Procedures Linear Array Transducer	1		