

| QTY | DESCRIPTION |
|-----|--|
| 1 | <p>LOGIQ S8 BT 11 USA Standard</p> <p>LOGIQ S8 general imaging ultrasound system provides superb image quality, simplified workflow and can be suited to your needs. Built upon Agile Acoustic Architecture technology, the LOGIQ S8 helps you achieve superb images even on your most difficult patients using innovative tools including CrossXBeam (Spatial Compounding), SRI HD (Speckle Reduction Imaging in High Definition), and Coded Harmonics. Productivity increases through many features such as Raw Data for post-processing of images, Automatic Optimization, Advanced 3D (w/ multiplanar displays) and Virtual Convex. Advanced ergonomics include a 19 inch color flat panel monitor (1280x1024) with fully articulating arm, fully adjustable console, 9.0 inch wide color LCD touch screen, four active transducer ports plus one parking port and an integrated gel warmer. Scanning modes include B-Mode, M-Mode, Color Flow, Pulsed Wave, and Power Doppler. Other system features include: 384MB cine memory, approximately 160 GB internal hard drive, footrest, user programmable presets and digital copy of user documentation (eDocs). A DICOM software package providing provides Verify, Print, Store, Multiframe, Modality Worklist, MPPS (Modality Performed Procedure Step), Storage Commitment, and Media Exchange. Additionally, the LOGIQ S8 supports Multi-Modality Query Retrieve and Structured Reporting. Does not include network hardware, which may be required. Initial installation includes connection to customer network, a one-year warranty and three days of On-site Applications Training. Additional On-site Applications Training days are available for purchase. Attendance to advanced technology training at the GE Healthcare Education Center in Metro Milwaukee can be purchased separately.</p> |
| 1 | <p>9L-D Linear Transducer</p> <p>Broad-spectrum linear transducer. Applications include: vascular, small parts, pediatric, and abdomen. Biopsy kit available.</p> |
| 1 | <p>ML6-15-D Matrix Linear Array Transducer</p> <p>Matrix array broad-spectrum linear transducer. Applications include: small parts, vascular, pediatrics, neonatal, breast, thyroid, scrotal. Biopsy kit available.</p> |
| 1 | <p>L8-18i-D Linear Transducer</p> |

| QTY | DESCRIPTION |
|-----|---|
| 1 | Broad-spectrum linear transducer. Preferred applications: musculoskeletal, small parts, vascular, intraoperative. |
| 1 | <p>B-Flow</p> <p>Technology to visualize real-time hemodynamic flow and vessel wall definition. B-Flow provides high resolution / high frame rates of B-Mode imaging with the ability to detect and display real-time blood flow. Sensitivity adjustments for heightened visualization of high and low flow states, small vessels and enhanced sensitivity. Includes B-Flow Color adding flow direction to the hemodynamics and improves tissue visualization. Currently functional on ML6-15-D, 9L-D, L8-18i-D, C1-5-D. transducers.</p> |
| 1 | <p>Sony UP-D897 B/W</p> <p>Sony UP897 B&W thermal printer for integrated mounting into the LOGIQ console. Includes accessories. Uses E8310KD paper.</p> |