

Artis zee floor / Artis zee III floor

All items listed below are included for this system: *(See Detailed Technical Specifications at end of Proposal.)*

Qty	Item Description
1	Interventional Cardiology X-ray angiography system with primary clinical use in interventional cardiology, including application-specific accessories.
1	Artis zee floor Universal floor-mounted C-arm angiography system with a high-resolution flat detector. The motorized rotation of the floor stand into the lateral position enables complete patient access at the head end and generous patient coverage. The powerful 100 kW generator and MEGALIX Cat Plus X-ray tube with its new flat emitter technology are the prerequisites for excellent image quality. The CLEAR functionality to optimize the image impression, the CARE package to reduce radiation exposure, and DICOM standards are all included. The system has been prepared for Siemens Remote Service.
1	Sys SW incl cardiac acquisition Imaging system software including cardiac acquisition with frame rates of 7.5, 10, 15, and 30 f/s. Acquisition, display, and storage in 1k/12-bit matrix.
1	DR, Single Img., 0,5 - 7,5 f/s, 1k Digital acquisition technology with frame rates of 0.5 to 7.5 f/s, 1k /12 bit matrix and digital real-time filtration. Serial acquisitions with time-controlled and manually variable frame rate.
1	CLEARstent CLEARstent enables an improved display of vascular supports (stents).
1	Cardiology Radiographic system for medical applications with emphasis on interventional cardiology.
1	XWP w. InSpace 3D FlashRT zee/zeego syngo X Workplace high-end post processing workstation, comprising Windows XP PC with syngo-based user software and network modules, equipped with the required HW and SW modules for real-time 3D reconstruction to virtually eliminate the time between the acquisition of a rotational angiographic examination and the display of the corresponding 3D reconstructed volume in the InSpace task card of the syngo Workplace: syngo X Workplace, syngo InSpace 3D Flash RT (incl. syngo iIdentify), InSpace 3D accessories as well as syngo iPilot to overlay calculated 3D reconstructions with live 2D fluoroscopy images.

Qty	Item Description
1	DynaCT Cardiac 20x20 FD syngo DynaCT Cardiac for 20x20 uses the proven 3D reconstruction algorithms for 3D reconstruction of ventricles and vessels of the heart from projection images of a rotational angiography from an Artis zee/zeego system with flat detector.
1	iPilot functionality for XWP syngo iPilot (enhanced functionality) allows the overlay of the colored 3D volume with regular fluoro as well as with subtracted fluoro (Roadmap) and acquisition series on the display of the syngo Workplace. Thus the iPilot information is available in parallel to the regular or subtracted fluoro or acquisition images on the live display of the acquisition system. syngo iPilot automatically updates all table, c-arm, zoom and SID changes. Even patient movement can be manually updated.
1	19in Color Flatscreen Display LCD color flatscreen display with high luminance and extended field of view.
1	Inroom Control SW-License Software extension for InSpace 3D and InSpace EP for remote control of the syngo Workplace from the examination room via touch panel and joystick.
1	syngo Angio Package Software package consisting of DSA Angio Viewer as well as High-Speed Review for real-time display of native and subtracted angiography images.
1	syngo IZ3D IZ3D reconstruction SW for calculating a 3D coronary model from at least two 2D projection images for cardiological vessel analysis with determination of degree of stenosis, distance measurement, diameter determination, and virtual stent planning.
1	syngo Coronary Vessel Analysis scientific analysis of the coronary vessels with determination of degree of stenosis, distance measurement and calibration.
1	syngo QVA Vascular Analysis Vessel analysis with determination of degree of stenosis, distance measurement and calibration.
1	syngo IZ3D - large vessel QVA 3D reconstruction SW for calculating a 3D vascular model from at least two 2D projection images for vessel analysis with determination of degree of stenosis, distance measurement, and diameter.
1	syngo LVA Quantification Analysis of the left ventricle with distance measurement and calibration.
1	syngo keyboard, USA Keyboard with special syngo keys.
1	Customer documentation, English
1	VA kit for syngo XWP VB21 Second documentation set for deliveries to the Veterans' Affairs Administration Hospitals in the U.S.
1	Image Memory Extension R640 XWP Option to expand image memory by 300 GB.
1	3D / 3D CARD Acquisition Native rotational angiography with angle and ECG-triggering, generating the image data required for 3D reconstruction of the heart.

Qty	Item Description
1	Detector 20X20 incl.Compnts. (F)-EP High-resolution, dynamic flat detector for fully digital imaging chain, with integrated, removable grid. CAREwatch measuring chamber for detection of the dose-area product. MEGALIX 2-focus high-performance X-ray tube assembly, rotatable card collimator including CAREfilter, and integrated collision protection.
1	Table with Tilt Floor-mounted swivelling patient table with telescopic foot, floating and tiltable tabletop; motor-driven stepping for digital peripheral angiography. Table control module, power-assisted.
1	Table Top & Mattress, Narrow Carbon fiber tabletop in narrow design with head-end recess, including matching special foam material mattress. Mattress including cover.
1	Foot Switch Monopl. (Cable) For release of fluoroscopy, exposure and table brake as well as a configurable additional function. Cable connection.
1	Connection Kit - 2nd Foot Switch Connection kit for connecting a second tableside foot switch.
1	Foot Switch Monopl.(Wireless) For release of fluoroscopy, exposure and table brake as well as a configurable additional function. Wireless connection via radio communication.
1	Large Display with DCS extended 56" or 60" color flat screen display (including cables) for the examination room, installed on a ceiling-mounted, longitudinally mobile, swiveling, rotating, and height-adjustable display suspension system (DCS extended) with extended working range. A video controller (MDM) that can process up to 21 video input signals. Direct selection of display configurations (max. 12) via the tableside control module.
1	LD MDM-Controller Medium 18 Inputs The Large Display Multi Display Manager Controller Medium is one of three different video controller sizes and can be equipped with up to 18 video input channels. Up to 18 video input channels also can be shown simultaneously on the large display (LD).
1	XWP/MMWP video cabling This connection kit is needed to display the video signal from a unit, for example the syngo X-Workplace, on a single display or on a large display in the display suspension system (DCS) in the examination room. Note the following conditions if image content from third-party provider video signals are to be displayed on the Artis displays: - The display of external video signals depends on the operational state of the Artis system. If the Artis system has a malfunction or is shut down, the display of external video signals is not available. For this reason, do not feed the video signal into the Artis system if lacking the external video signal could result in a hazardous situation. - A third-party provider's unit may be connected only if it corresponds to the specifications of the video interface (e.g., at the MDM). - The connection may only be established by a Siemens service technician. Note: The connection must be made with fiber-optic cables to ensure that the unit's galvanic isolation is maintained. The fiber-optic cables must be ordered separately. - A third-party provider's unit must be connected by a technician from the third-party provider or by a hospital technician responsible for the equipment. - It is strongly recommended that image quality be tested by the third-party provider prior to start-up. This test ensures that the required image quality is achieved. - The system configurator is responsible for ensuring that applicable standards are maintained in the current version, e.g. 4 kV insulation. Siemens will not be held liable for the inclusion of third-party provider units with respect to image quality and their suitability for clinical diagnosis.
1	LD Input external IR/CARD/NEURO kit Contains all required connection kits to connect the external analog and external digital video signals for the Large Display in IR / CARDIAC / NEURO applications.
1	LD input VGA ext. (ultrasound) Analog input for an analog VGA video signal, e.g. from the ultrasound.

Qty	Item Description
1	MMV - XWP/MMWP joystick/mouse Additional, dedicated joystick in the examination room for precise and fast control of a syngo Workplace parallel to mouse operation in the control room.
1	ACE Cable Set in Equipm.Room Image system interface to the displays in the control room if the image system is installed in the equipment room.
1	C-Room DVI 1xBWD-19 (Live) -36m One monochrome 19" flat-screen display with blue background color.
1	ECG Interface (1) Recording, storage and display of an ECG lead. Displayed together with the image information on a single monitor.
1	LV analysis Analysis of the left ventricle with distance measurement and calibration.
1	Vessel analysis Vessel analysis with determination of degree of stenosis, distance measurement and calibration.
1	Scientific QCA Scientific cardiac vessel analysis with determination of degree of stenosis, distance measurement and calibration.
1	IZ3D IZ3D reconstruction SW for calculating a 3D coronary model from at least two 2D projection images for cardiological vessel analysis with determination of degree of stenosis, distance measurement, diameter determination, and virtual stent planning.
1	Fluoro Loop (1) Storage and review of dynamic fluoroscopic sequences (Fluoro Loop). The maximum storable fluoroscopic time depends on the selected pulse rate, e.g. 34 s at 30 p/s, 68 s at 15 p/s (VC21 software required). Note: With VC14 software, the values are 17 s at 30 p/s, 34 s at 15 p/s.
1	Automap Automatic stand positioning depending on the selected reference image and automatic reference image selection depending on the stand positioning.
1	MULTISPACE.F Manual stand rotation for additional work positions.
1	DICOM HIS / RIS Import of patient/examination data from an external RIS/HIS patient management system with DICOM MWL (Modality Worklist).
1	DICOM MPPS Feedback of examination status via DICOM MPPS (Modality Performed Procedure Step) to an external RIS/HIS patient management system. Data such as the dose-area product can be transferred to the RIS.
1	DICOM Print Provision of DICOM Print service for connection to a laser camera or a network printer (postscript).
1	Head Side Support The head end holder can be attached at the head end of ARTIS tabletops (narrow = card). This is a special accessory rail holder enabling incorporation of the head supports, shoulder supports and articulated arm supports, and the anesthetic curtain.

Qty	Item Description
1	Handles with support (2pc.) Hand grips for patient positioning for examinations requiring the arms to be held in a specific position.
1	LB rad. protection w/ pivot arm For shielding the lower body against scattered radiation within the examiner's moving range. Specially designed for avoiding collisions with the tube during oblique projections, therefore especially suited for cardiology.
1	Upper Body Rad. Protection Artis-F To protect the upper body against scattered radiation within the operating range of the examiner, e.g. during interventional procedures.
1	Interface for C-Room Operation(MA) Interface for connecting the optional system control from the control room.
1	Control room emerg. stop module Safety button for switching off all system functions from the control room.
1	Hand switch manual Additional hand switch for radiation release and additional control functions.
1	Control Room Injector Interface Interface for controlling the contrast medium injector from the control room.
1	syngo Keyboard, English - US Keyboard with special syngo keys.
1	Intercom - Comfort Communication / intercom system for communication between examination room and control room.
1	Armholder (pair) Two arm holders for comfortable lateral arm positioning along the patient's body.
1	VA kit Artis zee systems Second set of documentation for deliveries to the Veterans' Affairs Administration Hospitals in the U.S.
1	Upper Body Rad. Protection Artis-F To protect the upper body against scattered radiation within the operating range of the examiner, e.g. during interventional procedures.
1	3 Reflector OR Lamp, 115V Ceiling-mounted OR lamp, 3 spots, with variable focusing of spot size for optimum illumination especially in deep lesions.
1	Examination lamp, 115 V Ceiling-mounted OR lamp (examination light class), flexibly adjustable towards the user, for diagnostics and minor surgery. Examination light Mach 130F with focusable dielectric light system. - Luminance: 35,000 Lux (3,255 fc) for 100 cm distance - Working distance: 70 to 140 cm - Color rendering index Ra (gen.): 96 - Color temperature: 4,300 Kelvin - Focusable spot size: 14 to 25 cm - Light body diameter: 22 cm - Halogen lamp: 22.8 V/50 W Examination light power connection 115 V Only in connection with upper body radiation protection 144 07 034 or 144 07 035. For direct connection with 115 V line voltage only. Max. arm length: 185 cm. Weight: 14 kg *2 May only be delivered in the USA with the local material no. or sales no. in the US price book
1	Customer documentation, English
1	Pre-install Artis-F (mono)
1	Pre-install Artis table, std

Qty	Item Description
1	Initial onsite training 32 hrs Up to (32) hours of on-site clinical education training, scheduled consecutively (Monday - Friday) during standard business hours for a maximum of (4) imaging professionals. Training will cover agenda items on the ASRT approved checklist. Uptime Clinical Education phone support is provided during the warranty period for specified posted hours. This educational offering must be completed (12) months from install end date. If training is not completed within the applicable time period, Siemens obligation to provide the training will expire without refund.
1	Follow-up training 32 hrs Up to (32) hours of follow-up on-site clinical education training, scheduled consecutively (Monday - Friday) during standard business hours for a maximum of (4) imaging professionals. Uptime Clinical Education phone support is provided during the warranty period for specified posted hours. This educational offering must be completed (12) months from install end date. If training is not completed within the applicable time period, Siemens obligation to provide the training will expire without refund.
1	Follow-up training 12 hrs Up to (12) hours of follow-up on-site clinical education training, scheduled consecutively (Monday - Friday) during standard business hours for a maximum of (4) imaging professionals. Uptime Clinical Education phone support is provided during the warranty period for specified posted hours. This educational offering must be completed (12) months from install end date. If training is not completed within the applicable time period, Siemens obligation to provide the training will expire without refund.
1	Eaton Powerware 9355 15 kVA UPS Includes UPS, battery, maintenance bypass panel, and one year on-site parts and labor coverage (24x7) by Eaton Powerware. This UPS is recommended when protection and uninterruptible power is required for the Artis' C-arm and table. Emergency fluoroscopy is not available with this UPS. If emergency fluoroscopy is required, the 9390 - 160 kVA UPS is recommended for the full system. One UPS per lab. Additional seismic brackets are required to make this system OSHPD approved.
1	Blue anti-fatigue floor mat for hospital
1	Horizon SF (2 DICOM connections)
1	Standard Rigging zee SP
1	OCS Mount,Mark 7 Arterion Injector The Arterion Mark 7 Overhead counterpoise contrast medium injector allows for the remote installation of the system power supply and installation of the injector head onto a ceiling mounted arm. The injector system includes: Power supply and injector head with corresponding cabling A desk mounted user control console with large touch screen Note: The appropriate Overhead Counterpoise System (OCS) must be ordered separately Functions Pressure limitation: for 150 ml syringes 689 to 8273 kPa, corresponds to 100 to 1200 psi. . Flow rates for 150 ml syringes: 0.1 to 45 ml/s in increments of 0.1 ml/s 0.1 to 59.9 ml/min in increments of 0.1 ml/min rise/fall: 0 to 9.9 s in increments of 0.1 seconds Release delay for injection or radiation: 0 to 99.9 s in increments of 0.1 s. Adjustable volume for 150 ml syringes: 1 ml to the max. syringe capacity in increments of 1 ml. Fill rate: Variable syringe filling speed 1-20ml/s. Injection protocols: Up to 40 injection protocols possible. Parameters currently displayed on the touch screen display and on the head display: Injection speed Injection volume Remaining volume Injection duration Applied pressure Contrast medium heating: Nominal 35°C (95°F)+-5°C (9°F) Injection data memory Up to 50 injection data items stored Included in the scope of delivery Injector standard configuration 150 ml SIEMENS interface cable Operator Manual Service manual (English). Power supply 200 V to 250 V; 50/60 Hz.
1	OCS 800mm Trolley Mount, Portegra2 Portegra 2 - Track Ceiling Mount - 80 cm post
1	Additional Rigging/Out of Scope Inbound
1	Additional Rigging/Out of Scope Outbound/Deinstall

Qty	Item Description
1	Offset Initial Training 32 hrs
1	Elevate Promo Artis to zee Single Plane Existing System must be de-installed by June 30, 2014.
1	AX ELEVATE #R Buy Back (I.I. mono) AX Elevate program for AXIOM Artis systems (monoplane) with image intensifiers which will be replaced by a new Artis zee system.
1	AXA BTL Deinstallation
1	Airfare for Comp Biomed for one engineer from FLL-RDU
1	Lodging for Comp Biomed for one engineer for 36 nights
1	Airfare for Additional Biomed for one engineer from FLL-RDU
1	Lodging for Additional Biomed for one engineer for 36 nights
1	One complimentary biomedical tuition is included with the purchase of this system. This training must be completed before the end of the warranty period.
1	XX2SYNGO- Syngo with Multimodality Workstation 5 Days
1	AX1ANGAPPL - Clinical Angio Applications 5 Days
1	AX2ARTZEE - Artis zee system - 20 Days

Detailed Technical Specifications

Artis zee floor / Artis zee III floor

/ Product	Description
Interventional Cardiology	<p>The accessories consist of:</p> <ul style="list-style-type: none"> - ECG cable clips
Artis zee floor	<p>System Configuration The monoplane C-arm system for digital acquisition techniques is designed to meet the requirements of state-of-the-art angiography and interventional procedures.</p> <p>C-arm floor-mounted stand:</p> <ul style="list-style-type: none"> - Up to 5 programmed work positions and additional 50 user-defined work positions. - One single joystick for patient angle oriented operation of C-arm and flat detector movements. - Integrated, computer-aided collision monitoring ICP (Intelligent Collision Protection). - C-arm positioning 0° to the head end and 35° to the left side of the patient longitudinal axis. - Double oblique projections: LAO/RAO: $\pm 130^\circ$ cranial max. 55°, 52° with isocenter 12 cm above patient tabletop caudal 45° - Variable C-arm speeds up to 25°/s. - Variable source-to-detector distance between 90 cm and 120 cm. - Isocenter-floor distance 106 cm. - Focus-isocenter distance 75 cm. <p>Operation An ideal workflow requires full user operation capabilities for the system including imaging system and generator under sterile conditions in the examination room. That way the user is able to operate the system by himself without the need to leave the examination room. The intuitive <i>syngo</i> operating elements allow for managing the whole process from preparation of the patient to image post processing in a safe, reliable, and time efficient way.</p> <p>In the examination room: Complete system operation through modular control elements directly at the patient table for controlling C-arm movements, patient table and multileaf collimator. Touchscreen with multi-functional joystick for operation of the imaging system, including post-processing and quantification as well as selection of the organ programs. It is based on <i>syngo</i> operation. The touchscreen is specifically configurable to individual clinical requirements. Data regarding system and table geometry, dose data with CAREwatch, as well as system messages, are shown in the live display</p> <p>In the control room: Standard Siemens <i>syngo</i> control via keyboard and mouse for all imaging system functions such as image post-processing, archiving and configuring of organ programs.</p> <p>Display of system data Data regarding system and table geometry, dose data with CAREwatch, as well as system messages, are shown integrated on the display in the examination room.</p> <p>imaging system High-resolution digital imaging system with CLEAR technology, DICOM network connection and <i>syngo</i> user interface.</p> <p>In order to provide highest level system availability, the imaging system consists of two independent computer systems that manage central tasks such as real-time image processing during fluoroscopy or acquisition as well as post-processing and networking functionality separately from one another. This ensures the system performance will always meet the highest possible demands.</p>

/ Product	Description
Artis zee floor	<p>Image storage capacity 25,000 images in 1k/12-bit image matrix (extendable).</p> <p>Operating modes</p> <ul style="list-style-type: none"> - Digital pulsed fluoroscopy with pulse frequencies of 10 p/s, 15 p/s, and 30 p/s in 1k/12 bit matrix. - Overlay fade: On-line overlay of active fluoroscopy and reference image. <p>CARE package Siemens follows the ALARA principle: "As Low as Reasonably Achievable"; the CARE package (Combined Applications to Reduce Exposure) was developed based on this research and development principle to protect the examiner and the patient.</p> <p>Dose saving</p> <ul style="list-style-type: none"> - CAREvision: Pulsed fluoroscopy with additional, reduced pulse rates of 7.5 p/s to 0.5 p/s. Adaptation of pulse rate to the current application requirements for significant reduction of radiation exposure, especially during interventional procedures. - CAREprofile: Radiation-free positioning of the primary and semi-transparent diaphragms by means of graphic display in the LIH (Last Image Hold). Collimator shutters and semi-transparent filters can be adjusted as a graphical overlay on the last-image-hold without any need for fluoroscopy. - CAREposition: Object repositioning without radiation through graphic display of the X-ray central beam and the image edges in the LIH (Last Image Hold). CAREposition enables the repositioning of an object under visual control without radiation. In case of table movements the current position of the central beam and the image edges are superimposed on the LIH image as orientation points. - CAREfilter is intelligent control software that helps minimize X-ray dose without negative impact on image quality. During fluoroscopy and acquisition special copper prefilters are inserted into the X-ray beam depending on current X-ray transparency calculated by CAREmatic. The five-step adaptive Cu prefiltration is used to reduce the equivalent dose of the skin and improve radiation quality through dose saving of low-energy X-ray radiation: Filter steps: 0.1; 0.2; 0.3; 0.6; 0.9 mm Cu. Selection is automatic depending on absorption. This is necessary to ensure that the optimal prefilter value is always active. This automation makes work easier for the user because the given optimal filter setting need not be adjusted manually. - CAREwatch: Display of the measured dose-area product and the calculated patient air kerma reference on the flat screen display. Electronics unit with DIAMENTOR measurement chamber integrated in the collimator housing for dose acquisition. Configurable screens on the data display and imaging system monitor: During fluoroscopy: Air kerma reference rate. During fluoroscopy interval: Accumulated air kerma reference or dose-area product or percentage of dose limit value (sum of fluoroscopy and acquisition). - Low dose acquisition: enables dose savings of up to 60 % during the examination. The low dose acquisition protocol can be released directly with the footswitch. <p>Dose monitoring</p> <ul style="list-style-type: none"> - CAREguard: enables three skin entry dose thresholds to be established. If the accumulated skin entry dose exceeds the configured threshold, a warning appears on the live display and tableside on the touchscreen control. This provides ideal skin entry dose monitoring during the examination. - CAREmonitor supports the physician by enabling dose-efficient examinations, thereby significantly reducing the risk of skin burns. It includes special monitoring of the skin entry dose, taking into account the geometric conditions of the system (device angulation, table position). This ensures that the skin entry dose applied to a specific region of the patient's body will not exceed a specified threshold, thereby better protecting the patient from the harmful effects of X-radiation. The critical equivalent skin dose to avoid X-ray-related skin injury is at about 2 Gy. CAREmonitor consistently calculates and displays the actual accumulated skin entry dose. This helps the user to detect a potential patient hazard quickly and with certainty. <p>Dose reporting</p> <ul style="list-style-type: none"> - CAREreport: part of the DICOM Structured Report; displays the dose information in DICOM format after every examination. This creates an integrated DICOM data set consisting of images and dose information, which can be sent together to a DICOM archive. The display of dose information in DICOM format permits the flexible analysis and further processing via a DICOM-capable analysis software/database. <p>CLEAR package</p>

/ Product	Description
Artis zee floor	<p>The CLEAR package enables optimized image quality through real-time processing of the image data without increasing the radiation dose.</p> <ul style="list-style-type: none"> - CLEARcontrol: The new histogram analysis provides a more homogeneous image impression by harmonizing over- and underexposed areas of the image. This is done fully automatically, thus eliminating any further manual user corrections through windowing. - CLEARview: Dose-dependent filtering of the image data efficiently suppresses image noise, enabling clear, sharp images, even for low-dose acquisitions. - CLEARvessel: Every pixel is analyzed in real time, and vessel edges are shown in high contrast without adding noise to the image. - CLEARmotion: Fine moving structures, such as small vessels and guidewires, are detected in the image and motion artifacts are suppressed efficiently. The visibility of small moving vessels and guidewires is improved significantly during fluoroscopy. <p>In addition there is Dynamic Density Optimization (DDO) for on-line harmonization of native series and single images.</p> <p>Image processing</p> <ul style="list-style-type: none"> - Positive/negative image display, windowing, contrast/brightness, electronic display (shutter), image shift (roaming), vertical and horizontal image inversion, magnifying glass, and zoom functions. - Automatic and manual pixel shift, remask, peak opacification for iodine contrast (MaxOpac) and CO₂ contrast (MinOpac), adding of the anatomical background (landmark) from 0 to 100% (only in connection with DSA option). - Storing of single images as reference images also during fluoroscopy. - Quantification: angle/length measurement, automatic and/or manual calibration. - Text functions: user-definable image annotation, free annotation or by means of text components, comments line for the image, R/L display. - Fast and direct access to all series, single images, and photo file via MULTIMAP both in the examination and in the control room. <p>DVD / CD burner (DICOM)</p> <p>DVD drive for automatic digital image storage in the background on DVD-/CD-ROM for off-line data exchange in DICOM format.</p> <p>Networking</p> <p>Network interface (1000 BaseT) with the following integrated DICOM services:</p> <ul style="list-style-type: none"> - DICOM Send: Sending of images into the DICOM network: The DICOM Send function enables fully automatic transfer of generated image data to a DICOM archive or a DICOM workstation. The user can perform his examinations without interruption, while the system is fully automatically transferring the images to the archive scene by scene. This is a background process, and thus does not interfere with the ongoing fluoroscopy or acquisition. - DICOM Storage Commitment (StC): Feedback from the image archive. The DICOM StC function automatically gives feedback on whether the generated image data were successfully transferred. This provides the necessary certainty to the user before deleting the acquired images locally in the imaging system. - DICOM-Query/Retrieve: Retrieval of archived images from a digital archive or from a workstation: Already archived image data from a previous examination can be fully retrieved and is then available for review and processing. The user can request CT or MR system images from the archive and display the data as a reference image in the examination room. There is no need for a separate workstation. - DICOM Structured Report: All the quantification results obtained on the system as well as all dose information on the individual radiation releases can be saved in DICOM SR (enhanced SR) format and transferred to a DICOM network. <p>Note concerning DICOM interface(s)</p> <p>The description in the DICOM Conformance Statement downloadable from the Internet is exclusively binding for the functionality of the DICOM interface(s).</p> <p>Functionalities across interfaces with/between partner systems require explicit validation, since the interpretation of the interface by the partner/target system is not part of the product's responsibility.</p> <p>A modification of the interface that might be required is not included in the offer; e.g. for the rare case that available</p>

/ Product	Description
<p>(Continued)</p> <p>Artis zee floor</p>	<p>configurations are not sufficient. With regard to expenses for interface configurations that might be required, the agreements on maintenance/service of the product apply.</p> <p>X-ray Generator Microprocessor-controlled high-frequency X-ray generator with automatic dose rate control.</p> <ul style="list-style-type: none"> - 100 kW at 100 kV (DIN 6822), nominal power max. 80 kW (100 kV, 800 mA, 0.1 s) with Megalix tube and the newest flat emitter technology. - SID tracking (automatic tube current adaptation to source-to-image receptor distance). - CAREmatic automatic X-ray control system for fully automatic calculation and optimization of exposure data based on fluoroscopic data. - Patient transparency monitoring. - Tube load monitoring with indication in the data display. <p>The optimal X-ray parameters depend on the transparency of the patient at the current angulation, measured during fluoroscopy. These parameters are continuously calculated and updated. Test shots are no longer required. This ensures superior image quality and minimum radiation exposure for physician and patient with every exposure release.</p> <p>Accessories included in the scope of delivery</p> <ul style="list-style-type: none"> - Unilateral armrest - Infusion bottle holder - Additional hand switch for radiation release and additional control functions. <p>Siemens Remote Service SRS™ Prepared for Siemens Remote Service SRS™ (during warranty, then with service contract):</p> <ul style="list-style-type: none"> - Hardware and software remote diagnosis. - System remote configuration, e.g. adding of a DICOM node. - Early warning system ensuring system operation. <p>syngo Evolve for Artis zee syngo Evolve is a service feature that is offered as a separate sales option for all systems of the Artis zee family. It is a key component of our upgrade strategy and allows the customer to take advantage of technological advancements.</p> <p>Customer Care. Life - the customer care solution by Siemens Healthcare From the moment you purchase your Siemens system you will benefit from many services that are offered by "Customer Care. Life", e.g.:</p> <ul style="list-style-type: none"> - initial application training, - interactive e-learning for various applications, - free customer magazines, - arrangements for clinical training via a global network, - and free trial licenses <p>You will find detailed information on our e-learning program and further details on general "Customer Care. Life" services on the internet.</p> <p>* "Customer Care. Life" offerings are not necessarily available to the full extent for all systems.</p>
	<p>The 1k image matrix with a bit depth of 12bit allows an excellent image contrast by using 4,096 shades of grey. Thus, the image quality meets highest expectations in angiography and fulfills all prerequisites for precise diagnostics and safe interventions.</p>
	<p>CLEARstent enables an improved display of vascular supports (stents) that are growing increasingly difficult to detect in fluoro images due to the increasing number of obese patients and the ever finer structures.</p> <p>Regardless whether contrast agent is injected during the scene or not, CLEARstent either generates a magnified still image of the highlighted stent or displays the vessel filled with contrast agent alternating with the still image.</p> <p>The still image from fluoroscopy can then be overlaid.</p>

Description

CLEARstent can be activated with a single operation, directly at the patient table.

syngo X Workplace

The functionality of the syngo X Workplace can be extended with additional software functions to suit specific user or clinical needs in angiography, surgery, and cardiology. The use of the licensed software is limited exclusively to the specific syngo X Workplace included with this configuration.

The base viewing system can be extended by adding a wide range of application options.

syngo X Workplace PC

High-performance workstation based on Windows XP Professional with upgraded 6/12 GB RAM and hard drive with 147 GB/300 GB for image data. The workstation is equipped with an Open GL accelerator board to support 3D applications. To exchange medical images on DICOM-compatible CD-Rs and DVDs, the system is equipped with a CD/DVD burner.

syngo X Workplace can be connected to an existing network via Gigabit/100 Mbit Ethernet.

syngo X Workplace Basic User Software

The syngo X Workplace software features an intuitive and thus easy to learn user interface developed from prototypes tested in close cooperation with users.

Standard functions such as filming or image review, and optional clinical application software, are performed in individual processes on dedicated task cards. A number of functions and input parameters, as well as the language used, can be selected according to individual requirements.

Package comprising the following software licenses

Basic software with CD and dongle for the following functions:

- Patient Browser
- Filming
- Viewer
- System services

Patient Browser:

- Patient management.
- DICOM communication with Send, Receive, Query/Retrieve, Print.
- Reading of CDs/DVDs.
- Module for writing DICOM CDs/DVDs for data exchange. Writing is in background mode.

Filming:

A virtual filmsheet shows a 1:1 display of the film sheets to be printed. This permits an effective preview of the filming job and the windowing of images, as well as providing a large number of evaluation functions.

Image Review:

Image Review supports interactive 2D review, evaluation and documentation functions. Multiple studies from the same patient can be displayed side-by-side for comparison.

- Image display: 1.024² screen matrix, configurable with up to 64 image segments.
- CINE display: Automatic or interactive dynamic presentation technique for the visualization of time and volume series.
- Synchronized viewing of multiple series.
- Measurement and annotation: Text annotation; distance, angle, circle, ROI and pixel lens, depending on information available from the acquisition system.

System services:

Microsoft Office 2003 Word, Excel, PowerPoint plus Outlook are supported (not provided!).

- Any user-selectable file, such as cardiac, DSA or InSpace AVI video sequences, can be burned to CD to prepare quality presentations and demos of pathologies.
- Network module: For connection to a local Ethernet (Gigabit or 100 Mbit) for communication with networked archives, printers, diagnostic and therapy workstations, and teleradiology routers.

Description

Scope of functions

- Network stations can be configured.
- Unlimited selection of stations.

syngo InSpace 3D Flash RT

syngo InSpace 3D Flash RT facilitates the interactive 3D reconstruction and visualization in real time of a volume in volume rendering technique, MPR, and MIP. InSpace 3D is focused to support the interventional radiologist and neuroradiologist in the angio lab.

Based on dedicated acceleration hardware the primary reconstruction results are available in full diagnostic quality in the examination room within 18 seconds for high contrast images and less than one minute for soft tissue DynaCT images. Subsequent secondary reconstructions are available even faster.

The application facilitates interactive volume rendering, accelerated by a high-end 3D graphics card. It offers support for large data records of up to 1,600 images (512 x 512 matrix).

***syngo* iDentify (Dual Volume Visualization)**

Enables the differentiation between two high-contrast 3D objects that have virtually the same contrast density and allows the display of one low contrast and one high contrast volume in one view. *syngo* iDentify enables clear differentiation between contrast-filled vessels, bones, stents and coils. Furthermore, visualization of the anatomical structure of tumors in combination with the feeding vessels becomes possible.

Features:

- Reconstruction protocols, for visualization of vessels, bones, clips and coils.
- The result of the reconstruction can be native or subtracted.
- Modification of reconstruction area to allow zoom via reconstruction.
- Visualization with shading and light source for an improved three-dimensional impression.
- Interventional volume measurement.

Image data:

- Volume data from AX, CT, MR, and PET modalities.
- Loading of two volume data sets simultaneously.
- Layouts: single (1on1), double (2 on1) and quadruple (4on1) for MPR display.
- Two displays are supported for simultaneous display of two volumes side-by-side.

Image display modes:

- VRT, Color VRT, MIP, MinIP, and MPR rendering.
- Thin slice renderings for VRT, MIP, and MinIP.
- Variable light source.
- Shading effects.

Volume editing:

- Cut planes.
- Editing of clip planes and control volumes.
- ROI punching.

Presets:

- Series-specific bookmarks, to store and retrieve volume visualization parameters.
- Global presets for series-unspecific application of volume visualization parameters.

Output:

- Radial ranges, including macro range definitions.
- 2D and 3D measurements, measurement grid, distance measurement and annotations.
- AVI format export with selectable compression format and compression ratio.
- TIFF, PNG, BMP, JPEG image export.
- Send to film sheet.

Description

Advantages and features of InSpace 3D Flash RT

In angiography the three-dimensional information is used for diagnosis, planning of therapy and documentation in the field of endovascular and non-endovascular interventional procedures.

Diagnosis and treatment can be performed in one session, thus providing a major advantage through the fully integrated workflow.

- Transfer of the projection angle to the C-arm stand.
- Indication whether the angulation can be achieved at the C-arm without collision with the patient or table.
- Interventional volume measurement.

InSpace 3D accessories

Includes the accessories required for 3D reconstruction and visualization:

- Plexiglas calibration phantoms
- Line phantom for image quality control
- Form filter
- 3D data link

syngo iPilot

For any projection, zoom, SID and table position the physician can create an iPilot - view, which is superimposed on the live fluoro image. Via a fade with the joystick the degree of visibility can be determined. The physician can perform the procedure with more confidence. No extra contrast is needed to make the vessel tree visible.

When the guidewire is visible on the live screen in the area the 3D reconstruction, the physician can press the "iPilot" button on the tableside control at any time.

An image is automatically calculated and sent to the reference storage of the imaging system. Via the Overlay Fade functionality the physician can show the 3D and 2D live information in one image.

DICOM

Industrial standard for the transmission of information between DICOM-compatible equipment from different manufacturers. The scope of functions is described in detail in the DICOM Conformance Statement and in the standard version includes the Transmission/ Reception, Query/ Retrieve and Basic Print functions.

Note concerning DICOM interface(s)

For diagnostic purposes, only hardcopy cameras/laser printers explicitly approved for this system may be used.

The description in the DICOM Conformance Statement downloadable from the Internet is exclusively binding for the functionality of the DICOM interface(s).

Functionalities across interfaces with/between partner systems require explicit validation, since the interpretation of the interface by the partner/target system is not part of the product's responsibility.

A modification of the interface that might be required is not included in the offer; e.g. for the rare case that available configurations are not sufficient. With regard to expenses for interface configurations that might be required, the agreements on maintenance/service of the product apply.

syngo DynaCT Cardiac for 20x20 FD allows the use of proven *syngo DynaCT* 3D reconstruction for contrasted X-ray projection images of ventricles and vessels of the heart. *syngo DynaCT Cardiac* for 20x20 FD contains reconstruction algorithms for

- ECG-triggered 3D acquisitions (multiple C-arm rotations, approx. 30 seconds exposure time) as well as for
- untriggered 3D acquisitions (one C-arm rotation, approx. 5 seconds exposure time).

ECG-triggered acquisitions provide greater temporal resolution, which is helpful for imaging cardiac morphology with a lot of motion.

Clinical applications currently supported by *DynaCT Cardiac*:

Electrophysiology:

- 3D visualization of the left atrium to support ablation of atrial fibrillation (segmentation of the left atrium using

ct	Description
	<p>InSpace EP, must be ordered separately)</p> <ul style="list-style-type: none"> - 3D visualization of the coronary venous tree to support biventricular pacemaker implantation <p>Interventional Cardiology/Surgery:</p> <ul style="list-style-type: none"> - Planning, support and follow-up before, during and after heart valve replacement through 3D visualization of the aortic valve and coronary ostia <p>Pediatrics:</p> <ul style="list-style-type: none"> - 3D visualization of the congenital heart defects before and after surgical interventions: There are low-dose organ programs especially developed for pediatric acquisitions available. <p><i>syngo</i> DynaCT Cardiac is especially suited for the planning, performance and follow-up of interventions through display of current cardiac 3D morphology directly in the cath lab.</p> <p><i>syngo</i> iPilot (order as separate option) enables simultaneous overlay of the live fluoro image (display of components used during the intervention) with 3D image data (display of 3D morphology); no separate recording procedure is required.</p> <p>DynaCT Cardiac Volume can also serve as a basis for magnetic navigation systems (e.g., Niobe Navigant) or (in connection with <i>syngo</i> InSpace EP Segmentation, separate option) can be used by electroanatomical mapping systems (CARTO, Ensite NavX) for increased precision of electrophysiological mapping as well as time savings.</p>
	<p><i>syngo</i> iPilot Workflow</p> <p>preparation for iPilot-guided intervention, the physician typically performs a 3D reconstruction to visualize the vessel tree or an anatomical structure as a volume.</p> <p>Upon selection of iPilot, this 3D reconstruction is overlaid with the live image.</p> <p>The degree of visibility of the 3D volume can be modified by the user.</p> <p>Patient movements can be compensated by adjusting the 3D volume accordingly.</p>
	<p>The Siemens 19" LCD flatscreen display features a very high contrast even under very bright ambient light conditions. The Gamma curve was precisely adapted to the CIE-/DICOM recommendation and is thus suited especially for gray scale display.</p> <p>LCD flatscreen display</p> <ul style="list-style-type: none"> - 19" (48 cm) screen size - Resolution: 1,280 x 1,024 (pixel) - guaranteed brightness for the entire service life: 137 cd/m² at a contrast ratio of 300:1 - Flicker-free and distortion-free image display - Anti-glare screen <p>The controlled background lighting provides stable lighting throughout the entire product life cycle.</p>
	<p>The InRoom Control software extension allows for remote control of the <i>syngo</i> Workplace from the examination room via touchscreen and joystick.</p> <p>For this, another set of functions is offered on the Artis touchscreen. These are implemented for 3D navigation and allow the user to manipulate the 3D image displayed on the optional display.</p>
	<p>The <i>syngo</i> Angio package enables dynamic review of DSA scenes (in subtracted or native display) and their postprocessing at the <i>syngo</i> Workplace, with functions such as:</p> <ul style="list-style-type: none"> - Remasking. - Pixelshift. - Anatomic background. - Opacification etc. - Review of DYNAVISON and PERIVISION scenes <p>The high-speed functionality increases the image review frequency, especially of biplane and single-plane cardiac scenes, depending on the frame rate and the <i>syngo</i> Workplace hardware used.</p>

<p>3t</p>	<p>Description</p> <p>With the current <i>syngo</i> Workplace hardware the following maximum image review frequencies of the scenes can be achieved:</p> <p>Biplane (native):</p> <ul style="list-style-type: none"> - 6 f/s with a 1024² matrix - 15 f/s with a 512² matrix <p>Monoplane (native):</p> <ul style="list-style-type: none"> - 15 f/s with a 1024² matrix - 30 f/s with a 512² matrix
	<p>IZ3D enables interactive 3D reconstruction and visualization of coronary segments, including bifurcations. IZ3D is especially suited for support in interventional cardiology; especially during stenting procedures.</p> <p>A three-dimensional coronary segment is reconstructed from at least two selected projections. Especially to be used for vessel sizes between 0.5 mm and 7 mm.</p> <p>Advantages and features of IZ3D</p> <p>In cardiac angiography three-dimensional information is used for diagnosis, therapy planning, and documentation within the scope of interventional procedures.</p> <ul style="list-style-type: none"> - Interventional length and distance measurement - Stenosis measurement. - Determination of diameter - Determination of bifurcation angle. - Virtual planning of stent placement in a vessel segment. - Display of 3D image data in the examination room via an in-room display. <hr/> <p>Scientific measuring program for clinically validated, objective, accurate and reproducible evaluation of coronaries.</p> <ul style="list-style-type: none"> - Automated contour detection. - Determination of degree of stenosis. - Automatic and manual reference diameter determination. - Stenotic Flow Reserve. - Automatic and manual calibration methods. - Distance and angle measurement. <p>Especially to be used for vessel sizes between 0.5 mm and 7 mm.</p> <p>QCA (Quantitative Coronary Analysis) is based on the gold standard in coronary analysis: CAAS II (Cardiovascular Angiography Analysis System Mark II) from Pie Medical, Netherlands.</p> <p>The algorithms come from the Thorax Center of the Rotterdam Erasmus University. They are clinically validated and internationally recognized for scientific purposes (Multicenter Studies).</p>
	<p>Scientific measuring program for objective, accurate and reproducible vessel evaluation:</p> <ul style="list-style-type: none"> - Automated contour detection. - Determination of degree of stenosis. - Automatic and manual reference diameter determination. - Automatic and manual calibration methods. - Distance and angle measurement. <p>Especially to be used for vessel sizes between 0.5 mm and 50 mm.</p> <hr/> <p>QVA 3D enables interactive 3D reconstruction and visualization of vessel segments, including bifurcations. QVA 3D is especially suited for support in interventional angiography; especially during stenting procedures.</p>

Description
<p>A three-dimensional vessel segment is reconstructed from at least two selected projections. Especially to be used for vessel sizes between 0.5 mm and 50 mm.</p> <p>Advantages and features of QVA 3D In interventional angiography three-dimensional information is used for diagnosis, therapy planning, and documentation.</p> <ul style="list-style-type: none"> - Interventional length and distance measurement - Stenosis measurement. - Determination of diameter - Determination of bifurcation angle. - Display of 3D image data in the examination room via an in-room display.
<p>Scientific measuring program for functional evaluation of the left ventricle.</p> <ul style="list-style-type: none"> - Automated and manual contour detection. - Automatic end-diastole/end-systole detection. - Calculation of ejection fraction, volumes and indices (area, length and Simpson methods). - Centerline, radial and regional wall movement analyses. - Automatic and manual calibration methods. - Distance and angle measurement.
<p>Keyboard for easy operation of syngo (browser, viewer, filming). There are special keys for windowing, scrolling, printing, marking and network communication.</p>
<p>Angle-triggered and ECG-gated, digital rotational angiography with corresponding image data transfer to a <i>syngo X Workplace</i> and native image display in 3D.</p> <ul style="list-style-type: none"> - Rotation speed is up to 60°/s (Artis zee ceiling, Artis zeego) and 45°/s (Artis zee floor, Artis zee biplane). - Angle triggering allows a reduction in dose through a reduced acquisition frame rate while at the same time achieving better image quality. - All parameters required for the 3D reconstruction are included in the organ program. This enables optimized image quality and easy handling. - Acquisitions with frame rates in 1k matrix from 0.5 to 7.5, 10, 15, 30 f/s (standard) and 60 f/s with reduced spatial resolution can be selected, <p>Includes DYNAVISION DR for native rotational angiography. Reconstruction at the <i>syngo X Workplace</i> is not possible with this operating mode.</p>
<p>Flat detector 20 x 20 The digital high-resolution dynamic flat detector with integrated removable grid is especially designed to fulfill the requirements of angiographic and interventional applications.</p> <p>184 µm pixel arrays provide highest spatial resolution and excellent contrast. Fluoroscopy as well as image acquisition are always done in 1k matrix and 14 bit gray scale resolution with high detail visibility. Acquisition frame rates of up to 30 f/s are possible.</p> <p>Usable input formats:</p> <ul style="list-style-type: none"> - Overview: 17.7 cm x 17.7 cm, diagonal 25 cm. - Zoom 1: 14 cm x 14 cm; diagonal 20 cm. - Zoom 2: 11 cm x 11 cm; diagonal 16 cm. - Zoom 3: 7 cm x 7 cm; diagonal 10 cm. <p>The very compact design with integrated collision protection provides maximum C-arm angulation range for excellent patient access.</p> <p>The flat detector is mounted on a motorized rotating turntable at the C-arm. This ensures upright presentation of the anatomy on the monitor screen independent of the relative position of the C-arm to the patient at all times.</p>

t	Description
	<p>Motorized adjustment of the detector-patient distance.</p> <p>Digital data transfer from the detector to the imaging system is via a high-speed Gigalink fiber-optic cable.</p> <p>Removable grid: The grid can easily be removed, saving the user time in examinations not requiring a grid. For example in pediatrics, where dose reduction is especially important.</p> <p>MediGuide Technology compatibility: The flat detector is prepared for the upgrade with the Siemens MediGuide Technology Ready Kit.</p> <p>Tube assembly MEGALIX Cat Plus 125/40/90-121GW Dual-focus high-performance X-ray tube assembly with flat emitter technology for cardiac angiography, with metal center tube in lubricated spiral groove bearing technology for permanent, noise-free rotation.</p> <ul style="list-style-type: none"> - Maximum tube voltage 125 kV - Focus: 0.4/0.8 (35/90 kW) - Anode angle 8° - Maximum anode heat storage capacity: 3,375,000 HU - Maximum tube current for fluoroscopy: 250 mA <p>High tube power provides brilliant image quality even with heavier patients. In addition there is no need for X-ray pauses even during lengthy cases. The X-ray tube is completely silent, which is an additional benefit for patient and user.</p> <p>Cardiac collimator Compact multileaf collimator for cardiac angiography with rectangular collimator and wedge-shaped filter.</p> <ul style="list-style-type: none"> - Automatic synchronous rotation of detector and collimator unit to compensate image rotation in the different working positions of the gantry. - Manual rotation of the detector and collimator unit using the control right on the detector housing. - Five-step adaptive Cu pre-filtration (CAREfilter) to reduce the equivalent skin dose and improve radiation quality through dose saving for the soft radiation parts. Filter steps: 0.1; 0.2; 0.3; 0.6; 0.9 mm Cu. - Electronics unit with DIAMENTOR measurement chamber integrated in the collimator housing, for acquisition of the dose-area product and the calculated patient entry dose (CAREwatch).
	<p>Floor-mounted patient positioning table designed for angiographic examinations and interventions.</p> <ul style="list-style-type: none"> - Direct patient access from all sides, both through the swiveling table and large tabletop cantilever. - $\pm 15^\circ$ head up/head down positioning. - Iso-tilt functionality for maintaining the projection during table tilt along the patient axis. - Motorized, power-dependent table movement in longitudinal direction when the table is tilted (power-assisted control). - Electromechanical release of table swivel at the touch of a button at the table. - Telescopic foot with motor-driven height adjustment. - Max. patient weight 200 kg. Accessories weighing up to 40 kg can also be installed.
	Carbon fiber tabletop in narrow design with head-end recess and matching special foam mattress, for example for cardiological applications. Tabletop tapered in the thorax area for maximum freedom of C-arm angulation.
	As a result, two foot switches can be connected directly to the table. One foot switch is connected via cable, the other is wireless.
	<p>Color flat display The 56" or 60" display area represents a new dimension in medical image display. Using a fully integrated tableside control panel with 12 layout variants, all examination-relevant data are displayed on the same large area screen. The result is high levels of flexibility in displaying individual screen layouts.</p> <p>Data such as live, assist and reference images, <i>syngo</i> X Workplace, Sensis/recording systems, PACS, HIS/RIS,</p>

Description
<p>ultrasound, ECG, external video, endoscope, mapping systems, system and table geometry, system messages and dose information can be individually positioned and displayed on the Large Display, if connected.</p> <p>The extended Roadmap function is included, if DSA is available:</p> <ul style="list-style-type: none"> - During fluoroscopy (FL), the native live FL image is displayed, otherwise the LIH image (Last Image Hold). - During Roadmap/subtracted fluoroscopy, the native live FL image is displayed, otherwise the LIH image (Last Image Hold). - During DSA acquisition, the native live image is displayed, otherwise the native max fill image. <p>Contains the dual reference function:</p> <ul style="list-style-type: none"> - An additional, static reference image for parallel display of two reference images on the Large Display. <p>Important images for diagnostic purposes can be displayed to scale in their original size, less important non-diagnostic information can be displayed at a reduced size. The enlarged display can be selected individually via the display configurations.</p> <p>For the diagnostic color display in TFT technology, with high luminance and extended viewing angle, the gamma curve has been adapted particularly for gray scale display according to the CIE / DICOM recommendation.</p> <p>Technical specification for the display:</p> <ul style="list-style-type: none"> - Display size (W x H) 56 " 124,4 cm x 70 cm or 60 " 133 cm x 74.8 cm - Screen size 56" (142.2 cm). or 60 " 153 cm - Resolution: 3840 x 2160 (pixels); 8 megapixels at 4 x HD. - Color depth 16.7 10⁶ colors. - Guaranteed brightness for the entire service life: 300 cd/m² at a contrast ratio of 800:1. - Flicker-free and distortion-free image display. <p>Multi Display Manager The Multi Display Manager (MDM) receives the different video signals and processes this information for visualization on the Large Display. Up to 21 external video sources can be connected (max. 21 DVI-D or 15 DVI-R plus max. 6 analog). Other digital/analog combinations are possible, but the sum must not exceed 21 channels.</p> <p>Display ceiling-mounted stand The longitudinally mobile, swiveling, rotating, and height adjustable display suspension system (DCS extended) with extended working range contains a large 56" color flat display. All cables are integrated into the universal mounted DCS with double-articulated arm. The double-articulated arm of the "extended" display suspension system provides greater flexibility and a greater positioning range for the Large Display.</p> <p>Technical specification for the display ceiling support:</p> <ul style="list-style-type: none"> - Longitudinal travel range 315 cm. - Height adjustment range 75 cm. - Swivel range between the articulated joint and the suspension at the ceiling-mounted carriage ± 150 degrees. - Swivel range between the freely-suspended cantilever arm and the articulated joint ± 120 degrees. - Display swivel range 330°. <p>Bypass concept In case of error, such as controller failure, the Large Display switches automatically to bypass mode and emergency fluoroscopy is displayed on the Large Display.</p> <p>Backup concept The Large Display has a backup concept to ensure against power supply failure (2 separate power supplies for the left and right sides of the Large Display).</p>
<p>The Multi Display Manager (MDM) Medium receives various internal and external video signals and processes this information for presentation to scale on the Large Display (LD). Up to 18 external and internal video sources can be connected (max. 14 DVI-D and 4 analog (VGA) channels).</p>

Description

Important images for diagnostic purposes can be displayed to scale in their original size on the LD. Less important, non-diagnostic information can be displayed at a reduced size in the interpolation algorithm for image information integrated in the MDM.

An enlarged or reduced display can be selected individually via the display configurations at the touch screen (ECC). The MDM controller then takes over interpolation and adaptation of image size.

In waveform images with high resolution, such as for electrophysiological recording systems, the curves are displayed free of artifacts because of a special interpolation algorithm.

Using the connection kit, one DVI-D video signal of a unit is duplicated. One of these is connected to one of the DVI-D video inputs of the Siemens video signal distributor. The second video signal is available for use by a display, for example in the control room. Using fiber-optic cables ensures the galvanic isolation of the video source.

The inputs support a maximum resolution of 1920x1200.

It includes the following components:

- a video splitter
- A DVI to fiber-optic cable adapter
- A fiber-optic cable (36 meters)
- A fiber-optic cable to DVI adapter
- Two 5 volt power supplies for the adapters

Including:

- 3 x LD Input External Digital Kit 14417161:
A digital kit 14417161 includes:
1 x digital input and connection kit for an external digital DVI-D video signal including cable and DVI-D video splitter.
For digital video signals, DVI-D, HDMI, comprising a DVI-D video splitter for the external monitor and the external video signal. The video splitter is needed if there is no second analog video output on the external device.
All required DVI-D cables, fiber-optic cables, power supplies, adapter and power plugs, and labels are also included.
- 2 x LD Input External Analog Kit 14417131:
An analog kit 14417131 includes:
Analog input and connection kit for external analog video signals including cable and video splitter.
For analog video signals, VGA, BNC VGA, DVI-I, BAS, PAL, NTSC, comprising an analog VGA video splitter for the external monitor and the external video signal. The video splitter is needed if there is no second analog video output on the external device.
All required VGA cables, fiber-optic cables, a converter, power supplies, adapter and power plugs, and labels are also included.

* To display images from third-party video sources on the Large Display interfaces for external video signals, note the following requirements:

- The connection of third-party devices is only permissible if they meet the specifications of the LD interface.
- The connection of the LD interface to the LD controller must be performed by a Siemens service technician.
- The connection to the third-party device must always be performed by the technician of the third-party company or by the responsible on-site hospital technician.
- Siemens cannot assume any warranty for the connection of the third-party device with respect to the image quality and its suitability for diagnosis.
- For this reason, it is strongly recommended that the image quality tests prescribed by the third-party manufacturer are performed again prior to use. These tests can ensure that the required image quality is achieved.
- The system configurator is responsible for ensuring that the valid versions of the relevant standards are met.

Should you have any questions, please call the LD hotline: +49 (9191) 18-8099. In the USA, please call the local LD hotline.

zt	Description
	<p>For analog video signals with SXGA 1280 x 1024 or VGA 640 x 480 output (e.g. ultrasound), directly connectible at the examination table.</p> <p>Consisting of:</p> <ul style="list-style-type: none"> - a video separator and OTV-VGA splitter for the external analog video monitor signal - two HD 15 VGA cables, one 40 m and one 5 m in length - a VGA adapter cable for 5 x BNC, 0.6 m and 1 m in length - an adapter - an MDM container slide-in tray for attaching the components in the container <p>* To display images from third-party video sources on the Large Display interfaces for external video signals, note the following requirements:</p> <ul style="list-style-type: none"> - The connection of third-party devices is only permissible if they meet the specifications of the LD interface. - The connection of the LD interface to the LD controller must be performed by a Siemens service technician. - The connection to the third-party device must always be performed by the technician of the third-party company or by the responsible on-site hospital technician. - Siemens cannot assume any warranty for the connection of the third-party device with respect to the image quality and its suitability for diagnosis. - For this reason, it is strongly recommended that the image quality tests prescribed by the third-party manufacturer are performed again prior to use. These tests can ensure that the required image quality is achieved. - The system configurator is responsible for ensuring that the valid versions of the relevant standards are met. <p>Should you have any questions, please call the LD hotline: +49 (9191) 18-8099. In the USA, please call the local LD hotline.</p>
	<p>19" high-contrast b/w display for live image display, as well as syngo operation in the control room. Table design with black frame.</p> <p>Display in monochrome TFT technology with high luminance and extended viewing angle.</p> <ul style="list-style-type: none"> - 19" (48 cm) monitor. - Resolution: 1,280 x 1,024 (pixel). - Guaranteed brightness for the entire service life: 400 cd/m² at a contrast ratio of 500:1. - Flicker-free and distortion-free image display. - Ambient light sensor for optimum adaptation to the room brightness.
	<p>Scientific measuring program integrated in the imaging system for evaluation of the functionality of the left ventricle.</p> <ul style="list-style-type: none"> - Automated and manual contour detection. - Automatic end-diastole/end-systole detection. - Calculation of ejection fraction, volumes and indices (area, length and Simpson methods). - Centerline, radial and regional wall movement analyses - Automatic and manual calibration methods. - Distance and angle measurement.
	<p>Measuring program integrated in the imaging system for objective, precise and reproducible evaluation of vessels.</p> <ul style="list-style-type: none"> - Automated contour detection. - Determination of degree of stenosis. - Automatic and manual reference diameter determination. - Automatic and manual calibration methods. - Distance and angle measurement. <p>The vascular analysis allows precise quantification under sterile conditions, direct at table side with the touchscreen control. This speeds up the intervention and makes the procedure safer for the patient. The reports</p>

t	Description
	<p>can be easily stored in the patient folder for documentation and to show the correct analysis of dilatations etc. Especially to be used for vessel sizes between 0.5 mm and 50 mm.</p>
	<p>Scientific measuring program integrated in the imaging system for clinically validated, objective, accurate and reproducible evaluation of coronaries.</p> <ul style="list-style-type: none"> - Automated contour detection. - Determination of degree of stenosis. - Automatic and manual reference diameter determination. - Stenotic Flow Reserve - Automatic and manual calibration methods. - Distance and angle measurement. <p>QCA allows precise quantification under sterile conditions, direct at table side with the touchscreen control. This speeds up the intervention and makes the procedure safer for the patient. The reports can be easily stored in the patient folder for documentation and to show the correct analysis of dilatations etc. Especially to be used for vessel sizes between 0.5 mm and 7 mm.</p> <p>QCA (Quantitative Coronary Analysis) is based on the gold standard in coronary analysis: CAAS II (Cardiovascular Angiography Analysis System Mark II) from Pie Medical, Netherlands. The algorithms come from the Thorax Center of the Rotterdam Erasmus University. They are clinically validated and internationally recognized for scientific purposes (Multicentre Studies).</p>
	<p>IZ3D enables interactive 3D reconstruction and visualization of coronary segments, including bifurcations. IZ3D is especially suited for support in interventional cardiology; especially during stenting procedures.</p> <p>A three-dimensional coronary segment is reconstructed from at least two selected projections.</p> <p>Advantages and features of IZ3D</p> <p>In cardiac angiography three-dimensional information is used for diagnosis, therapy planning, and documentation within the scope of interventional procedures.</p> <ul style="list-style-type: none"> - Interventional length and distance measurement - Stenosis measurement. - Determination of diameter - Determination of bifurcation angle. - IZ3D control from the tableside. - Virtual planning of stent placement in a vessel segment. - Display of 3D image data in the examination room on the reference image monitor - IZ3D is fully integrated into the cath lab and does not need a separate workstation. <p>Especially to be used for vessel sizes between 0.5 mm and 7 mm.</p>
	<p>Optimized procedure workflow, especially during interventions is the result of the automap-function. A selected reference image displaying the needed medical information (e.g. before dilatation) is used as the basis for moving the system to the correlated position automatically. The intervention can be continued immediately without manually repositioning the patient. Vice versa, an already stored reference image for a dedicated system position is automatically displayed when automap is selected, making it easy to switch from one angulation to another with instantly available image information.</p>
	<p>Manual stand rotation for free positioning of system and table relative to each other, for example for the following additional work positions:</p> <ul style="list-style-type: none"> - Left-side patient access. - OR work, standby and park position. - Orthogonal system control, along patient longitudinal axis.
	<p>DICOM MWL (Modality Worklist): Import of patient/examination data from an external RIS/HIS patient management system.</p>

t	Description
	<p>Note concerning DICOM interface(s) For diagnostic purposes, only hardcopy cameras/laser printers explicitly approved for this system may be used.</p> <p>The description in the DICOM Conformance Statement downloadable from the Internet is exclusively binding for the functionality of the DICOM interface(s).</p> <p>Functionalities across system borders with/between partner systems require explicit validation, since the interpretation of the interface by the partner/target system is not part of the product's responsibility.</p> <p>A modification of the interface that might be required is not included in the offer; e.g. for the rare case, that available configurations are not sufficient.</p> <p>With regard to expenses for interface configurations that might be required, the agreements on maintenance/service of the product apply.</p>
	<p>DICOM MPPS (Modality Performed Procedure Step) Sending of dose data, patient data, and examination data to an external RIS/HIS patient management system. Sent in MPPS:</p> <ul style="list-style-type: none"> - Total dose-area product - Number of exposures - kV per image (DICOM Exposure Dose Sequence) - ms per image - mA per image <p>Note concerning DICOM interface(s) For diagnostic purposes, only hardcopy cameras/laser printers explicitly approved for this system may be used.</p> <p>The description in the DICOM Conformance Statement downloadable from the Internet is exclusively binding for the functionality of the DICOM interface(s).</p> <p>Functionalities across system borders with/between partner systems require explicit validation, since the interpretation of the interface by the partner/target system is not part of the product's responsibility.</p> <p>A modification of the interface that might be required is not included in the offer; e.g. for the rare case, that available configurations are not sufficient.</p> <p>With regard to expenses for interface configurations that might be required, the agreements on maintenance/service of the product apply.</p>
	<p>DICOM Print: printing of images by means of a virtual filmsheet on a DICOM laser camera. Selecting "Auto-Print" automatically forwards the images stored in the virtual filmsheet to the laser camera. This optimizes the workflow, eliminating the need for user interaction. In addition, a specific layout can be configured on the virtual filmsheet, which the user can review and edit on the monitor at any time. As a result, printing is only required after the layout has been optimized on the monitor, saving time and costs.</p> <p>Note concerning DICOM interface(s) For diagnostic purposes, only hardcopy cameras/laser printers explicitly approved for this system may be used.</p> <p>The description in the DICOM Conformance Statement downloadable from the Internet is exclusively binding for the functionality of the DICOM interface(s).</p> <p>Functionalities across system borders with/between partner systems require explicit validation, since the interpretation of the interface by the partner/target system is not part of the product's responsibility.</p> <p>A modification of the interface that might be required is not included in the offer; e.g. for the rare case, that available configurations are not sufficient.</p> <p>With regard to expenses for interface configurations that might be required, the agreements on maintenance/service of the product apply.</p>
t	<p>In order to be able to move the image receiver (I.I. or flat detector) as closely as possible to the object during cardiological examinations, the patient's arms must be held in a specific position above his head. With this positioning aid the patient can hold on to the hand grips, his arms resting comfortably on the supports.</p>

t	Description
t	<p>The stainless steel hand grips and the radiolucent support are mounted to the accessory rails of the head-end holder.</p>
	<p>The lower body radiation protection can be attached to the accessory rails either on the right or on the left side of the patient positioning table. It consists of the following independent shielding units:</p> <ul style="list-style-type: none"> - A basic unit shielding the area between accessory rails and the floor. It is flexible and can be adapted to the examiner's preferences. - One LB radiation protection pivot swivel element that can move out of the way during collisions with the tube and still retain its protective function. - Two clip-on units pointing upwards from the upper edge of the basic unit with a length of 57 cm and 27 cm. <p>The scattered radiation shielding units can be attached to the basic unit in an overlapping and fan-shaped way to allow closed, adapted scattered radiation protection even in the lower thorax area. The maximum load of the accessory rails is 40 kg, the weight of the attached scattered radiation protection is 8 kg.</p>
	<p>Radiation protection attached via a ceiling-mounted, mobile stand for protection against scattered radiation; inc. 4 m ceiling rail.</p> <ul style="list-style-type: none"> - Swivable and rotatable around the fixing point, range of rotation 360°. - Counter-balanced, height-adjustable support arm. - Acrylic glass with Pb equivalent of 0.5 eq (w x h: 61 cm x 76 cm).
	<p>Keyboard for easy operation of <i>syngo</i> (browser, viewer, filming). There are special keys for windowing, scrolling, printing, marking and network communication.</p>
	<p>Communication / Intercom system for communication between examination room and control room, with additional footswitch for conversation selection in the examination room. Microphone and control box on the console in the control room. With adaptive acoustic filter for background noise suppression in the examination room. Microphone in the examination room installed on the ceiling.</p>
	<p>For Artis tabletops, the two arm holders help to laterally position the arms comfortably along the patient's body. They are slid laterally underneath the mattress, level with arms, and fixed by the patient's body weight. The patient's arms can be immobilized with commercially available fixing straps. Two pairs of arm holders of different length and height (matching the mattress height) are supplied, that are suitable both for thick and thin mattresses.</p>
	<p>Radiation protection attached via a ceiling-mounted, mobile stand for protection against scattered radiation; inc. 4 m ceiling rail.</p> <ul style="list-style-type: none"> - Swivable and rotatable around the fixing point, range of rotation 360°. - Counter-balanced, height-adjustable support arm. - Acrylic glass with Pb equivalent of 0.5 eq (w x h: 61 cm x 76 cm).
	<p>The 3-spot OR lamp is additionally attached to the ceiling-mounted stand of the mobile radiation protection and is thus fully integrated in the ceiling-mounted radiation protection system of the AXIOM Artis family. The extremely high luminance is of special advantage for illuminating deep lesions, whereas the luminance would not be sufficient with a single-spot OR lamp.</p> <ul style="list-style-type: none"> - Luminance: 100 000 Lux (9,300 fc) for 100 cm distance - working distance: 70 to 140 cm - color rendering index Ra (gen.): 96 - color temperature: 4,300 Kelvin - focusable spot size: 17 to 28 cm - 3 halogen lamps: 22.8 V/50 W

Description
<p>Power connection OR lamp 115 V.</p>
<p>This UPS is recommended when protection and uninterruptible power is required for the C-arm and table. Emergency fluoroscopy is not available with this UPS. If emergency fluoroscopy is required, the 9390 - 160 kVA UPS is recommended for the full system. One UPS per lab.</p> <p>Operation:</p> <ul style="list-style-type: none"> - Since this UPS is working completely uninterrupted, a power failure is observed when no radiation is available and the display shows "No X-ray please wait". - The Emergency power lamp (red) will light on the power display during a power failure. All stand movements are possible and the image system functions are protected against data loss. Guaranteed back up time: 10 min. - Restoring of hospital's main power supply is indicated when the generator boots again (also green Hospital power lamp lights). Full exposures are available after apx. 75 seconds. <p>Includes UPS, battery, maintenance bypass panel, and one year on-site parts and labor coverage (24x7) by Eaton Powerware.</p> <p>Additional seismic brackets are required to make this system OSHPD approved.</p>
<p>NT60010835 Interstate Mat Corporation Anti-fatigue Mat</p> <p>Industrial-grade anti-fatigue floor mat that provides comfort and durability. As a high-quality product designed to fight fatigue, it provides support for tired, aching feet, legs and back. Beveled edges for safety. Size 3'x5'.</p>
<p>Codonics Horizon SF Imager is a small format film and paper, color and grayscale imager. Media sizes include: 8" x 10" film in blue and clear, and A and A4 color and grayscale paper. Supports 2 DICOM connections and PostScript.</p> <p>Media included: 100 sheets of A size CV paper (with color ribbon), 80 sheets of A size DV paper, and 100 sheets of 8x10 blue film.</p> <p>Includes one year warranty with 24-hour swap service through Codonics. Installation by Codonics is available at an additional cost. Data sheet is available upon request.</p>
<p>The Arterion Mark 7 Overhead counterpoise contrast medium injector allows for the remote installation of the system power supply and installation of the injector head onto a ceiling mounted arm.</p> <p>The injector system includes:</p> <ul style="list-style-type: none"> - Power supply and injector head with corresponding cabling - A desk mounted user control console with large touch screen - Note: The appropriate Overhead Counterpoise System (OCS) must be ordered separately <p>Functions</p> <p>Pressure limitation:</p> <ul style="list-style-type: none"> - for 150 ml syringes 689 to 8273 kPa, corresponds to 100 to 1200 psi. . <p>Flow rates for 150 ml syringes:</p> <ul style="list-style-type: none"> - 0.1 to 45 ml/s in increments of 0.1 ml/s - 0.1 to 59.9 ml/min in increments of 0.1 ml/min - rise/fall: 0 to 9.9 s in increments of 0.1 seconds

Description

Release delay for injection or radiation:

- 0 to 99.9 s in increments of 0.1 s.

Adjustable volume for 150 ml syringes:

- 1 ml to the max. syringe capacity in increments of 1 ml.

Fill rate:

- Variable syringe filling speed 1-20ml/s.

Injection protocols:

- Up to 40 injection protocols possible.

Parameters currently displayed on the touch screen display and on the head display:

- Injection speed
- Injection volume
- Remaining volume
- Injection duration
- Applied pressure

Contrast medium heating:

- Nominal 35°C (95°F)+5°C (9°F)

Injection data memory

- Up to 50 injection data items stored

Included in the scope of delivery

- Injector standard configuration 150 ml
- SIEMENS interface cable
- Operator Manual
- Service manual (English).

Power supply

200 V to 250 V; 50/60 Hz.

Portegra 2 - Track Ceiling Mount - 80 cm post

Existing System must be de-installed by June 30, 2014.

AX Elevate is the „managed system upgrade program“ of Siemens, which supports you replacing your existing system to a new system and which therefore enables you to benefit of modern technologies and functionalities. The old system will be bought back by Siemens.
AX Elevate is part of our comprehensive customer care program, Life.