



1. BRIDGING: (CONT. THRU STUD PUNCHOUTS)
 - A. WALLS UP TO 10'-0" HIGH:
ONE ROW OF BRIDGING AT
MIDHEIGHT, TYP.
 - B. WALLS OVER 10'-0" HIGH:
BRIDGING AT 5'-0" MAX, TYP.
2. USE ALTERNATE DETAIL 14/- WHERE
REQUIRED PER STUD MANUF.
3. OMIT BRIDGING AT SHEAR WALLS WITH
PLYWOOD ON BOTH SIDES.

KING STUD SCHEDULE		
	OPENING SIZE	
	≤ 3'-0"	≤ 5'-0"
NUMBER OF FIELD STUDS	1	2

1. SEE 4/S-512 FOR L-HEADER ASSEMBLY.
2. USE OF L-HEADER AND CONNECTION TO KING STUD AT INTERIOR WALLS ACCEPTABLE UNLESS BOX HEADER IS SPECIFICALLY REFERENCED.

KING STUD SCHEDULE		
	OPENING SIZE	
	≤ 4'-0"	≤ 6'-0"
NUMBER OF FIELD STUDS	2	3

1. SEE 1/S-512 FOR BOX HEADER ASSEMBLY.
2. USE OF BOX HEADER AS AN ALTERNATE TO L-HEADER IS ACCEPTABLE.
3. SEE 3/S-512 FOR BOX HEADER CONNECTION.



9 HOLDOWN POST/
BUILT-UP STUD/BEAM MEMBER
N.T.S.



3 BEAM/BOX HEADER CONNECTION
TO WALL OR POST
N.T.S.

ARCHITECT/ENGINEERS: