

0

three inches = one foot

1

one and one half inches = one foot

2

one inch = one foot

3

three quarters inch = one foot

4

one half inch = one foot

5

three eighths inch = one foot

6

one eighth inch = one foot

7

one quarter inch = one foot

8

one eighth inch = one foot

9

one quarter inch = one foot

10

one eighth inch = one foot

11

one quarter inch = one foot

12

one eighth inch = one foot

13

one quarter inch = one foot

14

one eighth inch = one foot

15

one quarter inch = one foot

16

one eighth inch = one foot

17

one quarter inch = one foot

18

one eighth inch = one foot

19

one quarter inch = one foot

20

one eighth inch = one foot

21

one quarter inch = one foot

22

one eighth inch = one foot

23

one quarter inch = one foot

24

one eighth inch = one foot

25

one quarter inch = one foot

26

one eighth inch = one foot

27

one quarter inch = one foot

28

one eighth inch = one foot

29

one quarter inch = one foot

30

one eighth inch = one foot

31

one quarter inch = one foot

32

one eighth inch = one foot

33

one quarter inch = one foot

34

one eighth inch = one foot

35

one quarter inch = one foot

36

one eighth inch = one foot

37

one quarter inch = one foot

38

one eighth inch = one foot

39

one quarter inch = one foot

40

one eighth inch = one foot

41

one quarter inch = one foot

42

one eighth inch = one foot

43

one quarter inch = one foot

44

one eighth inch = one foot

45

one quarter inch = one foot

46

one eighth inch = one foot

47

one quarter inch = one foot

48

one eighth inch = one foot

49

one quarter inch = one foot

50

one eighth inch = one foot

51

one quarter inch = one foot

52

one eighth inch = one foot

53

one quarter inch = one foot

54

one eighth inch = one foot

55

one quarter inch = one foot

56

one eighth inch = one foot

57

one quarter inch = one foot

58

one eighth inch = one foot

59

one quarter inch = one foot

60

one eighth inch = one foot

61

one quarter inch = one foot

62

one eighth inch = one foot

63

one quarter inch = one foot

64

one eighth inch = one foot

65

one quarter inch = one foot

66

one eighth inch = one foot

67

one quarter inch = one foot

68

one eighth inch = one foot

69

one quarter inch = one foot

70

one eighth inch = one foot

71

one quarter inch = one foot

72

one eighth inch = one foot

73

one quarter inch = one foot

74

one eighth inch = one foot

75

one quarter inch = one foot

76

one eighth inch = one foot

77

one quarter inch = one foot

78

one eighth inch = one foot

79

one quarter inch = one foot

80

one eighth inch = one foot

81

one quarter inch = one foot

82

one eighth inch = one foot

83

one quarter inch = one foot

84

one eighth inch = one foot

85

one quarter inch = one foot

86

one eighth inch = one foot

87

one quarter inch = one foot

88

one eighth inch = one foot

89

one quarter inch = one foot

90

one eighth inch = one foot

91

one quarter inch = one foot

92

one eighth inch = one foot

93

one quarter inch = one foot

94

one eighth inch = one foot

95

one quarter inch = one foot

96

one eighth inch = one foot

97

one quarter inch = one foot

98

one eighth inch = one foot

99

one quarter inch = one foot

100

one eighth inch = one foot

FAN COIL SCHEDULE																					
NUMBER	37-FC-1.6	37-FC-1.7	37-FC-1.8	37-FC-1.9	37-FC-1.10	37-FC-1.11	37-FC-1.12	37-FC-1.13	37-FC-1.14	37-FC-1.15	37-FC-1.16	37-FC-1.17	37-FC-1.18 THRU 37-FC-1.21	37-FC-1.22	37-FC-1.23	37-FC-2.6	37-FC-2.7	37-FC-2.8	37-FC-2.9	37-FC-2.10	37-FC-2.11
TYPE	CONCEALED CEILING	CONCEALED CEILING	CONCEALED CEILING	CONCEALED CEILING	CONCEALED CEILING	CEILING CASSETTE	CONCEALED CEILING	CEILING CASSETTE	CONCEALED CEILING	CONCEALED CEILING	CONCEALED CEILING	CEILING CASSETTE	CEILING CASSETTE	CEILING CASSETTE	WALL MOUNTED	CONCEALED CEILING	WALL MOUNTED	CONCEALED CEILING	CONCEALED CEILING	CONCEALED CEILING	CONCEALED CEILING
MOUNTING	ATTIC	ATTIC	ATTIC	ATTIC	ATTIC	1-BAR	ATTIC	1-BAR	ATTIC	ATTIC	ATTIC	1-BAR	1-BAR	1-BAR	208/1	208/1	208/1	208/1	208/1	208/1	208/1
VOLTS/PHASE	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1
FLA/MCA	-/0.6	-/0.6	-/3.4	-/9.5	-/10.7	-/0.3	-/1.6	-/0.3	-/0.6	-/0.6	-/0.3	-/0.3	-/0.3	-/0.3	-/0.3	-/1.6	-/0.3	-/2.3	-/0.6	-/2.9	-/9.5
M.C.P.	15	15	33.1	54.9	73.4	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15
HSPF/SEER	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE	10.6/17.6	-/SEE NOTE	10.6/17.6	-/SEE NOTE	-/SEE NOTE	-/SEE NOTE
B WATTS																					
L SUPPLY CFM/SPEED	315/HI	335/HI	1370/HI	2040/HI	2540/HI	460/HI	630/HI	460/HI	335/HI	315/HI	1370/HI	460/HI	460/HI	460/HI	635/HI	630/HI	635/HI	880/HI	315/HI	1370/HI	2040/HI
O E.S.P. (IN. WC.)	0.4	0.2	0.4	0.4	0.4	0	0.4	0	0.2	0.4	0.4	0	0	0	0	0	0	0	0.4	0.4	0.4
W RPM																					
F DRIVE	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT
R MIN. O.A. (CFM)	100	0	105	80	525	60	110	30	90	45	385	30	25	30	0	95	0	95	40	250	220
C TOTAL CAP. (MBH)	7.2	11.6	41.6	58.4	89.9	9.6	17.5	10.2	11.9	7.2	45.8	8.5	8.2	8.8	18.0	17.4	18.0	28.8	7.3	42.4	61.3
O SENS. CAP. (MBH)	6.7	7.3	33.1	54.9	84.2	14.3	22.9	14.3	9.7	6.1	39.6	8.0	8.1	8.1	18.0	14.0	18.0	25.7	6.7	37.8	56.7
O E.A. DB/WB (°F)	81.8/66.1	75.7/46.1	77.4/63.2	76.9/61.6	81.5/65.2	78.0/68.7	80.4/66.3	78.3/62.9	82.9/66.8	79.5/66.2	83.5/65.7	77.5/64.2	77.1/63.3	77.7/65.0	75.8/46.1	79.8/66.1	75.8/46.1	83.3/65.9	79.4/66.6	82.0/63.7	79.2/62.8
L I.A. DB/WB (°F)	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5	103.5
N COIL TYPE	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.	DIRECT EXP.
G REFRIGERANT	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A
H HEATING CAP. (MBH)	9.8	13.5	57.8	84.2	125.9	11.2	22.9	14.3	15.2	9.4	62.9	11.1	11.0	11.1	22.2	22.2	22.2	38.9	9.2	62.3	88.1
I E.A. DB (°F)	60.4	69.7	66.1	67.8	61.3	66.2	62.8	66.3	69.1	64.3	58.5	66.7	67.1	66.8	—	64.2	—	62.9	65.0	62.5	65.2
A —	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
T	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13	2" MERV 13
SERVICE	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS	SEE PLANS
ACCESSORIES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES	SEE NOTES
OPER. WT. (LBS.)	60	60	110	330	330	60	90	60	60	60	110	60	60	60	40	90	40	90	60	110	330
MANUFACTURER	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN	DAIKIN
MODEL	FXM070PVJU	FXM012PVJU	FXM048PVJU	FXM072MVJU	FXM096MVJU	FXF009PVJU	FXM018PVJU	FXF012PVJU	FXM012PVJU	FXM021PVJU	FXM048PVJU	FXF009PVJU	FXF009PVJU	FXF009PVJU	FXF009PVJU	FXM018PVJU	FXM018PVJU	FXM030PVJU	FXM072PVJU	FXM048PVJU	FXM072MVJU
NOTES: 1. PROVIDE FACTORY TEMPERATURE SENSOR WITH COMMUNICATION TO MAIN CONTROLLER AND CONNECTION TO EMS. 2. PROVIDE FILTER DIFFERENTIAL PRESSURE SWITCH AND CONNECT TO EMS. 3. PROVIDE FACTORY CONDENSATE PUMP CAPABLE OF LIFTING CONDENSATE A MINIMUM OF 24". 4. PROVIDE REFRIGERANT LINE SIZE AND CONNECTIONS DIAGRAMS PRIOR TO INSTALLATION. 5. FC/ODU SYSTEM SHALL BE EQUAL TO SEER OF 17 AND COP OF 3.3 OR BETTER. 6. FC-1.7, FC-1.23 AND FC-2.7 SHALL BE SET TO COOL AT TEMPERATURES ABOVE 85°F, AND HEATING FUNCTION SHALL BE DISABLED. 7. UNITS MOUNTED ABOVE CEILING SHALL BE MOUNTED A MAXIMUM OF 12" ABOVE FINISHED CEILING. CEILING SHALL BE TAGGED WITH LABEL SHOWING ARROW AND UNIT NUMBER TO SHOW WHICH CEILING TILE IS TO BE REMOVED FOR UNIT ACCESS. CEILING WIRES FOR THIS TILE SHALL BE ANGLED SLIGHTLY OUTWARD FROM REMOVABLE PANEL FOR EASE OF ACCESS. PROVIDE ACCESS PANELS AS REQUIRED IN HARD CEILINGS. 8. CONTRACTOR SHALL COMPLETE MANUFACTURERS INSTALLATION TRAINING PRIOR TO INSTALLING ANY SPLIT SYSTEM EQUIPMENT AND MANUFACTURER SHALL PROVIDE FACTORY OPERATION AND MAINTENANCE TRAINING FOR (2) OWNER REPRESENTATIVES. 9. PROVIDE A CEILING OR DUCT SMOKE DETECTOR IN THE SUPPLY AIR DUCT TO SHUT OFF THE UNIT POWER UPON DETECTION OF SMOKE. WIRING BY ELECT. MECH. CONTRACTOR TO PROVIDE DETECTOR AND INSTALL IN DUCT. INSTALL IN STRICT ACCORDANCE WITH CURRENT CODES. 10. EQUAL UNITS MANUFACTURED BY TRANE OR MITSUBISHI SHALL BE ACCEPTABLE. 11. UNITS SHALL BE PROVIDED WITH SENSOR IN CONDENSATE DRAIN PAN THAT SHUTS OFF UNIT AND SENDS AN ALARM TO THE MAIN CONTROL PANEL WHEN CONDENSATE LEVEL IS TOO HIGH. NO SECONDARY DRAIN IS REQUIRED. 12. COORDINATE WITH GENERAL CONTRACTOR TO PROVIDE ACCESS IN ABOVE CEILING WALL FRAMING AS REQUIRED. 13. MOTOR ENCLOSURES AND EFFICIENCIES SHALL MEET OR EXCEED SPEC. SECT. 23 05 12, 2.1 MOTORS. 14. UNITS SHALL BE PROVIDED WITH (3) SETS OF FILTERS: (1) MERV 8 FOR DURING CONSTRUCTION - UNIT NOT RUNNING, (1) MERV 13 FOR LEED PURGE AND (1) MERV 13 FOR FINAL OCCUPANCY. UNIT SHALL BE PROVIDED WITH FACTORY FIELD INSTALLED MERV 13 FILTER KIT. SEE SPEC. SECT. 01 81 11 FOR ADDITIONAL FLUSH OUT REQUIREMENTS. 15. ALL UNITS SHALL BE DESIGNED FOR LESS THAN NC-35 SOUND RATING. 16. FC-1.7, 1.23 AND 2.7 SHALL BE ON EMERGENCY POWER. 17. FC-1.23 & 2.7 IS POWERED THRU OUTDOOR UNIT. 18. FC-1.10, 1.12 & 1.14 SHALL HAVE CO2 SENSOR LOCATED NEXT TO TEMP. SENSOR AND SEND ALARM THRU EMS IF CO2 LEVEL RISES ABOVE 1000 PPM. 19. FC-1.8, 1.10, 2.8 & 2.10 SHALL HAVE HUMIDITY SENSOR LOCATED NEXT TO TEMP. SENSOR TO CONTROL WATER VAPOR PRESSURE TO 0.277 PSI OR BELOW AT STANDARD PRESSURE.																					

KITCHEN HOOD	
NUMBER	37-KH-1.1
TYPE	DUCTED
AMPS	5.0
VOLTS/PHASE	120/1
CFM	300
SIZE	30"
SERVICE	SEE PLAN
MANUFACTURER	BROAN
MODEL	Q53
NOTES: 1. 7" DIA. DUCT CONNECTION. 2. PROVIDE APPROVED ROOF CAP AND FLASHING ASSEMBLY. 3. PROVIDE BACKDRAFT DAMPER. 4. INSTALL TO PROVIDE 30" CLEARANCE ABOVE COOKTOP PER C.M.C. 5. OWNER TO APPROVE MODEL AND COLOR PRIOR TO ORDERING & INSTALLATION. 6. 4-SPEED FAN WITH BOOST MODE AND HEAT SENSOR.	

COOLING TOWER SCHEDULE		
NUMBER	37-CT-1	37-CT-2
CFM	11700	87
OPM	87	87
EWI (°F)	95.0	95.0
LWT (°F)	85.0	85.0
DESIGN WET BULB (°F)	78	73
HORSE POWER	5	5
VOLTS/PHASE	460/3	460/3
MANUFACTURER AND MODEL (BASE DESIGN)	RECOLD JWL-25A	RECOLD JWL-25A
OPERATING WT. (LBS.)	3000	3000
NOTES: 1. PROVIDE VFD'S ON FAN MOTORS. 2. PROVIDE SPRING ISOLATION SYSTEM WITH ENGINEER CALCS FOR ATTACHMENT TO PLATFORM. 3. PROVIDE AUTOMATIC CHEMICAL FEED SYSTEM. 4. PROVIDE A WATER METER ON THE CONDENSER WATER & TOWER MAKE-UP LINE AND CONNECT TO EMS.		

PUMP SCHEDULE		
NUMBER	37-P-1	37-P-2
TYPE	CENTRIFUGAL	CENTRIFUGAL
MOUNTING	VERT. IN-LINE	VERT. IN-LINE
HORSEPOWER/BHP	3.0/1.92	3.0/1.92
VOLTS/PHASE	460/3	460/3
RPM	2977	2977
GPM/TDH (FT. WC.)	87/50	87/50
SERVICE	MAIN DIST.	MAIN DIST.
OPER. WT. (LBS.)	240	240
MANUFACTURER	ARMSTRONG	ARMSTRONG
MODEL	4300-0206-003.0	4300-0206-003.0
NOTES: 1. PROVIDE BUILT-IN VARIABLE FREQUENCY DRIVES (VFD) FOR PUMPS IN WEATHER TIGHT ENCLOSURE, REMOTE MOUNT ON RACK, SEE SHEET MH230 FOR LOCATION. 2. PROVIDE TEFC AND PREMIUM EFFICIENCY MOTORS.		

ENERGY RECOVERY VENTILATOR		
NUMBER	37-ERV-1	37-ERV-2
USE	SEE PLAN	SEE PLAN
VOLTS/PHASE	460/3	208/1
HP (OA FAN/EA FAN)	1.5/1.0	0.5/0.5
BHP (OA FAN/EA FAN)	1.46/0.89	0.42/0.19
EFF. (SA/EA)	66.4/76.2	63.1/84.4
MCA/MAX. COP	6.6/15	12.8/15
CFM (OA/EA)	2065/1800	870/650
ESP IN. WC. (OA/EA)	1.0/0.75	1.0/0.75
FILTER SIZE (IN.)	—	—
FILTER TYPE	MERV 13	MERV 13
ACCESSORIES	SEE NOTES	SEE NOTES
OPER. WT. (LBS.)	950	330
MANUFACTURER	GREENHECK	GREENHECK
MODEL	ERVE-20-30H	ERVE-10-20H
NOTES: 1. PROVIDE FACTORY OA AND EXH. AIR FILTERS. 2. INTERLOCK ERV WITH ODU. ERV SHALL BE SET TO RUN WHEN ODU IS ON. 3. MOTOR ENCLOSURES AND EFFICIENCIES SHALL MEET OR EXCEED SPEC. SECT. 23 05 12, 2.1 MOTORS. 4. PROVIDE A DUCT SMOKE DETECTOR IN THE SUPPLY AIR DUCT TO SHUT OFF THE UNIT POWER UPON DETECTION OF SMOKE. WIRING BY ELECT. MECH. CONTRACTOR TO PROVIDE DETECTOR AND INSTALL IN DUCT. INSTALL IN STRICT ACCORDANCE WITH CURRENT CODES. 5. PROVIDE OUTSIDE AIR SENSOR TO MONITOR QUANTITY OF AIR FLOW AND CONNECT TO EMS. 6. PROVIDE MANUFACTURER PRE-SLOPED ROOF CURB (MIN. 16" HIGH) FOR 1/2" PER FOOT SLOPED ROOF. 7. UNITS SHALL BE PROVIDED WITH (3) SETS OF FILTERS: (1) MERV 8 FOR DURING CONSTRUCTION - UNIT NOT RUNNING, (1) MERV 13 FOR 2-WEEK PURGE AND (1) MERV 13 FOR FINAL OCCUPANCY.		

AIR DISTRIBUTION SCHEDULE		
SYMBOL	TYPE	DESCRIPTION
A	CEILING SUPPLY	MODULAR CORE DIFFUSER WITH FRAME FOR LAY-IN T-BAR CEILING, FLUSH FACE MOUNTING. TITUS MODEL MCD-3
B	FILTER RETURN	SINGLE DEFLECTION 3/4" BLADE SPACING, STEEL CONSTRUCTION, 2" THICK FILTERS FOR T-BAR MOUNTING. PROVIDE 20"x20" FILTERS FOR USE IN 24"x24" T-BAR FRAME. TITUS MODEL 350RLF2-3.
C	CEILING SUPPLY	MODULAR CORE DIFFUSER WITH FRAME FOR SURFACE FLUSH FACE MOUNTING. TITUS MODEL MCD-1.
D	CEILING RETURN/EXHAUST	1/2X1/2X1/2 EGGCORE GRILLE, STEEL CONSTRUCTION WITH FRAME FOR SURFACE FLUSH FACE MOUNTING. TITUS MODEL 50F-1.
E	FILTER RETURN	SINGLE DEFLECTION 3/4" BLADE SPACING, STEEL CONSTRUCTION, 2" THICK FILTERS FOR SURFACE MOUNTING. PROVIDE 20"x20" FILTERS. TITUS MODEL 350RLF2-1.
F	SIDEWALL SUPPLY/EXHAUST	DOUBLE DEFLECTION LOUVERED FACE, 1/2" SPACING, 5' DOWN FRONT BLADES. TITUS MODEL 1700.
G	CEILING EXHAUST	PERFORATED FACE GRILLE WITH FRAME FOR T-BAR CEILING FLUSH FACE MOUNTING. TITUS MODEL PAR-3
NOTES: 1. EQUIVALENT MODELS OF KRUEGER, TITUS, PRICE, OR J&J ARE ACCEPTABLE. REFER TO THE FLOOR PLANS FOR NECK SIZE, CFM, AIR DIFFUSION PATTERN AND FIRE DAMPER, IF REQUIRED. 2. PROVIDE AIR CONTROL GRID FOR TYPE 'A' & 'C' CEILING SUPPLY DIFFUSERS SET AT 90'. 3. PAINT PAINT BLACK BEHIND FACE OF ALL GRILLES. 4. ALL GRILLES ARE SELECTED AT LESS THAN NC-20 SOUND RATING.		

CONDENSING UNIT SCHEDULE				
NUMBER	37-CU-1.1	37-CU-1.2	37-CU-1.3	37-CU-2.1
TYPE	WATER COOLED HEAT RECOVERY	WATER COOLED HEAT RECOVERY	AIR COOLED COOLING ONLY	WATER COOLED HEAT RECOVERY
VOLTS/PHASE	460/3	460/3	208/1	460/3
RATED LOAD AMPS	(2) 7.0	(3) 5.3	—	(3) 5.3
MIN. CIRCUIT AMPS	(2) 10.2	(3) 10.2	16.5	(3) 10.2
M.C.P.	(2) 15	(3) 15	20	(3) 15