

Salient Characteristics

POWER DRIVE PATIENT STRETCHERS

- A. DESCRIPTION: The Agency requires four patient stretchers with a “Four-wheel, center-locking brake system with dual end activators” and “dual side-mounted foot control hydraulics with uni-lower pedal.”

MUST MEET OR EXCEED THESE SALIENT CHARACTERISTICS:

- The stretcher must be **electric**.
- The stretcher must have a “Thermoformed ABS base with extra capacity storage tray.”
- The stretcher must have a “700 lb Weight Capacity.”
- The stretcher must have a “30 inch (76 cm) wide patient surface” with a 3-inch mattress.
- The stretcher must have a “23 inch low height.”
- The stretcher must have an “Integrated utility tray.”
- The stretcher must have a “Litter- mounted oxygen bottle holder” with gliding side rails.
- The stretcher must have “4 integrated IV receptacles.”
- The stretcher must have integrated bumpers.
- The stretcher must have “ +/- Trendelenburg.”
- The stretcher must have “8-inch Omni Surface™ Casters with integrated wheel covers.”
- The stretcher must have a Powered backrest with Lift Assist manual functionality.
- The stretcher must have a “Powered Knee Gatch” with quick release lowering.
- The stretcher must have a “Retractable Cord Reel.”
- The stretcher must have “Foot end” patient lockout controls.