

XR PORT RAD, VAMC LOUISVILLE, KY

PO# 603-B40029

Item	CAT #	QTY	Description
1		1	DRX Revolution
		1	DRX-Revolution Mobile X-Ray System Carestream's innovative mobile X-ray room on wheels. The DRX-Revolution offers bins for gloves, paperwork, markers, bags and a lockable storage space for the detector. The collapsible column allows increased visibility and safety when driving the system. The tube arm can reach over 53 in (135 cm) to accommodate larger beds and crowded rooms while the system has 32 kW of power for shorter exposure times and more flexible technique selection. Dual, independent drive motors provide easy maneuverability and a maximum dirve speed up to 3.5 m/h (5.6 km/h). An integrated proximity badge reader automatically logs the operator into the software and displays the patient worklist. Two touch-screen displays provide dual work zones with a 19 in. main monitor and 8 in. tube head monitor that allow the user to: <ul style="list-style-type: none">• display the patient worklist• review prior images (optional software)• copy or change technique• accept or reject images Other features include: <ul style="list-style-type: none">• Integrated 1D barcode reader• 2 integrated battery chargers for detector batteries

Item	CAT #	QTY	Description	List Unit	Govt.	Govt. Unit	Ext. Net
			<ul style="list-style-type: none"> • Integrated storage bins for 1 DRX-1 detector, 1 2530C detector, 1 portable grid holder or grid alignment device • Wired exposure switch • Direct access to RIS/PACs <p>X-Ray Generator:</p> <ul style="list-style-type: none"> • Maximum Power Output 32kW • Vp Range 40 to 150 kVp • mAs Range 0.1 to 320 mAs X-RAY Tube: <ul style="list-style-type: none"> • Focal Spot Size: 0.6 mm / 1.2 mm • Target Angle: 14 degrees • Anode Heat Capacity: 300 kHU (212 kJ) Tube Head Movement: <ul style="list-style-type: none"> • Maximum SID to Floor: 2022 mm (79.6 in.) • Minimum SID to Floor: 683 mm (26.9 in.) • Tube Arm Reach: 1351 mm (53.2 in.) • Column Rotation Range: +/- 270 degrees • Tube Rotation: +180 degrees CW/-135 degrees CCW • Tube Tilt: -10 to +90 degrees • Collimator Rotation Range: +/- 90 degrees Physical Characteristics: <ul style="list-style-type: none"> • Weight: 575 kg (1268 lbs) • Height (column collapsed): 1295 mm (51.0 in.) • Height (column extended): 1956 mm (77.0 in.) • Width: 576 mm (22.7 in.) • Length: 1219 mm (48.0 in.) 				

Item	CAT #	QTY	Description	List Unit	Govt.	Govt. Unit	Ext. Net
		1	<p>EVP Plus Imaging Processing Software</p> <p>Provides highly automated, state-of-the-art image processing. Uses multi-frequency image processing to increase latitude while preserving detail contrast in both over-penetrated and under-penetrated areas. Automatically processes and delivers diagnostic quality images to PACs based on look preference that can be uniquely specified by each site. Includes grid line suppression that prevents aliasing artifacts and application of a collimator mask. Five independent controls are available for the user for image adjustments in an intuitive user interface.</p>				
		1	<p>IHE Schedule Workflow Software</p> <p>Automatically notifies the HIS/RIS about the status of the exams. Includes DICOM Modality Performed Procedure Step (MPPS) that can send exposure Information including DAP values (if installed) to the HIS/RIS.</p>				
		1	<p>Modality Worklist Software</p> <p>Facilitates automatic transfer of patient and procedure data from your HIS/RIS system, eliminating manual data entry, and increasing technologist productivity.</p>				
		1	<p>RMS</p> <p>RMSSW allows remote access to Revolution for diagnostic service access and the ability to download software when required.</p>				
		1	<p>Portable Grid and Holder 200 LPI 8:1 40-72 DECUB</p>				

Item	CAT #	QTY	Description	List Unit	Govt.	Govt. Unit	Ext. Net
			<p>Ultra lightweight grid holder with two handles for easy positioning in any orientation. Rounded edges and smooth surfaces allow it to slide easily behind patients. Hard rubber corners, internal cushioning and energy absorbing design help to reduce shock from dropping.</p> <ul style="list-style-type: none"> • Grid holder with handle on both the long and short axis • Ratio is 8:1 • Al interspace material • Resolution is 200 lp/inch grid (short axis lines) • 40-72 Focal Distance Decubitus (grid lines parallel to short axis) • 1.61 kg (3.55 lb) 				
		1	<p>Remote Exposure Switch</p> <p>Wireless, remote x-ray exposure switch for maximum mobility in making portable exposures</p>				
		1	<p>DRX-1 Detector</p> <p>Wireless, cassette-size, 35 x 43 cm GOS Detector</p>				
		1	DRX Detector Battery				
		1	<p>DAP Meter</p> <p>Measures the Dose Area Product of the x-ray tube for an exposure and documents this in the DICOM header. With the optional IHE Scheduled Workflow Software the DAP data will be sent to the RIS via DICOM Modality Performed Procedure Step (MPPS).</p>				
		2	DRX Detector Battery				

Optional

Item	CAT #	QTY	Description
3		1	Professional Services Biomed Training for 1 person.
		1	DR - Customer DRX REVOLUTION Mobile Xray System Service Training Technical DRX REVOLUTION Mobile Xray System Training for Biomedical Engineers
		1	Operator Console Training Class
		1	Training Travel Package - Week 1 (Government sales only) Training travel package available to Government customers only. Tuition covers airfare, hotel, limited meals for up to a 1 week training class
4		1	Professional Services Biomed Training 2 Person Total
		2	DR - Customer DRX REVOLUTION Mobile Xray System Service Training Technical DRX REVOLUTION Mobile Xray System Training for Biomedical Engineers
		2	Operator Console Training Class
		2	Training Travel Package - Week 1 (Government sales only) Training travel package available to Government customers only. Tuition covers airfare, hotel, limited meals for up to a 1 week training class
5		1	Professional Services

Item	CAT #	QTY	Description	List Unit	Govt.	Govt. Unit	Ext. Net
			On Site Training for Technologist Additional 1 Week Follow Up				
		5	Basic User Training (1 Day)				
6		1	Trade - In Trade In Credit for GE AMX-4 Portable. This is Optioned and Not Included in Current Pricing.				
		1	GE AMX -4/4+ Trade-In Credit				
7		1	DR Accessories				
		1	DRX-1C Detector Wireless, cassette-size, 35x 43 cm CsI Detector				
		1	2D Barcode Reader 2D barcode scanner and counter charging dock allows patient wrist bans containing 2D bar code information to be utilized to confirm patient identity.				
8		1	DR Accessories				
		1	DRX 25x30C Detector Wireless, 25 x 30 cm, DR Detector designed for high productivity and instant access to images. The detector utilizes Cesium Iodide (CsI) for dose-sensitive pediatric applications. The smaller size is ideal for orthopedic tabletop imaging offering flexible positioning and easy handling. Product Specifications: <ul style="list-style-type: none"> Wireless standard: 802.11n Image size: 25 x 30 cm Pixel Pitch: 0.139 mm 				

Item	CAT #	QTY	Description	List Unit	Govt.	Govt. Unit	Ext. Net
			<ul style="list-style-type: none"> External Dimensions: 28.4 x 41.5 x 1.6 cm 				
		1	FLAT TAPE ON GRID FOR 25X30 DETECTOR				
		1	NO CHARGE BATTERY FOR 25X30 DETECTOR				
9		1	DR Accessories				
		1	<p>ICU Software Package</p> <p>Package includes:Tube and Line Visualization SoftwareCreates a companion image from the original exposure with optimized processing for clearer, easier visualization of PICC lines and tubes. With a single exposure, the software It increases confidence that tubes and lines are placed correctly.Pneumothorax Visualization SoftwareCreates a companion image from the original exposure that is optimized to accentuate the appearance of free air in the chest cavity.Auto-Correct for Image DisplayAnalyzes the image content and presents chest images in the proper orientation regardless of detector orientation</p>				
10		1	DR Accessories				
		1	<p>Administrative Analysis and Reporting Software</p> <p>Provides consolidated user-friendly reports from all Carestream CR and DR systems on the network. Example reports include repeat statistics by user and exam type, exposure data by user and exam, detector usage, system use by radiographer and</p>				

Item	CAT #	QTY	Description	List Unit	Govt.	Govt. Unit	Ext. Net
			much more. Users can also generate custom reports. Helpful for performance tracking and operational improvements.				
11		1	DR Accessories				
		1	Prior Image Review Retrieve and review images from PAC's to review anatomy and positioning and copy techniques to the current exam in order to standardize exposure techniques for optimal image quality.				
12		1	DR Accessories				
		1	Patient CD Burns patient images on a CD that includes a DICOM viewer which can be provided to patients for their records or to supply to a referring physician.				
13		1	DR Accessories				
		1	DR Total Quality Tool Software and Phantom Package Includes Phantom and SW license for one Carestream DR system console. Performs objective image tests and QC measurements on Carestream DR detectors. The software analyzes flat field, dark noise and phantom image test performance. Test results are provided automatically with historical trending. The user can export the data for independent analysis. The software uses the same interface as that used for patient exams. Perform these tests when it's				

Item	CAT #	QTY	Description	List Unit	Govt.	Govt. Unit	Ext. Net
			convenient for you - without interrupting workflow or incurring the cost of third-party testing.				
14		1	DR Accessories				
		1	DR Total Quality Tool Software Software used in conjunction with the DR Total Quality Tool Phantom. Performs objective image tests and QC measurements on Carestream DR detectors. The software analyzes flat field, dark noise and phantom image test performance. Test results are provided automatically with historical trending. The user can export the data for independent analysis. The software uses the same interface as that used for patient exams. Perform these tests when it's convenient for you - without interrupting workflow or incurring the cost of third-party testing.				
15		1	DR Accessories Pass Through Pricing from Reina Imaging				
		1	DRX-1 Mobile DRP Weight Distribution Cap 750 lbs				