

Qty	Description
1	<p>Customer Loyalty Upgrade Optima XR220amx Digital Mobile Radiographic system</p> <p>The Optima XR220amx is a self-contained battery operated mobile radiographic digital X-Ray imaging system designed for performing radiographic exams at the point of care</p> <p>Key Features</p> <ul style="list-style-type: none">• 15 KW generator• Wireless Digital Flashpad Detector with 6:1 removable grid, Back-up tether, QAP (Quality Assurance Procedure)• Dose Area Product Meter (DAP)• Capable of 100-240V nominal, 50/60Hz operation• Stand-by mode to eliminate boot up cycles and allow exposure within 25 seconds Exposures can be taken and processed while the unit is charging• Detector battery charges automatically while the detector is in the bin• Optimized GUI - Technique, image aquisition and display tools in a single integrated user interface• The detector can be used in additional wireless enabled GE radiographic systems: please refer to the current literature for system compatibility <p>Productivity</p> <ul style="list-style-type: none">• Up to 1,200 w of power available to minimize charge time• System can be driven within 4 seconds of activation• Pre-programmed techniques per anatomy and patient size• Systems can be used without the detector• Modality Perform Procedure Step (MPPS; SPS/PPS configurable)• Automated and customizable image transfer to PACS and printers• Can reprocess images post acquisition and during an exam• Usage reporting tools by individuals and user groups• System Health dashboard for system status• Bin stores detector and grid• Built in storage for cleaning wipes, gloves and lead apron• Self-propelled single drive handle control with variable speed of up to 5km/h (3.1mph on flat surfaces) forward and reverse to automatically adjust to the operators pace <p>Wireless Digital Detector Specifications</p>

Qty	Description
	<ul style="list-style-type: none"> • Detector battery can take up to 45 exposures per hour and provide enough power for 3 hours of use on a single charge • Single panel (non-tiled) amorphous silicon detector with a Cesium Iodide scintillator • Image area 40.4cm x 40.4cm (15.9in x 15.9in) • Active matrix 2022 x 2022 pixels • 8mb raw image file size • Pixel Pitch 200 microns • Typical upper dynamic range 7.8mR • Typical DQE @ Olp/mm: 68%) • 2 handgrips • Dimensions: L-23.1in x H-17.8in, T-0.94in (L-580mm, H-452mm, T-24mm) • Wireless point-to-point network between the system and detector for transferring image data <ul style="list-style-type: none"> – Communication over wide 500MHz channels to achieve very high data rates – Designed to co-exist with 802.11 networks without interference – Frequency: 3.1-10.6 GHz – Max Power Output: -41.3 dBm – Max PHY Data rate: 480 Mbps – Effective Throughput: 30-70 Mbps <p>Worklist can be retrieved from HIS/RIS systems and images can be transmitted through the DICOM interface to printers, archival devices (PACS), servers or review workstations.</p> <ul style="list-style-type: none"> • RJ45 10/100/1000 Base T Ethernet port <p>Please refer to DICOM conformance statement for complete definition of supported DICOM services.</p> <p>Generator</p> <ul style="list-style-type: none"> • 300 mA max • kVp and mAs controls • Less than 2% low frequency ripple • Frequency: greater than 100 kHz, Super resonant inverter with varying frequency <p>X-ray Source</p> <ul style="list-style-type: none"> • Nominal Tube Voltage (Radiographic) - 150kV • Nominal Focal Spot size (IEC 60336): <ul style="list-style-type: none"> – Large Focus: 1.3mm – Small Focus: 0.6mm

Qty	Description
	<ul style="list-style-type: none"> Anode Rotation Speed (minimal): 3200 min Permanent Filtration: 0.9mm Al/75 kV IEC60522: 1999 Maximum X-ray Tube Current <ul style="list-style-type: none"> Large Focus: 500 mA Small Focus: 200 mA Maximum Continuous Heat Dissipation: Without Air-circulator: 170W (238 HU/s)
	Collimator A pair of independent collimator blades controls the X-ray field
	<ul style="list-style-type: none"> 180 lux (1000 Lumen/mt2) light field lamp The collimator rotates +/-180 degrees with detents at -180, -90, 0, +90 St +180 degrees Full 43cm x 43cm (17in) coverage at a 100cm SID The column may be rotated up to +/- 270 degrees from the part position Drive Inhibit keypad access Password protected access to patient information for compliance with confidentiality regulations Automatic safety brake: Operator must hold drive handles to allow system movement Integrated front bumper stops unit and activates brakes when activated
1	<p>Wireless Connectivity for Optima XR220amx and Optima XR200amx</p> <p>802.11 a/b/g n-compatible wireless connectivity to hospital network</p> <p>Wi-Fi Certified</p> <p>Compatible with:</p> <ul style="list-style-type: none"> 802.11i, Wi-Fi Protected Access 2 (WPA2), WPA 802.1X AES - TKIP 64-, 128-WEP VPN: IPSec - IKE Management Frame Protection (MFP) EAP Types: <ul style="list-style-type: none"> LEAP LEAP + 128-WEP LEAP + WPA EAP - TLS EAP-TTLS/MSCHAPv2 EAP-FAST PEAP-GTC PEAP/MSCHAPV2

Qty	Description
1	Blue Tooth Bar Code Reader
1	<p data-bbox="395 226 1161 248">Optima XR220amx Upgrade Training: 3 Days Onsite (2 Days + 1 Day)</p> <p data-bbox="395 280 1398 342">One 2 day and one 1 day TIP onsite training visit for Optima XR200amx to Optima XR220amx upgrade.</p> <p data-bbox="395 367 1086 389">Includes TELL expenses. Days provided in two customer visits.</p> <p data-bbox="395 412 1398 479">This training program must be scheduled and completed within 12 months after the date of product delivery.</p>