

XR PORT RAD, VAMC SALISBURY, NC

PO# 659-B40019

Item	CAT #	QTY	Description
1		1	<b>DRX Revolution</b>
		1	<p><b>DRX-Revolution Mobile X-Ray System</b></p> <p>Carestream's innovative mobile X-ray room on wheels. The DRX-Revolution offers bins for gloves, paperwork, markers, bags and a lockable storage space for the detector. The collapsible column allows increased visibility and safety when driving the system. The tube arm can reach over 53 in (135 cm) to accommodate larger beds and crowded rooms while the system has 32 kW of power for shorter exposure times and more flexible technique selection. Dual, independent drive motors provide easy maneuverability and a maximum drive speed up to 3.5 m/h (5.6 km/h). An integrated proximity badge reader automatically logs the operator into the software and displays the patient worklist. Two touch-screen displays provide dual work zones with a 19 in. main monitor and 8 in. tube head monitor that allow the user to:</p> <ul style="list-style-type: none"> <li>• display the patient worklist</li> <li>• review prior images (optional software)</li> <li>• copy or change technique</li> <li>• accept or reject images</li> </ul> <p>Other features include:</p> <ul style="list-style-type: none"> <li>• Integrated 1D barcode reader</li> <li>• 2 integrated battery chargers for detector batteries</li> </ul>

Item	CAT #	QTY	Description
			<ul style="list-style-type: none"> <li>• Integrated storage bins for 1 DRX-1 detector, 1 2530C detector, 1 portable grid holder or grid alignment device</li> <li>• Wired exposure switch</li> <li>• Direct access to RIS/PACs</li> </ul> <p>X-Ray Generator:</p> <ul style="list-style-type: none"> <li>• Maximum Power Output 32kW</li> <li>• Vp Range 40 to 150 kVp</li> <li>• mAs Range 0.1 to 320 mAs</li> </ul> <p>X-RAY Tube:</p> <ul style="list-style-type: none"> <li>• Focal Spot Size: 0.6 mm / 1.2 mm</li> <li>• Target Angle: 14 degrees</li> <li>• Anode Heat Capacity: 300 kHU (212 kJ)</li> </ul> <p>Tube Head Movement:</p> <ul style="list-style-type: none"> <li>• Maximum SID to Floor: 2022 mm (79.6 in.)</li> <li>• Minimum SID to Floor: 683 mm (26.9 in.)</li> <li>• Tube Arm Reach: 1351 mm (53.2 in.)</li> <li>• Column Rotation Range: +/- 270 degrees</li> <li>• Tube Rotation: +180 degrees CW/-135 degrees CCW</li> <li>• Tube Tilt: -10 to +90 degrees</li> <li>• Collimator Rotation Range: +/- 90 degrees</li> </ul> <p>Physical Characteristics:</p> <ul style="list-style-type: none"> <li>• Weight: 575 kg (1268 lbs)</li> <li>• Height (column collapsed): 1295 mm (51.0 in.)</li> <li>• Height (column extended): 1956 mm (77.0 in.)</li> <li>• Width: 576 mm (22.7 in.)</li> <li>• Length: 1219 mm (48.0 in.)</li> </ul>

Item	CAT #	QTY	Description
		1	<p><b>Portable Grid and Holder 200 LPI 8:1 40-72 DECUB</b></p> <p>Ultra lightweight grid holder with two handles for easy positioning in any orientation. Rounded edges and smooth surfaces allow it to slide easily behind patients. Hard rubber corners, internal cushioning and energy absorbing design help to reduce shock from dropping.</p> <ul style="list-style-type: none"> <li>• Grid holder with handle on both the long and short axis</li> <li>• Ratio is 8:1</li> <li>• Al interspace material</li> <li>• Resolution is 200 lp/inch grid (short axis lines)</li> <li>• 40-72 Focal Distance Decubitus (grid lines parallel to short axis)</li> <li>• 1.61 kg (3.55 lb)</li> </ul>
		1	<p><b>DRX-1C Detector</b></p> <p>Wireless, cassette-size, 35x 43 cm CsI Detector</p>
		1	<p>DRX Detector Battery</p>
		1	<p><b>ICU Software Package</b></p> <p>Package includes:  Tube and Line Visualization Software  Creates a companion image from the original exposure with optimized processing for clearer, easier visualization of PICC lines and tubes. With a single exposure, the software It increases confidence that tubes and lines are placed correctly.  Pneumothorax Visualization Software</p>

Item	CAT #	QTY	Description
			<p>Creates a companion image from the original exposure that is optimized to accentuate the appearance of free air in the chest cavity.</p> <p>Auto-Correct for Image Display Analyzes the image content and presents chest images in the proper orientation regardless of detector orientation</p>
		1	DRX Detector Battery
		1	STANDARD SIDE PANELS FOR DRX-REVOLUTION
		1	STANDARD COLLIMATOR FOR DRX-REVOLUTION
		1	Cord Reel (USandC)
		1	<p><b>EVP Plus Imaging Processing Software</b></p> <p>Provides highly automated, state-of-the-art image processing. Uses multi-frequency image processing to increase latitude while preserving detail contrast in both over-penetrated and under-penetrated areas. Automatically processes and delivers diagnostic quality images to PACs based on look preference that can be uniquely specified by each site. Includes grid line suppression that prevents aliasing artifacts and application of a collimator mask. Five independent controls are available for the user for image adjustments in an intuitive user interface.</p>
		1	<p><b>Modality Worklist Software</b></p> <p>Facilitates automatic transfer of patient and procedure data from</p>

Item	CAT #	QTY	Description
			your HIS/RIS system, eliminating manual data entry, and increasing technologist productivity.
		1	<p><b>Administrative Analysis and Reporting Software</b></p> <p>Provides consolidated user-friendly reports from all Carestream CR and DR systems on the network. Example reports include repeat statistics by user and exam type, exposure data by user and exam, detector usage, system use by radiographer and much more. Users can also generate custom reports. Helpful for performance tracking and operational improvements.</p>
		1	RMS
		1	<p><b>2D Barcode Reader</b></p> <p>2D barcode scanner and counter charging dock allows patient wrist bans containing 2D bar code information to be utilized to confirm patient identity.</p>
		1	<p><b>Remote Exposure Switch</b></p> <p>Wireless, remote x-ray exposure switch for maximum mobility in making portable exposures</p>
		1	<p><b>DAP Meter</b></p> <p>Measures the Dose Area Product of the x-ray tube for an exposure and documents this in the DICOM header. With the optional IHE Scheduled Workflow Software the DAP data will be sent to the RIS via DICOM Modality Performed Procedure Step (MPPS).</p>
		1	<b>Prior Image Review</b>

Item	CAT #	QTY	Description
			Retrieve and review images from PAC's to review anatomy and positioning and copy techniques to the current exam in order to standardize exposure techniques for optimal image quality.
		1	<p><b>Tech Assist Chest QA Software Package</b></p> <p>Package includes:  Contrast Noise Ratio - target contrast and lower limit is set by the Radiologist. If the CNR on the acquired image is outside of this range the user is notified.  Anatomy Clipping Software - outlines areas where the software has determined the chest anatomy may have been collimated off of the image  Deviation Index - Quantifies the deviation of the actual exposure index from the preset target range which is set by the Radiologist. If the DI on the acquired image is outside of this range the user is notified.</p>
		1	<p><b>DR Total Quality Tool Software</b></p> <p>Software used in conjunction with the DR Total Quality Tool Phantom. Performs objective image tests and QC measurements on Carestream DR detectors. The software analyzes flat field, dark noise and phantom image test performance. Test results are provided automatically with historical trending. The user can export the data for independent analysis. The software uses the same interface as that used for patient exams. Perform these tests when it's convenient for you - without</p>

Item	CAT #	QTY	Description
			interrupting workflow or incurring the cost of third-party testing.
		1	FIPS OPTION/FOR DRX-REVOLUTION
2		1	<b>Professional Services</b>
		2	<b>Applications DRX REVOLUTION Key Operator Training - 2 days</b> To provide the Operator with the skills necessary to use the Revolution system and produce images for diagnostic interpretation. It also provides an overview of Key Operator functions to allow the Key Operator to define system requirements and procedures necessary to configure the system according to the site's workflow environment. The Key Operator training is provided using the train-the-trainer philosophy, thus Key Operators can continue training your current staff as well as new staff in the future.
3		1	<b>DR Accessories</b>
3		1	DRX Accident Protection for Warranty Year