












one eighth inch = one foot
one quarter inch = one foot
one half inch = one foot
three eighths inch = one foot
one inch = one foot
one inch and one half inches = one foot
three quarters inch = one foot
two inches = one foot
three inches = one foot
four inches = one foot
five inches = one foot
six inches = one foot
seven inches = one foot
eight inches = one foot
nine inches = one foot
ten inches = one foot
eleven inches = one foot
twelve inches = one foot
thirteen inches = one foot
fourteen inches = one foot
fifteen inches = one foot
sixteen inches = one foot
seventeen inches = one foot
eighteen inches = one foot
nineteen inches = one foot
twenty inches = one foot
twenty one inches = one foot
twenty two inches = one foot
twenty three inches = one foot
twenty four inches = one foot
twenty five inches = one foot
twenty six inches = one foot
twenty seven inches = one foot
twenty eight inches = one foot
twenty nine inches = one foot
thirty inches = one foot
thirty one inches = one foot
thirty two inches = one foot
thirty three inches = one foot
thirty four inches = one foot
thirty five inches = one foot
thirty six inches = one foot
thirty seven inches = one foot
thirty eight inches = one foot
thirty nine inches = one foot
forty inches = one foot
forty one inches = one foot
forty two inches = one foot
forty three inches = one foot
forty four inches = one foot
forty five inches = one foot
forty six inches = one foot
forty seven inches = one foot
forty eight inches = one foot
forty nine inches = one foot
fifty inches = one foot
fifty one inches = one foot
fifty two inches = one foot
fifty three inches = one foot
fifty four inches = one foot
fifty five inches = one foot
fifty six inches = one foot
fifty seven inches = one foot
fifty eight inches = one foot
fifty nine inches = one foot
sixty inches = one foot
sixty one inches = one foot
sixty two inches = one foot
sixty three inches = one foot
sixty four inches = one foot
sixty five inches = one foot
sixty six inches = one foot
sixty seven inches = one foot
sixty eight inches = one foot
sixty nine inches = one foot
seventy inches = one foot
seventy one inches = one foot
seventy two inches = one foot
seventy three inches = one foot
seventy four inches = one foot
seventy five inches = one foot
seventy six inches = one foot
seventy seven inches = one foot
seventy eight inches = one foot
seventy nine inches = one foot
eighty inches = one foot
eighty one inches = one foot
eighty two inches = one foot
eighty three inches = one foot
eighty four inches = one foot
eighty five inches = one foot
eighty six inches = one foot
eighty seven inches = one foot
eighty eight inches = one foot
eighty nine inches = one foot
ninety inches = one foot
ninety one inches = one foot
ninety two inches = one foot
ninety three inches = one foot
ninety four inches = one foot
ninety five inches = one foot
ninety six inches = one foot
ninety seven inches = one foot
ninety eight inches = one foot
ninety nine inches = one foot
one hundred inches = one foot

GENERAL TECHNOLOGY EQUIPMENT SCHEDULE			
THE SYMBOLS AND THE MATERIAL LIST ARE FOR THE CONVENIENCE OF THE CONTRACTOR. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION OF QUANTITIES AND SHALL FURNISH ALL MATERIAL, REQUIRED OR NOT, TO PRODUCE A SATISFACTORY WORKING SYSTEM.			
CATALOG NUMBERS SHALL NOT BE CONSIDERED COMPLETE BUT ARE GIVEN ONLY TO AID THE CONTRACTOR IN THE SEARCH FOR MATERIAL. NO MATERIAL SHALL BE ORDERED BY MANUFACTURER AND CATALOG NUMBER ONLY. EACH CONTRACTOR SHALL FIRST READ THE COMPLETE DESCRIPTION OF THE MATERIAL ON THESE DRAWINGS AND SPECIFICATIONS. THE FIRST MANUFACTURER LISTED IS THE BASIS OF DESIGN. "STANDARD COLOR" INDICATES FACTORY FINISH AVAILABLE AT NO ADDITIONAL CHARGE.			
ITEM NO.	SYMBOL	DESCRIPTION	APPROVED MANUFACTURERS
1	CCTV-PS-2	RACK MOUNT CCTV POWER SUPPLY, INDOOR, 120VAC INPUT, 24/28 VAC OUTPUT, MINIMUM 8 OUTPUTS SIZED AS REQUIRED FOR NUMBER OF OUTPUTS SERVED, POWER TO EXTERIOR CAMERAS.	ALTERNATE R24 SERIES OR APPROVED EQUAL
2	CCTV-NVR	NETWORK VIDEO RECORDER. APPLIANCE WITH EMBEDDED OS, CAPABLE OF RECORDING 32 CAMERAS WITH CAPACITY FOR 30 DAYS.	MILESTONE GENETEC ONSSI, EXACO OR APPROVED EQUAL
3	SC-RGB-1	RACK GROUND BAR, SOLID COPPER, 1/8" THICK X 2" WIDE	MIDDLE ATLANTIC BB-## WHERE ## DEFINES LENGTH OR APPROVED EQUAL
4	MON-1	CCTV MONITOR, LCD TYPE, LCD, 1920X 1080 RESOLUTION, HDMI, DVI, VGA AND S VIDEO INPUTS, 65" REFER TO SPECIFICATION SECTION 28 23 00 FOR COMPLETE INFORMATION.	NEC ORION VIEWZ OR APPROVED EQUAL
5	VMS-1	CCTV SYSTEM HEADEND SOFTWARE, REFER TO SPECIFICATION SECTION 28 23 00 FOR COMPLETE INFORMATION.	MILESTONE GENETEC ONSSI, EXACO OR APPROVED EQUAL
6	CCTV-PS	EXTERIOR PTZ CAMERA POWER SUPPLY, OUTDOOR, 120VAC INPUT, 24/28VAC OUTPUT, AC POWER INDICATOR WITH MASTER ON/OFF SWITCH, 1-4 INDIVIDUALLY FUSED OUTPUTS, POWER SUPPLY SIZED AS REQUIRED FOR NUMBER OF CAMERAS SERVED.	PELCO WCS SERIES OR APPROVED EQUAL
7	SC-MPP-1	MODULAR PATCH PANEL, 48 MODULAR RJ-45 TERMINATIONS, MOUNTS DIRECTLY TO EIA/TIA STANDARD 19" RELAY RACK, PORT IDENTIFICATION NUMBERS, PROVIDED WITH COLOR CODING AND LABEL HOLDER KITS, U.L. LISTED, REQUIRES (2) 1.75" MOUNTING SPACES.	PANDUIT CAT 6: CPKKT 48 WBL ORTRONICS THE SEMON COMPANY SYSTIMAX ADC CORNING
8	SC-PS-1	POWER STRIP, HORIZONTALLY MOUNTS IN A STANDARD EIA/TIA 19" RACK, (10) REAR RECEPTACLES, 125VAC/60Hz, PROVIDE WITH 10" OF CORD, INTERNAL CIRCUIT BREAKER, U.L. LISTED, REQUIRES (1) 1.75" MOUNTING SPACE.	HUBBELL HPPWPR PANDUIT HOMACO INC. CHATSWORTH PRODUCTS TRIP LITE
9	SC-TTB-1	TELECOMMUNICATIONS TERMINAL BOARD, 4' X 8' X 3/4" A-C GRADE FIRE-RATED PLYWOOD, EXPOSED SIDE SHALL BE SMOOTH, MOUNT VERTICALLY WITH TOP OF PLYWOOD AT 8" A.F.F.	
10	SC-ER-1	ENCLOSED CABINET RACK, 79.5" HIGH X 35" DEEP, STANDARD 19" MOUNTING SPACE, LOOKING, VENTILATED FRONT AND REAR DOORS, VENTILATED TOP COVER WITH FANS, MEETS EIA-310-E REQUIREMENT, PROVIDES (42) 1.75" MOUNTING SPACES.	HUBBELL SVR84 ORTRONICS HOMACO INC. CHATSWORTH PRODUCTS PANDUIT
11	SC-FDC-1	OPTICAL FIBER DISTRIBUTION CABINET, HIGH DENSITY, MINIMUM 144 FIBER CAPACITY, PROVIDE WITH CLAMP AND GROUNDING KIT, COUPLING PANELS, SC CONNECTORS, COUPLINGS AND JUMPERS, REQUIRES 4 1.75" MOUNTING SPACES.	PANDUIT FRME SERIES ORTRONICS THE SEMON COMPANY SYSTIMAX ADC CORNING
12	SC-QND-1	WALL-MOUNT GROUND BAR, 4" H X 12" L X 1/4" D COPPER, ELECTRICALLY ISOLATED BY INSULATORS INTEGRAL TO MOUNTING BRACKETS. PROVIDE UNIT CONFIGURED WITH SIXTEEN (16) SETS OF 5/16" HOLES SPACED 5/8" ON CENTER TO ACCOMMODATE "A" SPACED TWO-HOLE COMPRESSION LUGS AND THREE (3) SETS OF 7/16" HOLES SPACED 1" ON CENTER TO ACCOMMODATE "C" SPACED TWO-HOLE COMPRESSION LUGS. ANSI/EIA/TIA-607 AND BICSI COMPLIANT. UL LISTED. REFER TO 8/00TY301 FOR ADDITIONAL INFORMATION.	CHATSWORTH PRODUCTS 401ES-012 PANDUIT ERICO HARBER
13	HC-1	HORIZONTAL CROSS-CONNECT, SEE PLANS FOR LOCATIONS AND LAYOUT.	.
14	SC-FDC-2	OPTICAL FIBER DISTRIBUTION CABINET, COMBINATION SHELF, 36 FIBER CAPACITY, SLIDE OUT RAILS TO FACILITATE FRONT ACCESS, JUMPER TROUGH IN CONNECTOR PANELS TO REDUCE MOUNTING SPACE, PROVIDE WITH CLAMP AND GROUNDING KIT, COUPLING PANELS, SC CONNECTORS, COUPLINGS AND JUMPERS, REQUIRES (1) 1.75" MOUNTING SPACES.	PANDUIT FMD SERIES ORTRONICS THE SEMON COMPANY SYSTIMAX ADC CORNING
15	SC-MEDIA	MEDIA CONVERTER, 100BASE-TX(RJ-45) TO 100BASE-FX 1300nm (SC), FOR PROTECTING THE NETWORK FROM LIGHTNING SURGES ON EXTERIOR PTZ CAMERAS, INCLUDE ASSOCIATED RACK MOUNT CAGE AND POWER SUPPLY(IES)	TRANSITION NETWORKS E-100B1X-FX-05(SC) WITH RM019-SAA-01 OR APPROVED EQUAL
16	SC-PIRREX	PIR REQUEST TO EXIT MOTION DETECTOR, DOOR MONITOR WITH SOUNDER ALERT, ADJUSTABLE LATCH TIME, SELECTABLE FAIL SAFE/FAIL SECURE, ADJUSTABLE SOUNDER VOLUME, ACTIVATION LED, 12VDC OPERATION, SEQUENTIAL LOGIC INPUT, TWO FORM C CONTACTS	BOSCH DS180 OR APPROVED EQUAL
17	SEC-WS	SECURITY MANAGEMENT SYSTEM WORKSTATION, FOR USE WITH INTEGRATED SECURITY MANAGEMENT SYSTEM, REFER TO SPECIFICATION SECTION 28 13 00 FOR COMPLETE INFORMATION.	.
18	SMS-SRV	SECURITY MANAGEMENT SYSTEM SERVER, FOR USE WITH INTEGRATED SECURITY MANAGEMENT SYSTEM, ACCESS CONTROL, REFER TO SPECIFICATION SECTION 28 13 00 FOR COMPLETE INFORMATION.	.
19	SEC-1	INTRUSION DETECTION SECURITY CONTROL PANEL, TO BE DETERMINED, REFER TO SPECIFICATION SECTION 28 13 00 FOR COMPLETE INFORMATION. EIGHT PARTITIONS, SUPPORTS WIRELESS, UL COMMERCIAL.	HONEYWELL VISTA 50 P UL DMP OR APPROVED EQUAL
20		CARD READER, PROVIDED AS INTEGRAL PART OF SECURITY MANAGEMENT SYSTEM, REFER TO ACCESS CONTROL SYSTEM DOOR SCHEDULE FOR COMPLETE INFORMATION, CARD READERS SHOWN ON PLANS TO IDENTIFY INTENDED MOUNTING LOCATION, REFER TO SPECIFICATION SECTION 28 13 00 FOR COMPLETE INFORMATION.	HID ICLASS SE SERIES, BASE PART NUMBER 900/910/920 BASED ON MOUNTING LOCATION
21		CARD READER, PROVIDED AS INTEGRAL PART OF SECURITY MANAGEMENT SYSTEM, REFER TO ACCESS CONTROL SYSTEM DOOR SCHEDULE FOR COMPLETE INFORMATION, CARD READERS SHOWN ON PLANS TO IDENTIFY INTENDED MOUNTING LOCATION, REFER TO SPECIFICATION SECTION 28 13 00 FOR COMPLETE INFORMATION.	HID ICLASS SE SERIES, WITH KEYPAD, BASE PART NUMBER 921
22		DURESS BUTTON, SPDT, WIRELESS, DESK MOUNT, SINGLE BUTTON. EACH DURESS BUTTON SHALL TRANSMIT SIGNALS TO THE ASSOCIATED WIRELESS RECEIVER WHICH SHALL BE WIRED TO THE NEAREST ACCESS CONTROL SYSTEM OR INTRUSION SYSTEM CONTROLLER AS A SYSTEM INPUT. EACH DURESS SWITCH SHALL INITIATE A BREAKOUT ALARM ON THE SECURITY MANAGEMENT WORKSTATION INDICATING UNIQUE SWITCH LOCATION.	HONEYWELL INOVONICS LINEAR OR APPROVED EQUAL
23		DURESS BUTTON, WIRELESS, WALL MOUNT, PUSH PLATE ACTUATOR LABELED EMERGENCY, TAMPER PROOF SCREWS. EACH DURESS BUTTON SHALL TRANSMIT SIGNALS TO THE ASSOCIATED WIRELESS RECEIVER WHICH SHALL BE WIRED TO THE NEAREST ACCESS CONTROL SYSTEM OR INTRUSION SYSTEM CONTROLLER AS A SYSTEM INPUT. EACH DURESS SWITCH SHALL INITIATE A BREAKOUT ALARM ON THE SECURITY MANAGEMENT WORKSTATION INDICATING UNIQUE SWITCH LOCATION.	HONEYWELL INOVONICS LINEAR OR APPROVED EQUAL ALARM CONTROLS PSI-111 PUSH PLATE, OR APPROVED EQUAL
24		ACCESS CONTROL SECURITY SYSTEM, SYMBOL INDICATES THAT DOOR HAS SECURITY FUNCTIONALITY, REFER TO ACCESS CONTROL SYSTEM DOOR SCHEDULE FOR COMPLETE REQUIREMENTS FOR EACH DOOR. REFER TO SPECIFICATION SECTION 28 13 00 FOR COMPLETE INFORMATION.	NA.
25		DOOR POSITION INDICATOR SWITCH, INTEGRAL PART OF ACCESS CONTROL AND INTRUSION DETECTION SYSTEM, 1/4" DIAMETER, MAGNETIC, STANDARD GAP, RECESSED IN DOOR FRAME, COORDINATE INSTALLATION WITH GENERAL CONTRACTOR AND DOOR SUPPLIER. REFER TO SPECIFICATION SECTION 28 13 00	GE SECURITY 1055 SERIES OR APPROVED EQUAL

TECHNOLOGY EQUIPMENT SCHEDULE (CONTINUED)			
26		MOTION DETECTOR, CEILING MOUNTED, DUAL TECHNOLOGY MICROWAVE/PIR, FORM C, 30' RADIUS RANGE, INSTALL ACCORDING TO MANUFACTURERS SPECIFICATIONS.	BOSCH DS180 OR APPROVED EQUAL
27		MOTION DETECTOR, WALL MOUNTED, DUAL TECHNOLOGY MICROWAVE/PIR, FORM C, TWO SELECTABLE RANGES: APPROX 60' X 60' AND 25' X 25', ANTI-MASKING, DRAFT AND INSECT IMMUNITY, INSTALL ACCORDING TO MANUFACTURERS SPECIFICATIONS, CONTRACTOR SHALL FURNISH APPROPRIATE MOUNTING BRACKET.	BOSCH IISC-POL1-WA18X OR APPROVED EQUAL
28	AV-KP1-W	KEYPAD, INTRUSION DETECTION DEVICE, ALPHANUMERIC, BACKLIT KEYS, CUSTOM TEXT.	HONEYWELL 616405 OR AS COMPATIBLE WITH INTRUSION DETECTION SYSTEM.
29		INFORMATION OUTLET, WALL MOUNT, 2-PORT COVERPLATE AS INDICATED ON DRAWINGS, SEE DETAIL 00TY503 FOR PIN CONFIGURATION. * # * - INDICATES INFORMATION OUTLET FACEPLATE CONFIGURATION AS INDICATED ON THE PLANS, SEE DETAIL 00TY503. INSTALL INFORMATION OUTLET IN A 4" SQUARE BACKBOX WITH A SINGLE GANG PLASTER RING, INSTALL A 1" EMT CONDUIT TO ABOVE ACCESSIBLE CEILING, PROVIDE REMOVABLE BLANK INSERTS FOR UNUSED PORTS (PANDUIT CMB OR APPROVED EQUAL).	COVERPLATE: PANDUIT [CPPEZ SERIES] ORTRONICS THE SEMON COMPANY SYSTIMAX ADC JACK: PANDUIT (CAT6) C6688TP SERIES ORTRONICS THE SEMON COMPANY SYSTIMAX ADC OSCO 45030E SERIES HP BROCADE OSCO 2980 SERIES HP BROCADE OSCO 2980 SERIES HP BROCADE DETEX ES411-K0 OR APPROVED EQUAL SECURITRON MK SERIES OR APPROVED EQUAL SOFTWARE HOUSE, LENEL, GE, HIRSHCH NO APPROVED EQUAL DYNALOCK 8290 APPROVED EQUAL HUBBELL HSQ4826 WITH REXOR GROUND KIT AND HINTELCO FAN KIT CHATSWORTH PRODUCTS B-LINE GREAT LAKES INC. HOMACO APC SMART UPS RT SERIES MINUTEMAN UPS ENDURAVOR SERIES OR APPROVED EQUAL APC SMART UPS SERIES MINUTEMAN UPS ENTERPRISE PLUS SERIES OR APPROVED EQUAL BLACK BOX OR APPROVED EQUAL MIDDLE ATLANTIC RM-16B-LCD-17 OR APPROVED EQUAL HONEYWELL, INOVONICS, LINEAR OR APPROVED EQUAL NEC ORION VIEWZ OR APPROVED EQUAL
30	SC-SW-3	NETWORK CORE SWITCH, (48) 10/100/1000 802.3af PORTS, DUAL POWER SUPPLIES, MINIMUM (16) 1 GB SFP MODULES WITH LC CONNECTORS	
31	SC-SW-2	NETWORK EDGE SWITCH, (48) 10/100/1000 802.3af POE+ PORTS, DUAL POWER SUPPLIES, 1GB SFP MODULES WITH LC CONNECTORS.	
32	SC-SW-1	NETWORK EDGE SWITCH, (24) 10/100/1000 802.3af POE+ PORTS, DUAL POWER SUPPLIES, 1GB SFP MODULES WITH LC CONNECTORS.	
33	AC-ANN	AUDIBLE ANNUNCIATOR DOOR ALARM, SIGNALS TO SECURITY COMMAND CENTER (SCC), AND SCC CAN SHUNT ACTIVATION VIA OUTPUT FROM SECURITY SYSTEM	
34	AC-KEYSWT	KEYSWITCH FOR SHUNTING DOOR POSITION SWITCH INPUT TO AUDIBLE ANNUNCIATOR, 12/24 VDC OPERATION WITH BI COLOR LED. DPDT TO SHUNT DOOR SWITCH AND TO NOTIFY SCC THAT DOOR HAS BEEN SHUNTED. CYLINDER SHALL BE INCLUDED AND CHANGEABLE.	
35	SC-ACP-1	ACCESS CONTROL PANEL WITH ASSOCIATED POWER SUPPLY(IES)	
36	SC-PB REX	REQUEST TO EXIT BUTTON, 0-60 SECOND PNEUMATIC ACTION, DPDT, RED MUSHROOM BUTTON.	
37	SC-ER-2	WALL MOUNTED EQUIPMENT RACK, 48"H x 19.75"W x 26" D, OPENS TO LEFT OR RIGHT, STRUCTURAL GRADE ALUMINUM OR COLD ROLLED STEEL, VELLODO STRAPS INCLUDED, 200 POUND EQUIPMENT CAPACITY, UNIVERSAL MOUNTING HOLE PATTERN, BLACK POWDER COAT FINISH, MEETS EIA-310-E REQUIREMENTS. PROVIDES (26) 1.75" MOUNTING SPACES, VENTED SIDES, FRONT DOOR AND REAR LOCKABLE AND KEYED ALIKE, FRONT AND REAR DOOR TAMPER SWITCHES SHALL BE INCLUDED.	
38	SC-UPS-1	MDP ONLINE UPS, RACKMOUNT, REMOTELY MANAGEABLE, SIZED WITH BATTERIES TO PROVIDE A MINIMUM OF FOUR HOURS OF RUN TIME, 208V INPUT, 120V OUTPUT, RJ-45 10 /100 BASE-T INTERFACE, SINE WAVE OUTPUT, 6 VOLTAGE OUTPUTS.	
39	SC-UPS-2	TR ROOM ONLINE UPS, RACKMOUNT, REMOTELY MANAGEABLE, SIZED WITH BATTERIES TO PROVIDE A MINIMUM OF FOUR HOURS OF RUN TIME, 120V INPUT, 120V OUTPUT, RJ-45 10 /100 BASE-T INTERFACE, SINE WAVE OUTPUT, 6 VOLTAGE OUTPUTS.	
40	SC-KVM	4 PORT KVM SWITCH WHICH SUPPORTS THE INTERFACE CABLES AND OS OF CONTRACTOR FURNISHED SERVERS.	
41	AC-KBD/MON	RACKMOUNT LCD MONITOR,KEYBOARD AND TOUCHPAD MOUSE, 17" MONITOR, 1 RU HIGH.	
42	AC-RCVR-RF	WIRELESS RECEIVER FOR PANIC SYSTEM, COMPATIBLE WITH CONTRACTOR FURNISHED TRANSMITTERS, MINIMUM 16 OUTPUTS CONFIGURED ONE PER TRANSMITTER OR SERIAL COMMUNICATION TO CONTROL PANEL, 12-24 V AC/DC, QUANTITY OF REPEATERS AND RECEIVERS REQUIRED FOR RECEIPT OF SIGNALS, INDIVIDUALLY ZONED. EACH TRANSMITTER SHALL BE INDIVIDUALLY ZONED FOR REPORTING.	
43	MON-2	CCTV MONITOR, LCD TYPE, LCD, 1920X 1080 RESOLUTION, HDMI, DVI, VGA AND S VIDEO INPUTS, 55" REFER TO SPECIFICATION SECTION 28 23 00 FOR COMPLETE INFORMATION.	
52	CCTV-RADIO	WIRELESS SYSTEM FOR VIDEO TRANSMISSION, 2.4 OR 5GHz, RATED FOR OUTDOOR USE, EACH RADIO SHALL HAVE A MINIMUM THROUGH PUT OF 25Mbps	FLUORESH W100 OR ENDO PRETRAILER 7000 SERIES UBQUITI AIRMAX OR APPROVED EQUAL

APPROVED:	APPROVED:President AF.G.C. 2250	APPROVED:Energy Engineer	APPROVED:Medical Center Director	Drawing Title: TECHNOLOGY EQUIPMENT SCHEDULE	Project Title: REPLACE SURVEILLANCE SYSTEM	Date: 08.23.13	Department of Veterans Affairs
APPROVED:	APPROVED:	APPROVED:Safety Manager	APPROVED:Associate Director	Scale: AS SHOWN	Approved: TWC - JCMVAMC Checked By: DAVLAR Drawn By: KEIEVE	Project No. 623.12.105	
APPROVED:	APPROVED:	APPROVED:Infection Control Nurse	APPROVED:Chief of Staff	Building Number: SITE	Location: Jack C. Montgomery VA Medical Center - Muskogee, OK	Drawing No. 00 TY600 Dwg. 38 of 122	
APPROVED:	APPROVED:	APPROVED:Industrial Hygienist	APPROVED:Chief of Engineering Service				
APPROVED:	APPROVED:						

No.	Description	Date	CONSULTANTS:	ARCHITECTS/ENGINEERS:	Dept. of Veterans Affairs Jack C. Montgomery Medical Center 1011 Honor Height Drive Muskogee, Oklahoma 74401
1	ADDENDUM #7	12/12/14	 KJWW ENGINEERING CONSULTANTS Experience you can build on. 870 DUNN DRIVE, SUITE 104 ST. LOUIS, MISSOURI 63104 314.713.1238 FAX: 314.651.1173 WWW.KJWW.COM STRUCTURAL MECHANICAL ELECTRICAL TECHNOLOGY MEDICAL EQUIPMENT SOLUTIONS AECOM Missouri State University of Architecture, Engineering	 303rd Engineering Group, LLC Service-Disabled Veteran-Owned Small Business 1925 ARDENVALE STREET ST. LOUIS, MO 63118 PHONET: (314) 564-7338/2 HTTP://WWW.303ENGINEERING.COM	
Revisions					

VA FORM 08-6231 PRINTED ON: December 11, 2014 ORIGINAL SIZE OF SHEET IS 30" X 42"

ISSUED FOR CONSTRUCTION