

SUPPLY WAREHOUSE :B40124 .
V.A. Medical Center
7400 MERTON MINTER BLVD
SAN ANTONIO, TX 78229-4404
P.O.# 671-B40124

Qty	Item Description
1	Cios Alpha Cios Alpha is a high-end X-ray C-arm system with a dynamic flat panel detector for fluoroscopy and single image mode. The compact, mobile system was developed for use in, e.g. cardio/vascular surgery, gastroenterology, urology, emergency surgery, orthopedics, and general surgery.
1	FD 30x30 High-resolution, dynamic flat panel detector with indirect converter technology (amorphous silicon) having a size of 30 cm x 30 cm, with a matrix of 1536 x 1536 pixels.
1	Single Tank w. 25kW High-voltage generator with 25 kW (IEC) and rotating anode, incl. integrated active cooling system
1	Dose measuring chamber System-integrated dose measuring chamber for displaying the dose area product or air kerma value. The cumulative dose area product is displayed for the current patient and saved under the patient data. The cumulated dose is automatically transferred to a radiation summary report and can be retrieved at any time. For each patient a cumulative value is saved in the patient database. Alternatively: Display of air kerma values
1	Standard basic chassis C-arm chassis
1	Monitor trolley w. flex plus column Mobile workstation including monitor column with motorized height adjustment and 240°vertically rotatable monitors (-30°to +210°) for flexible positioning of the TFT displays with integrated cable routing and fold-up function for transport and park position.
1	2 x 19" b/w High bright TFT monitor Two 19" b/w TFT displays with high luminance for live and reference image display.
1	DVI video splitter 2x Connection for an external live monitor (monitor A) and an external reference monitor (monitor B) via DVI connection.
1	Standard foot switch Standard foot switch for radiation release and storing
1	DICOM Send/SIC Digital, unidirectional image transfer of single images or complete folders to a network in DICOM format. Feedback from the image archive (Storage Commitment).
1	DICOM Print For sending and printing of images by means of a virtual filmsheet to a DICOM laser camera or printer. Provision of DICOM Print service for connection to a laser camera or a network printer (postscript-capable).
1	Spacer Single-tank spacer

Qty	Item Description
1	C-Arm drape/peel-away (10) Sample case of c-arm drapes (quantity of 10) for the Siemens C-Arms product portfolio. The drape was designed by Siemens and has a pull-away section to accommodate the outer section of the C-arm to allow arm movement while maintaining a sterile environment. Drapes are individually packaged and sterile. Drape reorders will be sold in case of 20 and use Siemens part CF31772.
1	Initial onsite trng 24 hrs Up to (24) hours of on-site clinical education training, scheduled consecutively during standard business hours for a maximum of (4) imaging professionals. Training will cover agenda items on the ASRT approved checklist. Uptime Clinical Education phone support is provided during the warranty period for specified posted hours. This educational offering must be completed (12) months from install end date. If training is not completed within the applicable time period, Siemens obligation to provide the training will expire without refund.
1	SPC Freight Costs

Qty

Item Description

1

Basic chassis motorization w. position m

C-arm base unit with motorization of orbital and angular movement. The attached control module for motorized movements includes position storage keys for storage of 2 orbital and angular positions with corresponding collimator values.

This item has been quoted as a substitute for Part No. 14436406 - "Standard basic chassis" that has been included in the quotation.

Qty	Item Description
1	Int. detector laser light localizer Integrated laser aimer on the detector which transmits a crosshair laser.
1	2D measurement function Measurement of angles and distances
1	Vascular software Subtraction angiography with vascular display as a subtraction series or roadmap, including - Pixelshift - Remask - Landmark - Dual channel function - contrast medium: iodine or CO2
1	Sony Printer UP 970 Thermal printer for economical and fast image documentation (gray-scale printing) on thermal paper - Print speed: 8 seconds per image - Cost per image: € 0.35 - Series UPP-210 printer paper - No further consumable material