

**SECTION 10 14 00
SIGNAGE**

PART 1 - GENERAL

1.1 DESCRIPTION

- A. This section specifies interior signage for room numbers, directional signs, and code required signs.

1.2 RELATED WORK

- B. Lighted EXIT signs for egress purposes are specified under Division 26, ELECTRICAL.

1.3 MANUFACTURER'S QUALIFICATIONS

Sign manufacturer shall provide evidence that they regularly and presently manufactures signs similar to those specified in this section as one of their principal products.

1.4 SUBMITTALS

- A. Submit in accordance with Section 01 33 00, SHOP DRAWINGS, PRODUCT DATA AND SAMPLES.
- B. Samples: Sign panels and frames, with letters and symbols, each type. Submit 2 sets. One set of samples will be retained by Resident Engineer, other returned to Contractor.
 - 1. Sign Panel, (9 inches x 9 inches), with letters.
 - 2. Color samples of each color, (6 inches x 6 inches. Show anticipated range of color and texture.
 - 3. Sample of typeface, arrow and symbols in a typical full size layout.
- C. Manufacturer's Literature:
 - 1. Showing the methods and procedures proposed for the concealed anchorage of the signage system to each surface type.
 - 2. Manufacturer's printed specifications, anchorage details, installation and maintenance instructions.
- D. Samples: Sign location plan, showing location, type and total number of signs required.
- E. Shop Drawings: Scaled for manufacture and fabrication of sign types. Identify materials, show joints, welds, anchorage, accessory items, mounting and finishes.
- F. Full size layout patterns for dimensional letters.

1.5 DELIVERY AND STORAGE

- A. Deliver materials to job in manufacturer's original sealed containers with brand name marked thereon. Protect materials from damage.

- B. Package to prevent damage or deterioration during shipment, handling, storage and installation. Maintain protective covering in place and in good repair until removal is necessary.
- C. Deliver signs only when the site and mounting services are ready for installation work to proceed.
- D. Store products in dry condition inside enclosed facilities.

1.6 APPLICABLE PUBLICATIONS

- A. The publications listed below form a part of this specification to the extent referenced. The publications are referenced in the text by the basic designation only.
- B. American Society for Testing and Materials (ASTM):
 - B209-07.....Aluminum and Aluminum-Alloy Sheet and Plate
 - B221-08.....Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Shapes, and tubes.
- C. Federal Specifications (Fed Spec):
 - MIL-PRF-8184F.....Plastic Sheet, Acrylic, Modified.
 - MIL-P-46144C.....Plastic Sheet, Polycarbonate

1.7 MINIMUM SIGN REQUIREMENTS

- A. Permanent Rooms and Spaces:
 - 1. Tactile and Braille Characters, raised minimum 0.793 mm (1/32 in). Characters shall be accompanied by Grade 2 Braille.
 - 2. Type Styles: Characters shall be uppercase, Helvetica Medium, and serif font shown on basis of design drawings from Creative Signage System drawings.
 - 3. Character Height: Minimum 16 mm (5/8 in) high, Maximum 50 mm (2 in).
 - 4. Symbols (Pictograms): Equivalent written description shall be placed directly below symbol, outside of symbol's background field. Border dimensions of symbol background shall be minimum 150 mm (6 in) high.
 - 5. Finish and Contrast: Characters and background shall be eggshell, matte or other non-glare finish with adequate contrast with background.
 - 6. Mounting Location and Height: As shown. Mounted on wall adjacent to the latch side of the door and to avoid door swing and protruding objects.
- B. Overhead Signs:
 - 1. Type Styles: As shown. Characters shall have a width-to-height ratio between 3:5 and 1:1. Characters shall have a stroke width-to-height ratio of between 1:5 and 1:10.

2. Character Height: minimum 75 mm (3 in) high for overhead signs. As shown, for directional signs.
3. Finish and Contrast: Same as for signs of permanent rooms and spaces.
4. Mounting Location and Height: As shown.

1.8 COLORS AND FINISHES:

Section 09 06 00, SCHEDULE FOR FINISHES.

PART 2 - PRODUCTS

2.1 GENERAL

- A. Signs of type, size and design shown on the drawings and as specified.
- B. Signs complete with lettering, framing and related components for a complete installation.
- C. Provide graphics items as completed units produced by a single manufacturer, including necessary mounting accessories, fittings and fastenings.
- D. Do not scale drawings for dimensions. Contractor to verify and be responsible for all dimensions and conditions shown by these drawings. Resident Engineer to be notified of any discrepancy in drawing, in field directions or conditions, and/or of any changes required for all such construction details.
- E. The Sign Contractor, by commencing work of this section, assumes overall responsibility, as part of his warranty of work, to assure that assemblies, components and parts shown or required within the work of the section, comply with the Contract Documents. The Contractor shall further warrant: That all components, specified or required to satisfactorily complete the installation are compatible with each other and with conditions of installations.

2.2 PRODUCTS

- B. Cast Acrylic Sheet: MIL-PRF-8184F; Type II, class 1, Water white non-glare optically clear. Matt finish water white clear acrylic shall not be acceptable.
- C. Polycarbonate: MIL-P-46144C; Type I, class 1.

2.3 SIGN STANDARDS

- A. Typography:
 1. Type Style: Helvetica Medium and serif font as shown on Creative Signage Systems Basis of Design. Initial caps for Room Names or all caps for Tactile Lettering.
 2. Arrow: See graphic standards in drawings.

3. Letter spacing: See graphic standards on drawings.
4. Letter spacing: See graphic standards on drawings.
5. All text, arrows, and symbols to be provided in size, colors, typefaces and letter spacing shown. Text shall be a true, clean, accurate reproduction of typeface(s) shown. Text shown in drawings are for layout purposes only; final text for signs is listed in Sign Message Schedule.

B. Project Colors and Finishes: Creative Signage Systems Basis of Design

2.4 SIGN TYPES

A. General:

1. The interior sign system is comprised of sign types families that are identified by a number and a letter symbol from Creative Signage System which is the basis of design..

B. Interchangeable Component System:

1. Sign Type Families:

Sign Type 1 Room Number and Name (Creative Signage System-D1 A/F/W)

Sign Type 2 Room Number (Creative Signage System-D1 A/W)

Sign Type 3 Restroom (Creative Signage System-SA /W)

Sign Type 4 Overhead (Creative Signage System-C4 DF)

Sign Type 5 Directional (Creative Signage System-E1 F/W)

2. Interior sign system capable of being arranged in a variety of configurations with a minimum of attachments, devices and connectors.
 - a. Interchangeable nature of the system shall allow for changes of graphic components of the installed sign, without changing sign in its entirety.
 - b. Component Sign System is comprised of the following primary components:
 - 1) Rail Back utilizing horizontal rails, spaced to allow for uniform, modular sizing of sign types.
 - 2) **Clear acetate insert** for name of office or suite.
 - 3) Top panel-Tactile and Braille.
 - 4) VA watermark printed on clear acetate insert.#20 Clear Satin Anodized Beveled Square Frame.
 - c. Rail Back, Rail Insert and End Caps in anodized extruded aluminum to allow for tight tolerances and consistent quality of fit and finish.
 - d.

- e. Sign configurations shall vary in width from (3 inches) to (48 inches), and have height dimensions of, 75 mm (3 inches), 225 mm (9 inches) and (9 1/2 inches).
3. Rail Back functions as internal structural member of sign using extruded satin aluminum.
 - a. Shall accept an plastic insert on one sign or on both sides.
 - b.
 - c. Rail shall allow for a variety of mounting devices including wall mounting for screw-on applications, using pressure sensitive tape, freestanding mount, ceiling mount and other mounting devices as needed.
4. Rail Insert functions as a mounting device for Copy Panels on to the Rail Back. The Rail Insert mounts to the back of the Copy Panel with adhesive suitable for use with the particular copy insert material.
 - a. Shall allow Copy Panels to slide or snap into the horizontal Rail Back for ease of changeability.
 - b. Shall mount to the back of the Copy Panel with adhesive suitable for use with particular Copy Panel material.
5. Copy Panels shall accept various forms of copy and graphics, and attaches to the Rail Back with the Rail Insert. Copy Panels shall be either ABS plastic with integral color or an acrylic lacquer finish; photo polymer; or, acrylic.
 - a. Interchangeable by sliding horizontally from either side of sign, and to other signs in system of equal or greater width or height.
 - b. Cleanable without use of special chemicals or cleaning solutions.
 - c. Copy Insert Materials.
 - 2) Photo polymer Inserts - 3 mm (.125 inches) phenolic photo polymer with raised copy etched to 2.3 mm (.0937 inches), bonded to an ABS plastic or extruded aluminum insert with adhesive. Background color is painted in acrylic enamel.
 - 3) Changeable Acetate/ Insert Holder - Extruded insert holder with integral Rail Insert for connection with structural back panel in aluminum with a satin finish. Inserts into holder are acetate with a clear 0.7 mm (.030 inches) textured cover. Background color is painted in acrylic lacquer.
 - 4) Acrylic - 2 mm (.080 inches) non-glare acrylic. Pressure bonded to extruded Rail Insert using adhesive. Background color is painted in acrylic lacquer or acrylic enamel.

5) Extruded aluminum with a satin finish Insert Holder with integral Rail Insert for connection with Structural Back Panel to hold a 0.7 mm (.030 inches) textured polycarbonate insert and a Sliding Tile which mounts in the Inset Holder and slides horizontally.

10) Typography

- a) Vinyl First Surface Copy (non-tactile) - Applied Vinyl copy.
- b) Subsurface Copy Inserts - Textured 1 mm (.030 inches) clear polycarbonate face with subsurface applied Vinyl copy. Face shall be back sprayed with paint and laminated to an extruded aluminum carrier insert.
- c) Integral Tactile Copy Inserts - phenolic photo polymer etched with 2.3 mm (.0937 inches) raised copy.
- d) Silk-screened First Surface Copy (non-tactile) - Injection molded or extruded ABS plastic or aluminum insert with first surface applied enamel silk-screened copy.

4.

D. Sign Type 1, 2, 3, 5:

1. Tactile sign is to be made from a material that provides for letters, numbers and Braille to be integral with sign plaque material such as: photosensitive polyamide resin, etched metal, sandblasted phenolic or embossed material. Do not apply letters, numbers and Braille with adhesive.
2. Numbers, letters and Braille to be raised 0.793 mm (.0312 inches) from the background surface. The draft of the letters, numbers and Braille to be tapered, vertical and clean.
3. Braille dots are to conform with standard dimensions for literary Braille; (a) Dot base diameter: 1.5 mm (.059 inches) (b) Inter-dot spacing: 2.3 mm (.090 inches) (c) Horizontal separation between cells: 6.0 mm (.241 inches) (d) Vertical separation between cells: 10.0 mm (.395 inches)
4. Entire assembly is painted in specified color. After painting, apply white or other specified color to surface of the numbers and letters. Entire sign is to have a protective clear coat sealant applied.
5. Complete sign is to have an eggshell finish (11 to 19 degree on a 60 degree glossmeter).

E. Sign type 4

1. Ceiling mounted signs required mounting hardware on the sign that allows for sign disconnection, removal and reinstallation and reconnection.

2.5 FABRICATION

- A. Design components to allow for expansion and contraction for a minimum material temperature range of 56 °C (100 °F), without causing buckling, excessive opening of joints or over stressing of adhesives, welds and fasteners.
- B. Form work to required shapes and sizes, with true curve lines and angles. Provide necessary rebates, lugs and brackets for assembly of units. Use concealed fasteners whenever and wherever possible.
- C. Shop fabricate so far as practicable. Joints fastened flush to conceal reinforcement, or welded where thickness or section permits.
- D. Contact surfaces of connected members be true. Assembled so joints will be tight and practically unnoticeable, without use of filling compound.
- E. Signs shall have fine, even texture and be flat and sound. Lines and miters sharp, arises unbroken, profiles accurate and ornament true to pattern. Plane surfaces be smooth flat and without oil-canning, free of rack and twist. Maximum variation from plane of surface plus or minus 0.3 mm (0.015 inches). Restore texture to filed or cut areas.
- F. Level or straighten wrought work. Members shall have sharp lines and angles and smooth sulrfaces.
- G. Extruded members to be free from extrusion marks. Square turns and corners sharp, curves true.
- H. Drill holes for bolts and screws. Conceal fastenings where possible. Exposed ends and edges mill smooth, with corners slightly rounded. Form joints exposed to weather to exclude water.
- I. Finish hollow signs with matching material on all faces, tops, bottoms and ends. Edge joints tightly mitered to give appearance of solid material.
- J. All painted surfaces properly primed. Finish coating of paint to have complete coverage with no light or thin applications allowing substrate or primer to show. Finished surface smooth, free of scratches, gouges, drips, bubbles, thickness variations, foreign matter and other imperfections.
- K. Movable parts, including hardware, are be cleaned and adjusted to operate as designed without binding or deformation of members. Doors and covers centered in opening or frame. All contact surfaces fit tight and even without forcing or warping components.

- L. Pre-assemble items in shop to greatest extent possible to minimize field splicing and assembly. Disassemble units only as necessary for shipping and handling limitations. Clearly mark units for re-assembly and coordinated installation.
- M. No signs are to be manufactured until final sign message schedule and location review has been completed by the Resident Engineer & forwarded to contractor.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Protect products against damage during field handling and installation. Protect adjacent existing and newly placed construction, landscaping and finishes as necessary to prevent damage during installation. Paint and touch up any exposed fasteners and connecting hardware to match color and finish of surrounding surface.
- B. Mount signs in proper alignment, level and plumb according to the sign location plan and the dimensions given on elevation and sign location drawings. Where otherwise not dimensioned, signs shall be installed where best suited to provide a consistent appearance throughout the project. When exact position, angle, height or location is in doubt, contact Resident Engineer for clarification.
- C. Contractor shall be responsible for all signs that are damaged, lost or stolen while materials are on the job site and up until the completion and final acceptance of the job.
- D. Remove or correct signs or installation work Resident Engineer determines as unsafe or as an unsafe condition.
- E. At completion of sign installation, clean exposed sign surfaces. Clean and repair any adjoining surfaces and landscaping that became soiled or damaged as a result of installation of signs.
- F. Locate signs as shown on the Sign Location Plans.
- G. Certain signs may be installed on glass. A blank glass back up is required to be placed on opposite side of glass exactly behind sign being installed. This blank glass back up is to be the same size as sign being installed.
- H. Contractor will be responsible for verifying that behind each sign location there are no utility lines that will be affected by installation of signs. Any damage during installation of signs to utilities will be the sole responsibility of the Contractor to correct and repair.

- I. Furnish inserts and anchoring devices which must be set in concrete or other material for installation of signs. Provide setting drawings, templates, instructions and directions for installation of anchorage devices which may involve other trades.

- - - END - - -

Signage

Sign Type 1


Type D1A - 3" x 9" w/
1-1/2" x 1/32" ADA
Tactile Numerals
& Grade II Braille

Type F - 6" x 9"
Removable F-Unit

VA Seal Watermark
on 5-3/16" x 9"
Clear Acrylic Insert

5-3/16" x 9"
Clear Acetate Insert
w/Copy

#2020 Clear Satin
Anodized Beveled Frame



VA Baltimore, MD

Scale: 1:2	Designer: Peter Van Allen	Drawn By: MEA/XHZ
Date: 9.4.14	Revised:	

Type: D1A/F/W




CREATIVE SIGNAGE SYSTEMS
 9101 51st PLACE COLLEGE PARK, MARYLAND 20740
 PHONE 301.345.3700 FAX 301.220.0289 WWW.CREATIVESIGNAGE.COM

VA/Balti/Dw/F/StandSigns

VA PROJECT NO.: 512-14-102

Section 10 14 00

Signage Sign Type 2



VA Baltimore, MD

Scale: 1:2	Designer: Peter Van Allen	Drawn By: MEA/XHZ
Date: 9.4.14	Revised:	

Type: D1A/W



CREATIVE SIGNAGE SYSTEMS


9101 51st PLACE COLLEGE PARK, MARYLAND 20740
PHONE 301.345.3700 FAX 301.220.0289 WWW.CREATIVESIGNAGE.COM

VA/Balti/Dw/FStandSigns

VA PROJECT NO.: 512-14-102

Section 10 14 00

Signage Sign Type 3



VA Baltimore, MD

Scale: 1:2	Designer: Peter Van Allen	Drawn By: MEA/XHZ
Date: 9.4.14	Revised:	

Type: SA/W



CREATIVE SIGNAGE SYSTEMS



9101 51st PLACE COLLEGE PARK, MARYLAND 20740
 PHONE 301.345.3700 FAX 301.220.0289 WWW.CREATIVESIGNAGE.COM

VA/Balti/Dw/FStandSigns

VA PROJECT NO.: 512-14-102

Section 10 14 00

Signage Sign Type 4



C4 D/F

Type C4 Used for wayfinding at high traffic intersections and for major area identification.

VA Baltimore, MD

Scale: 1" : 8"	Designer: Peter Van Allen	Drawn By: MEA/XHZ
Date: 9.4.14	Revised:	

Type C4 DF



CREATIVE SIGNAGE SYSTEMS

9101 51st PLACE COLLEGE PARK, MARYLAND 20740
 PHONE 301.345.3700 FAX 301.220.0289 WWW.CREATIVESIGNAGE.COM

VA/Balti/Dw/F/StandSigns

Note: All drawings, notations and design themes expressed herein remain the sole property of Creative Signage Systems and may not be reproduced without written consent.

VA PROJECT NO.: 512-14-102

Section 10 14 00

Signage Sign Type 5


Subsurface Black
Arrow

Type F - 6" x 9"
Removable F-Unit

VA Seal Watermark
on 5-3/16" x 9"
Clear Acrylic Insert

5-3/16" x 9"
Clear Acetate Insert
w/Copy

#2020 Clear Satin
Anodized Beveled Frame



VA Baltimore, MD

Scale: 1:2	Designer: Peter Van Allen	Drawn By: MEA/XHZ
Date: 9.4.14	Revised:	

Type: E1/F/W



CREATIVE SIGNAGE SYSTEMS

9101 51st PLACE COLLEGE PARK, MARYLAND 20740
PHONE 301.345.3700 FAX 301.220.0289 WWW.CREATIVESIGNAGE.COM



VA/Balti/Dw/F/StandSigns

20"

TNR Burgundy Copy
Black Diamonds

Gannett Off
White Background
TNR Black Copy

#2020 Clear Satin
Anodized Beveled Frame



VA Baltimore, MD

Scale:	Designer: Peter Van Allen	Drawn By: MEA/XHZ
Date: 9.4.14	Revised:	

Type: C1/W

CREATIVE SIGNAGE SYSTEMS
 9101 51st PLACE COLLEGE PARK, MARYLAND 20740
 PHONE 301.345.3700 FAX 301.220.0289 WWW.CREATIVESIGNAGE.COM

VA/Balti/Dw/F/StandSigns

Note: All drawings, notations and design themes expressed herein remain the sole property of Creative Signage Systems and may not be reproduced without written consent.