

SCALE: NONE

NONE

SCALE: NONE

ONE

NOTE:

PROVIDE CONTROL MODULE TO PROVIDE FULL CONTROL AND MONITORING FROM DDC SYSTEM

NOTES:

1. NORMALLY CLOSED DAMPER TO OPEN WHEN ACTIVATED BY THE SPACE DETECTOR LOCATED AT THE TOP OF THE ELEVATOR HOIST WAY.
2. DAMPER POSITION STATUS TO BE MONITORED BY THE CENTRAL DDC SYSTEM.

SPLIT SYSTEM - CONDENSER UNIT SCHEDULE												
TAG NUMBER	SERVICE	NOMINAL CAPACITY (TONS)	DESIGN AMBIENT (DEG F)	FAN QTY	WEIGHT (LBS)	REFRIGERANT		ELECTRICAL			BASIS OF DESIGN	
						TYPE	COMP. TYPE	VOLTS/ PHASE	MCA	MAX FUSE	MANUF.	MODEL
CU-1	AC-1	2	95	1	175	R-410a	INVERTER	208/3	16.5	20	DAIKIN	RZR24PVJU
NOTES:												
1. FACTORY INSTALLED WIRED LOCKING DISCONNECT SWITCH, FAN SPEED CONTROL.												
2. FACTORY STANDARD WARRANTY												
3. PROVIDE ROOF SUPPORT SYSTEM TO RAISE THE UNIT 12" ABOVE THE ROOF.												
4. LOW AMBIENT CONTROL												
5. PROVIDE CONTROL MODULE FOR CONNECTION TO DDC SYSTEM												

SPLIT SYSTEM - INDOOR UNIT SCHEDULE														
TAG	SERVICE	COOLING CAPACITY (MBH)	SENSIBLE CAPACITY (MBH)	HEATING CAPACITY (MBH)	FILTER TYPE	AIRFLOW HIGH / LOW (CFM)	SOUND RATING (dB-A)	ELECTRICAL				BASIS OF DESIGN		UNIT WEIGHT (LB)
		24	18	—		635 / 470	43	VOLT	PH	MCA	MAX. FUSE	MANUF.	MODEL	
AC-1	SERVICE ELEVATOR MACH RM				REUSABLE			208	1	0.4	15	DAIKIN	FAQ24PVJU	40

NOTES:

1. REMOTE WIRELESS CONTROLLER.
2. INDOOR UNIT POWER TO BE FED FROM OUTDOOR UNIT.

SCALE: NONE

SCALE: NONE

[illegible]