

| WEST ROXBURY VA B51010
V.A. Medical Center
Warehouse Bldg 7
1400 VFW Parkway
West Roxbury, MA 02132
P.O.# 523-B51010

Item	Part Number - Description	Qty
1	<p>- X-Porte Ultrasound Kiosk System with Stand</p> <p>The SonoSite X-Porte is a high resolution, all digital ultrasound kiosk designed to meet the needs of the demanding clinical environment. The X-Porte Kiosk includes: a capacitive multi-touch panel user interface, adjustable high resolution 19" LED monitor for image display and review, a system stand featuring a triple transducer connection, battery pack and a storage basket.</p> <p>In addition to high resolution 2D imaging the system includes the following imaging modes: M-mode, Pulsed Wave Doppler, Continuous Wave Doppler, Velocity Color Doppler, Color Power Doppler and Tissue Doppler Imaging, and Simultaneous M-Mode.</p> <p>The X-Porte kiosk features proprietary software technologies: XDI – Extreme Definition Imaging™, Steep Needle Profiling™, SonoHD2 Imaging Technology, SonoMB® Multibeam Technology, SonoADAPT™ Tissue Optimization Technology, Pulse Inversion Tissue Harmonic Imaging, Color HDTM Technology, AutoGain (see key for Technology descriptions) ,</p> <p>For maximum imaging performance the X-Porte visualization tool features proprietary software technologies: XDI – Extreme Definition Imaging, Steep Needle Profiling, SonoHD2 Imaging Technology, SonoMB Multibeam Technology, SonoADAPT Tissue Optimization Technology, Pulse Inversion Tissue Harmonic Imaging, Color HD Technology, AutoGain</p> <ul style="list-style-type: none"> - XDI Extreme Definition Imaging -shapes the ultrasound beam to pinpoint precision. As a result, tissue resolution is improved and side lobe image artifacts are minimized to produce images with less haze and increased clarity. - Steep Needle Profiling Technology - enhances needle visualization while maintaining image quality of the target and surrounding anatomy. - SonoHD2 Imaging Technology - reduces speckle noise and image artifacts while enhancing tissue margins, thereby dramatically improving contrast and structural resolution. - SonoMB MultiBeam Technology - improves contrast resolution; tissue differentiation of small structures and enhances border delineation. - SonoADAPT Tissue Optimization Technology – provides continuous automatic adaptive manipulation of multiple imaging parameters to reduce manual time consuming system adjustments. - Pulse Inversion Tissue Harmonic Imaging, utilizes higher frequencies from the ultrasound signal to create high resolution images with dramatically cleaner and sharper contrast between structures. - Color HD Technology- increasing color performance, sensitivity and frame rates for more diagnostic information. 	1

Item	Part Number - Description	Qty
	<p>- AutoGain – provides automatic 2D gain image optimization with the push of a button.</p> <p>The Triple Transducers Quick Connect allows 3 transducers to be simultaneously connected to the system, for efficient selection of transducers.</p> <p>Image Storage and Connectivity is accomplished through: - The kiosk has 64GB of on-board Flash memory to retain enough data for 320 exams and features thumbnail review of saved images and video clips. - 6 USB ports for sharing of images (jpeg and bmp) and video clips (AVI) to a PC or Mac. - Embedded Digital Video Recorder for customized digital video capture. - DICOM package with the capability to store image and clips and interface within your PACS network with the complete offering of DICOM Print, Store, Modality Worklist, Perform Procedure Step (PPS), and Storage Commitment. - Wireless capabilities (B and G networking) for transmission of images and information wirelessly. (Subject to Country Certification) - VGA out capability</p> <p>The Kiosk features SonoSite's Visual Guides, a library of animated learning tutorials are featured on-board the kiosk for just in time learning and reference. The learning tutorials are displayed on the control panel so users can view the tutorials and scan simultaneously. Visual Guide packages included are: Ultrasound Basics, Acute Care Procedures, MSK and Anesthesia.</p> <p>X-Porte's reliability and durability are backed by a five-year standard warranty, which is included in the price of the system. Software upgrades to the main system are accomplished through a USB ports on the system.</p> <p>With the purchase of your SonoSite X-Porte, you will receive four consecutive hours of installation training provided by a SonoSite Clinical Specialist. The installation includes: an overview of the product and accessories purchased, training on the features, functions, user interface and system care/maintenance. Additional days of system installation training can be purchased separately as needed.</p> <p>X-Porte Ultrasound Kiosk Transducers: P21XP, L25XP, ICTXP, HFL50XP, C60XP, L38XP, HFL38XP, HSL25XP</p> <p>(1) One Transducer is required with each system purchase. Transducer selection may be changed, and transducers may be added or removed as required to support specific clinical applications.</p>	
2	<p>- P21XP / 5-1 MHZ Transducer</p> <p>P21xp/5-1 MHz multi-frequency, broadband, 21 mm phased array transducer for cardiac, TCD, orbital, abdominal, obstetrics and gynecology exams. This transducer is biopsy compatible with a maximum depth of penetration of 35 cm. Transducers are designed for 1 meter drop test durability.</p>	1
3	<p>- HFL50XP / 15-6 MHZ Transducer</p> <p>HFL50xp/15-6 MHz multi-frequency, broadband, 50 mm linear array transducer for nerve, musculoskeletal, breast and small parts exams. This transducer is biopsy compatible with a maximum depth of penetration of 6 cm. Transducers are designed for 1 meter drop test durability.</p>	1
4	<p>- L38XP / 10-5 MHZ Transducer</p> <p>L38xp/10-5 MHz multi-frequency, broadband, 38 mm linear array transducer for arterial, venous, nerve, and superficial exams. This transducer is biopsy</p>	1

Item	Part Number - Description	Qty
	compatible with a maximum depth of penetration of 9 cm. Transducers are designed for 1 meter drop test durability.	
5	- User Guide, X-Porte, English (Paper) X-porte User Guide (CD Only), English	1
6	- Service Manual, X-Porte X-Porte Ultrasound System Service Manual	1
7	- Service Manual, X-Porte X-Porte Ultrasound System Service Manual	1
8	5-YR-WARRANTY - 60 MONTHS - STANDARD COVERAGE WARRANTY 60 MONTHS - STANDARD COVERAGE WARRANTY <i>Please refer to Warranty Schedule.</i>	1
9	5-YR_SW_MAINT - X-PORTE SOFTWARE MAINTENANCE 5-YR Warranty and FUJIFILM SonoSite Software and Firmware Maintenance - 60 Months - Standard Warranty and Maintenance for FUJIFILM SonoSite Software and Firmware (excludes optional third party software).	1
10	- SonoSite EDGE SonoSite EDGE high-resolution, all-digital, 8.5-pound (3.85 kg) ultrasound system with 12.1in. LED display. This product is designed with SonoSite's proprietary Chip Fusion Technology that integrates digital signal processing and multiple system functions into a custom application-specific integrated circuit (ASIC) microchip. As a result complex system functions that typically require several large circuit boards can be accomplished using a small chip in a compact space. SonoSite EDGE high-resolution, all-digital, 8.5-pound (3.85 kg) ultrasound system with 12.1in. LED display. This product is designed with SonoSite's proprietary Chip Fusion Technology that integrates digital signal processing and multiple system functions into a custom application-specific integrated circuit (ASIC). The purchase of the EDGE visualization tool includes the following software technologies: - 2D grayscale with SonoMB Multi Beam Technology - Auto Gain with SonoADAPT Tissue Optimization Technology - M-Mode - Clips Storage - Application specific calculation packages The EDGE combines the high performance of cart-based systems with the speed, flexibility and durability of hand-carried ultrasound. 8 GB of on-board Flash memory will retain enough data for over 40 standard exams (or 2,400 seconds of clips, 1,200 still frames and 40 report pages) even after power is turned off. The system supports USB media playback, and connectivity is accomplished through one of two USB slots on the system, which allow for direct sharing of images (JPEG) and Clips (MPEG4) to a PC or Mac. Additional connectivity is achieved via the EDGE Mini-Dock, to meet your specific needs. The system supports a HIPAA compliance tool set for the protection of sensitive information and PC direct connectivity capability (through USB Memory Stick or via SiteLink and USB Cable ordered separately). EDGE's reliability and durability are backed by a five-year standard warranty, which is included in the price of the system. Software upgrades to the main system and transducer databases are accomplished through one of two USB	1

Item	Part Number - Description	Qty
	<p>ports on the system. Also includes battery, ultrasound gel, and user guide on a CD (Printed user guides also available as a purchasable option).</p> <p>Additional features available to add to the Edge system include: SonoMBe, PW Doppler, TDI PW, CW Doppler, DICOM, Worksheets, and a full array of multi-frequency, broadband transducers.</p> <p>Included with the purchase of your SonoSite EDGE, you will receive the system battery, ultrasound gel, a user guide CD.</p>	
11	<p>- Color Application Software Package Edge</p> <p>This package provides the following capabilities for the transducers that support these features:</p> <ul style="list-style-type: none"> - Tissue Harmonic Imaging (THI), a capability in which the system transmits at one frequency and receives at a higher harmonic frequency to reduce noise and clutter and improve resolution. - SonoHD Imaging Technology, technology which significantly reduces speckle noise while enhancing tissue margins, thereby dramatically improving contrast and structural resolution. - Velocity color flow imaging provides the clinician with the color sensitivity to perform color Doppler examinations with all transducers during a clinical procedure. - PW Doppler is available on all transducers. - CW Doppler is a quantitative assessment of blood flow with Duplex imaging for higher flow velocities. 	1
12	<p>- SonoMBe, EDGE</p> <p>Proprietary software that enhances the systems ability to aid needle visualization.</p>	1
13	<p>- C11X / 8-5 MHZ Transducer</p> <p>C11x / 8-5 MHz broadband curved array transducer for abdomen, neonatal, vascular, and nerve exams. Supports 2D with SonoMB Multi Beam Technology and Auto Gain capabilities, SonoHD Imaging Technology, M-mode, Color Power Doppler, Velocity Color Flow Doppler, and Pulsed Wave Doppler. 1 meter drop-test durability. Maximum depth is 10 cm.</p>	1
14	<p>- L25X / 13-6 MHZ Transducer Transverse Biopsy Compatible</p> <p>L25x / 13-6 MHz multi-frequency, broadband, 25 mm linear array transducer for nerve, vascular, venous, ophthalmic, musculoskeletal, and superficial exams. Supports 2D with SonoMB Multi Beam Technology and Auto Gain capabilities, SonoHD Imaging Technology, M-mode, Color Power Doppler, Velocity Color Flow Doppler and Pulsed Wave Doppler. Transverse biopsy guide available. 1-meter drop-test durability. Maximum depth is 6 cm.</p>	1
15	<p>- L38xi / 10-5 MHZ transducer Biopsy Compatible</p> <p>L38xi / 10-5 MHz multi-frequency, broadband, 38 mm linear array transducer. Supports 2D with SonoMB Multi-beam Imaging and auto gain capabilities, SonoHD Imaging Technology, M-Mode, Color Power Doppler, velocity Color Flow Doppler, and Pulsed Wave Doppler. Maximum scan depth 9 cm.</p>	1
16	<p>- EDGE Stand</p>	1

Item	Part Number - Description	Qty
	Ergonomic stand and mobile work platform for the EDGE system and transducers. Complete with power supply, mini-dock and accessory basket. OEM peripherals include: B/W or color printer. Unable to use together	
17	P16535 - Triple Transducer Connect (TTC) w/ quick disconnect Three-transducer module for mobile docking system that allows connection of up to three transducers simultaneously while the system is docked in the Stand	1
18	P15200 - User Guide EDGE, English EDGE Ultrasound System User Guide, English	1
19	P15644 - Service Manual, Edge EDGE Ultrasound System Service Manual	1
20	P15644 - Service Manual, Edge EDGE Ultrasound System Service Manual	1
21	S_EDGE_TRADE_IN - S Series to EDGE Customer Loyalty Program <i>Serial No:s/n 03HN5F</i>	1
22	5-YR-WARRANTY - 60 MONTHS - STANDARD COVERAGE WARRANTY 60 MONTHS - STANDARD COVERAGE WARRANTY <i>Please refer to Warranty Schedule.</i>	1
23	L05013 - S Series Update Current software level for the S Series system	1
24	P13984 - SonoMBe, S Series Proprietary software that enhances the systems ability to aid needle visualization. <i>For use with SN=03R9JN</i>	1
25	P07691 - L25X / 13-6 MHZ Transducer Transverse Biopsy Compatible L25x / 13-6 MHz multi-frequency, broadband, 25 mm linear array transducer for nerve, vascular, venous, ophthalmic, musculoskeletal, and superficial exams. Supports 2D with SonoMB Multi Beam Technology and Auto Gain capabilities, SonoHD Imaging Technology, M-mode, Color Power Doppler, Velocity Color Flow Doppler and Pulsed Wave Doppler. Transverse biopsy guide available. 1-meter drop-test durability. Maximum depth is 6 cm.	1
26	P07699 - SLAx / 13-6 MHZ Transducer SLAx / 13-6 MHz transducer is a 26-mm broadband linear array for vascular, venous, nerve, superficial and musculoskeletal exams. Supports 2D, M-Mode, SonoRES, Color Flow Doppler, and Pulsed Wave Doppler. Maximum depth is 6.0 cm. STERIS(R) SYSTEM 1 Compatible.	1
27	P16871 - Triple Transducer Connect (TTC) w/ quick disconnect	2

Item	Part Number - Description	Qty
	Three-transducer module for mobile docking system that allows connection of up to three transducers simultaneously while the system is docked	
28	5-YR-WARRANTY - 60 MONTHS - STANDARD COVERAGE WARRANTY 60 MONTHS - STANDARD COVERAGE WARRANTY	1
29	1-YR-WARRANTY - 12 MONTHS - STANDARD COVERAGE WARRANTY 12 MONTHS - STANDARD COVERAGE WARRANTY (For Designated Products)	1