

WAREHOUSE(119F) B44007

V.A. Medical Center

7305 N MILITARY TR

WPB, FL 33410-6400

PO#: 548-B44007

Line #	Description	Qty
--------	-------------	-----

1	DigitalDiagnost 4.1 HiPerf	1
---	----------------------------	---

DigitalDiagnost is a premium direct digital radiography system with flat detector technology, based on modular components to allow for customization for all radiographic applications and workload requirements. It benefits from years of developmental experience and suggestions from satisfied customers all over the world who have had conventional and digital Philips Bucky systems.

The system combines all the advantages of a digital radiography unit with the latest Philips advanced features for easy and ergonomic workflow. Please note that depending on the particular room setup chosen, some options might not be available or already be included in the setup.

Main benefits at a glance

- Flexible component-based geometry to fit specific needs
- High efficiency and high patient throughput due to powerful automated features
- Uncompromising ergonomics due to complete system integration and special design
- Integrated one, two or three Cesium Iodide (CsI) digital flat panel detector(s), depending on setup
- Ample detector area for full diagnostic information even with large patients
- Dose reduction due to high detector quantum efficiency
- Decrease in the number of repeat exposures due to the reduction of overexposed and underexposed images
- Superb image quality due to state-of-the-art detector technology and exclusive UNIQUE image processing
- Total radiation dose monitoring by an integrated area dose calculator
- Ceiling suspension with handy handle, control buttons, and release brake, as well as convenient color-coding of movements
- Wide 16.5 cm (6.5") LCD display on tube head for clear information and statuses
- Integrated centering laser in the tube head for easy positioning
- Various generators, depending on setup
- Customizable Eleva touch screen user interface
- High flexibility for integrating into hospital network infrastructure
- Support of relevant IHE profiles
- State-of-the-art IT security and patient privacy architecture
- Professional serviceability and remote service capabilities

The ceiling suspension carrying the X-ray tube allows the freedom for a wide range of longitudinal and transverse movements in the room, allowing performing table and vertical stand examinations, as well as lateral projections and free exposures using the SkyPlate detector or PCR cassettes. Thanks to a four-part telescopic column and an award-winning control handle, the system can be operated with only one hand and easily positioned close to the patient with the option to be fully motorized. The clear and wide LCD information display and controls on the tube head, combined with the Eleva alternative workflow concept, automatic tube tracking, detector alignment and move to position functions, provide high projection flexibility plus quick and easy

handling. A convenient room height adjustment at installation allows the system to fit almost any room height, to achieve the necessary source-image distance above the table, and to go down to the floor for lower extremity work.

The innovative Eleva workspot of DigitalDiagnost lets you experience simplicity like never before. Designed with input from customers, it provides a clear and intuitive touch screen user interface. It is easy to learn and use, and is highly configurable to adapt to particular needs and specific workflows, resulting in high room efficiency.

The high workflow automation possible through the Advanced Eleva concept allows concentrating on patients instead of on the system. The touch screen user interface, the integrated generator controls, and the automatic setting of exposure parameters based on patient and examination information coming from the RIS, provide quick and easy access to all functions a busy technologist needs to achieve an efficient workflow. In addition, the Eleva alternative workflow concept provides the flexibility to adapt to particular situations and change the planned examination protocol without readjusting any exposure settings.

The Philips Eleva Workflow plus package provides smart tools for an improved and fast workflow and is complementary to the Advanced Eleva functionality standardly provided with the X-ray system. Especially designed for high throughput environments, the Eleva Workflow plus package helps the user to focus on the patient and the examination instead of on system handling and workflow. Automatic markers are generated, displayed and stored/ printed automatically for CR and DR images. The intuitive RIS- code learning feature allows for “on-the-fly” configuration of new or changed RIS codes directly within the worklist environment. The RIS can be filtered on a detailed level for improved schedule planning and fast access to specific patient information. The “Generator only” mode allows additionally for free exposures on e.g. CR cassettes or film cassettes without the need to schedule the patient in the system worklist. Furthermore, the Eleva Workflow Plus package allows access to Eleva’s “advanced user” environment for individual customization and configuration of the user interface, such as tool bar configuration, user management, analyzing system statistics and adaptation of the anatomical data base and image processing.

The Philips Eleva Review plus package was developed for workflows, where intense image review plays an important role. Dedicated tools help to manipulate, compare, measure and prepare images before being archived in a PACS or being printed on film. The full screen mode allows for improved clinical review and quality management of images. Thanks to the multiple image display (display 1, 2 or 4 images), previous images can be directly compared to newly acquired images. Additional zoom and pan functions, dedicated zoom settings to the point of interest, size calibration and extended measurement functions like distance and angle are required for precise quantitative image analysis. Semi-automatic rotation and free image rotation in 0.5 degree steps provide fast image correction in the case of angulated or oblique projections. Annotations such as free text or pre-defined markers (e.g. L/R) can be customized and freely placed within images.

The simple ranger tool allows for dedicated image processing of an anatomically relevant image area for optimal display of challenging structures, e.g. metal implants or small foreign particles.

Thanks to Philips outstanding UNIQUE (UNified Image Quality Enhancement) advanced multi-resolution image processing, images are always displayed fully processed. UNIQUE provides an optimal contrast harmonization with enhanced details, while the overall impression remains natural. When used in combination with Philips integrated CR, it provides a comparable image impression for all CR and DR images.

The Eleva Advanced Dose Reporting allows printing of the individual patient dose report as well as the cumulative daily dose reports via network connection on a paper printer in PostScript format (not part of this package) for easy dose management.

DigitalDiagnost provides built-in privacy according to HIPAA recommendations, and security and interoperability standards. It integrates seamlessly into the hospital network and provides embedded anti malware measures as well as restricted access to prevent the system from unauthorized use. It supports connection to a Radiology Information System (RIS), to DICOM-compatible diagnostic units and archives and to DICOM imagers, according to the relevant IHE profiles.

## Specifications

- Ceiling Suspension CSM
  - Four-part aluminum telescopic column with spring counter balanced holder for X-ray tube assembly, adaptable to individual room heights
  - Ceiling height at source-image distance 110 cm (44"): 2.65 m to 3.20 m (8' 8.3" to 10' 5.9")
  - Minimum ceiling source distance: 87.1 cm (34.3")
  - Possible room height adjustment: 37.5 cm (14.8")
  - Lowest tube position: 30 cm (11.8") measured from center of beam to the floor
  - Length of rails: base rails 4.3 m (14' 1.3"), optional rails extension 2.7 m (8' 10.3")
  - Longitudinal travel with Comfort Track and Comfort Move: 3.44 m (11' 3.4"), 6.14 m (20' 1.7") with rails extension option
  - Longitudinal travel with Comfort Position: 3.28 m (10' 9.1"), 5.98 m (19' 7.4") with rails extension option
  - Transverse travel: 1.50 m (4' 11") with short transverse rails, 3.22 m (10' 6.7") with long transverse rails
  - Vertical travel: 1.65 m (5' 5.2")
  - Rotation of focal spot around vertical axis of column: 360° ( $\pm 180^\circ$ ), with rotation stop  $+180^\circ/-165^\circ$  and lock position every 45°
  - Angulations of focal spot around horizontal axis:  $\pm 125^\circ$ , lock positions 0° and  $\pm 90^\circ$
  - Prepared for motorized movements in 5 axis
- Control handle
  - Centering device in longitudinal and transversal directions
  - Brake/locking controls and central three-axis brake-release at lowest position of handle
  - Wide 16.5cm (6.5") LCD information display and control buttons
- Collimator
  - Motorized automatic collimation, manual overrule possible, with light field indicator
  - Angle of aperture and rotation: 2 x 15°,  $\pm 45^\circ$ , depending on the collimator (see type number plate)
  - Timer switch: up to 30 s
  - Inherent filter value: <0.3 mm at 100 kV, depending on the collimator
  - Added filters: 2 mm Al or 1 mm Al + 0.1 mm Cu or 1 mm Al + 0.2 mm Cu
  - Source-image distance measurement tape
- Eleva workspot computer
  - Processor: Intel® Core i5-2400 (3.40 GHz, 6 MB Cache) or better
  - Hard disk: 250 GB SATA, 12 GB used for operating system and application software
  - Image storage: 200 GB for typically 4000 images
  - 8 GB memory or better

- 48x CD/DVD reader/ writer
- Ethernet 10/100/1000 Base-T Gigabit
- Geometry interface
- Detector interface
- Integrated generator control
- Memory stick support to access quality control and statistic data
- Keyboard and mouse

#### Comprising

- Ceiling suspension CSM
  - Four-part telescopic column
  - X-ray tube assembly with collimator
  - Control handle with buttons and LCD screen
  - Rail system
  - Installation cables and high voltage cables
  - Set of marker for preferred source-image distance
  - Philips Comfort Track system motorization
- Eleva workspot
  - Eleva workspot computer, keyboard and mouse, cables
  - Eleva application and examination database software and licenses
  - Eleva Workflow Plus license
  - Eleva Review Plus license
  - Eleva Advanced Dose Reporting license
  - Windows 7 system software and licenses
  - UNIQUE advanced multi-resolution image processing
  - Dynamic reconstruction image processing software
  - Shutter and Image Verification tool
  - Solid Core Software and license
  - Instruction for use
  - Quick reference guide
  - User documentation

The Eleva examination Control Advanced combines brilliant image display and excellent ergonomics.

#### Main benefits at a glance

- Takes full advantage of Eleva advanced user interface and ease of use
- Optimizes space in the control room, workflow and efficiency
- Touch technology compatible with rubber gloves
- Wide screen size
- Wide viewing angle
- Calibrated according to DICOM GSDF standard for better image fidelity
- Qualified for second reviewing
- Clear to read & easy to clean glass surface

Its smart design combines two consoles in one, allowing space saving in the control room and a more efficient workflow: the flat 19" LCD color display provides touch screen technology for intuitive and efficient use and the sturdy hardware buttons on the frame offer integrated control of the generator to modify the most frequently adjusted exposure parameters.

For more convenience during particular procedures like trauma, the microwave touch screen technology allows touch use also with rubber gloves. The glass plate in front of the screen ensures clear display and ease of cleaning.

#### Specifications

- 19" flat panel color TFT LCD display
- Resolution 1280 x 1024 pixels
- Luminance 220 cd/m<sup>2</sup>
- Hardware buttons commands: on/off, default examination, help, adjust kV, adjust mA, adjust mS, last used values

#### Comprising

- Active Matrix TFT LCD display with anti-reflex touch front, hard coated top sheet
- Integrated hardware buttons for control of exposure parameters
- Integrated hardware buttons for system power on/off and help
- Software licenses
- User documentation

Uninterruptible Power Supply (UPS) for the Eleva workspot computer and monitor.

The device provides emergency power to the Eleva workspot in case of electrical network power failure, allowing to bridge time to safely store images and complete the last tasks.

It provides instantaneous protection from input power interruptions by means of an integrated battery and electronic circuitry, allowing to continue working for approximately 60 minutes.

#### Specifications

- Allows using the Eleva workspot for approximately 60 minutes after main power interruption
- Typical charging time: approximately 4 hours
- Typical heat emission: 4 W (5 W max) in standby, 86 W (99 W max) in operation
- Dimensions: depth 48.3 cm (19"), width 21 cm (8.3"), height 43.2 cm (17")
- Weight: 25 kg (55 lbs)

#### Comprising

- UPS device including holder for vertical positioning, power cable

For longitudinal carriages of CS monitor ceiling suspension or auxiliary ceiling suspension; length 4.3 M.

Comprising:

- 2 CS rails
- Adjustable end/stops
- Spacer strips
- Fixing parts
- Brake rails

Compatible with:

- CS 2 CS 4
- Monitor ceiling suspension
- Rail extension 9890 010 01622
- Rail for cable carrier 9890 010 02422

## CABINET BOX

Pre-deliverable mounting material.

## Cable Carrier CS

Additional carrier for suspension of cable hose from CS 2/4 or TV- monitor.

Comprising:

- Carriage for CS- ceiling rail with adapter for different cable hoses

Handover OnSite Education: Philips Education Specialists will provide twenty-eight (28) hours of education for up to four (4) students, selected by customer, including technologists from night/weekend shifts if necessary. Students should attend all 28 hours, and must include any OffSite education attendees if applicable. CEU credits may be available if the participant meets the guidelines provided by Philips. Depending on your system configuration, the first four (4) hours onsite may be spent configuring new equipment for specific clinical needs, as well as reviewing important safety features and quality procedures. Please read guidelines for more information. Site must be patient-ready. Philips personnel are not responsible for actual patient contact or operation of equipment during education sessions except to demonstrate proper equipment operation.

Recommendations: In order to enhance customer satisfaction with image quality over the first year, we highly recommend that part# 989801292145, XR Add OnSite Clin Educ 16h is purchased. This training will assist the customer in maximizing the unique image quality pre-sets to suit their facilities needs. Clinical Education highly suggests the image quality visit occur two to four weeks post initial handover.

Education expires one (1) year from equipment installation date (or purchase date if sold separately). Ref # 522-100614

Philips height-adjustable TH digital table has a proven and smart design that makes no compromise on robustness, quality and work efficiency, even with challenging patients and difficult examination conditions. It allows a variety of routine skeletal table examinations.

#### Main benefits at a glance

- X-ray from head to toe, for all radiographic applications
- Easy fine positioning through an eight-way floating tabletop with wide movement range
- Two tabletop widths available, 75 cm (29.5") or 85 cm (33.5")
- Tray to place a 35 x 43 cm (14 x 17") Philips SkyPlate
- Easy-to-operate tray, allowing the positioning of SkyPlate in portrait or landscape orientation
- SkyPlate can be taken out of the table at any time for free exposures
- Motorized height adjustment
- Easy horizontal and vertical patient positioning with large movement range
- Extremely robust with maximum patient load of 375 kg (820 lbs)
- Hands-free operation via large footswitches
- Footswitches lock button to avoid accidental movements and ensure patient safety
- Optional hand switch controlling all movements, which can be clamped at any place on both tabletop sides
- Three-field automatic exposure control chamber for optimal image quality and dose
- Automatic tube height adjustment depending on table height (tracking)
- Automatic collimation for X-ray beam limitation to digital flat detector, according to pre-programmed examination parameters
- Removable grid for optimal image quality and dose
- Convenient grid storage within the detector unit for immediate and safe storage
- Electromagnetic brakes for a high level of patient security

The floating tabletop provides significantly more coverage due to a wide travel range, allowing quick and effortless positioning. Thus the patient can be better examined and not moved during the examination, which is particularly important for emergency and trauma. The high weight capacity enables examination of bariatric patients.

The motorized height adjustment gives a total lift of 40 cm (15.7") to adjust to a comfortable and safe working height. The lowest position allows loading a patient who is in a wheelchair. All motorized height movements and floating tabletop are activated with wide and easy-to-use footswitches. The footswitches can be locked for more safety during examination.

An integrated three-field automatic exposure control chamber ensures optimum image quality at the lowest possible dose even for difficult projections. The removable grid can be conveniently and safely stored directly in the detector unit.

The integrated tray allows placing a Philips SkyPlate in portrait or landscape orientation, to offer full diagnostic information even with large patients. At any time, the detector can be taken out of the table tray to perform free exposures in the room with high flexibility, even for the most challenging projections. This feature is particularly useful to perform laterals, oblique, weight bearing feet or examinations in bed or wheelchair.

#### Specifications

- Maximum patient weight: 375 kg (820 lbs) in static center position, 318 kg (700 lbs) in center with all movements, 210 kg (460 lbs) off center with all movements

- Motorized height adjustment from 51.5 to 91.5 cm (20.3" to 36")
- Floating tabletop of sandwich design with Getalit overlay
- Tabletop size: 240 x 75 cm (7' 10.5" x 29.5"), optional wide tabletop 240 x 85 cm (7' 10.5" x 33.5")
- Tabletop travel: longitudinal  $\pm 60$  cm ( $\pm 23.6$ " ), transverse  $\pm 13$  cm ( $\pm 5.1$ " ) or  $\pm 18$  cm ( $\pm 7.1$ " ) with optional wide tabletop
- Tabletop attenuation equivalent: = 0.75 mm Al (at 100 kV)
- Tabletop edge section: flat locking rails for attaching Philips accessories
- Tray where a Philips SkyPlate can be placed in portrait or landscape orientation
- Footswitches functions: table height adjustment up/down, disengagement of tabletop brakes in longitudinal and transverse directions, ability to switch on cross light in the collimator (all footswitches), footswitch interlock
- Optional hand switch: all footswitch functions for manual operation at the backside of the table
- Detector horizontal travel range:  $\pm 22.7$  cm ( $\pm 8.9$ " )
- Removable grid 40/12/110: 40 lines/cm (100 lines/inch), ratio 12, focus 110 cm (44") for use with source-image distance from 90 to 150 cm (36" to 59")

#### Comprising

- Digital BuckyDiagnost TH height-adjustable table base and tabletop
- Tray for SkyPlate
- Default grid 40/12/110: 40 lines/cm (100 lines/inch), ratio 12, focus 110 cm (44"). A different default grid can be chosen in order questionnaire. Additional grids are available in accessories.
- Software licenses
- Documentation

**3**

#### **Digital VM vertikal stand ext. with fix detector**

**1**

With the VM multipurpose stand extension, Philips redefines the benchmark for high performance rooms with a highly flexible configuration. An outstanding concept featuring a unique movable vertical stand, easy handling and excellent ergonomics, open new perspectives like never before, without any application limitations.

Combined with the Digital TH table, this versatile system is designed for environments with high patient load. It features a revolutionary moveable multi-purpose vertical stand with an integrated detector, which can be used around the table for a perfect complement of the table detector, or away from table for all kind of general x-ray procedures.

#### Main benefits at a glance

- Vertical stand sliding on a floor-mounted rail, optimal for all general X-ray examinations like chest, wall Bucky applications, table work, cross table laterals, and angulated projections
- Optional single-side suspended, motorized height-adjustable TH-S table, with wide floating tabletop, especially designed to use in combination with the VM movable vertical stand
- Movable vertical stand column sliding on a rail along the table for easy placement in various positions at the table or away from the table
- Swiveling detector arm and detector tilting on both horizontal and vertical axes, to allow exact positioning even for difficult projections



- Motorized vertical stand height adjustment, with two different speeds plus manual operation for precise positioning
- Optional motorization of the column on the rail for more automation
- Customizable pre-defined positions (move-to-position) and numerous other well-planned features that significantly reduce the physical demands placed on the technologist
- Easy patient positioning with counterbalanced large movement range
- Large and ergonomic patient grips on both left and right sides of the detector for safe and comfortable patient positioning
- Optional rotatable patient stretch grip on top left or right side of the detector
- Convenient user interfaces on both left and right sides of the detector, for quick and easy adjustment of movements, collimation, field alignment and orientation, selection of automatic exposure control chambers and tracking mode
- Wireless remote control providing all commands of the side user interfaces
- Wide size 43 x 43 cm (17 x 17") integrated digital flat detector
- Five-field automatic exposure control chamber for optimal image quality and dose, and positioning flexibility especially on the table
- Automatic tube height adjustment to detector or table height (tracking)
- Automatic collimation for X-ray beam limitation to digital flat detector, according to pre-programmed examination parameters
- Optional display on vertical stand column, for patient data in the examination room
- Removable oscillating grid for optimal image quality and dose
- Convenient storage for two grids within the detector unit for immediate and safe storage

The VM vertical stand allows positioning the detector vertically alongside the table to easily perform lateral projections without moving the patient. It can also be placed under the table top, on the side of the table detector. Moving the VM vertical stand to the end of the table, it becomes a digital chest unit. Lowering the detector in horizontal or angulated position, it turns into an ideal extremity examinations device.

In vertical position, the motorized height adjustment from 35 to 185 cm (13.8" to 6' 08") measured at center of detector above the floor, gives a total lift of 150 cm (4' 11.1") to adjust to a comfortable and safe working height with a choice of two different speeds.

The wide size 43 x 43 cm (17 x 17") integrated detector covers all relevant anatomy and offers full diagnostic information. Its Cesium Iodide (CsI) technology provides excellent quantum efficiency (DQE) and helps to reduce the required patient dose.

An integrated five-field automatic exposure control chamber ensures to get optimum image quality at the lowest possible dose even for difficult projections, as well as gives positioning flexibility for various examinations without the need of moving the patient. The removable oscillating grid can easily be put in the convenient and safe storage directly in the detector unit.

Not only can the vertical stand be put in numerous positions to achieve the required projection, but the detector is always locked fixed and precise, greatly simplifying patient positioning work for the technologist, especially for lateral and angulated exposures. In combination with the five-field automatic exposure control chamber, it results in optimal image quality and dose even for difficult projections like axial hips.

#### Specifications

- VM movable vertical stand

- Counterbalanced rugged column for motorized and manual movements of the detector
- Vertical movement range: 35 to 185 cm (13.8" to 6' 08"), measured at center of detector
- Horizontal movement range: motorized 3.475 m (11' 4.8"), non-motorized 3.71 m (12' 2.1"), with extension rails motorized or non-motorized 5.5 m (18' 0.5")
- Installation: floor attachment in combination with wall or ceiling attachment
- Multi-purpose detector arm: swiveling range from 0° to 90° (right or left orientated execution), lock-in positions manual or every 15°
- Angle of tilt of detector unit: -20° to +90° on horizontal axis (motorized tilting), +45° to -23° on vertical axis (manual tilting)
- Detector unit size: 59.6x57.5 cm (23.5"x22.6")
- Automatic exposure control (AEC): 5 AEC measuring fields
- Operating: 2 user interfaces (left & right) and wireless remote control
- Removable oscillating grid 40/8/140: 40 lines/cm (100 lines/inch), ratio 8, focus 140 cm (56") for use with source-image distance from 110 to 180 cm (44" to 71")
- Grid storage: for up to 2 grids within the detector unit
- Detector
  - Wide size 43 x 43 cm (17 x 17") integrated digital flat detector with Cesium Iodide (CsI) technology
  - Active detector area 42.0 x 42.5 cm (16.5 x 16.7")
  - Resolution 8.2 megapixel (2840 x 2874 pixels)
  - Pixel pitch 0.148 mm
  - Pixel depth 16 bits
  - Image resolution: up to 3.4 line pairs per mm

#### Comprising

- DigitalDiagnost VM vertical stand and sliding rail
- Digital flat detector 43 x 43 cm (17 x 17")
- Default oscillating grid 40/8/140: 40 lines/cm (100 lines/inch), ratio 8, focus 140 cm (56"). A different default grid can be chosen in order questionnaire. Additional grids are available in accessories.
- Software licenses
- Documentation

4

### Three-phase 80 kW X-ray generator

1

Generator featuring modern architecture based on a modular design using high performance components to enable a customer specific solution.

#### Main benefits at a glance

- Modern architecture based on a modular design using high performance components
- Tube overload protection
- Automatic mains voltage compensation
- Automatic Exposure Control (AEC)
- Fully compatible with VarioFocus (optional)
- Small footprint

The tube overload protection monitors temperature conditions in order to protect tube and housing parts from being damaged or destroyed by overstress. The automatic exposure control sets the exposure time according to exposure voltage and object characteristics in order to automatically obtain the correct exposure.

#### Specifications

- Computer controlled converter X-ray generator
- Converter generator generates high voltage equivalent to DC voltage
- Nominal power (IEC): 80 kW
- Power: 80 kW
- Three phases, 400 - 480 VAC, 50/60 Hz
- Low or dual speed rotor control, depending on tube
- Max voltage: 150 kV
- Max current (at 80 kV): 1000 mA
- mAs product: 0.5 to 850 mAs
- Exposure time: 1 ms to s
- Maximum mains resistance at 400V: 0.2 Ohm
- Maximum mains current at 400V: 160 A

#### Comprising

- Generator 80 kW in cabinet

#### Compatible with

- DigitalDiagnost 3.1 and above
- VarioFocus option
- Philips tube SRO 33100

## 5

### Comfort Position

## 1

With Philips Comfort Position the entire system geometry is motorized to support a fast, smooth, secure and highly automated workflow within the daily routine in the X-ray room. With virtually unlimited positions for the detector in the table or the vertical stand, the tube positioning can be pre-defined, including a position for free exposures with the SkyPlate or CR cassettes. The pre-defined positions are linked to dedicated examinations/ views within the Eleva database. One touch on the Eleva UI selects the desired view including all exposure and processing parameters as well as the appropriate pre-defined position. The movement of the system geometry will be initiated by the remote control inside the X-ray room. Built-in safety measures include collision detection, force limitation, break management and dead-man control to position the system safely with the patient in the room. Once the system has stopped it can be re-started to move to its final position simply by using the remote control.

Collimation and collimation- light are set automatically to further release the user from making manual adjustments for routine procedure steps. Automatic Image Stitching exams (optional) with the fixed detector as well as with the large SkyPlate can be fully performed automatically with the vertical stand or on the table, including precise tube rotation and linear detector movements.

Manual movements or fine positioning of detectors and tube are possible at any time.

The motorization of the X-ray table allows for easy table height adjustments to accommodate the requested working height. This capability removes the need for physical involvement from the user or the patient. The motorization of the vertical stand makes it easy to set the appropriate detector

height according to the height of the patient. The motorized tilting for the VS vertical extends the possible application range to extremities, skeletal examinations, and even under-table examinations using a trolley. This capability offers additional workflow enhancements on the system by enabling the upright Bucky unit to be automatically placed in different pre-defined positions as well as individual positions from  $-20^{\circ}$  to  $+90^{\circ}$ .

With a single click at the tube control, the tube and detector can be linked to keep the source-image-distance (SID) constant between the tube and detector in the table while adjusting the proper working height of the X-ray table (tube tracking). At the vertical stand the tube will be kept centered to the detector while setting the correct height of the detector. For specific examinations, the tube can automatically be positioned off-center to align the X-ray beam with the upper or lower border of the detector.

Additionally for systems with the movable vertical stand VM

The movable vertical stand VM can be tilted with motor assistance for fast placement in the upright position as well as the horizontal (below the table) position. The motorization of the VM column brings further workflow enhancements to the system by enabling automatic horizontal movements of the vertical stand.

It provides an extended move-to-position function, which enables the detector to automatically move from the chest position to the under the table position. This capability is especially advantageous for immobile patients (for trauma, elderly or bigger patients) because the detector can be placed virtually all around the patient instead of moving the patient to the detector. The pre-defined positions help to reduce the amount of physical involvement by the technologist, even for difficult cross-lateral projections.

Main benefits at a glance

- Fully automatic positioning of detectors in the table and wall stand as well as the tube
- The number of pre-defined positions are virtually unlimited and linked to dedicated examinations within Eleva
- Including a free position for free exposures, e.g. in the patient bed or trauma stretcher
- Dedicated safety architecture including built-in collision detection, force limitation, break management, patients zones and dead-man control
- Easy to learn, change and extend
- Manual movements for fine adjustments are possible at any time
- Motorized height adjustable table
- Manual and motorized vertical movement and detector tilting with the vertical stand
- Motorized height adjustable VS vertical stand adjusts from 30 to 180 cm (11.8" to 5' 11")
- Motorized height adjustable VM movable vertical stand adjusts from 35 to 185 cm (13.8" to 6' 08")
- Motorized movement of the VM column
- Convenient user interfaces are located on both the left and right sides of the Bucky unit, for quick and easy adjustment of movements
- Two different speeds, plus manual operation for precise positioning
- Automatic tube height adjustment in vertical direction (Tube Tracking)
- Automatic tube and detector alignment/centering
- Automatic tube positioning for upper, centered or lower detector alignment at vertical stand
- Auto-collimation of the tube, depending on the selected examination
- Automatic tube rotation around the horizontal axis  $\pm 125^{\circ}$

Comprising

- Fully-functional 5 axis motorization of the ceiling suspension CSM
- Motorization of the X-ray table TH or TH-S
- Motorization of detector tray on the table
- Motorization of vertical stand VS or VM
- Dedicated remote control incl. dead- man function
- Software license and documentation

6

### **Philips dual-focal high power SRO 33100 X-ray tube**

1

This Philips dual-focal rotating anode high power X-ray tube can be used for all general radiography applications. It is particularly adapted for examinations requiring high power. The anode target angle allows a 43 x 43 cm (17 x 17") X-ray field at minimum source-image distance of 100 cm (39.4").

Main benefits at a glance

- All radiography applications including bariatric
- High load capacity
- Fast speed-up (1 second)
- Fully compatible with Philips VarioFocus option
- Superimposed dual focal spots
- Fast rotating anode (up to 10,800 revolutions per minute)
- Housing with 90° horn angle position with free air convection cooling

To increase continuous power and minimize downtime for more demanding applications, the tube assembly can be equipped with an additional blower.

Specifications

- Two focal spots: 0.6 and 1.2
- Maximum power: 33 kW with focal spot 0.6, 100 kW with focal spot 1.2
- Anode angle: 13°
- Maximum tube voltage: 150 kV
- Anode heat storage capacity: 220 kJ (300 kHU)
- Assembly heat capacity: 1,247 kJ (1,700 kHU)
- Minimum anode speed: between 8,000 and 10,000 revolutions per minute
- Build in filter 2 mm Al (5/64")
- Total filtration minimum: 2.6 mm Al (105/1024")
- Double tube overload protection
- Total weight: 23 kg

Comprising

- Philips X- ray tube SRO 33100
- X-ray housing ROT 360 or ROT 380 (with CSM cnfiguration)
- Standard clamp fitting
- Two thermal safety switches (tube housing temperature)

7

### **SkyPlate Infrastructure Kit**

1

The SkyPlate Infrastructure Kit is comprised of a wireless access point, a battery charger and a back-up cable.

#### Main benefits

- All-in-one kit to set the customer up with the necessary parts for working with the Skyplate
- State-of-the art components

The access point enables the wireless transmission of clinical images from the SkyPlate to the access point. The access point is hard wired to the radiography system and images are sent from there to the Eleva work station for review, editing and further distribution. The battery charger is designed to charge up to three batteries simultaneously. The back- up cable enables the transmission of clinical images in the case that there is no wireless transmission between the SkyPlate and the wireless access point possible.

#### Specifications

- Wi-Fi access point
  - according to regional requirements for Wi-Fi transmissions
- SkyPlate battery charger
  - It offers a 4 bar charge status color indication per battery: 0-25%, 25-50%, 50-75%, 75-100%.
  - IP41 compliant (IEC60529).
  - Dimensions 172 x 322 x 48 mm
  - SkyPlate back- up cable

#### Compatible with

- SkyPlate large 35 x 43 cm (14 x 17")
- SkyPlate small 24 x 30cm (10 x 12")

8

#### **SkyPlate Small (24 x 30 cm, approx. 10 x 12 inch)**

1

Philips SkyPlate is the next generation of wireless portable detectors. It is an integrated part of the Eleva platform and defines a new dimension of flexibility and freedom within the radiography room.

#### Main benefits at a glance

- DR speed and excellent image quality with the positioning flexibility of CR
- ISO compliant cassette size format 24 x 30 cm, 10 x 12 inch to fit into standard incubators
- Easy handling for difficult applications
- Extremely lightweight: 1.6 kg / 3.5 lbs including battery
- Reduced patient infection risk and easy handling thanks to the detector's cable-free design
- Flexible positioning for lateral or oblique projections
- Instant image display
- State-of-the-art CsI detector technology and UNIQUE image processing for optimal image quality at the lowest dose
- Robust shell of the detector to protect it from water drops and dust

- Easy, precise and safe positioning around the patient, even for difficult projections, provided by a rich set of dedicated accessories
- SkyPlate sharing license, to use the wireless detector on another compatible Philips X-ray system

The SkyPlate small with its detector area of 24 x 30 cm /approx. 10 x 12 inch is especially suitable for difficult projections, such as skull, shoulder, C-spine views. It also fits ideally into common incubator models and enables X-rays of premature babies directly underneath the baby or in a specifically designed tray. Combined with Philips advanced UNIQUE image processing, grid-line removal algorithm and state-of-the-art Cesium Iodide (CsI) technology, it has an excellent detective quantum efficiency (DQE) and helps to reduce the required patient dose. It provides instant image display with superb image quality on the Eleva workspace for increased diagnostic confidence.

Thanks to its cable-free design, the SkyPlate small allows quick and efficient procedures with high hygienic standards. Its robust design offers easy, safe and quick positioning throughout the hospital. Its slim design is optimized for critical environments and minimizes the risk of interfering with life supporting equipment, cables, tubes and catheters.

The detector features advanced low-power WiFi connection technology and is designed according to IEC 60601-1-2. It is compliant with life supporting devices designed according to IEC 60601-1-2 and with pacemakers designed according to IEC (EN) 45502-2-1 when keeping indicated distances. The SkyPlate battery can be removed and recharged in the battery charging station. Once a battery is empty, a new one can be inserted to immediately continue working with the SkyPlate.

SkyPlate sharing allows taking the SkyPlate from the system and using it with other compatible Philips radiography systems. Thereby, SkyPlates can be used efficiently wherever needed and help driving down investment costs. Compatible systems need to carry the SkyPlate Sharing license to participate in SkyPlate sharing.

## Specifications

- Size: 24 x 30 cm (approx. 10 x 12 inch) SkyPlate small wireless digital flat detector with Cesium Iodide (CsI) technology, active detector area 22.20 x 28.41 cm (8.75 x 11.2 inch) (1500 x 1920 pixels), pixel pitch 0.148 mm
- Image resolution: up to 3.38 line pairs per mm
- Typical weight: 1.6 kg (3.5 lbs) including battery
- Maximum patient weight: 100 kg (220 lbs) for weight-bearing examinations
- WLAN network standard: IEEE802.11 a, b, g or n (configurable)
- Encryption: default WPA2
- Optional attachable grid 40/8/130: 40 lines/cm (100 lines/inch), ratio 8, focus 130 cm (51 inch)

## Comprising

- SkyPlate small 24 x 30 cm (approx. 10 x 12 inch)
- Two Exchangeable batteries
- Set of 100 hygienic bags
- Software licenses
- SkyPlate sharing license
- Documentation

Compatible with

- DigitalDiagnost Release 4.x
- MobileDiagnost wDR Release 2.x
- ProGrade 1.x
- Attachable grid for SkyPlate 24 x 30 cm (approx. 10x12 inch) in portrait orientation

**9**

**2nd controller for TH/TF table**

**1**

This extra controller allows the same controls as the table footswitches (table up and down, release of floating tabletop), even if the footswitches are locked. It can be conveniently clamped anywhere on the tabletop side rails and provides a spiral cable for flexible handling.

Comprising:

- Controller with push buttons, spiral cable and integrated clamp mechanism.

Remark: with the BuckyDiagnost TF table, no motorized height adjustments are possible

**10**

**Wide tabletop for  
BuckyDiagnost TH table**

**1**

Completely flat, wide carbon fiber tabletop with plain surface, with convenient aluminum rails on both long sides for fixing accessories.

Specifications

- Type: X-ray transparent floating tabletop
- Material: carbon fiber
- Dimensions: 240 x 85 cm (7' 10.5" x 33.5")
- Tabletop travel: longitudinal  $\pm 60$  cm ( $\pm 23.6$ " ), transverse  $\pm 18$  cm ( $\pm 7.1$ " )
- Attenuation equivalent: less or equal to 0.75 mm (0.03") Al at 100 kV

Comprising

- Wide tabletop
- This option replaces the standard 240 x 75 cm (7' 10.5" x 29.5") tabletop

Remark

With DigitalDiagnost, the wide tabletop must be selected to allow the combination with an additional VM vertical stand.

**11**

**LCD display for VS or VM  
vertical stand**

**1**

LCD information display fixed on the side of the vertical stand column, showing patient and examination data.

This convenient display simplifies workflow, permits closer contact to the patient and avoids errors, which is particularly important for a high patient throughput. All vital parameters are directly displayed while positioning the patient. This allows the patient to be addressed personally and enables the technologist to check parameters without frequently walking over to the Eleva



acquisition workspot.

An adjustable attachment is used to orientate the display to the best convenience.

For privacy reasons, patient information is automatically removed from the display after the first exposure.

#### Specifications

- Type: 16.5cm (6.5") adjustable LCD information display
- Data displayed: patient first and last name, date of birth, ID/Accession number, examination name, grid inserted yes/no
- Compatible with VS and VM vertical stands

#### Comprising

- LCD information display
- Attachment sets for VS and VM vertical stands

12

#### **Adapt. Transf. 415-480 V**

1

#### Comprising:

- three-phase transformer for mains supply voltage adaptation of 415/440/460/480 V to 400 V and for 380/400 V for mains supply without N (neutral) to be built into the base of generator.

#### Compatible with:

- Generator OPTIMS 50, 1tube
- second tube connection
- extension to 65 kW
- extension to 80 kW

13

#### **Automatic Image Stitching**

1

Optional patient stand for better patient positioning

The Automatic Image Stitching software is an advanced orthopedic feature to perform long lengths imaging fully automatically. After the automatic acquisition of the image set (up to three images depending on the requested body part), a composite image is created instantly on the DigitalDiagnost Eleva workspot.

Depending on the examination, images can be acquired in upright position at the vertical stand as well as horizontally on the table.

Due to the precise rotation of the tube around a defined center point, image acquisition is performed with a single focus instead of multiple foci resulting in more accurate image overlaps and minimized image distortion.

UNIQUE image processing is applied automatically to the completed composite image to ensure a harmonized image contrast and image impression. The automatic image stitching package includes tools to measure Cobb's angle, femoral head difference and vertical alignment of the vertical spine.

When combined with PCR integration (DigitalDiagnost R2.x or above), this software also allows performing automatic image stitching with long view PCR cassettes. From DigitalDiagnost R4.1 onwards also automatic image stitching with SkyPlate is supported.

#### Main benefits at a glance

- Simple to use for the technologist by only defining the collimation on the patient
- System automatically acquires the number of necessary images based on the defined collimation
- Automatic tube and detector movements during acquisition
- Acquisition of two or three images depending on collimation
- Single-focus tube rotation to minimize image distortions
- Automatic software stitching images together in one composite image
- Stitching procedures vertically as well as horizontally
- Support of CR and DR stitching (fixed detectors as well as with SkyPlate)
- Dedicated orthopedic measurements included
- Stitching software algorithm based on anatomical structures and lead ruler

#### Specifications with fixed detector

- Number of acquired images: up to 3
- Patient coverage: up to 120 cm (47") with minimum source-image distance 260 cm (102")
- Patient coverage on TH table: up to 90 cm (35.4")
- Overlap area between images: 4.5 cm (1.8")

#### Specifications with SkyPlate

- Number of acquired images: up to 3
- Patient coverage at vertical stand
- Portrait orientation: 117,3 cm (46.2")
- Landscape orientation: 94,5 cm (37.2")
- Patient coverage at the table
- Portrait and landscape orientation: 90 cm (35.5")
- Overlap area between images: 4.5 cm (1.8")

#### Comprising

- Automatic Image Stitching software and license
- Removable stitching oscillating grid:
  - For DigitalDiagnost release 3 and above: grid 40/8/180: 40 lines/cm (100 lines/inch), ratio 8, focus 180 cm (71") for use with source-image distance from 126 to 315 cm (50" to 124")
  - For other DigitalDiagnost versions: grid 36/8/180: 36 lines/cm (90 lines/inch), ratio 8, focus 180 cm (71") for use with source-image distance from 126 to 315 cm (50" to 124")
- Lead ruler
- Stitching Application Guide

#### Compatible with

- High speed rotor control only
- X-Rax Tube SRO0951, SRO2550, SRO33100
- DigitalDiagnost software release 1.5 and above
  - Requires CS Motorization (Rel.1.x, Rel.2.x Rel.3.x and Rel.4.0, optional)
  - Requires min. Comfort Move (from Rel.4.1 onwards)
- VS and VM vertical stands
- Not for systems with VE or VT vertical stand or 2nd ceiling suspension
- Horizontal stitching with VM vertical stand in a single detector configuration (e.g. Flex Room) requires the TH-S table

Remark: Ceiling suspension with long transverse rails is recommended to easily reach the necessary source-image distance of 3 m (118")

**14** **Package incl. Print, Image Export, WLM, MPPS,Media** **1**  
 This package provides all DICOM communication features available with the Eleva platform:

- DICOM Worklist Management
- DICOM MPPS
- DICOM Image Export (including Storage Commitment)
- DICOM Print
- DICOM Media

For further details, please refer to the DICOM Conformance Statement.  
 Buying this feature once for a system will make the functionality available on all Eleva workspots that have been purchased for this system.

#### DICOM Worklist Management

Interface to Radiology Information System (RIS).  
 Worklist handling via a DICOM Basic Worklist Management (BWLM).

The DICOM connection allows the Eleva workspot to automatically load the acquisition modality's worklist from a RIS server. The worklist query can be performed broad (generic) or specific (patient oriented) and both interactively (on operator request) and automatically (in the background).

#### DICOM MPPS

DICOM Modality Performed Procedure Step (MPPS)  
 DICOM service for notifying the RIS server about start and end of performed procedure steps. The messages contain references to the originating worklist items (patient and procedure data), a list of exported DICOM images and post exposure data.

MPPS requires that the DICOM Worklist Management feature is enabled.  
 Note: for Essenta DR, Essenta DR Compact and PCR Eleva systems, generator data will not be reported automatically.

#### DICOM Image Export

## DICOM Storage and DICOM Storage Commitment

The DICOM Image Export feature provides the DICOM Storage service to send images to PACS, archive or any other DICOM destination in DICOM format.

The Eleva workspot supports DICOM Greyscale Display Standard. Calibration of Eleva workspot and the receiving DICOM node will result in consistently same high image quality. DICOM Image Export also includes the DICOM Storage Commitment service, allowing the Eleva workspot to be informed by storage destination if images have been securely stored. This trigger is used by the Eleva workspot to allow related images to be deleted locally.

## DICOM Print

DICOM Print interface for manual and automatic printing.

DICOM Print allows for manual and automatic printing directly from the Eleva workspot. It enables the user to transfer images to a networked DICOM imager with the choice of different printing modes:

- Autoprint: automatic printing of images on predefined film layouts according to the examination
- Manual print: Manual image placement on predefined film layouts or image placement on free layout composing

Please note that only printing via DICOM protocol is possible.

## DICOM Media

Write media in DICOM format.

This feature provides the possibility to write all Patient images, Studies and single images onto CDs or DVDs directly on the Eleva workspot.

The Eleva workspot will burn CDs or DVDs, which comply to the DICOM Media Interchange format.

Each CD or DVD will include a standalone Philips DICOM viewer.

Viewing the CD or DVD content will be possible on:

- Any workstation that supports the DICOM Media Interchange format
- Any standard PC with the help of the Philips DICOM viewer on the CD or DVD

Please note that viewing images from CD or DVD will not be possible on the Eleva workspot directly.

## Comprising

- DICOM Worklist Management software license
- DICOM MPPS software license
- DICOM Image Export software license
- DICOM Print software license
- DICOM Media software license

## Compatible with

- DigitalDiagnost 4.0 and above
- DuraDiagnost 2.0 and above
- MobileDiagnost wDR 2.0 and above
- ProGrade 1.0 and above
- 

15

### **Dose Reporting in DICOM Structured Report format**

1

This DICOM service allows exporting patient radiation dose details in the Structured Report DICOM standard format.

Main benefits at a glance

- Standard, modern and comprehensive format for exporting patient radiation exposure information
- Exports dose information on study (accumulated) and exposure levels
- Allows detailed exposure dose monitoring on the PACS or dedicated dose management system

Typically, one dose report is created at the end of each procedure step performed on the system. This dose report collects together all the irradiation events from the procedure step and cumulates all dose values for the procedure step as a whole.

By exporting patient radiation dose in a comprehensive, very detailed and standard format, DICOM Structured Report allows to perform precise dose monitoring and analysis on the PACS or with a dedicated dose management system. This assists institutions to ensure their policies, procedures and protocols are adequate and being followed appropriately in the department. Moreover, it can help determining how changes in techniques and protocols impact radiation dose as well as image quality, to maintain patient doses As Low As Reasonably Achievable (ALARA).

Comprising

- Software license

Compatible with

- DigitalDiagnost 3.1 and above
- MobileDiagnost wDR 1.1. and above (Dose Area Product Meter required)
- EasyDiagnost 5.0
- ProGrade Rel 1 and above

16

### **Clinical Quality Control software**

1

This powerful image statistic tool provides the advanced user with functionality to analyze rejected images regarding operators and rejection reasons. It serves as well for monitoring and analyzing general parameters. The data files can be downloaded in standard format for further usage or archiving on a PC.

It perfectly supports the quality standards of the department and teaching situations.

Buying this feature once for a system will make the functionality available on all Eleva workspots that have been purchased for this system.

Note: for Essenta DR, Essenta DR Compact, EasyUpgrade DR and PCR Eleva systems, generator data will not be reported automatically.

Comprising

- Software license

Compatible with

- DigitalDiagnost 2.0 and above
- DuraDiagnost 1.0 and above
- Essenta DR 1.0 and above
- Essenta DR Compact 1.0 and above
- MobileDiagnost wDR
- EasyUpgrade DR 1.0 and above
- PCR Eleva 1.0 and above
- ProGrade Rel 1 and above

**17** **SkyPlate cable and holder pack** **1**

Users may in some cases want to disable the WiFi connection to the SkyPlate detector on purpose. In order to operate the SkyPlate without WiFi connection the 7m (23') SkyPlate cable can be connected. System communication to the SkyPlate and image data transfer are performed securely also in cases when the WiFi connection is lost.

The wall mountable cable holder was designed to store the SkyPlate cable properly in the X-Ray room.

Comprising

- 7m (23') SkyPlate cable
- Connectors
- Wall mountable holder for the SkyPlate cable

Compatible with

- DigitalDiagnost Rel. 4.1
- ProGrade Rel. 1.1
- Not to be used with previous releases.

**18** **Stand for easy patient positioning** **1**

The patient support is a movable stand recommended to facilitate long length acquisitions like legs and spine stitching procedures with a vertical stand.

Main benefits at a glance

- Makes stitching examinations easy and reliable by having the patient standing comfortable, confident and still
- Comfortable and secure for the patient to stand on, thanks to a wide and stable footplate and large height adjustable handles to hold to
- Easy to step on, thanks to a low height profile step
- Four wheels allow easy placement in front of the vertical stand and storage
- Metal fasteners on the floor to place the wheels in and lockable wheels, for precise, stable and secure placement in front of the vertical stand

#### Specifications

- Height: 199 cm (78.3")
- Width: 111 cm (43.7")
- Length: 88.1 cm (34.7")
- Weight: 70 kg (154 lbs)
- Maximum patient weight: 225 kg (496 lbs)

#### Comprising

- Patient support for stitching
- Label for color blind user

#### Compatible with

- DigitalDiagnost vertical stands VE, VT, VS and VM
- DigitalDiagnost release 1.3.1 and above
- Automatic Image Stitching license is required to stitch the individual images together
- Ceiling suspension with long transverse rails is recommended to easily reach the necessary source-image distance of at least 3 m (118")

19

#### **Mobile holder for the wireless portable detector**

1

The wireless detector mobile holder is designed to take full advantage of the wireless portable detector to perform free exposures in optimal conditions.

#### Main benefits at a glance

- Mounted on wheels for easy moving and positioning in the room
- Holds the wireless portable detector in a safe and precise position
- Very easy to put the detector in and to take it out
- High detector positioning flexibility
- Can hold the wireless portable detector with or without a grid on it
- Brakes on the wheels for fixed and safe positioning
- Also compatible with 35 x 43 cm (14 x 17") CR cassettes

The mobile holder provides outstanding positioning flexibility for the wireless portable detector. Mounted on wheels, it is easily positioned in the room and all around the patient. With or without a grid on it, the wireless portable detector can be held in various positions depending on projection requirements. The positioning is achieved quickly and easily, thanks to very intuitive use and self-

locking joints. Featuring a height adjustable arm with swivel, the detector is safely held and can be lifted, tilted, swiveled or rotated to the best convenience.

#### Specifications

- Dimensions: length 68 cm (26.8"), width 67 cm (26.4"), height 150.7 cm (59.3")
- Vertical movement range of holder arm: 68 to 128 cm (26.8 to 50.4"), center of large portable detector
- Weight: 53.2 kg (117 lbs)

#### Comprising

- Mobile detector holder

#### Compatible with

- Wireless portable detector 35 x 43 cm (14 x 17") and CR cassettes 35 x 43 cm (14 x 17")

20

#### **Bed holder for the wireless portable detector 1**

The wireless detector bed holder is designed to take full advantage of the wireless portable detector to perform free exposures at the patient bed.

#### Main benefits at a glance

- Slim design for easy positioning at the patient bed, Bucky table or trolley
- Holds the wireless portable detector in a safe and precise position, in portrait or landscape orientation
- Can hold the detector in a tilted position for angulated projections
- Very easy to put the detector in and to take it out
- Can hold the wireless portable detector with or without a grid on it
- Also compatible with 35 x 43 cm (14 x 17") CR cassettes

#### Specifications

- Dimensions: length 41.5 cm (16.3"), width 23 cm (9.1"), height 72 cm (28.3")
- Weight: 4 kg (8.8 lbs)

#### Comprising

- Bed holder

#### Compatible with

- Wireless portable detector 35 x 43 cm (14 x 17") and CR cassettes 35 x 43 cm (14 x 17")

21

#### **Grid 44/8/130 Portrait for SkyPlate large 1**



Attachable, fixed grid in portrait orientation for SkyPlate large 35 x 43 cm (14 x 17").

#### Main benefits at a glance

- Easy to attach/detach to/from the SkyPlate, thanks to its click-on mechanism
- Convenient handle for safe and easy handling
- For examinations where the detector is used in portrait orientation
- Can be used with source-image distance from 96 to 203 cm (38 to 80 inch)
- Fiber interspaces and carbon fiber cover plates ensure higher contrast and lower required dose than conventional aluminium interspaces grids
- Combined with Philips advanced UNIQUE image processing and grid-line correction algorithm, it provides optimal image quality for increased diagnostic confidence

#### Specifications

- Fixed grid 44/8/130: 44 lines/cm (112 lines/inch), ratio 8, focus 130 cm (51 inch), for source-image distance from 96 to 203 cm (38 to 80 inch)
- Fiber interspaces and carbon fiber cover plates
- Interspaces in portrait orientation
- Dimensions: 46.8 x 47.6 x 2.5 cm (18.4 x 18.8 x 1 inch), including handle
- Weight: 1.9 kg (4.2 lbs)

#### Comprising

- Attachable, fixed grid

#### Compatible with

- SkyPlate large 35 x 43 cm (14 x 17")

22

#### **Grid 40/8/130 Landscape for SkyPlate large**

1

Attachable, fixed grid in landscape orientation for SkyPlate large 35 x 43 cm (14 x 17").

#### Main benefits at a glance

- Easy to attach/detach to/from the SkyPlate, thanks to its click-on mechanism
- Convenient handle for safe and easy handling
- For examinations where SkyPlate is used in landscape orientation
- Can be used with source-image distance from 100 to 185 cm (39 to 73 inch)
- Fiber interspaces and carbon fiber cover plates ensure higher contrast and lower required dose than conventional aluminium interspaces grids
- Combined with Philips advanced UNIQUE image processing and grid-line correction algorithm, it provides optimal image quality for increased diagnostic confidence

#### Specifications

- Fixed grid 40/8/130: 40 lines/cm (100 lines/inch), ratio 8, focus 130 cm (51 inch), for source-image distance from 100 to 185 cm (39 to 73 inch)

- Fiber interspaces and carbon fiber cover plates
- Interspaces in landscape orientation
- Dimensions: 46.8 x 47.6 x 2.5 cm (18.4 x 18.8 x 1 inch), including handle
- Weight: 1.9 kg (4.2 lbs)

Comprising

- Attachable, fixed grid

Compatible with

- SkyPlate large 35 x 43 cm (14 x 17")

**23**

### **Protector for SkyPlate**

**1**

The SkyPlate protector has been designed to be placed over the SkyPlate detector on the floor when performing an antero-posterior view during a weight bearing feet examination, allowing to exam patients up to 220 kg (485 lbs).

Main benefits at a glance

- Allows performing of weight bearing feet examinations with patients up to 220 kg (485 lbs)
- Easy positioning over the wireless portable detector on the floor
- Convenient handle for positioning and carrying
- Slim and stable design for secure patient examination
- Also compatible with 35 x 43 cm (14 x 17") CR cassettes

Specifications

- Attenuation equivalent: less than 1.1 mm (0.04") Al at 100 kV
- Maximum patient weight: 220 kg (485 lbs)
- Dimensions: 51 x 43 x 5 cm (20.1 x 19.9 x 2 inch)
- Weight: 2.9 kg (6.4 lbs)

Comprising

- SkyPlate protector

Compatible with

- SkyPlate large 35 x 43 cm (14 x 17") and CR cassettes 35 x 43 cm (14 x 17")

**24**

### **Wall mountable holder for WPD Grids or SkyPlate**

**1**

The wall mounted holder is designed to either safely park the grids of a wireless portable detector (WPD) or SkyPlates in both sizes (large and small) when not used. SkyPlates can be placed with or without grids or with handle.

With its robust, painted metal design, it is made to be fixed on the wall in the radiography room for convenient, safe and quick grids handling.

Specifications

- Holds 2 wireless portable detector grids or
- Holds 2 SkyPlates (large or small) incl. grids or handle.
- Dimensions (approximately): depth 15 cm (5.9"), width 60 cm (23.6"), height 25 cm (9.8")
- Weight (approximately): 4.8 kg (10.3 lbs)

Comprising

- Holder and wall mounting accessories

**25**

**Handle for SkyPlate Large 1**

Attachable frame with handle for SkyPlate large 35 x 43 cm (14 x 17").

Main benefits at a glance

- Easy to attach/detach to/from the SkyPlate, thanks to its click-on mechanism
- Convenient handle for safe and easy handling

Specifications

- Dimensions: 46.8 x 47.6 x 2.5 cm (18.4 x 18.8 x 1 inch), including handle
- Weight: 1 kg (2.2 lbs)

Comprising

- Attachable frame with handle

Compatible with

- SkyPlate large 35 x 43 cm (14 x 17")

**26**

**Additional SkyPlate battery 1**

The additional battery for Philips SkyPlate extends the SkyPlate uptime and is recommended for workflows with increased patient throughput or sensitive environments such as emergency departments or intensive care units.

Comprising:

- One rechargeable battery for Philips SkyPlate
- Documentation

Compatible with

- Philips SkyPlate large
- Philips SkyPlate small

**27**

**Stretch grip f. wall stands 1**

To keep the patient's arm overhead or beside the Bucky unit during exposure.

To be insert at the Bucky unit at right or left side.

Comprising:

- Arm rest, U- shaped for different grip height, tiltable from –90° to +90° for height and side position
- wall holder for parking

Compatible with:

- BuckyDiagnost VS (advanced package)
- BuckyDiagnost VS with digital detector and DigitalDiagnost VM

28

### Trade in Allowance

1

Customer represents and warrants that (i) Customer has, and shall have when title passes, good and marketable title to the equipment being traded in and (ii) has the authority to effect such trade in.

Product: 712050 Digital Diagnost  
Serial Number: 80220  
Manufacturer: PHILIPS HEALTHCARE

Trade-In authorization number: 35570

De-install Date: Not later than 180 days after receipt of Order

Customer will be trading-in equipment that is described on the attached System Disclosure Form (the "Trade-In"), which Trade-In the parties agree (i) will be removed on the De-install Date and (ii) is currently in the condition as represented on the System Disclosure Form. In addition, the parties agree as follows:

1. Customer represents and warrants that Customer has good and marketable title to the Trade-In as of the date of this Quotation and will have good and marketable title when Philips removes the Trade-In from Customer's site (the "Removal Date");
2. Title to the Trade-In shall pass from Customer to Philips on the Removal Date, unless otherwise agreed by Philips and the Customer;
3. Notwithstanding anything to the contrary in any Business Associate Addendum, Customer represents and warrants that as of the Removal Date all Protected Health Information will have been de-identified or removed from the Trade-In;
4. Philips may test and inspect the Trade-In prior to de-installation. If the condition of the Trade-In is not substantially the same on the Removal Date (ordinary wear and tear excepted) as it is identified on the System Disclosure Form, then Philips may reduce the price quoted for the Trade-In;
5. If the removal date is delayed until after the De-Install Date, unless Philips causes the delay, then Philips may reduce the price quoted for the Trade-In by six percent (6%) per month.
6. Philips is responsible for normal de-installation costs of the Trade-In.
7. The trade-in value will not include costs associated for any facility modifications and/or rigging required for de-installation and must be accounted for separately.
8. Customer is responsible for all plumbing necessary to properly drain coolant from chiller system and cap the lines.
9. Prior to the Removal Date, Customer shall remove from the room all equipment that is not being de-installed.