

one eighth inch = one foot
one quarter inch = one foot
one eighth inch = one foot
three eighths inch = one foot
one half inch = one foot
three quarters inch = one foot
one inch = one foot
one and one half inches = one foot
two inches = one foot
three inches = one foot
four inches = one foot
five inches = one foot
six inches = one foot
seven inches = one foot
eight inches = one foot
nine inches = one foot
ten inches = one foot
eleven inches = one foot
twelve inches = one foot
thirteen inches = one foot
fourteen inches = one foot
fifteen inches = one foot
sixteen inches = one foot
seventeen inches = one foot
eighteen inches = one foot
nineteen inches = one foot
twenty inches = one foot
twenty one inches = one foot
twenty two inches = one foot
twenty three inches = one foot
twenty four inches = one foot
twenty five inches = one foot
twenty six inches = one foot
twenty seven inches = one foot
twenty eight inches = one foot
twenty nine inches = one foot
thirty inches = one foot
thirty one inches = one foot
thirty two inches = one foot
thirty three inches = one foot
thirty four inches = one foot
thirty five inches = one foot
thirty six inches = one foot
thirty seven inches = one foot
thirty eight inches = one foot
thirty nine inches = one foot
forty inches = one foot
forty one inches = one foot
forty two inches = one foot
forty three inches = one foot
forty four inches = one foot
forty five inches = one foot
forty six inches = one foot
forty seven inches = one foot
forty eight inches = one foot
forty nine inches = one foot
fifty inches = one foot
fifty one inches = one foot
fifty two inches = one foot
fifty three inches = one foot
fifty four inches = one foot
fifty five inches = one foot
fifty six inches = one foot
fifty seven inches = one foot
fifty eight inches = one foot
fifty nine inches = one foot
sixty inches = one foot
sixty one inches = one foot
sixty two inches = one foot
sixty three inches = one foot
sixty four inches = one foot
sixty five inches = one foot
sixty six inches = one foot
sixty seven inches = one foot
sixty eight inches = one foot
sixty nine inches = one foot
seventy inches = one foot
seventy one inches = one foot
seventy two inches = one foot
seventy three inches = one foot
seventy four inches = one foot
seventy five inches = one foot
seventy six inches = one foot
seventy seven inches = one foot
seventy eight inches = one foot
seventy nine inches = one foot
eighty inches = one foot
eighty one inches = one foot
eighty two inches = one foot
eighty three inches = one foot
eighty four inches = one foot
eighty five inches = one foot
eighty six inches = one foot
eighty seven inches = one foot
eighty eight inches = one foot
eighty nine inches = one foot
ninety inches = one foot
ninety one inches = one foot
ninety two inches = one foot
ninety three inches = one foot
ninety four inches = one foot
ninety five inches = one foot
ninety six inches = one foot
ninety seven inches = one foot
ninety eight inches = one foot
ninety nine inches = one foot
one hundred inches = one foot

FLOOR DRAIN & CLEANOUT SCHEDULE			
TAG	DESCRIPTION	MANUF. & MODEL #	REMARKS/ APPLICATIONS
FD-A	GENERAL PURPOSE, NICKEL BRONZE FLOOR DRAIN WITH 8" ROUND STRAINER & 1/2" TRAP PRIMER CONNECTION	JAY R. SMITH FIG. 2010-A-P050	SEE PLUMBING PLANS FOR SIZES
FD-B	SAME AS FLOOR DRAIN FD-A, EXCEPT WITH 7" ROUND HUB STRAINER	JAY R. SMITH FIG. 2010-F37NB-P050	SEE PLUMBING PLANS FOR SIZES
CODP	CLEANOUT DECKPLATE	JAY R. SMITH FIG. NO. 4020	COORDINATE FINISH WITH CONTRACTING OFFICER'S REPRESENTATIVE (COR)
TP-1	AUTOMATIC TRAP PRIMER VALVE WITH AIR GAP FITTING	PRECISION PLUMBING PRODUCTS PR-500 TRAP PRIMER VALVE WITH AG-500 AIR GAP FITTING	LOCATE IN A CONCEALED SPACE. PROVIDE 12x12 ACCESS DOOR IF REQUIRED. INSTALL PER MANUFACTURER'S INSTRUCTIONS.
TP-2	AUTOMATIC TRAP PRIMER VALVE WITH DISTRIBUTION UNITS AND AIR GAP FITTING.	PRECISION PLUMBING PRODUCTS PR-500 TRAP PRIMER VALVE WITH DU-2 DISTRIBUTION UNIT & AG-500 AIR GAP FITTING.	LOCATE IN A CONCEALED SPACE. PROVIDE 12x12 ACCESS DOOR IF REQUIRED. INSTALL PER MANUFACTURER'S INSTRUCTIONS.
NOTES: 1. COORDINATE FLOOR DRAINS WITH FLOORING MANUFACTURER/INSTALLER AND LAYOUT. 2. VERIFY THAT AUTOMATIC TRAP PRIMERS ARE REQUIRED BY CONTRACTING OFFICER'S REPRESENTATIVE (COR). PROVIDE TRAP PRIMERS FOR FLOOR DRAINS AS INDICATED ON THE DRAWINGS. INSTALL OFF NEAREST CW MAIN PER MANUFACTURER'S INSTRUCTIONS. 3. REFER TO PLUMBING PLANS FOR FLOOR DRAIN SIZES. 4. MODEL NUMBERS LISTED IN SCHEDULE ARE FOR GENERAL REFERENCE ONLY AND NOT FOR ORDERING. CONTRACTOR SHALL REVIEW MODEL NUMBERS AND SPECIFIED FEATURES WITH THE FACTORY BEFORE PLACING THEIR FINAL ORDER.			

PLUMBING FIXTURE SCHEDULE							
TAG	DESCRIPTION	WASTE	VENT	HOT WATER	COLD WATER	MANUFACTURER & MODEL NO.	REMARKS & APPLICATIONS
WC-A	VITREOUS CHINA ELONGATED WATER CLOSET, FLOOR MOUNTED, TOP SPUD, 1.6 GPF, BATTERY OPERATED FLUSH VALVE, HEAVY DUTY OPEN FRONT NO COVER SEAT	4"	2"	-	1-1/4"	KOHLER MODEL NO. K-436B WITH SLOAN MODEL NO. 111-SMO FLUSH VALVE AND OLSONITE MODEL NO. 855C SEAT	ADA HEIGHT - 17" TO RIM
LAV-A	WALL HUNG VITREOUS CHINA 20"x27" LAVATORY, 4 INCH CENTERS, GOOSENECK FAUCET WITH WRIST BLADE TYPE HANDLES, GRID STRAINER	1-1/2"	1-1/2"	1/2"	1/2"	AMERICAN STANDARD MODEL NO. 0355.012 WITH CHICAGO FAUCETS MODEL NO. 802-V317CP FAUCET	ADA HEIGHT - MOUNT AT 34" AFF. OFFSET TRAP AT WALL & INSULATE PIPING FOR ADA USE.
LAV-B	OVAL SOLID SURFACE LAVATORY, 8 INCH CENTERS, GOOSENECK FAUCET WITH WRIST BLADE TYPE HANDLES, GRID STRAINER	1-1/2"	1-1/2"	1/2"	1/2"	LAVATORY BY G.O. WITH CHICAGO FAUCETS MODEL NO. 802-V317CP FAUCET	OFFSET TRAP AT WALL & INSULATE PIPING FOR ADA USE.
SK-A	SINK, 18x16x7 STAINLESS STEEL, SINGLE COMPARTMENT COUNTERTOP SINK WITH 2 HANDLE, ADA COMPLIANT DECKMOUNT 2.2 GPM FAUCET & BASKET STRAINER DRAIN	2"	1-1/2"	1/2"	1/2"	ELKAY MODEL NO. PSR1918 WITH LK35 DRAIN FITTING & WITH CHICAGO FAUCETS MODEL NO. 1100-317ABCP FAUCET	OFFSET TRAP AT WALL & INSULATE PIPING FOR ADA USE.
SK-B	32x18x9" OVERALL DIMENSION STAINLESS STEEL, DOUBLE COMPARTMENT UNDERMOUNT SINK WITH 12.25"x16.5" & 16.5"x16.5" INTERIOR COMPARTMENTS. TWO FAUCETS, L-TYPE SWING SPOUT & WRISTBLADE FAUCET AND SINGLE BLADE HANDLE WITH PULL OUT HAND SPRAY FAUCET & BASKET STRAINER DRAINS.	2"	1-1/2"	(2) 1/2"	(2) 1/2"	ELKAY MODEL NO. ELUHA00321793219 WITH LK98 DRAIN FITTING & WITH CHICAGO FAUCETS MODEL NO. 1100-317ABCP & ELKAY MODEL NO. LK6000CR FAUCETS	REFER ARCHITECTURAL PLANS FOR TRIM PLACEMENT.
SK-C	16x18x6-7/8" STAINLESS STEEL, SINGLE COMPARTMENT UNDERMOUNT SINK WITH GOOSENECK & WRISTBLADE FAUCET & BASKET STRAINER DRAIN.	2"	1-1/2"	1/2"	1/2"	ELKAY MODEL NO. ELUHAD131655PD WITH LK35 DRAIN FITTING & WITH CHICAGO FAUCETS MODEL NO. 895-317ABCP FAUCET	
SK-D	17x17x9" STAINLESS STEEL, SINGLE COMPARTMENT UNDERMOUNT SINK WITH GOOSENECK & WRISTBLADE FAUCET & BASKET STRAINER DRAIN	2"	1-1/2"	1/2"	1/2"	ELKAY MODEL NO. ECTRU17179 WITH LK35 DRAIN FITTING & WITH CHICAGO FAUCETS MODEL NO. 895-317ABCP FAUCET	OFFSET TRAP AT WALL & INSULATE PIPING FOR ADA USE.
SH-A	PRESSURE BALANCED SHOWER MIXING VALVE OPERATING AT 2.5 GPM FLOW RATE WITH SHOWER HEAD W/FLOW CONTROL, WALL/HAND HELD SHOWER, 5' HOSE, 30" SLIDE BAR, DIVERTER AND ADDITIONAL INDIVIDUAL MIXING VALVE W/WALL BOX.	2"	1-1/2"	1/2"	1/2"	SYMMONS MODEL NO. BP-56-500-830-V PRESSURE BALANCED SHOWER MIXING VALVE ASSEMBLY WITH LEONARD MODEL NO. 170-LF	COORDINATE W/ARCHITECTURAL DRAWINGS & EXISTING CONDITIONS TO LOCATE TRIM & MIXING VALVE. REFER TO SHOWER PIPING SCHEMATIC.
SH-B	SAME AS SH-A EXCEPT PROVIDE HAND HELD SHOWER WITH 10 FEET OF HOSE.	2"	1-1/2"	1/2"	1/2"	SAME AS SH-A EXCEPT COORDINATE W/SYMMONS TO PROVIDE TWO 5 FOOT HOSE LENGTHS WITH CONNECTION FITTING.	COORDINATE W/ARCHITECTURAL DRAWINGS & EXISTING CONDITIONS TO LOCATE TRIM & MIXING VALVE. REFER TO SHOWER PIPING SCHEMATIC.
BT	SPA BATHER RECLINING BATHTUB SYSTEM WITH AUTO-FILL & BATTERY BACK-UP	2"	1-1/2"	3/4"	3/4"	ARJOHUNTLEIGH GETINGE PARKER BATH	FIELD COORDINATE PLUMBING CONFIGURATION WITH MANUFACTURER'S INSTALLATION INSTRUCTIONS.
WM-A	WASHING MACHINE WALL BOX, GALVANIZED W/CENTER DRAIN OUTLET AND TOP SUPPLY VALVE CONNECTIONS	2"	1-1/2"	1/2"	1/2"	GUY GRAY MODEL NO. BB200TS	
FBS	FLUSHING RIM SINK 20x25x8 - FLOOR MOUNT W/RIM GUARDS, WRIST BLADE FAUCET VACUUM BREAKER & WALL BRACE, TOP SPUD FLUSH VALVE, BEDPAN WASHER WITH FOOT PEDAL MIXING VALVE, VACUUM BREAKER & WALL HOOK OUTLET	4"	2"	3/4"	1-1/2"	KOHLER MODEL NO. K-6676 FLUSHING RIM SINK WITH ZURN MODEL NO. ZB42D6 -LSI-EXT FAUCET, SLOAN MODEL NO. 117 FLUSH VALVE & T&S BRASS MODEL NO. 0676 FOOTPEDAL BEDPAN WASHER W/VACUUM BREAKER & WALL HOOK OUTLET	COORDINATE W/ARCHITECTURAL DRAWINGS & VA STANDARD CLINIC SERVICE SINK ROUGH IN DETAILS & MANUFACTURER'S INSTALLATION INSTRUCTIONS.
MSB	24x24 MOP SERVICE BASIN OF MOLDED STONE W/ CHROME PLATED FAUCET W/PAIL HOOK, 3/4" HOSE THREAD OUTLET, INTEGRAL VACUUM BREAKER & HOSE WITH HOSE BRACKET	3"	1-1/2"	1/2"	1/2"	FIAT MODEL NO. MSB-2424 WITH 830AA FAUCET AND PAIL HOOK	
NOTES: 1. ALL FIXTURES SHALL HAVE INDIVIDUAL CHROME ANGLE STOPS, TRAPS AND ESCUTCHEONS. 2. ALL WALL MOUNTED FIXTURES SHALL BE SUPPORTED BY CONCEALED, FLOOR MOUNTED PLUMBING FIXTURE CARRIERS. WALL BRACKETS OR CLIPS ARE NOT ACCEPTABLE. NOTIFY ENGINEER OF ANY CONFLICTS WITH INSTALLATION OF CONCEALED CARRIERS. 3. LAV-A SHALL BE SUPPORTED BY JAY R. SMITH FIG. 0700-27-M31 CONCEALED ARM FIXTURE CARRIER. 4. PROVIDE SUBMITTALS FOR ALL FIXTURES. PROVIDE COPIES TO CONTRACTING OFFICER'S REPRESENTATIVE (COR) FOR REVIEW OF ALL FIXTURES AND FIXTURE FINISH COLORS. 5. MODEL NUMBERS LISTED IN SCHEDULE ARE FOR GENERAL REFERENCE ONLY AND NOT FOR ORDERING. CONTRACTOR SHALL REVIEW MODEL NUMBERS AND SPECIFIED FEATURES WITH THE FACTORY PRIOR TO PLACING THEIR FINAL ORDER. 6. PROVIDE SHOCK ARRESTORS ON CW SUPPLY PIPING TO FLUSH VALVES ACCORDING TO PLUMBING DRAINAGE INSTITUTE SIZING CRITERIA. 7. CONTRACTING OFFICER'S REPRESENTATIVE (COR) TO REVIEW PLUMBING FIXTURE SELECTION AND APPROVE PRIOR TO ORDERING.							

		CONSULTANTS:		ARCHITECT/ENGINEERS:		Drawing Title PLUMBING SCHEDULES		Project Title Renovate 4B for Community Living Center (CLC) Stratton VA Medical Center		Project Number VA 528A8-12-890		Office of Construction and Facilities Management Department of Veterans Affairs	
		Hyman Hayes 1511 Route 22 - Suite C-24 Brewster, New York 10599 p: 845.278.7710 f: 845.278.7750 adelaidelc.com		Sigma Psi Consulting Mechanical, Electrical, Plumbing Engineers, PLLC 4 Collamer Road, Malta, NY 12020 PH (518) 581-9428 FX (518) 580-9325		Approved Project Director 		Location Albany, New York		Building Number 1			
REVISED PER COMMENTS 12/29/14 REVISED PER COMMENTS 12/11/14 100% SUBMISSION 10/22/14 Revisions: _____ Date _____		1511 Route 22 - Suite C-24 Brewster, New York 10599 p: 845.278.7710 f: 845.278.7750 adelaidelc.com		STATE OF NEW YORK SEAL OF THE STATE OF NEW YORK OFFICE OF THE STATE ENGINEER JANUARY 1, 2015				Date 10-22-2014		Checked _____		Drawing Number P0.21 Dwg. 44 of 79	