

XR-U/S, VAMC COLUMBIA, SCPO# 544-5B5007 TRADE IN

TRADE-IN LOGIQ E - 3 PROBES ICU GE LOGIC ULTRASOUND MACHINE, 544-EE-1020081 /SN# 124172SU8  
ICU 4C-RS PROBE, 544-EE-1026664 / SN#: 15392DWX4  
ICU 8L-RS PROBE, NO EE NUMBER / SN#: 63605PDO  
ICU 3S-RS PROBE, NO EE NUMBER / SN#: 72651WX3

- 1 NextGen GOVT LOGIQ\* e Compact Digital Ultrasound Console (Made in USA)  
NextGen LOGIQ e portable high performance digital laptop ultrasound system. Standard package includes LOGIQ e Needle Recognition Software Option which helps provide precise and accurate display of the needle, anatomy and motion even in Color and Power Doppler. This feature harnesses pattern recognition technology that recognizes and accurately reveals the structure of a needle within the anatomy, without distortion of the needle and compromising the target. Also includes the ability to adjust needle gain and angle. Standard package includes AC power cord (USA), internet cord 3 meter in length CAT-5 type, PC to HUB structure, system software on USB, Optional Function Key Label, Aquasonic 100 Ultrasound Transmission Gel .25L, English Basic Service Manual CD and English User Guide. The following scanning modes are included: B-mode, M-mode, anatomical M-mode, color flow mode, power Doppler imaging, pulsed wave Doppler and Ophthalmic. USA version includes; 5 year standard warranty and one day of On-site Applications Training. Additional On-site Applications Training days are available for purchase.  
\*LOGIQ e is a trademark of the General Electric Company or one of its subsidiaries.
- 1 C1-5-RS Transducer (USA PoC Only)  
C1-5-RS Wide Band Convex. Applications include: Abdomen, Obstetrics, Gynecology, Urology, Pediatric/Neonatal, Nerve Block, MSK, ER (FAST Pleural). Only for sale in USA PoC.
- 1 12L-RS Linear Array Transducer  
Multi-Frequency transducer with bandwidth between 5 and 13 MHz. Applications include: Small Parts, Peripherals, Vascular, Pediatric and Orthopedic Applications. FOV 38.4mm.
- 1 L8-18i-RS Linear array transducer 'hockey stick'.  
L8-18i-RS Linear Array Surgical Transducer. 8-18 MHz broadband, multi-frequency capability. Applications include: Intraoperative & surgical procedures, small parts and vascular.
- 1 Power cord  
AC Power cord USA

---

1

---

LOGIQ\* e R6 docking cart with 3 probe port

LOGIQ\* e R6 docking cart with 3 probe port

---