


3.02	Concrete slab on grade over 10 mil. vapor barrier over compacted aggregate base. See Structural Drawings.
4.09	Cast stone trim.
4.13	8" split face concrete masonry unit U.N.O. See Structural Drawings.
5.28	Metal stud framing.
5.29	Double studs at jamb, typ.
5.30	Steel bar joist. Refer to Structural Drawings.
5.31	3/58" 20 GA metal stud @ 16" O.C.
5.41	2" Steel tube @ 4'-0" O.C. Weld tube to 3 1/2" x 6" x 1/2" thick steel plate. Fasten plate to top of slab with 4 - 1/2" dia. expansion bolts evenly spaced, 1" embedment minimum.
5.49	Vertical reinforcement. See Structural Drawings.
5.58	Horizontal reinforcement.
6.08	Fire retardant treated 2x wood blocking.
6.20	Pressure treated 2" x 4" wood stud framing @ 16" O.C.
6.22	1/2" Solid surface material over 3/4" plywood, with 1/4" radius eased edge.
6.28	Solid surface apron. Ease edge 1/4" radius.
6.48	3/4" Fire retardant treated plywood.
7.23	8 1/4" smooth fiber cement board lap siding with 7" exposure, over air and moisture barrier over 5/8" exterior grade plywood sheathing. Finish to be selected by Resident Interior Designer.
7.29	Continuous fire-stopping @ rated walls, each side.
7.67	UL approved expanded firestop system that can be sanded to a flush finish.
7.82	Continuous acoustic sealant @ non-rated walls each side.
7.92	2 1/2" min. closed cell, medium density spray polyurethane foam insulation, 7-14 min. install per wall system manufacturers instructions.
7.93	Hygic Buffer Matt. Install per wall system manufacturers' instructions.
7.95	2 1/2" cementitious wood fiber deck planks attached to steel structure. See Structural Drawings.
7.98	5/8" Exterior grade plywood sheathing. See Specifications.
9.01	5/8" non-structural metal framing @ 16" O.C.
9.02	5/8" non-structural metal framing @ 16" O.C.
9.03	6" non-structural metal framing @ 16" O.C.
9.24	Paint gypsum board flat black where exposed at reveal before mounting apron. Both sides typical.
9.42	Wall base, see Finish Plans.
9.80	Acoustic bat insulation.
9.83	5/8" Type "X" abuse resistant gypsum board. See Wall Types. Refer to underside of deck. Finish to be selected by Resident Interior Designer.
9.84	5/8" Type "X" abuse resistant gypsum board.
10.30	Corning fixture. See detail Sheet A401.
22.01	Plumbing fixture. See Plumbing Drawings.

[illegible]

Project Title			
REPLACEMENT WORK THERAPY GREENHOUSE			
Location			
Chillicothe, Ohio			
Date	Checked	Drawn	
04/17/2015	WS	VR	

Office of
Construction
and Facilities
Management

