

SECTION 07 46 00

SIDING

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. Fiber-cement siding and trim.
- B. Related Sections:
 - 1. Section 061000 "Rough Carpentry" for wood furring, grounds, nailers, and blocking.

1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product indicated. Include construction details, material descriptions, dimensions of individual components and profiles, and finishes.
- B. Samples for Initial Selection: For siding and soffit including related accessories.
- C. Samples for Verification:
 - 1. 24-inch- (600-mm-) wide-by-36-inch- (900-mm-) high Sample panel of siding assembled on plywood backing.
 - 2. 12-inch- (300-mm-) long-by-actual-width Samples of trim and accessories.

1.4 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For qualified vinyl siding Installer.
- B. Product Certificates: For each type of siding and soffit, from manufacturer.
- C. Product Test Reports: Based on evaluation of comprehensive tests performed by a qualified testing agency, for fiber-cement siding.
- D. Research/Evaluation Reports: For each type of siding required, from the ICC.
- E. Warranty: Sample of special warranty.

1.5 QUALITY ASSURANCE

- A. Labeling: Provide fiber-cement siding that is tested and labeled according to ASTM C 1186 by a qualified testing agency acceptable to Contracting Officer's Representative (COR).

- B. Source Limitations: Obtain each type, color, texture, and pattern of siding and soffit, including related accessories, from single source from single manufacturer.
 - C. Mockups: Build mockups to verify selections made under sample submittals and to demonstrate aesthetic effects and set quality standards for fabrication and installation.
 - 1. Build mockups for siding and soffit including accessories.
 - a. Size: 48 inches (1200 mm) long by 60 inches (1800 mm) high.
 - b. Include outside corner on one end of mockup.
 - 2. Approval of mockups does not constitute approval of deviations from the Contract Documents contained in mockups unless COR specifically approves such deviations in writing.
 - 3. Approved mockups may become part of the completed Work if undisturbed at time of Substantial Completion.
 - D. Preinstallation Conference: Conduct conference at Project site.
- 1.6 DELIVERY, STORAGE, AND HANDLING**
- A. Store materials in a dry, well-ventilated, weathertight place.
- 1.7 COORDINATION**
- A. Coordinate installation with flashings and other adjoining construction to ensure proper sequencing.
- 1.8 WARRANTY**
- A. Special Warranty: Standard form in which manufacturer agrees to repair or replace siding and soffit that fail(s) in materials or workmanship within specified warranty period.
 - 1. Failures include, but are not limited to, the following:
 - a. Structural failures including cracking, deforming, and fading.
 - b. Deterioration of metals, metal finishes, and other materials beyond normal weathering.
 - 2. Fading is defined as loss of color, after cleaning with product recommended by manufacturer, of more than 5 Hunter color-difference units as measured according to ASTM D 2244.
 - 3. Warranty Period: ~~25 years~~ **50 years** from date of Substantial Completion. **(AMEND 1)**

PART 2 - PRODUCTS

2.1 FIBER-CEMENT SIDING

- A. General: ASTM C 1186, Type A, Grade II, fiber-cement board, noncombustible when tested according to ASTM E 136; with a flame-spread index of 25 or less when tested according to ASTM E 84.
 - 1. Shingle Pattern: 48-inch- (1200-mm-) wide, straight-edge notched sheets with wood-grain texture, 5-inch exposure.
 - 2. Factory Finish: ~~Match CertainTeed WeatherBoards,~~
~~Silverpalte~~/Sterling Gray. (AMEND 1)

2.2 ACCESSORIES

- A. Siding Accessories, General: Provide starter strips, edge trim, outside and inside corner caps, and other items as recommended by siding manufacturer for building configuration.
 - 1. Provide accessories made from same material as adjacent siding unless otherwise indicated.
- B. Decorative Accessories: Provide the following fiber-cement decorative accessories as indicated:
 - 1. Door and window casings.
 - 2. Fasciae.
 - 3. Moldings and trim.
 - 4. And others as detailed on Drawings
- C. Colors for Decorative Accessories: Match adjacent siding.
- D. Flashing: Provide stainless-steel flashing complying with Section 076200 "Sheet Metal Flashing and Trim" at window and door heads and where indicated.
- E. Fasteners:
 - 1. For fastening to wood, use ribbed bugle-head screws of sufficient length to penetrate a minimum of 1 inch (25 mm) into substrate.
 - 2. For fastening to metal, use ribbed bugle-head screws of sufficient length to penetrate a minimum of 1/4 inch (6 mm), or three screw-threads, into substrate.
 - 3. For fastening fiber cement, use stainless-steel fasteners.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates for compliance with requirements for installation tolerances and other conditions affecting performance of siding, soffit and related accessories.

- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Clean substrates of projections and substances detrimental to application.

3.3 INSTALLATION

- A. General: Comply with siding and siding manufacturer's written installation instructions applicable to products and applications indicated unless more stringent requirements apply.
 - 1. Do not install damaged components.
 - 2. Center nails in elongated nailing slots without binding siding to allow for thermal movement.
- B. Install fiber-cement siding and related accessories.
 - 1. Install fasteners no more than 24 inches (600 mm) o.c.
- C. Install joint sealants as specified in Section 079200 "Joint Sealants" and to produce a weathertight installation.

3.4 ADJUSTING AND CLEANING

- A. Remove damaged, improperly installed, or otherwise defective materials and replace with new materials complying with specified requirements.
- B. Clean finished surfaces according to manufacturer's written instructions and maintain in a clean condition during construction.

- - - END - - -