



NOTES

1. FOR GENERAL NOTES SEE DRAWING SI-1.
2. FINISHED INTERSTICE FLOOR EL. 146'-7" U.O.N.
(TOP OF LOW DENSITY POLYURETHANE INSULATION)
3. TOP OF STEEL EL. 146'-3 3/16" U.O.N. THUS (-).
4. TYPICAL INTERSTITIAL PURLIN IS W6X9, GRADE 36 U.O.N.
5. TYPICAL HANGER RODS SUPPORTING W6X9 PURLINS ARE TO BE 3/4" DIAMETER. HANGER RODS SUPPORTING PURLINS LARGER THAN W6X9 ARE TO BE 1" DIAMETER.
6. FOR TYPICAL HANGER ROD DETAILS SEE DRAWING S7-2. SI, S2, S3 ETC. DEMOTE SLAB CONFIGURATIONS, FOR INFORMATION SEE GENERAL NOTES ON DRAWING SI-1.
7. CONTACTOR IS TO COORDINATE LOCATIONS AND DIMENSIONS FOR ALL OPENINGS THROUGH THE INTERSTITIAL DECK. FOR REINFORCEMENT OF UNSCHEDULED OPENINGS REFER TO DETAILS ON DRAWING S7-2.
8. FOR TYPICAL DETAILS SEE DRAWINGS S7-2 AND S7-3.

Plot Date:	5555DATE5555	Plot File:	5555555555GHSPEC555555555555	Plot Time:	555555TIME555555
------------	--------------	------------	------------------------------	------------	------------------