

Addendum items.

LOCATION	ITEM
00 31 00 - 1	Delete paragraph B under subsection 1.1 Summary
00 31 00 - 1	Change the title of subsection 3. ASBESTOS SURVEYS to 1.2 MATERIAL SURVEYS
00 31 00 - 1	In paragraph B under subsection 1.2 MATERIAL SURVEYS change the second sentence to read: Removal procedures shall conform to requirements contained in Specification Section 02 82 13.13 GLOVEBAG ASBESTOS ABATEMENT
08 71 00 - 1	Change paragraph C under subsection 1.2 RELATED WORK to read: Painting: Section 09 91 00 PAINTING AND SPECIAL COATINGS.
09 65 16 - 1	Change paragraph A under subsection 1.2 RELATED WORK to read: Removal of existing sheet flooring: Section 02 05 00 MINOR DEMOLITION FOR RENOVATION.
09 91 00 - 13	Change paragraph B under subsection 3.10 MECHANICAL & ELECTRICAL WORK FIELD PAINTING SCHEDULE to read: B. In spaces not scheduled to be finish painted in Section 09 06 00 MATERIALS AND FINISH SCHEDULE paint as specified under paragraph F, Color.
09 91 00 - 13	Change number 1 under subsection 3.10, letter F. Color to read: 1. Paint items having no color specified in Section 09 06 00 MATERIALS AND FINISH SCHEDULES to match surrounding surfaces as approved by Architect.
09 91 00 - 13	Change number 2 under subsection 3.10, letter F. Color to read: 2. Paint Colors as specified in Section 09 06 00 MATERIAS AND FINISH SCHEDULE except for the following:
26 41 00 - 1	Delete paragraphs C & D under subsection 1.2 RELATED WORK
26 41 00 - 1	Delete subsection 1.3 QUALITY ASSURANCE.
26 41 00 - 1	Change paragraph A under subsection 1.4 Submittals to read: A. Submit in accordance with Section 01 33 23 SHOP DRAWINGS, PRODUCT DATA, AND SAMPLES
26 41 00 - 4	Change paragraph P under subsection 3.1 Installation to read: Grounding: Test the ground resistance to earth by standard methods.
33 46 13 - 1	Delete paragraph A under subsection 1.3 Related Work
07 41 13 - 3	Add 16 oz. ZT Alloy Coated Copper - Freedom Gray from Revere as an aceptalble material for Metal Roof Panels

07 60 00 - 2	Add 16 oz. ZT Alloy Coated Copper - Freedom Gray from Revere as an acceptable material for Flashing and Sheet Metal
--------------	---

07 31 26 - 2	Change paragraph 2.1 B to read: Screws: Stainless steel of length sufficient to penetrate 3/4" thru the wood deck.
--------------	--

07 31 26 - 3	Add the following to paragraph G: Screws shall be installed in pre-drilled holes in wood deck.
--------------	--

07 31 26 - 2	Add the following to paragraph 2.1.A.2: The edges of factory or field cut slate shall be hand chiseled to produce uniform "chiseled" appearance in all slate.
--------------	---

07 31 26 - 1	Add the following to paragraph 1.5 Submittals: Submit samples of factory or field cut slate with chiseled edges for approval prior to order and installing slate.
--------------	---