



RIDGE BEAM NOTES:

1. RIDGE BEAM CONSTRUCTION IS THE SAME FOR BOTH SIDES OF UNIT (MIRRORED).
2. RIDGE BEAM IS CONSTRUCTED WITH 3/4" 5-PLY, 5-LAYER GROUP 1 SPECIES PLYWOOD.
3. RIDGE BEAM CONSTRUCTION SHALL BE IN ACCORDANCE WITH APA PLYWOOD DESIGN SPECIFICATION, SUPPLEMENT 5.

AMTEX CORP. 832 EAST WALNUT
GARLAND, TX 75040
P: 972-275-7626 / F: 972-526-0451

1. SOIL CAPACITY IS ASSUMED TO BE 2000 PSF.
2. PIER SPACING BASED ON ASSUMED PAD SIZE OF 24" ROUND x 42" DEPTH.
3. BLOCKS ADDED EACH SIDE OF EXT. DOORS (TYP.)
4. **FINAL FOUNDATION / PIER DESIGN IS SUBJECT TO P.E. REVIEW.**

MARK STEELE, P.E.
5139 N. TOM MURRAY AVE.
GLENDALE, AZ. 85301 P#: 602.385.2173

AMTEX INC. 832 EAST WALNUT
GARLAND, TX 75040
P: 972.276.7626 / F: 972.526.0457

VA FORM 08-6231, OCT 1978