

**Project Location:** Hampton National Cemetery, Cemetery Road at Marshall Avenue, Hampton, VA 23669

**Project Title:** Remove and Reset Brick Pavers

**Project Control #:** 849-M&R17-03

**Statement of Work Summary:**

Contractor shall provide all labor, tools, materials, equipment, design services, and supervision necessary to remove and reset 2400 square feet of brick pavers surrounding the Hampton National Cemetery (849) Administration building as required by the specifications and drawings.

**SPECIFICATION SECTIONS:**

01 00 02	General Requirements
01 33 23	Shop Drawings, Product Data, and Samples
01 45 29	Testing Laboratory Services
01 74 19	Construction Waste Management
02 41 10	Demolition and Site Clearing
31 20 11	Earth Moving
32 14 16	Brick Unit Paving

**DRAWINGS:**

849M&R1703-01 Hampton NC Brick Paver South Section  
849M&R1703-02 Hampton NC Brick Paver North Section  
839M&R1703-03 Hampton NC Typical Paver New Construction Detail

**SPECIFIC WORK ITEMS:**

The contractor shall remove all brick pavers surrounding the Hampton National Cemetery Administration building, as partially depicted in the photos below, and reset them in new bedding sand on recompact aggregate base course or new aggregate base course. Work shall be in compliance with all applicable Federal, State, & Local Codes, and VA specifications.



The VA specifications include, but are not limited to, the following requirements:

- A. The Contractor shall complete all plans and submittals prior to removing patio furnishings, pavers, or beginning tree removal.

- B. Contractor shall move all mats, benches and picnic tables from the brick paver area to a cemetery location designated by the Contracting Officer Representative (COR).
- C. Contractor shall remove and set aside all landscaping timbers and mulch to allow for construction of the pavement.
- D. Contractor shall remove pavers and segregate on pallets based on color. Chipped, cracked, deformed, or permanently stained pavers should be disposed of. The contractor should assume that 10 percent of the existing bricks will need to be replaced.
- E. Contractor to remove and dispose of the concrete pavers in front of the grave locator kiosk and concrete edge blocks surrounding the two trees in the middle of the patio area.
- F. Contractor shall remove and dispose of any existing edge restraints and all paver bedding sand. In areas designated the Contractor shall remove the existing aggregate base material. Contractor should retain a portion of the existing base material to level any areas of the existing pavement that are not designated to have new aggregate base installed.
- G. In designated areas the Contractor shall compact the existing subgrade, install geotextile fabric, place new aggregate base to a depth of 6 inches, and compact.
- H. In areas not receiving new aggregate base the Contractor shall recompact the base using any removed base material to fill in areas that do not meet elevation tolerance requirements.
- I. Contractor shall install edge restraints on all pavement edges not abutting concrete curbs, stairs, or foundations. Contractor shall place mortared edge paver course per approved pattern plans.
- J. Contractor shall place bedding sand, screed the sand, place pavers per the approved pattern plans, vibrate the pavers, and place joint sand.
- K. After acceptance of all paver work, the Contractor shall restore all adjacent landscaping timbers and mulch, and return all mats and patio furnishings to designated locations. Contractor shall replace any adjacent bushes, shrubs, or turf damaged during construction.

**Pre-Bid Site Visit:** Bidders are urged and expected to inspect, site investigate by observation, and Request for Information (RFI) and responses through the Contracting Office to satisfy their understanding of the work to be done, all general, local and technical conditions that may affect the cost and the feasibility of their proposal. In no event shall failure to inspect the site constitute grounds for a claim after award. Visitors planning to conduct a site visit shall contact the Cemetery Director to make arrangements:

Cemetery POC(s):

Janice M. Hill, Hampton Cemetery Director  
(757) 723-7104 or [Janice.Hill@va.gov](mailto:Janice.Hill@va.gov)  
Michael Lawrence, Maintenance Technician  
(757) 723-7104 or [michael.lawrence2@va.gov](mailto:michael.lawrence2@va.gov)

District Technical POC:

Timothy P. Sullivan, North Atlantic District (NAD) Engineer  
(215) 381-3787 (ext. 4664) or [timothy.sullivan5@va.gov](mailto:timothy.sullivan5@va.gov)

**PRICE SCHEDULE**

DESCRIPTION	QTY	UNIT	TOTAL PRICE
Contractor shall provide all labor, tools, materials, equipment, design services, and supervision necessary to remove and reset 2400 square feet of brick pavers surrounding the Hampton National Cemetery (849) Administration building as required by the specifications and drawings.	1	JOB	\$ _____

Duration: Term of the contract shall be ninety days (90 days) from date of award. The Contractor shall complete all work within 90 calendar days after receipt of Notice of Award, subject to all terms, conditions, provisions and schedules of the contract.

**(END OF PRICE SCHEDULE)**

11/21/2016

**X** Timothy Sullivan

Timothy P. Sullivan PE, PMP

Project Engineer

Signed by: Timothy P. Sullivan 1409410