

**SECTION 11 52 13
PROJECTION SCREENS**

PART 1 - GENERAL

1.1 DESCRIPTION

This section covers manually operated projection screens.

1.2 RELATED WORK

- A. Color and finish of case: Section 09 06 00 SCHEDULE FOR FINISHES

1.3 SUBMITTALS

- A. Submit in accordance with Section 01 33 23, SHOP DRAWINGS, PRODUCT DATA, AND SAMPLES.
- B. Manufacturer's Literature and Data: For each type of product indicated.

PART 2 - PRODUCTS

2.1 MANUALLY OPERATED PROJECTION SCREENS

- A. General: Manufacturer's standard spring-roller-operated units, consisting of case, screen, mounting accessories, and other components necessary for a complete installation.
 - 1. Tab Tensioning: Provide units that have a durable low-stretch cord, such as braided polyester, on each side of screen connected to edge of screen by tabs to pull screen flat horizontally.
 - 2. Provide mechanism so screen can stop at intermediate positions.
 - 3. Screen to gently retract to closed position with a gentle tug on the handle.
 - 4. Finish: Matte white.
 - 5. Case length: 1930 mm (76 inches).
 - 6. Mounting: Ceiling recessed.
 - 7. Trim Flange: 203 mm (8 inch) wide with 54 mm (2 1/8 inch) screen slot.
- A. Fabricate from formed-steel sheet or from aluminum extrusions; with flat back design and vinyl covering or baked-enamel finish.

PART 3 - EXECUTION

3.1 PROJECTION SCREEN INSTALLATION

- A. Install projection screen at locations indicated to comply with screen manufacturer's written instructions.
- B. Mount to deck above with 9.5 mm (3/8 inch) diameter rods, 3 per side. Brace rods per manufacturer recommendations.

- - - E N D - - -