

100243 Allura Xper FD20

System Type: New
Freight Terms: FOB Destination
Warranty Terms: Part numbers beginning with two (2) asterisks (**) are covered by a Per Contract. All other part numbers are third (3rd) party items.
Special Notations: Contingencies must be removed 120 days before scheduled shipment to assure delivery on specified date.
Any rigging costs are the responsibility of the Purchaser.
Additional Terms:

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

1		AlluraClarity_FD20 Ceiling	1		
---	--	-----------------------------------	---	--	--

The AlluraClarity FD20 (Ceiling) single-plane cardiovascular system comprises a ceiling mounted C-arm stand and digital imaging X-ray system for cardiovascular diagnostic and interventional procedures.

ClarityIQ technology is the foundation of AlluraClarity systems touching every part of the imaging system.

ClarityIQ incorporates powerful state-of-the-art image processing technology, developed by Philips research, all working in real-time enabled by the latest computing technology:

- Noise and artifact reduction, also on moving structures and objects
- Image enhancement and edge sharpening;
Automatic real-time patient and accidental table motion correction on live images.
- Flexible digital imaging pipeline
- ClarityIQ systems have a flexible digital imaging pipeline from tube to display that is tailored for each and every application area such as Cardio or Neuro. This gives the flexibility to select virtually unlimited application-specific configurations.
- With ClarityIQ over 500 system parameters are fine-tuned for each application area; the result of years of Philips clinical leadership. It is now possible to filter out more X-ray radiation, use smaller focal spot sizes, shorter pulses, thereby fully utilizing the unique capabilities of the Philips MRC X-ray tube.

The AlluraClarity FD20 system uses an integrated single-host concept. The system is comprised of five functional building blocks: Geometry, X-ray Generation, Image Detection, Viewing, and User Interface. Each functional building block is explained in further detail including accessories.

GEOMETRY

The AlluraClarity FD20 Stand

The Allura stand consists of a ceiling-mounted C-arm. The stand has the following capability:

- The L-arm can be rotated and can be moved in longitudinal direction allowing a three-sided patient approach and total body coverage.
 - L-arm rotation around the patient table: +90, 0, -90 degrees.
 - L-arm longitudinal movement: 300 cm
 - This movement features auto-stops at the parking position, cardio/neuro position and lower peripheral position.

The Allura stand allows a very wide range of projections, including PA and AP imaging.

- In the head position (0 degrees position, L-arm parallel to patient table):
 - C-arm rotation range (degrees): 120 LAO to 185 RAO

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- C-arm angulation range (degrees): 90 CA to 90 CR
- (Full angulation capability determined by patient position)
- In the side position (+90 / -90 degrees position, L-arm perpendicular to patient table):
 - C-arm rotation range (degrees): 90 LAO to 90 RAO
 - C-arm angulation range (degrees): 185 CA to 120 CR or 120 CA to 185 CR
 - (Full angulation capability determined by patient position)
- The stand provides fully motorized fast movements with variable and configurable maximum speed.
 - Variable C-arm rotation speed, up to 25 degrees per second
 - Variable C-arm angulation speed, up to 18 degrees per second
- L-arm rotation and longitudinal movement: motorized and manual
- C-arm depth is 90 cm
- The FD20 Dynamic Flat Detector features Xper Access which allows the flat detector to be positioned in either portrait or landscape imaging modes in 3 seconds.
- The variable source image distance between focus and Dynamic Flat Detector input screen is motorized from 86.5 to 123 cm.
- The stand features BodyGuard a capacitive sensing collision avoidance system for patient protection.

Patient support

The Xper Table

- Patient support with flat carbon fiber tabletop
- Table top length of 319 cm, width 50 cm
- Metal-free overhang 125 cm
- Floating table-top movement of 120 cm longitudinal and 35 cm transversal range.
- Motorized height adjustment from 74.5 to 102.5 cm
- Maximum cantilever of 223 cm , for full patient coverage
- Maximum patient weight 250 kg plus 500 N for CPR (or 225 kg plus 1000 N) in any longitudinal position of the table top
- Xper Geometry and Imaging Modules for exam room controls.
 - The operating modules can be attached to either side of the table.

Patient Support Accessories set

- One cerebral filter
- Three rail accessory clamps
- One IV stand
- One slow recovery foam mattress
- One Set of Arm Supports (FCV0248)
- One Set of Patient Straps (FCV0250)
- One Head Support (FCV0251)
- One Arm Support (FCV0258)
- One Table-mounted Radiation Shield
- One anti-fatigue mat with Philips logo

X-ray Generation

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

The AlluraClarity FD20 comprises an integrated dedicated X-ray system, micro-processor controlled Certeray generator based on high frequency converter technique. The user interface control of this X-ray Generator is incorporated in the Xper module, Xper Desktop Viewing Console, and the Xper on-screen displays.

- The Certeray generator comprises:
 - X-ray generator: 100 kW
 - Voltage range: 40 - 125 kV
 - Program selection:
 - Pulsed X-ray up to 3.75 , 7.5 , 15 , 30, frames/s for digital dynamic exposures
 - Pulsed X-ray for pulsed fluoroscopy (3.75, 7.5, 15, 25, 30 frames/s).
 - Minimum exposure time of 1ms.
 - ECG triggered acquisition: allows acquiring one exposure for each QRS peak with selectable delay time
 - Automatic kV and mA control for optimal image quality prior to run to save dose
 - Optimal X-ray tube load incorporated in the Certeray generator
 - An X-ray collimator with single semi-transparent wedged filter with manual and automatic positioning.
 - SpectraBeam filtering of low energy radiation to optimize image quality and dose efficiency with the MRC-GS 0508 X-ray tube.
 - Xper Beam Shaping, which means that, both shutters and wedges can be positioned on the Last Image Hold without the need for X-ray radiation.

Fluoroscopy

- Three programmable fluoroscopy modes
 - Each mode can be set to different composition of dose rate, pulse speed, filter setting, and image processing (noise reduction, adaptive contour enhancement, and adaptive harmonization).
- Roadmap Pro
 - Roadmap Pro can be selected from the Xper imaging module and/or Xper module.
 - A vessel map is created and superimposed with (un)subtracted live fluoroscopy. Acquisition runs can be done during Roadmap without losing the vessel map. Roadmap Pro features Smart Settings in special clinical modes that are optimized to visualize special materials such as coils and glue. Live processing of the vessel map, the device map and the landmark map can be done on the Xper Module. Xres for vascular procedures is standard part of Roadmap Pro.
 - **Disclaimer:** AMC only corrects movement artifacts in two dimensions. Three dimensional movements such as swallowing or rotation of the head cannot be corrected.
 - In Roadmap Pro R2 "Automatic Motion Compensation" (AMC) is added to the roadmap functionality. During roadmap, small movements of the patient can lead to subtraction artifacts. These artifacts might conceal important clinical information. "Automatic Motion Compensation" compensates for rigid, uniform (skeletal/table) translations and is therefore very effective in interventional (neurology) applications where subtraction imaging is applied.
 - Disclaimer: AMC only corrects movement artifacts in 2 dimensions. 3 dimensional movements like swallowing or rotation of the head cannot be corrected.

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- Xper Fluoro Storage, a grab function allows storage and archiving of both a fluoro image and the last 20 seconds of Fluoroscopy, called Xper Fluoro Storage. These fluoro images or fluoro runs can be archived as a regular exposure run.

X-ray tube

The AlluraClarity FD20 has the Maximus ROTALIX Ceramic grid switch tube assembly MRC 200 GS 0407 integrated in the C-arc. This MRC tube has an anode heat storage capacity of 2.4 MHU and 0.4/0.7 mm. nominal focal spot values. The tube has a maximal loading of 30 and 67 kW.

Dynamic pulsed fluoroscopy uses grid switching technology to eliminate soft radiation and improve image quality. SpectraBeam allows for filtration of the x-ray beam with (a combination of) 0.2, 0.5 or 1 mm CU-equivalent filters.

Tube housing ROT-GS 1004 is for oil-cooling and has a build-in thermal safety switch. A rotor control unit is build-in for continuous rotation of the anode disk. The heat exchanger CU 3101 is for direct and continuous forced cooling with oil.

IMAGE DETECTION

The AlluraClarity FD20 comprises the following image detection chain:

- A 30 cm by 40 cm FD20 Dynamic Flat Detector with eight imaging modes.
 - 30 x 38, 30 x 30, 26 x 26, 22 x 22, 19 x 19, 16 x 16, 13.5 x 13.5, and 11 x 11 cm
- The digital output of the FD20 flat detector is 2k*2.5k image matrix at 16 bits depth for the largest mode
- The flat detector subsystem features Xper Access, the detector can be rotated over 90 degrees, it moves from portrait to landscape back & forth
- DQE (Detective Quantum Efficiency) >77 %
- The pixel pitch: 154 x 154 microns

Viewing

The AlluraClarity FD20 comprises the following components in order to display the clinical images in the control and examination room:

Displays

Examination Room

Two 19-inch monochrome LCD monitors designed for medical applications. The first display is used for viewing live images. The second display is the reference monitor.

- 19-inch monochrome TFT-LCD display with a 160 degree viewing angle.
- Native format 1280x1024 SXGA
- 10-bit gray-scale resolution with gray-scale correction

These monitors are not delivered when FlexVision XL, EP Cockpit or EP Cockpit XL is selected.

The monitor ceiling suspension in the exam room can be configured to accommodate 3, 4, 6 or 8 LCD monitors and includes motorized height adjustment. The height-adjust feature is dependent on the room ceiling height. When FlexVision XL, EP Cockpit or EP Cockpit XL is selected the monitor ceiling suspension is configured for one of those options.

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- Of the two medical monochrome LCD monitors included in the MCS, one is used for viewing of live images and the other serves as the first reference display. Reference images or runs are controlled by infra-red remote-control Xper ViewPad.
- The On-Screen Display provides status information on stand rotation, angulation, display of system messages, X-ray tube load status, selected fluoroscopy mode, selected detector Field of View, and both the rate and accumulation of the dose area product and skin dose. For cardiac applications, the system also monitors and displays body zone specific Air Kerma data (10 zones).

Control Room

One 19-inch color LCD monitor used as a data monitor.

- 19-inch color TFT-LCD display
- Native format 1280x1024 SXGA

One 19-inch monochrome LCD monitor (Xper review monitor) designed for medical applications.

- 19-inch monochrome TFT-LCD display
- Native format 1280x1024 SXGA
- 10-bit gray-scale resolution with gray-scale correction

These control room monitors are not delivered when EP Cockpit or EP Cockpit XL is selected. The Graphical User Interface on the monochrome monitor has the following features and functions:

- Step through file, run, or images
- File, and run overview
- Contrast, brightness, and edge enhancement settings
- Flagging of runs or images for transfer
- Applying text annotation in images
- Optional DICOM printing
- Executing Quantitative Analysis Packages if available
- Subtraction functionality
- Zoom/pan functionality
- Electronic shutters
- Video invert
- View trace, stacking of images
- Landmarking

Acquisition

The acquisition segment coordinates the parameters for automatic exposure control. The program is selected via the Xper module or Xper Desktop Console.

Exposure techniques:

- Serial imaging for DA and DSA with automatic exposure setting
- Single shot mode

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- Acquisition frame rates:
 - 0.5 to 6 fps at 2048 x 2048
 - 15 and 30 fps at 1024 x 1024

The AlluraClarity FD20 offers a storage capacity of:

- 50,000 images at matrix size of 1024 x 1024
- 12,500 images at matrix size of 2048 x 2048
- Maximum number of examinations is 999, with no limit to the maximum number of images per examination

USER INTERFACE

Xper is comprised of three elements: 1) Xper Settings, which customizes the system to each user preferred settings. 2) Xper User Interface 3) Xper Integration, which makes advanced integration functionality available such as DICOM Query / Retrieve, background archiving, and Xper Fluoro Storage.

The Xper User Interface uses User Interface modules in the Examination Room with On-Screen Display.

The On-Screen Display is positioned on the left side of the reference monitor. The following system information is displayed

- X-ray indicator and X-ray tube temperature condition
- Gantry position in rotation, angulation, and Source Image Distance
- Detector field size display
- General System messages
- Selected Frame speed
- Fluoroscopy mode
- Integrated fluoroscopy time
- Skin Dose and Dose Area Product
- Stopwatch

The Xper ViewPad contains the preprogrammed function settings. The system is provides with two Xper Viewpads. The following functions are provided:

- Run and image selection
- File and run cycle
- File overview
- Store to Reference image file
- Copy image to photo file
- Digital (fixed) zoom and panning
- Recall reference images
- Laser pointer, intended to point at regions of interest on the imaging monitors
 - LED indication of laser pointer on/off and battery low
- Subtraction on/off
- Remasking
- Landmarking

Remote Intercom

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

The separate intercom which is connected independently from the system that allows separate placement of the intercom at the preferred working position in the control room and examination room.

Table Side Modules

Two Xper Modules are provided for use. The first Xper Module is mounted tableside. The Second Xper Module (NCVA778) is located in the control room. These modules use a touch screen, which can be operated when draped with sterile covers. The Xper Module contains the following functionality:

- Acquisition settings
- Selection of Xper Setting allows the user to set frame rates and X-ray generation settings applicable for the type of the preferred intervention
- Image Processing

The Xper Geometry module can be positioned on all sides of the patient table, while keeping the button operation intuitive. The Xper Geometry module provides the following functionality:

- Tabletop float and table height position
- Source Image Distance selection
- Longitudinal movement of the Gantry along the ceiling
- Gantry rotation in an axis perpendicular to the ceiling
- Store and recall of two scratch gantry positions including SID
- Emergency stop button

The Xper Imaging module can also be positioned on three sides of the patient table, while keeping the button operation intuitive. The Xper Imaging module provides the following functionality:

- Fluoroscopy Flavor selection defined per Xper Setting
- Shutters and Wedge positioning
- Xper Fluoro Storage and Grab
- Selection of the Detector field size
- Shutter positioning
- Reset of the fluoroscopy buzzer

Pan Handle

- The Pan Handle is an extension of the control facility for floating movements of the tabletop.

Control Room

The control room comprises a Xper Review Module, Xper Desktop Module, a keyboard, and a mouse. The Xper Review Module offers the basic functions for review. The Xper Review Module contains the following functionality:

- Power on/off
- Tagarno wheel to control the review of a patient file
- File and run cycle
- Contrast, Brightness, and Edge enhancement settings

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
		<ul style="list-style-type: none">• File, Run, Image stepping and run and file overview• Delete run• Image invert and digital zoom• Reset fluoroscopy timer and enable/disable X-ray			

System information is displayed on the bottom of the data monitor:

- Stopwatch and Time
- System guidance information
- Dose Area Product (DAP) and Skin Dose, and accumulative dose
- Frame speed settings, fluoroscopy mode, and accumulated fluoroscopy time
- Exposure and fluoroscopy settings as Voltage (kV), Current (mA) and pulse time (ms)
- Geometry information as rotation, angulation, and SID

Scheduling

The patients can be listed and selected per date, physician, and intervention type. Previous DICOM patient studies can be uploaded with the DICOM Query Retrieve function in the Allura system.

Patient management protocols are flexible and allow for multiple studies to be selected under one patient identification number. This means that new studies can be appended to an earlier patient file. Furthermore, each study can contain multiple examinations to allow for split administrative purposes. Each examination contains multiple files, like acquisition file, reference file, and QA results file.

Preparation

The preparation page provides the information of the room and patient preparation of each individual physician. The preparation page is customizable per Xper Setting and allows each physician to provide his own room protocols. This preparation page makes hard copies of the protocol instructions redundant.

Acquisition

The acquisition page contains information on the current selected patient.

Review

The review page allows for reviewing of patients:

- Previous examination cases
- Review of other DICOM XA or DICOM SC studies

Vascular Quantification Software Package

Functions:

- vessel diameter / stenotic index
- automated vessel analysis
- calibration routines

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

In addition the package allows manual measurements of line lengths (absolute and ratio's) and angulations. Multiple measurements in one image are possible.

RIS/CIS DICOM Interface

This package allows communication of the Allura Xper system with a local information system (CIS or RIS). The interface uses the DICOM Worklist Management (DICOM WLM) and Modality Performed Procedure Step (DICOM MPPS) standards.

If a hospital has an Allura Xper system and an information system it can receive patient and examination request information from the information system and report examination results in order to:

- Eliminate the need for retyping patient information on the Allura Xper
- Prevent errors in typing patient names and registration numbers (ensuring consistency with IS information to prevent problems in archive clusters auto-search for a name in case of later retrieval)
- Inform the IS about the acquired images and radiation dose

Upon request from the Allura Xper system the complete worklist with all relevant patient and examination data is returned from the IS to the Allura Xper system. For each patient the following information will be shown on the Allura Xper after it has been retrieved from the IS:

Patient Identification:

- Patient name
- Patient ID
- Birth date
- Sex

Examination/Request Information:

- Accession number
- Scheduled procedure step start time
- Scheduled performing physician's name

It is possible at all times to enter patient demographics information manually within the Allura Xper system in case of an emergency or in case the local Information System connection is down.

On request of the clinical user the Allura Xper will report the following information about the selected patient to the IS:

Patient Identification:

- Patient name
- Patient ID
- Birth date
- Sex

Examination/Request Information:

- Accession number
- Performed procedure step status start/end date and time
- Performing physician's name

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- Referenced image sequence

Radiation dose:

- Total time of fluoroscopy
- Accumulated fluoroscopy dose
- Accumulated exposure dose
- Total dose
- Total number of exposures
- Total number of frames

Further detailed information can be found in the Allura Xper DICOM Conformance Statement.

The interface requires an EasyLink (hardware and software) if the IS is not compliant with DICOM Work List Management and Modality Performed Procedure Step.

Radiation Dose Structured Report Collection of dose relevant parameters and settings and export to a DICOM database (e.g. PACS, RIS), according IEC60601-2-43, 2nd Edition.

The reported data can be used for, for example:

- Quality improvement: evaluating trends in X-ray dose performance per facility, system and operator.
- RDSR enables analysis of average dose levels & variance for routinely performed exams and procedures.
- Typical system usage can be extracted from the data.

Secondary Capture Dose Report

- The Secondary Capture Dose Report function allows the user to save & transfer, manually or automatically, a patient Dose Report to PACS in DICOM secondary capture format.
- The dose report will be stored in the related patient image folder.

Archive

Continuous Autopush (NCVA090)

Continuous Autopush is an archive accelerator, which ensures that background archiving continues with minimal disruptions.

Clinical studies can be archived to a CD or a PACS. The archive process can be completely automated and customized with Xper Settings. Parameters like multiple destinations, archive formats can be selected to the individual needs and wishes for programming under the Xper Settings,

The Xper DICOM Image Interface enables the export of clinical images to PACS. The export formats are based on DICOM 3.0 protocols. The system exports clinical studies in Cardiac DICOM XA Multi-Frame or DICOM Secondary Capture formats.

- The export format is configurable in 512x512, 1024x1024 2048 x 2048 (unprocessed) matrix.
- The examination can be sent to multiple destinations for archiving and reviewing purposes.

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- The Xper DICOM Image Interface provides DICOM Storage and DICOM Storage Commitment Services.
- The DICOM Query/Retrieve function allows older DICOM XA MF and DICOM SC studies to be uploaded in the system. Furthermore, additional information can be appended to a study, while keeping the patient identification the same.

Remote Service

Access to the system from a Remote location is possible via network or modem connection. Remote access to a system can shorten the time needed for e.g. changing system settings or problem diagnosis.

Clinical Education Program for the Allura Xper System

Essentials OffSite Education:

Philips will provide up to two (2) Cardiovascular Technologists, Registered Technologists Registered Nurses, or other system operator as selected by customer, with in-depth didactic, tutorial, and hands-on training covering basic functionality and work-flow of the cardiovascular imaging system. In order to provide trainees with the ability to apply all fundamental functioning on their system, and to achieve maximum effectiveness, this class should be attended no earlier than two weeks prior to system installation.

In the event that an EP Navigator workstation has also been ordered, the offsite training course will be tailored to focus on the electrophysiology functionality of the FD system and the EPN workstation.

In the event that your main FD system will be dedicated to Cardiac applications your offsite training course will be tailored to focus on the Cardiac functionality.

This twenty-eight (28) hour class is located in Cleveland, Ohio, and is scheduled based on your equipment configuration and availability. Due to program updates, the number of class hours is subject to change without notice. Customer will be notified of current, total class hours at the time of registration. This class is a prerequisite to your equipment handover OnSite Education. CEU credits may be available for each participant that meets the guidelines provided by Philips. Please refer to guidelines for more information. **Travel and lodging are not included, but may be purchased through Philips. It is highly recommended that 989801292102 (CV Full Travel Pkg OffSite) is purchased with all OffSite courses.**

Handover OnSite Education:

Philips Education Specialists will provide twenty-eight (28) hours of education for up to four (4) students, selected by customer, including technologists from night/weekend shifts if necessary. Students should attend all 28 hours, and must include the two OffSite education attendees. CEU credits may be available for each participant that meets the guidelines provided by Philips. Please refer to guidelines for more information. Note: Site must be patient-ready. Philips personnel are not responsible for actual patient contact or operation of equipment during education sessions except to demonstrate proper equipment operation. **It is highly recommended for systems that are fully loaded or for customers with a large number of staff members to also purchase 989801292099 (CV Add OnSite Clin Educ 24h).**

Education expires one (1) year from equipment installation date (or purchase date if sold separately). Ref #106107-110915

2	FlexVision_XL 8 Input Package	1
	The FlexVision XL8 input package provides eight isolated wall connection boxes. Isolated Wall Connection Box	

This Isolated Wall connection Box facilitates connection of the video source via standard DVI cable/connector and lossless transfer of the video signal over the approximate 30 m cable distance. It can be mounted in the exam room or in the control room, depending on the location of the video source.

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

The quantity of the VWCB's has to be calculated as follows:

For each video signal to FlexVision XL on Vascular System: 8 VWCB

Note:

No VWCB is required in case a video signal is connected directly to a dedicated LCD from the following sources:

1) Xper Live/ref Slaving

2) Interventional HW (XtraVision), ViewForum, Xcelera (only if workstations are powered by Allura Xper)

3)Xper IM

3	30Fr/sec Extension	1
----------	---------------------------	----------

Frame Rate Extension increases the system acquisition speed for cardiac applications that require high speed imaging. The frame rate extension increases the acquisition speed to 15fps and 30fps with a 1024x1024 matrix.

4	FlexVision XL,XperHD,Snapshot	1
----------	--	----------

FlexVision XL is an integrated viewing solution designed to give you full control over your viewing environment.

The FlexVision XL provides the ability to:

- Display information from up to 8 sources simultaneously (incl. third party systems) on the Philips 58-inch color LCD with LED backlight in the Exam Room.
- Resize and/or enlarge information at any stage during the case.
- Select and customize viewing lay-outs of the Philips 58-inch color LCD via the Xper table-side module
- Overview connected equipment (incl. third party systems) from a single location.

XperHD on FlexVision XL brings High Definition viewing for clinical images. Native resolution of FD20 can be displayed. Excellent sharp and crisp clinical images can be displayed at full size without digital zoom.

Xper HD brings:

- High Definition imaging
 - Sharp images at full size without zoom
- High Definition display at native resolution
 - Up to 2k*2k image display fully integrated
- High Definition for the ultimate detail
 - Enhanced small vessel visualization

The FlexVision XL consists of:

- DVI video composition unit.
 - o The DVI video composition unit allows the user to direct and switch the video output of all connected medical equipment to specific sub windows of the Philips 58-inch color LCD with LED backlight in the Exam Room.
 - o The DVI video composition unit is operated from the Xper tableside module.
 - o The DVI video composition unit supports a wide variety of display formats (up to 1920x1200)
 - o Up to 9 external inputs are connected to the DVI video composition unit via Wall Connection Box(es).
- Medical grade, high resolution color LCD in the Exam Room

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- o This display supports the image quality requirements for monochrome X-ray images as well as color images and replaces all displays normally delivered with an Allura Xper FD or AlluraClarity system for the Exam Room.
- o Main characteristics are:
 - 58-inch, 8 Megapixel color LCD
 - Native resolution: 3840x2160
 - Brightness: Max: 700 Cd/m2 (typical) stabilized: 400 Cd/m2
 - Contrast ratio: 4000:1 (typical)
 - Wide viewing angle (approx. 176 degrees)
 - Constant brightness stabilization control
 - Lookup tables for gray-scale, color and DICOM transfer function
 - Full protective screen Ingress Protection: IP-21
 - Large color LCD control (Xper Module)
- o Resize and/or enlarge information at any stage during the case via the Xper tableside module in the Exam or Control Room
- o Select viewing lay-outs via the Xper table-side module in the Exam Room
- o Create new layouts by matching inputs to desired locations on preset templates.

- Monitor Ceiling Suspension

- o Monitor ceiling suspension for use in the Exam Room carries the 58-inch color LCD screen, providing highly flexible viewing capabilities. The monitor ceiling suspension is height-adjustable and moveable along ceiling rails. It can be positioned on either side of the table.

- Snapshot

- o The snapshot function allows the user to store/save a screen-capture of any image on the 58-inch display as a DICOM Secondary Capture image to a connected PACS. The snapshot-all function allows the user to store/save a screen-capture for each displayed image in the Exam Room / Control Room as separate DICOM Secondary Capture images .

5

Set of 2 additional 21in. LCDs

1

Two 21inch additional displays are located on top of the monitor ceiling suspension frame which carry the 56 inch large screen color LCD display.

These 2 additional LCD's can be used to display additional video sources or used as display back up for Hemo and Xray Live images. These LCD's have a fixed content.

Main characteristics of back-up displays are:

- 21.3 inch, 2 Megapixel color LCD display
- Max. resolution: 1600x1200
- Brightness: 450 Cd/m2
- Contrast ratio : 550:1

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- Wide viewing angle (approx. 170 degrees)
- Constant brightness stabilization control
- Independently selectable brightness settings for monochrome and color images
- Independently selectable lookup table for gray-scale, color and DICOM transfer function

FCV0587, "XPer Live/Ref Slaving" required when displaying X-Ray Live as back-up.

6	StentBoost sw Rel. 2.0	1
----------	-------------------------------	----------

StentBoost is a unique interventional tool to improve visualization of stents in the coronary arteries during interventions. This, Philips exclusive, innovative interventional tool produces a highly augmented image of a deployed stent in coronary arteries - while the catheter is still in place. The StentBoost image helps clinicians to make a thorough check of stent expansion, and see the position of stents in relation to other objects, like other stents, without the use of extra contrast or other 'expensive' consumables. This allows interventional cardiologists to immediately take any corrective action required while your patient is still in the examination room.

The way it works

StentBoost automatically detects the stent delivery markers image after image. In each image StentBoost aligns the markers with the markers of the previous image. By doing this all radiopaque material in the close proximity of the markers will be enhanced and items further away from the markers will be greyed out.

The result provides enhanced contrast of the environment surrounding the markers, including the stent, while background noise is faded out.

StentBoost Workflow

1. Image acquisition

StentBoost is based on a maximum of 40 frames out of a cine run. Depending on the frames speed this takes the user 2-3 seconds.

2. Image transfer

The run will automatically be transferred to the interventional workstation and show up in the StentBoost software.

The Real time link (NCVA590) is a unique option within the Allura Xper FD10 R.2 and Allura Xper FD10/10 and allows instant access to the StentBoost image.

3. Region of Interest definition

The StentBoost software shows the acquired run with a predefined Region of interest. With the region of interest user has to indicate where the markers of the stent delivery markers are located in the image run.

4. StentBoost

After definition of the region of interest, the user presses next and within seconds, the boosted image shows up on the screen.

A real time operation user interface is available with StentBoost, providing:

- Review of StentBoost runs, before and after processing
- Viewing tools like Brightness/Contrast, Pan and Zoom to optimize the image displayed
- Automatic stent delivery system marker identification
- Reliability feedback regarding the enhanced run
- Manual quality improvement; Manual correction possibility for marker identification
- View patient info like, Birth date, Gender, Patient ID, Exam ID, Exam date, Run date, Run time, Hospital name, Physician name, RAO/LAO
- Creation of exportable items:

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- movies (AVI format)
- snapshots (jpeg format)
- The step 5, 6 and 7 are not mandatory.

5. Calibration

To create a StentBoost image no calibration is needed. For the measurement support tool four calibration methods are included:

- No calibration
- Auto calibration based on calibration data generated by the Allura Xper system when the autocall function is installed (MCV5681),
- Marker distance of the stent delivery markers,
- Catheter calibration

6. "Measurement"

"Measurement" an option within the StentBoost package supports the clinician in his/her decision-making in determining the percentage of remaining stenosis in the stent.

7. Archiving

Transfer to:

- Optional Hard Copy unit (DICOM Print)
- Optional third party station (snapshots images in DICOM Secondary Capture format)
- Any computer via a web server functionality with images in a standard file format (JPEG, AVI movies)
- One or multiple DVD's, CD-ROM(s) for easy archiving
- Store a subset of exportable objects (snapshots and AVI Movies) to a USB removable memory device.

8. StentBoost release 2.0 comprises:

- StentBoost release 2.0 Software Package
- User manual on compact disc
- Software release bulletin
- DICOM Conformance Statement
- StentBoost IQ verification Phantom

9. Compatible with:

- Allura Xper FD10 R 1.x
- Allura Xper FD20
- Allura Xper FD10 R. 2
- Allura Xper FD10/10

10. Pre-requisite for StentBoost R 2.0:

- Interventional Hardware (NCVA106)

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

This option contains a kit to split the Live or Ref video source from the Allura Xper. The total amount of Xper Live/Ref Slaving that can be selected is maximal. 4. Additional monitors are not included in this option and must be ordered separately. This kit contains a video splitter and a cable set for one slave monitor. The Slave monitor is not powered by Allura.

8 **FD Rotational Angio** **1**

Rotational angiography provides real-time 3D impressions of complex vasculature and coronary artery tree. It acquires multiple projections with just one contrast injection via a fast rotational scan of the region of interest.

Rotational Angiography can be used during screening procedures to quickly determine the optimal projection for the study as the angle (rotation/angulation) of the projection is indicated on each image.

Compared with traditional angiography, Rotational Angiography can save considerable time, dose and contrast, while providing image detail required for diagnostic and therapeutic decisions.

A rotational scan is possible both with the Allura Xper systems in the side position (ceiling mounted systems) and in the head position, providing the flexibility to perform procedures virtually from head to toe.

C-arm in side position:

- Max. rotation Speed: 30 degrees/s
- Max. rotation Angle: 180 degrees

C-arm in head position:

- Max. rotation Speed: 55 degrees/s
- Max. rotation Angle: 305 degrees

Max. Frame speeds are given by the framespeed specifications of the system configuration.

The speed and range of rotation are the highest available (see table). The very high speed allows using less contrast, whereas the very wide rotation range provides a complete evaluation of the anatomy.

A contrast run can be followed up with a mask run, to allow image/run subtraction.

The stand is designed for a very high mechanical stability. It offers precise positioning and high reproducibility, assuring you of high quality images and excellent subtraction studies.

Operation of Rotational Angiography is extremely easy. The procedure is selected, set up and executed virtually in a matter of seconds, supporting the highest patient throughput.

A set of dedicated acquisition programs is available on the Xper Module and can be selected at the touch of a button. The rotation end- and start-positions are easily selected. The procedure is controlled from the exposure hand- or footswitch.

9 **Subtracted Bolus Chase** **1**

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

For visualization of vessel structures when the blood flow is difficult to estimate, in particular in the lower peripherals.

Bolus Chase solves the problem of cumbersome step movements, the mismatch between blood flow and selected program, and lack of real-time image information.

During digital acquisition in non-subtracted mode with uninterrupted real-time image display, the contrast bolus is followed (chased) interactively by a motorized table scan movement using a hand-hold speedcontroller to adapt the speed of the table scan to the contrast flow. The framespeed can be adapted as well.

The bolus run is followed with a mask run while using the same speedcurve and framespeed as generated during the bolus run. Viewing is possible in the subtracted and non-subtracted mode. If subtracted viewing is not required, the mask run can be skipped.

Subtracted Bolus Chase gives fast, accurate results for increased patient throughput and improved patient management. Automated exposure control and precise speed control assure a high quality images and excellent subtraction studies.

Comprising:

- automatic exposure control
- tabletop motordrive and hand-held speed controller (tableside)
- technique selection using Xper module, available both tableside and in control room (Xper FD20, FD20/10)

10	FD Dual Fluoro	1
-----------	-----------------------	----------

Dual Fluoro for Flat detector systems

The Dual Fluoroscopy mode allows digitally processed fluoroscopy in parallel with trace subtract fluoroscopy, providing a non subtracted reference fluoro image for complex interventions.

This option provides an additional fluoro channel in parallel to the default fluoro channel. The Dual fluoroscopy mode is selected via the Xper module.

The trace subtracted fluoro image will be displayed on the exam monitor, the non-subtracted fluoro image is displayed on the reference monitor.

In Dual Fluoro mode, The fluoroscopy image on the exam monitor can be zoomed digitally with a factor 2, providing a larger view of the region of interest for complex interventions. The fluoro zoom function is controlled via the Xper module.

11	FD SmartMask	1
-----------	---------------------	----------

SmartMask simplifies roadmapping procedures by overlaying a selected reference image with fluoroscopy on the live monitor in the exam room.

The reference image can be faded in/out with variable intensity, controlled from tableside.

SmartMask uses the reference image displayed on the reference monitor.

Any previously acquired image can be used as reference.

SmartMask facilitates pre- and post- intervention comparisons to assess treatment results

12	FULL AUTOCAL	1
-----------	---------------------	----------

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

The AutoCal option is a software package to be used in conjunction with quantitative analysis software packages. It provides an auto calibration procedure for an object to be analyzed that is placed in the iso-center. When the object to be analyzed (e.g. Left Ventricle Vessel Segment) is placed in the iso-center AutoCal avoids the need to:

- acquire an additional image series containing a sphere or grid for calibration purposes
- calibrate manually on a calibration object (e.g. catheter) displayed in the image or image series to be analyzed

13	Ventricular Quant.Sw pkg(Xper)	1
----	---	---

Left Ventricular Quantification Software Package. Software package for the analysis of single plane Left ventricular angiograms. Calculates the Ejection fraction and local wall motion parameters in different formats.

Functions:

- Various LV-volumes
- Ejection Fraction
- Cardiac Output
- Centerline Wall Motion
- Slager Wall Motion
- Regional Wall Motion
- Calibration routines

In addition the package allows manual measurements of line lengths (absolute and ratio's) and angulations. Multiple measurements in one image are possible.

Comprising:

- software license

Compatible with:

. Allura Xper FD 10 Rel 3 and FD10/10 Rel 2 onwards
. Allura Xper FD20 Rel 2, FD20/10 Rel 2 onwards

14	Coronary Quant.Sw pkg(Xper)	1
----	------------------------------------	---

Functions:

- diameter measurement along the selected segment
- cross sectional area
- %-stenosis
- pressure gradient values
- stenotic flow reserve
- calibration routines

In addition the package allows manual measurements of line lengths (absolute and ratio's) and angulations. Multiple measurements in one image are possible.

Comprising:

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- software license

Compatible with:

- . Allura Xper FD 10 Rel 3 and FD10/10 Rel 2 onwards
- . Allura Xper FD20 Rel 2, FD20/10 Rel 2 onwards

15	Wireless footswitch: mono-plane version	1
-----------	--	----------

The wireless footswitch is an option for our Allura systems. It provides the possibility to have one wireless footswitch in the exam room.

A wireless footswitch provides workflow optimization, flexibility at table-side, removes cable clutter on the floor and provides easier cleaning of the footswitch.

The mono-plane wireless footswitch is a 3 pedal version; one pedal for fluoroscopy, one for exposure and one to control the roomlight/single shot. The pedals can be configured according customers preferred lay-out.

The wireless footswitch is working via RF technology and is fully tested and released for medical use. It has an active range up to 10 meters, depending on structures within this range.

The wireless footswitch has a lithium battery which only needs to be recharged once per week. During recharging the footswitch still can be used and is fully functional. In parallel, a wired footswitch can also be used.

The status of the battery is indicated by an LED-indication on the footswitch itself, so that the user can decide when the footswitch needs to be recharged.

The wireless footswitch can easily be cleaned in water. It has the highest water ingress protection standard (IPX8).

The wireless footswitch has an on/off switch. It can be switched off when not in use. When the footswitch is active, but not in use, it will go into a sleep-mode. It will be re-activated when touched or when one of the pedals is pressed.

16	Cath Arm Support	1
-----------	-------------------------	----------

For brachial catheterisation and digital imaging technique

The support is made of X-ray transparent material with exception of the fixingclamp and pivots.

17	Peripheral X-ray Filter	1
-----------	--------------------------------	----------

Set of flexible x-ray filters to provide an uniform density in angiographic examinations of the lower peripheral area.

Comprising:

- one central filter, at the top edge provided with sizing markers at every 5 cm, length : 1 m
- two side filters, length: 1 m

18	Pivot for table base.	1
-----------	------------------------------	----------

For angiographic- and interventional procedures of the upper peripherals.

Provides improved table access for patient transfer.

Allows pivoting of the table base around its vertical axes.

Pivot range from -90 degrees to + 180 degrees (or -180 to +90 degrees) with locked positions on 0, -13/+13 (facilitating arm-angiography) and -90/+90 and 180 degrees.

Comprising:

- pivot device with graduated scale to be mounted on the universal floor plate of the table.

Compatible with Xper Table

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
19		Table top brake kit for the Xper Table	1		
		The table top brake kit prevents the table top from floating in case of a power off situation. A friction brake is applied to stop the longitudinal and lateral movement of the table top.			
20		Xcelera on Xper Module	1		
		This option integrates the Xcelera network application in the Allura Xper system. It allows operation of the Xcelera viewer with the Xper module in the examination room during an examination.			
		Display of Xcelera imaging in the examination room has to be arranged for the monitor ceiling suspension with an additional monitor or with MultiVision (sharing an existing monitor). Following Xcelera viewing functions are available on the Xper module:			
		<ul style="list-style-type: none"> • study selection • replay control (start/stop/autocycle, run step, image step) • Report selection (with page step, close report) • image settings (adjust Contrast, Brightness, Edge enhancement) and reset to original settings 			
21		Real time image link	1		
		Real Time digital image link to an off-line Allura Interventional Hardware station. This applies on the applications 3D-RA, StentBoost and 3D-CA on the Interventional Hardware. This dedicated digital link sends raw or processed image data (depending on the application) real time during monoplane exposures to the connected Interventional Hardware station, to allow instant results of the applicable reconstruction after the exposure run.			
		In biplane systems, this digital link is available for the frontal channel only.			
22		Rad Shield w/ Arm (Contoured)	1		
		61X76			
		Contoured Rad Shield with Arm rest. 61X76			
23		Cable Spooler	1		
24		Ceiling Track w/Column & Handle Ext	1		
		Mavig 2.5m Ceiling Track with Ceiling trolley, 360 degree column, and brake handle extension.			
25		LED Single Color Exam Lamp	1		
		LED Single Color M LED130F Examination Lamp			
		Portegra2 Extension/Spring Arm Combination with M LED 130F, Single Color, incl. Power Supply			
		Light in new dimension LED lamps support your daily operations through innovative technology and design. In addition to advantages provided by MAVIG with all light equipment, LED technology offers the following enhanced features:			
		<ul style="list-style-type: none"> • Faceted multi-lens system • In-depth illumination 			

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- Superior color rendition
- Extension arm 750mm
- Spring arm 900mm
- LED-Examination-light
- Operating voltage is 24V DC. The lamp is supplied with a transformer, should it be used with 230V.

Technical data LED 130F:

- Light intensity at 1 meter distance: 60.000 Lux
- Color rendering index: Ra = 95
- Focusable: yes
- Focusable size of the light field: 14-25 cm
- Color temperature: 4500 Kelvin
- Electronic light intensity control at the lamp head: standard dimming range: 50 - 100 %
- Temperature increase in head area: 0.5° C
- Mains: 230 V / 60 Hz
- Power consumption: 28 W
- Number of LEDs: 19
- Life-span of the LEDs: > 40.000 h
- Diameter of the lamp head: 33 cm
- Working distance: 70 - 140 cm
- Height Adjustment: 117 cm

26 **Single Phase UPS** **1**

The single phase UPS (Uninterruptable Power System) enables a proper shut-down of the Allura system processor-units in case of a hospital mains power failure.

Note:

In case a (local) three phase UPS is used, the single phase UPS is not required.

27 **25 kVA Fluoro only UPS - UPC** **1**

25 kVA Fluoroscopy Only Solution, Release 8.2 Ready.

This system includes the following components:

25 kVA UPS

- 480v AC 3 phase input; 480v AC 3 phase output
- Fully rated Static Bypass Switch
- Input Isolation Transformer; Output AutoTransformer
- Dimensions: 36.3D x 20"W x 59.8H"
- Weight: 998 lbs (approximate).

Universal Power Controller (UPC)

- Combines the Battery Cabinet and Universal Transfer Switch Functions.
- Provides 12.5 Minutes of runtime at full load on battery

100243 Allura Xper FD20

Line #	Part #	Description	Qty	Each	Price
--------	--------	-------------	-----	------	-------

- Provides all interconnections to fully integrate into CV Lab.
- All previous 480V system functionality retained from previous separate component design.
- All connections are via external terminal blocks, rear access.
- All breakers are externally accessible from front.
- Isolated compartments for Battery and Switch sections.
- Fully ETL tested and certified UL, cUL and CSA Compliant.
- Dimensions: 31.5"D x 17.2"W x 59.8"H
- Weight: 1020 lbs (approximate).

DC Power Supply

- Artesyn/Emerson Part Number 73610129
- Single Unit Included for Mono Plane Systems
- Dimensions: 13.9" L x 6" W x 3" H
- Weight: 40 lbs (approximate).

Wiring Harness

- Complete Harness connecting UPC and UPS to MA Cabinet, includes control and Auxiliary connections and wire sizes per schematics. 50ft UPC to MA and 15ft UPC to UPS.
- Shipping Dimensions: Approx 31"L x 28"W x 22"D
- Weight: 140 lbs (approximate).

R8.2.1 UPS Control Kit

- Knife Switch rated 100A at 600V
- 120V rated Aux Switch Contacts
- Wall Mounted NEMA Enclosure
- Dimensions: 20"Hx 15"W x 8"D
- Weight: 25lbs

Included in UPC:

- Contactor MC3

28**Black Anti-Fatigue Floor Mat w/
Blue Logo****1**

Blue Anti-Fatigue Floor Mat w/ Logo