

## Discovery XR656 Plus 2D

### Discovery XR656 Plus Base System with TWO FlashPad Detectors

The Discovery XR656 Plus is an advanced digital radiographic imaging system that provides excellent image quality, a variety of image manipulation and post-processing tools as well as the option to utilize GE Healthcare's exclusive advanced clinical applications. Powered by FlashPad, GE's wireless digital detector, workflow is streamlined with TWO portable detectors that can be used in the table, wall-stand or freely to best accommodate most 2D exam requirements as well as advanced radiographic requirements.

At its core, the Discovery XR656 Plus delivers improved productivity through an efficient and intuitive workflow. The base system comes equipped with a systems cabinet, acquisition review workstation, image processing tools, short-term storage and quick in-room viewing of images. Also included is a host of networking and connectivity options, dose reporting and system maintenance. These features are designed to make this system easy to use and reliable while providing high quality radiographic images in a digital environment.

The Discovery XR656 Plus's core feature set can help streamline even the toughest exam. Consistent image quality helps reduce retakes, and unique image processing helps save time. With DICOM connectivity, the Discovery XR656 Plus connects easily to HIS, RIS or PACS for efficient data transfer.

The Discovery XR656 Plus base system includes:

Two wireless Digital Detectors with batteries and optional tether.

- Single panel (non-tiled) amorphous silicon detector with a Cesium Iodide scintillator and two handgrips that facilitate easy positioning and a secure grip.
- Wireless connectivity through Ultrawide Band Technology for fast, efficient and secure communications between the detector and the base system.
- Image area 40.4 cm x 40.4 cm (15.9 in. x 15.9 in.)
- Active matrix 2022 x 2022 pixels.
- Pixel pitch 200 microns.
- Typical upper dynamic range 7.8 mR @ RQA5.
- Typical DQE 68 @ 0lp @ RQA5.
- Weighs 4.32 kg (9.52 lb.) without battery, 0.18 kg (0.40 lb.) battery weight.
- Dimensions: L 580 mm, H 452 mm, T 24 mm.
- Can support up to 160 kg (352 lb.) of distributed load.
- Battery or tethered operated. Includes two rechargeable and exchangeable batteries and 7 m cable (4 m or 10 m optional) for optimal connectivity and power.

- One 6:1 clip-on grid for FlashPad detectors.
- Battery allows for 150 images to be taken in 3 hours.
- QAP (Quality Assurance Procedure)
- FlashPad detector can support Advanced Applications that are options available on the Discovery XR656

#### Acquisition Workstation

The Acquisition Workstation is the primary interface to the network and provides image post-processing capabilities. The System Controller Module provides single point control, directing and coordinating overall system operation, while monitoring all system modules automatically through software.

The Acquisition Workstation includes:

- Two 19-inch Flat Panel Monitors that help minimize desktop space required.
- Keyboard and Mouse
- CPU Tower with 6GB RAM, 320 GB of hard drive storage and capacity for over 22,000 images.
- 120/140 VAC, 50/60 Hz.
- Easy Image Manipulation and
- Image Display Tools which include:
  - Window width and level
  - Gray scale/contrast invert
  - Interpolated zoom and roam
  - Image flips (horizontal, vertical) with automatic indicator
  - Image Rotate - 90 degree increments
  - Free rotation - 360 degrees
  - Image orientation management
  - Electronic Left/Right Markers
  - Free text annotation
  - Manual shuttering
  - Image Annotations and Measurement Tools
  - Multi-Resolution Post Processing
  - Customizable Image Processing to Match
  - User Preferences
  - CD-RW and DVD Drive for Image Archive

- Image Viewer on Archive CD's and DVD's

#### Acquisition Control System

- Single Point System Control and Monitoring.
- Auto-Protocol Programming: comes with default set of exam and view protocols and the ability to build an infinite number of exams or views through the editor function. User also has the ability to attach acquisition protocols.
- System manager allows equipment error logging and provides resident power-up diagnostics.
- kVp selections range from 40-150 in 1 kVp increments
- Focal Spot Sizes of 0.6 and 1.2 mm - mA

#### Patient Management

- DICOM Modality Worklist for HIS/RIS - SCU (with programmable auto refresh)
- Patient edit/auto-folding (Copy exam)
- Patient Dose Reporting Calculated Dose Monitoring (mGy)
- "Patient Directory" provides fast access to the image and exam database for case reviews and file management.
- Detector Exposure Indicator: tool for detector dose feedback to ensure exposure was within normal limits.
- Emergency Patient Exam Capability Emergency patient feature - allows user to open exam and acquire images without a worklist entry.
- The Copy Patient function allows merging of the patient information with the exam images.
- Fast Image Display - Average time for a partially processed image is approximately three seconds and less than eight seconds for a fully processed image. Times may vary based on how the detector is connected to the system (i.e. docked, tethered or wireless)
- Set of default adult and pediatric protocols allows quick selection of the appropriate techniques for common procedures/exams with the ability to define unlimited number of custom protocols.
- Set of 4 Factory (GE pre-set) image processing selections (looks) optimized for each anatomical view with the ability to define multiple Custom looks for each anatomical view/ patient size combination.
- Automatic image storage and print with DICOM 3.0 and IHE Compliant networking, further increasing exam throughput and decreasing examination time for patients.

#### Image Quality and Dose

- Multi-resolution image processing capability

- Tissue Equalization used to correct over-penetrated and under-penetrated areas within the image.
- Auto and manual image shuttering cropping tool.
- Automated brightness/contrast setting (Smart Windowing)
- Orthopedic Magnification/Print.
- Detector Exposure Index (DEI) - dose tracking and QC metric.
- Dose Area Product (DAP) - entrance dose metric.
- Grid Line Reduction (selectable)
- Intelligent Collimator Edge Detection automated, image based cropping/shuttering tool that relies solely on image information to locate the collimator edges present in the image.
- Orthopedic Magnification/Print

DICOM and Standard Networking Capabilities Images may be transmitted manually or automatically through the DICOM interface to printers, archival devices, servers or review workstations.

Please refer to the DICOM Conformance Statement for complete definition of supported DICOM connectivity services.

DICOM and Standard Networking Capabilities include:

- Ethernet Network Link - DICOM 3.0.
- DICOM Storage (with auto-send to different locations)
- DICOM Storage Commitment (with programmable auto delete function)
- DICOM Modality Worklist for HIS/RIS (with auto refresh)
- DX/CR Worklist Filtering.
- DICOM Media Interchange on DVD-R.
- DICOM Modality Perform Procedure Step (MPPS) feedback to the HIS/RIS (SPS PPS)
- DICOM Grayscale Print (with print layout at the console)
- DICOM Query/Retrieve (retrieves images back from PACS)
- System Access & Authorization Control to support HIPAA Compliance.
- Full Range of Printing Options.
- Numerous Layout and Format Options.

Systems Cabinet

- Built-in System Distribution Power Module and Circuit Breaker for Single Point Power Feed to Room Subsystems
- Modular Designed X-ray Systems Based on a Digital Communications Network for

### Improved Reliability and Image Quality.

#### Quality Control/System Reliability Features

Preventing customer experienced system failures and reducing unplanned system downtime are critical.

The following features help to achieve these goals:

- Using the integrated system Quality Assurance Procedure (QAP), image quality checks can be easily performed by the customer.
- The QAP includes a phantom, optimized for Digital Image Quality testing and is included with the system.
- System changes are highlighted and can be corrected before they become a problem.

#### Discovery XR656 Overhead Tube Suspension

The Overhead Tube Suspension (OTS) system with motorized movement delivers excellent levels of operational support for efficient operation and precise positioning.

The Overhead Ceiling Tube Suspension Package includes:

- Auto-Positioning Package (included in base)
- Auto-Positioning enables the users to select a predefined system position from the system console and automatically move the equipment by simply holding the "Auto Positioning" buttons. This feature reduces user fatigue and increases the productivity of the operator.
- Auto-Positioning is controlled at the acquisition workstation or with the IR remote control, allowing the user to remain in the room while moving the system.
- Pre-set positions at the table, wallstand and park position at various SIDs and vertical and horizontal orientations.
- Auto-Positioning will incorporate angulation of the tube, longitudinal, lateral, rotational and vertical positioning of OTS, table detector longitudinal positioning, wallstand detector vertical positioning.
- Auto-Positioning comes with 7 default positions and up to 10 additional user defined positions can be added to the system.
- Tube and Detector Tracking Synchronized tube and detector tracking enables convenient workflow by keeping the tube correctly aligned with the wall-stand or table detector.
- Motorized 5-axis movements Supported Positions: park, table 100 cm SID (head, center, foot), wallstand 100 cm and 180 cm CID, and horizontal wallstand 100 cm SID.
- IR Remote - The infrared remote is an in-room control allowing the technologist greater flexibility & ability to pre-position the system automatically in preparation for the next clinical exam/view.

- Auto or manual positioning with single lock release and auto detents for assisted manual positioning.
- Touch-screen user interface with LCD screen display helps confirm patient data, review techniques, receptor selection and modify/confirm wireless detector association. The easy to Read, Auto Rotating user screen also includes a message readout line and easy to see light indicators.
- Patient Side Touch Screen User provides the following functions to the user:
  - Lock, Detent Control
  - Field of View Image Size Selection
  - Collimator Field Light Selection
  - Technique Adjust (kVp, mAs)
  - Receptor Selection (table, wallstand, wireless or cassette)
  - Exam Inhibit Display
  - Collimator Manual Override
  - Position Display (Source-to-Image Distance, X-ray Tube Angle, Column Rotation Angle)
  - Display of Patient Name for In-Room Verification (this feature can be disabled)

1	2, 3, or 4 Meter Longitudinal Drive Belt Kit
	2, 3 or 4 Meter Longitudinal Drive Belt Kit
1	Inboard Rail Select
	2, 3 or 4 Meter Longitudinal Rail Select (Dependent on Room Size)
1	2, 3, or 4 Meter Bridge Select
	2, 3 or 4 Meter Bridge Select (Dependent on Room Size)
1	2, 3, or 4 Meter Bridge Cable Select
	2, 3 or 4 Meter Bridge Cable Select
1	2, 3, or 4 Meter Bridge Cable Drape Select
	2, 3 or 4 Meter Bridge Cable Drape Select
1	Required Language Labels
	Required System Language Labels - English
1	80kW High Frequency Generator
	80kW High Frequency Generator, 50 or 60Hz The high frequency 80kW power unit is designed

for radiographic applications and utilizes microprocessor controlled power and parameter adjustment

Specifications:

- 1000mA at 80kVp
- 800mA at 100kVp

Input Power: 360-480VAC, 3 Phase, 60Hz

kVp Range: 40-150kVp, 1kVp increments

kVp Accuracy: 3% +/-2kVp mA Range:

- Small Focal Spot: 10-320mA
- Large Focal Spot: 160-1000mA

1 Table without Detector

Elevating table with floating tabletop and 3 AEC ion-chamber. Includes cross lateral detector holder.&

1 Table Top FlashPad Lateral Detector Holder

Table Top Lateral Detector Holder

Wireless DR detector holder, designed specifically for GE, secures the detector in a vertical position on the tabletop for cross-table imaging.

1 656 Plus Ext WS w 3 Grids

Discovery XR656 Plus Tilting Wallstand with Extended Length Arm

Discovery XR656 Plus Digital Tilting Wallstand is designed for radiography applications with the patient standing, sitting or lying on a gurney.

The Discovery XR656 Plus wallstand is designed for use with GE's exclusive FlashPad wireless digital detector, overhead tube suspension, ion chamber and removable non-reciprocating grid. The FlashPad wireless digital detector can be operated docked, tethered, or in a wireless digital cassette mode

- The wallstand is motorized Electromagnetic braking secures vertical motion.
- Motorized receptor tilting controlled with either IR remote control or hand switches located on the arm.
- Vertical motorization of the wallstand with foot switch or IR remote control.
- Auto-tracking from the overhead tube suspension.
- Graphic outlines of image sizes and ion chamber scan areas on the front panel enhance accuracy and safety. Preparation is fast and simple for better patient throughput.

- The wallstand tilts from -20 degrees to 90 degrees.
- The wallstand grids are removable from the side.
- It is configurable for either left or right side insertion.
- The wallstand comes with one removable grid
- 130 cm Focus Grid
- 180 cm (72 in.) focus grid with a SID range of 145 cm - 245 cm (70 lines/cm, 13:1 ratio)
- Automatic Exposure Control (AEC) utilizes three ion chamber sensors, which are mounted between the patient and digital detector.
- Automatic Exposure Control (AEC) on this extended arm utilizes three ion chamber sensors which are mounted between the patient and digital detector on the wallstand. The addition of the 4th ion chamber provides for supine chest and abdominal imaging when a stretcher is used (anytime the wallstand housing is horizontal ). The standard right, left and center ion chambers are available when the wallstand is in the vertical position.
- Includes patient handgrips and a lateral support bar.

100 cm Focus Wallstand Grid - 100 cm (40 inch) focus - 13:1 ratio, 70 lines/cm

1

Dual Energy - Chest and Abdomen

Dual Energy Subtraction Chest and Abdomen

Dual Energy Subtraction is an Advanced Clinical Application.

Provides three diagnostic images:

- Standard
- Soft tissue only
- Bone only
- Technique is available for PA/AP chest and abdomen imaging.

1

VolumeRAD Table and Wallstand - 4 Sweeps

VolumeRAD at Wallstand and Table with Extended Arm (4 sweeps)

VolumeRAD is an advanced application for radiographic X-ray imaging. It allows retrospective reconstruction of a number of planes (slices) from a series of low dose exposures acquired within a limited angular range. These slices show anatomical structures at different depths

This application supports the following four sweeps at wallstand:

- Table Horizontal sweep of the tube over the table for prone or supine imaging
- Vertical tube sweep at the wallstand for upright imaging
- Horizontal sweep of the tube over the stretcher for prone or supine imaging (requires the



selection of the extended arm wallstand)

- Lateral tube sweep at the wallstand for cross table imaging over the stretcher for prone or supine imaging

1

#### Repeat and Reject Analysis for the Discovery XR656

##### Repeat and Reject Analysis for the Discovery XR656

The Repeat and Reject Analysis (RRA) software package is a quality control (QC) application available for the Discovery XR656 that allows for repeat or reject images to be captured and categorized by technologist. It is designed to help track and analyze the X-ray repeat rate

- The easy-to-use operator interface helps technologists classify each image they reject and to select a specific reason for the repeat /image rejection.
- RRA can be a helpful teaching tool because it includes links to actual JPEGs of the rejected images to help the user analyze why the image was rejected.
- The RRA application tracks the rejected image data by operator, exam type, date and reason code.
- Reports can be exported in DVD, CD or USB format for ease of use.

1

#### Auto Protocol Assist for the Discovery XR656

##### Auto Protocol Assist for the Discovery XR656

Auto-Protocol Assist - the Discovery XR656 system will automatically transition directly to the Acquire screen when the protocol code downloaded from the HIS/RIS (automatically performed with worklist refresh) matches the exam code contained in the protocol database. This tool eliminates the user steps required to select patient exam types and initiate an exam.

1

#### Barcode Reader

##### Barcode reader

The barcode scanner is a fast, easy way to enter data into the system. The printed bar code information comes from a RIS or HIS system through a network.

- Select the procedure from the Worklist.
- Add a patient to the Worklist

1

#### Infrared Remote

##### Infrared Remote Control

The infrared remote optionally allows remote control of several system features (e.g., collimator light, FOV selection, wallstand and OTS motorization).

- 1 130cm 6:1 Clip on Grid for FlashPad  
6:1 Clip on Grid  
Wireless DR detector snap on grid
- 130cm (51in) focus grid
  - 6:1 ratio, 70 lines/cm
- 1 UPS  
Uninterrupted Power Supply
- 1 100cm Focus Grid  
100 cm Focus Table Grid  
- 100 cm (40 inch) focus - 12:1 ratio, 70 lines/cm
- 1 Mid-Range 130cm Focus Grid  
Mid-Range Wallstand Grid  
- 130 cm (51 inch) focus - 10:1 ratio, 70 lines/cm - Used for SID ranges from 90 to 190 cm
- 1 700 VA Partial UPS for XR640, XR650, D8000, XR2-d  
700 VA Partial System UPS - XR640, XR650, Definium 8000, XR2-d  
Tested with all MR system computers, the 700VA Partial System UPS provides reliable, clean, consistent power for the data processing portion of the imaging system. The use of the double conversion UPS enables the XR system data processing portion electronics to operate when there is a power anomaly or total power loss. Valuable data and the system operating software are protected, if there is an extended outage the UPS allows for an orderly shutdown of the system.
- FEATURES/BENEFITS
- True double-conversion, online technology provides reliable operation and uninterrupted glitch free power
  - Automatic frequency selection eases startup, i.e., 50 or 60 Hz compatible
  - Integral Electronic Static Bypass switch means zero transfer time
  - Improves user productivity, system reliability, reduces service costs and increases system uptime
  - Advanced Battery Management (ABM) software monitors / indicates battery health and improves battery service life

#### COMPATIBILITY

- Optima XR640, Discovery XR650, Definium 8000, XR2-d

#### NOTES

- This is a partial system UPS - it covers only the computer, not the entire MR imaging system. After a power event portions of the system will have to be reset before operation can resume
- Customer is responsible for rigging and arranging for installation with a certified electrician
- ITEM IS NON-RETURNABLE AND NON-REFUNDABLE

1

25 KAIC X-Ray Main Disconnect Panel 80 Amp, 480 V / 208 V

25 KAIC X-Ray Main Disconnect Panel 80 Amp, 480 V / 208 V

#### FEATURES/BENEFITS

- Serves as the main power disconnect between the X-Ray system and the facility 480V or 208V power source
- Provides emergency shut down, undervoltage protection and overcurrent protection for the X-Ray power distribution cabinet
- Standardized design provides a platform for future upgrades of the system
- Offers a number of advantages by combining a variety of individual components into a single pre-engineered and factory tested panel
- UL and cUL listed for compliance with NEC Article 100 and Article 110-3
- Remote emergency off pushbutton located by X-Ray control provides immediate shut down of the entire system to comply with NEC required disconnecting means
- Surface or semi-flush mounting

#### SPECIFICATIONS

- Dimensions (H x W x D): 48" x 20" x 6.68"
- Weight: 80 lbs.
- Mounting: via keyhole slots; Width is 16" on centers, Height is 45.5" on centers

#### COMPATIBILITY

- GE Three Phase X-Ray generators

#### NOTES:

- Customer is responsible for rigging and arranging for installation with a certified electrician
- ITEM IS NON-RETURNABLE AND NON-REFUNDABLE

---

1	6 Day X-ray System Training 6 Day XR System Training One 4 day and one 2 day TiP Onsite Training visits for the X-ray system. Includes T&L expenses. Days provided consecutively. This training program must be scheduled and completed within 12 months after the date of product delivery.
1	WALLSTAND CABLE SELECT Connection cables for the wallstand
1	TABLE CABLE SELECT Connection cables for the table