

three inches = one foot  
one and one half inches = one foot  
one inch = one foot  
one inch = one foot  
three quarters inch = one foot  
one half inch = one foot  
one eighth inch = one foot  
one quarter inch = one foot  
one eighth inch = one foot

| Equip ID | Equipment Name                            | New Qty | Reuse Qty | Manufacturer                  | Model                          | Part                        | Provides   | Installs   | Specifies  | Approves | Mounting | HVAC     | Plumb | Volts  | ~ | Hz        | Phase | Amps    | Watts  | "w | "d  | "h  | Weight (lbs.) | Description | Henry Adams' Drawing No.  |   |        |
|----------|---|---------|-----------|-------------------------------|--------------------------------|-----------------------------|------------|------------|------------|----------|----------|----------|-------|--------|---|-----------|-------|---------|--------|----|-----|-----|---------------|-------------|---|---|--------|
| IDCHR63  | Task Chair with Arms                      | 7       | 0         | Humanscale                    | Freedom Chair                  |                             | Owner      | Owner      | Int Des    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 24  | 24  | 40            |             |   | EQ-043  |        |
| IDCHS15  | Allowance- Conference Chair with Casters  | 11      | 0         | KI (Krueger International)    | TGWAW Torsion on the Go!       |                             | Owner      | Owner      | Int Des    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 24  | 24  | 33.3          |             | Upholstered seat. Seat and back are field replaceable. Chairs can be nested.  | EQ-044  |        |
| IDCHS46  | Upholstered Guest Chair, Standard-Width   | 2       | 0         | Bialek Environments           | Snowball 1; Std 18.5" w Seat   | (1801) Four Point with Arms | Owner      | Owner      | Int Des    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 23  | 22  | 33            |             | Stacks 10 high with dolly, 6 on the floor. Chairs can be freestanding or connected. Ability to gang chairs with connecting clips or connecting bars. Separate seat and back. Seat and back can be upholstered in different fabrics at no upcharge. Seat and back upholstered. Exceeds BIFMA Seating Durability Test to 500 lbs per chair. Seat shell is made from 100% recycled plastic. Spec offers a variety of anti-bacterial and anti-microbial Crypton and Vinyls through our fabric supply partners. Exposed back bracket. Frame is 0.875" in diameter. |   |        |
| IDCHS47  | Upholstered Guest Chair, Midsize-Width    | 2       | 0         | Bialek Environments           | Snowball 1; Midsize 22" w Seat | (1804) Four Point with Arms | Owner      | Owner      | Int Des    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 27  | 22  | 33            |             | Stacks 4 high with dolly, 6 on the floor. Chairs can be freestanding or connected. Ability to gang chairs with connecting clips or connecting bars. Separate seat and back. Seat and back can be upholstered in different fabrics at no upcharge. Seat and back upholstered. Exceeds BIFMA Seating Durability Test to 500 lbs per chair. Seat shell is made from 100% recycled plastic. Spec offers a variety of anti-bacterial and anti-microbial Crypton and Vinyls through our fabric supply partners. Exposed back bracket. Frame is 0.875" in diameter.  |   |        |
| IDCHT01  | Task Chair with Arms                      | 5       | 0         | Bialek Environments           | Embody                         |                             | Owner      | Owner      | Int Des    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 30  | 30  | 43.5          |             |   |   |        |
| IDCUB50  | Allowance- Modular Casework Segment       | 5       | 0         | Herman Miller Inc.            | (to be defined)                |                             | Owner      | Vendor     | Vendor     | Owner    | Maj Inst |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| IDTBT08  | Flip-Top Conference Table, 60" w x 24" d  | 4       | 0         | Vecta (a Steelcase Company)   | Akira Rectangle Flip-Top       | AKF6024RLC (Grade 2)        | Owner      | Owner      | Int Des    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 60  | 24  | 28.5          |             | Table has casters.  | EQ-047  |        |
| INCUI06  | Biological Indicator Test Incubator 58°C  | 1       | 1         | Advanced Sterilization Prod.  | 21005                          | (for Sterrad)               | Owner      | Owner      | Eq Plnr    | Owner    | Counter  |          |       | 120 AC |   | 60 Single |       | 0.4     | 48     |    | 7.8 | 5.5 | 9             |             | Incubates up to 18 biological indicators at 58°C (+/- 2°C). Open well design provides viewing of vial contents while incubating. Use only Sterrad CycleSure biological indicator to achieve specified incubator performance.  | EQ-048  |        |
| INCUI07  | Incubator Biological Indicator, Steam     | 0       | 2         | 3M Health Care                | Attest Auto-Reader 390         |                             | Owner      | Owner      | Eq Plnr    | Owner    | Counter  |          |       | 120 AC |   | 60 Single |       | 0.6     |        |    | 9   | 9   | 3.5           |             | Biological indicators are used for load control monitoring which is the process by which a load is monitored and released based on the result of a biological indicator (BI) The Attest Auto Reader has rapid readout biological indicators and test packs for 250°F/121°C Gravity and 270°F/132°C Vacuum Assisted Steam Sterilizers.   | EQ-049  |        |
| MATAF03  | Anti-Fatigue Matting, 60"x 36"            | 4       | 0         | Cactus Mat Manufacturing Co.  | Cushion Comfort C Style        | Style 1075                  | Owner      | Owner      | Eq Plnr    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 60  | 36  | 0.5           | 15          | 1/8" Marbleized Rubber surface. Drrable surface bonded to sponge base. The rubber surface material provides the best resistance to abrasion and will provide maximum product life for heavy traffic areas. The edges are beveled. Excellent anti-fatigue qualities. Not for use in wet areas or with high heels or stools, which may puncture surface.  | EQ-051  |        |
| MATAF05  | Anti-Fatigue Matting, 72"x 36"            | 7       | 0         | Cactus Mat Manufacturing Co.  | Cushion Comfort C Style        | (Smooth Rubber Top) 1075    | Owner      | Owner      | Eq Plnr    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 72  | 36  | 0.5           | 18          | Smooth rubber top laminated to 3/8" foam backing. Not for use with high heels. Marbled design. All edges beveled.   | EQ-052  |        |
| MIXDF10  | Four-Chamber Cleaning Solution Dispenser  | 2       | 0         | Johnson Wax                   | Butcher's Command Center       |                             | Contractor | Contractor | Eq Plnr    | Owner    | Wall-Mtd |          | Y     |        |   |           |       |         |        |    | 24  | 14  | 24            | 100         | Dilution control system has no chemical contact and lockable cabinet for safety and security. Easy to use push-button convenience with 4 gpm bucket fill options. A wide range of super-concentrates are available. Coice of dispensing, bucket or bottle fill. Bottles fill at 1 gallon per minute. Low foam, no mess. Fills buckets, autoscrubbers and extractors at 4 gallons per minute. Each button can be adapted for either bucket or bottle fill.   | EQ-053  |        |
| OVENM75  | Commercial Countertop Microwave, 1000 W   | 1       | 0         | Summit Appliances Division    | SCM1000S5                      |                             | Owner      | Owner      | Eq Plnr    | Owner    | Counter  |          |       | 115 AC |   | 60 Single |       |         | 1000   |    | 21  | 17  | 12.3          | 39          | Commercially approved to NSF standards. Brushed Stainless Steel exterior and interior. Digital controls. 0.9 cu. ft. Capacity. Includes a programmable child lock and function to count how many times the oven has been used.  | EQ-054  |        |
| PASST03  | Pass-Through Rack Return                  | 1       | 0         | STERIS Corporation            | Amsco Reliance 444 Rack Return | FD24-100                    | Contractor | Contractor | Eq Plnr    | Owner    | Maj Inst |          |       |        |   |           |       |         |        |    | 35  | 47  | 67.3          | 235         | Allows washer accessories and manifold racks to be returned from prep and pack area to the decontamination room. Door spring system allows self-closing action; doors remain closed when there is room pressure differential. Optional barrier wall flanges seal the wall opening between the rack return and the building wall. 31" h loading height.  | EQ-055  |        |
| PASST03X | Vendor Installation of Rack Return        | 1       | 0         | STERIS Corporation            | (for 444 Rack Return)          | SE101402                    | Contractor | Vendor     | Eq Plnr    | Owner    |          |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| PASST13  | Pass-Through Window Assembly              | 2       | 0         | STERIS Corporation            | CG71005 (Confirm #)            |                             | Contractor | Contractor | Eq Plnr    | Owner    | Maj Inst |          |       |        |   |           |       |         |        |    |     |     |               |             |   | Mounted in building wall. Tempered, safety glass window provides opening for transferring clean items from decontamination area to preparation/packaging area. Stainless-steel counter, mounted below pass-thru window, for receiving and holding items that were manually cleaned in the decontamination area. | EQ-056 |
| PASST13Y | Vendor Installation of Pass-Thru Window   | 2       | 0         | STERIS Corporation            | CG74012                        | SE101412                    | Contractor | Vendor     | Eq Plnr    | Owner    | Maj Inst |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| PATTR50  | 42" LCD Display for Patient Tracking Sys  | 0       | 0         | (Manufacturer Unknown)        |                                |                             | Contractor | Contractor | Eq Plnr    | Owner    | Wall-Mtd |          |       | 120 AC |   | 60 Single |       | 0.9     | 337    |    | 40  | 3.5 | 24            | 69.4        | 42" LCD display panel. Host of stands and mounting options available.   | EQ-055  |        |
| PHONE27  | Conference Phone                          | 1       | 0         | Polycom, Inc.                 | SoundStation2 EX               |                             | Owner      | Owner      | Telecom    | Owner    | Counter  |          |       | 120 AC |   | 60 Single |       |         |        |    | 12  | 15  | 2.5           | 1.8         | Tabletop console contains audio processing functions and keypad. Wall module contains power and telephone line interfaces. Cables consist of 21 ft (6.4 m) single-cord connection to tabletop console and 7 ft (2.1 m) connection to RJ-11 telephone jack. 3 cardioid microphones with intelligent mic mixing and 10-foot pickup range. Adjustable volume with dynamic noise reduction. Caller ID, graphical backlit LCD, user selectable ring tones. 12-Key telephone keypad with mute, volume up/down keys.   | EQ-056  |        |
| PHONE27A | Two Extension Mics for Conference Phone   | 1       | 0         | Polycom, Inc.                 | SoundStation2 External Mics    | 2200-07840-001 (2 Pack)     | Owner      | Owner      | Telecom    | Owner    | Counter  |          |       |        |   |           |       |         |        |    |     |     |               |             | 2 For use with SoundStation2 EX only. Increases Soundstation2 EX capacity to 16 users. One year warranty.   | EQ-057  |        |
| PRINY52  | Black & White Laser Printer               | 5       | 0         | Hewlett-Packard Business Sys. | HP LaserJet P3015dn            | CE528A                      | Owner      | Owner      | Info Sys   | Owner    | Counter  |          |       | 120 AC |   | 60 Single |       |         | 780    |    | 18  | 16  | 12.4          | 35          | Recommended monthly volume: 1,500 to 5,000 pages. Duty cycle: up to 100,000 pages. Printing speed of 42 ppm, 600 sheet paper capacity (2 trays). 540 Mhz processor. 128 MB memory; expandable to 640 MB. Automatic two-sided printing.  | EQ-058  |        |
| PUMPE11  | Automated Endoscopy Flushing Pump         | 2       | 0         | PCI Medical Inc.              | Endo-Flush EFP-500             |                             | Owner      | Owner      | Eq Plnr    | Owner    |          |          | Y     | 120 AC |   | 60 Single |       | 0.7     |        |    | 6.5 | 8.5 | 8.3           | 11          | Automated solution to cleaning endoscopes prior to high-level disinfection in an automated endoscope reprocessor. Unit replaces the process of manual flushing of endoscopes with a syringe. Unit can be placed on a countertop or be wall mounted. EFP-500 is computer controlled and programmed to ensure that each channel receives the correct amount of detergent, water and air. Cut sheet lists complete list of compatible endoscopes.  | EQ-059  |        |
| RACSW04  | Mobile Sterile Wrap Rack                  | 2       | 0         | InterMetro Industries Corp.   | SWR566DC                       | plus top shelf              | Owner      | Owner      | Eq Plnr    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 60  | 24  | 68            | 85.4        | Tiered-design with four bars. Wire bottom shelf. Stainless steel. Top shelf ordered separately part # 2460 NC.  | EQ-061  |        |
| REFRZ74  | 13.8 cf Refrigerator/Bottom Freezer/Lock  | 1       | 0         | Summit Appliances Division    | FFBF280W (with LL Lock)        |                             | Owner      | Owner      | Eq Plnr    | Owner    | FloorStd |          | Y     | 110 AC |   | 60 Single |       | 2.5 max |        |    | 28  | 26  | 75.3          | 200         | 13.8 cubic feet refrigerator with bottom freezer has locks for both doors. Also includes adjustable glass shelves, two crispers, and door racks.  | EQ-062  |        |
| SCANB05  | Handheld Barcode Scanner                  | 6       | 0         | Metrologic Instruments Inc.   | Voyager CG                     | MS9540                      | Owner      | Owner      | Eq Plnr    | Owner    | Counter  |          |       | 5 DC   |   | Single    |       |         |        |    | 3.1 | 7.8 | 1.6           | 0.3         | Single-line laser scanning of all standard 1D bar codes. 650-nanometer laser.   | EQ-064  |        |
| SEALH04  | Heat Sealer                               | 2       | 0         | Rennco Inc.                   | 18 LS                          |                             | Owner      | Owner      | Eq Plnr    | Owner    | Counter  |          |       | 120 AC |   | 60 Single |       | 5       |        |    | 19  | 10  | 7.3           | 46          | Capable of sealing products up to 18" ( 457mm) wide. Produces a 0.5" (12mm) seal and is ideal for sealing polyethylene, flat or gusseted laminated paper/plastic pouches, or TYVEK pouches. Includes variable heat control feature.   | EQ-065  |        |
| SFURN01  | Systems Furniture- Herman Miller Canvas   | 1       | 0         | Bialek Environments           |                                |                             | Owner      | Vendor     | Sys Furn   | Owner    | FloorStd |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SFURN02  | Systems Furniture- Herman Miller Canvas   | 1       | 0         | Bialek Environments           |                                |                             | Owner      | Vendor     | Sys Furn   | Owner    | FloorStd |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SFURN03  | Systems Furniture- Herman Miller Canvas   | 1       | 0         | Bialek Environments           |                                |                             | Owner      | Vendor     | Sys Furn   | Owner    | FloorStd |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SFURN11  | Systems Furniture- Herman Miller CoStruc  | 1       | 0         | Bialek Environments           |                                |                             | Owner      | Vendor     | Sys Furn   | Owner    | FloorStd |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SFURN12  | Systems Furniture- Herman Miller CoStruc  | 1       | 0         | Bialek Environments           |                                |                             | Owner      | Vendor     | Sys Furn   | Owner    | FloorStd |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SFURN14  | Systems Furniture- Herman Miller CoStruc  | 1       | 0         | Bialek Environments           |                                |                             | Owner      | Vendor     | Sys Furn   | Owner    | FloorStd |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SFURN15  | Systems Furniture- Herman Miller CoStruc  | 1       | 0         | Bialek Environments           |                                |                             | Owner      | Vendor     | Sys Furn   | Owner    | FloorStd |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SFURN16  | Systems Furniture- Herman Miller CoStruc  | 1       | 0         | Bialek Environments           |                                |                             | Owner      | Vendor     | Sys Furn   | Owner    | FloorStd |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SHELM48  | Wall-Mounted Wire Shelving, 48" w x 18" d | 2       | 0         | InterMetro Industries Corp.   | 18WB5C, 1848C, 1848C           |                             | Owner      | Contractor | Contractor | Eq Plnr  | Owner    | Wall-Mtd |       |        |   |           |       |         |        |    | 48  | 18  | 31.7          | 33.5        | Mount consists of two shelf supports and mounting brackets. Bolts or screws not included- select according to wall type. Two wire shelves.  | EQ-066  |        |
| SHELW39  | Mobile Shelving Unit, 36" w x 18" d       | 4       | 0         | InterMetro Industries Corp.   | Mobile 5 Wire Tiers & 1 Solid  |                             | Owner      | Owner      | Eq Plnr    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 36  | 18  | 80            |             | Mobile 6 shelf unit includes 5 wire shelves and 1 solid galvanized bottom shelf.  | EQ-067  |        |
| SHELW48  | Mobile Wire Shelving, 48" w x 24" d       | 26      | 0         | InterMetro Industries Corp.   | Stem Caster Cart, 6 Tiers      | (Solid bottom shelf)        | Owner      | Owner      | Eq Plnr    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 48  | 24  | 80            |             | For specifications: Posts 74" high and casters 6" high.   | EQ-068  |        |
| SHELW60  | Mobile Wire Shelving, 60" w x 24" d       | 72      | 0         | InterMetro Industries Corp.   | Stem Caster Cart, 6 Tiers      |                             | Owner      | Owner      | Eq Plnr    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 60  | 24  | 80            |             | 5 wire shelves, 1 solid shelf on bottom.  | EQ-069  |        |
| SINKM49  | Height-Adj. Two-Sink Cleanup Counter      | 1       | 0         | STERIS Corporation            | CCPS317735AH                   |                             | Contractor | Contractor | Eq Plnr    | Owner    | Maj Inst |          | Y     | 120 AC |   | 60 Single |       |         |        |    | 77  | 31  | 39            |             | Electrically height-adjustable two-bay clean-up sink. 300 Series Stainless Steel; welded construction. Etched gallon indicators for measuring detergents and chemicals. Pump: 1.0 kg maximum load; maximum lift speed with electric motor: 30mm/second (1.18"/second). Total lift length up to 300mm (11.82"). This two-bay sink is 77" overall.  | EQ-070  |        |
| SINKM49X | Vendor Installation of Clean-Up Sink      | 1       | 0         | STERIS Corporation            | SE101432                       |                             | Contractor | Vendor     | Eq Plnr    | Owner    | Maj Inst |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SINKM54  | Height-Adj. Three-Sink Cleanup Counter    | 2       | 0         | STERIS Corporation            | CCPS319753AH                   |                             | Contractor | Contractor | Eq Plnr    | Owner    | Maj Inst |          | Y     | 120 AC |   | 60 Single |       |         | 140 VA |    | 98  | 31  | 39            |             | Electrically height-adjustable triple-bay clean-up sink. 300 Series Stainless Steel; welded construction. Etched gallon indicators for measuring detergents and chemicals. Pump: 1.0 kg maximum load; maximum lift speed with electric motor: 30mm/second (1.18"/second). Total lift length up to 300mm (11.82"). This three-bay sink is 97.5" w overall.   | EQ-071  |        |
| SINKM54X | Vendor Installation of Clean-Up Sink      | 2       | 0         | STERIS Corporation            |                                | SE101432                    | Contractor | Vendor     | Eq Plnr    | Owner    | Accsry   |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| SINKM55  | Height-Adj. Two-Sink Cleanup Counter      | 1       | 0         | STERIS Corporation            | Custom with 16" d wells        |                             | Contractor | Contractor | Eq Plnr    | Owner    | Maj Inst |          | Y     | 120 AC |   | 60 Single |       |         |        |    | 77  | 31  | 39            |             |   |   |        |
| SINKM55X | Vendor Installation of Clean-Up Sink      | 1       | 0         | STERIS Corporation            | SE101432                       |                             | Contractor | Vendor     | Eq Plnr    | Owner    | Maj Inst |          |       |        |   |           |       |         |        |    |     |     |               |             |   |   |        |
| STAPR15  | Printer/Fax Stand                         | 1       | 0         | Safco Products Company        | 1934                           |                             | Owner      | Owner      | Eq Plnr    | Owner    | FloorStd |          |       |        |   |           |       |         |        |    | 24  | 28  | 30            | 36          | Top surface measures: 24" w x 28" d. 1" laminate top may be reversed between Mahogany and Medium Oak. Black steel base with full width 6.75" d steel shelf and privacy panel. Cable routing cutouts for installation along a wall. Assembly required. Weight capacity: 50 lbs. Five year manufacturer warranty.   | EQ-072  |        |
| STERJ21  | Pass-Through Steam Sterilizer, 66" d      | 3       | 0         | STERIS Corporation            | Evolution Vac 66" Double Door  | Hinged                      | Contractor | Contractor | Eq Plnr    | Owner    | Maj Inst |          | Y     | 480 AC |   | 60 Three  | 6     |         |        |    | 48  |     |               |             |   |   |        |

|                                 |          |
|---------------------------------|----------|
| Revision No.3 - Trailer Removal | 06/26/17 |
| Addendum No. 2                  | 08-17-17 |
|                                 |          |
|                                 |          |
|                                 |          |
|                                 |          |
|                                 |          |
|                                 |          |
|                                 |          |
|                                 |          |
| Revisions:                      | Date     |

CONSULTANTS:

ROBERT L. SEYMOUR & ASSOCIATES, INC.

TRANSPORTATION  
ROBERT L. SEYMOUR & ASSOCIATES  
180 Thomas Johnson Drive  
SUITE 200  
FREDERICK, MARYLAND 21702

ALPHA CORPORATION  
1800 WASHINGTON BOULEVARD  
SUITE 405  
BALTIMORE, MD 21203

HENRY ADAMS  
Consulting Engineers  
MECHANICAL ELECTRICAL & PLUMBING ENGINEERS

KORBEL ASSOCIATES  
Fire Protection Engineers  
MEDICAL EQUIPMENT PLANNING

KORBEL ASSOCIATES INC.  
8700 WEST 27TH STREET, SUITE 279  
MINNEAPOLIS, MN 55408

INDUSTRIAL HYGIENISTS  
ADDRESS: MONITORING & ANALYSIS, INC.  
1331 ASHTON ROAD, P.O. BOX 646  
HANOVER, MARYLAND 21076

ARCHITECTS / ENGINEERS:

ERNEST BLAND ASSOCIATES, P.C.  
TECHNICAL FACILITIES DESIGN

802 SLIGO AVENUE, SILVER SPRING, MARYLAND 20910  
TELEPHONE (301) 589-4811 FAX (301) 589-3810

Project Status

Drawing No. **EQUIPMENT SCHEDULE**

Approved: Project Director

Project Title **SPS RENOVATION**

Location **WASHINGTON DC VA MEDICAL CENTER**

Date **06-26-2017** Checked **Checker** Drawn **Author**

Project Number **688-14-003**

Building Number **BUILDING NO. 1**

Drawing Number **EQ105**

Office of Construction and Facilities Management

Department of Veterans Affairs