

AIR DEVICE SCHEDULE (SUPPLY)																
MARK	TYPE	AIR FLOW				MAX APD		MOUNTING	PANEL/FRAME SIZE		NECK SIZE		NC	DAMPER	FINISH	REMARKS
		MIN		MAX		N	WG		IN x IN	[mm x mm]	IN	[mm]				
		CFM	[L/s]	CFM	[L/s]											
SD-1	PERFORATED FACE	VARIABLE	VARIABLE	VARIABLE	VARIABLE	0.030	[8]	DRYWALL/LAY-IN	18x18	[500x500]	VARIABLE	VARIABLE	20	INTEGRAL	WHITE	PROVIDE DAMPER AT BRANCH, SEE PLANS FOR MOUNTING. THROWER MANUFACTURER'S RECOMMENDATIONS TO MAINTAIN COMFORT THROUGH RANGE OF FLOWRATES.
SD-2	PERFORATED FACE	VARIABLE	VARIABLE	VARIABLE	VARIABLE	0.030	[8]	LAY-IN	24x24	[600x600]	VARIABLE	VARIABLE	20	INTEGRAL	WHITE	PROVIDE DAMPER AT BRANCH, SEE PLANS FOR MOUNTING. THROWER MANUFACTURER'S RECOMMENDATIONS TO MAINTAIN COMFORT THROUGH RANGE OF FLOWRATES.