

BR3 FAMILY


PROGRAMMABLE 3-RELAY LOGIC MODULES



PRIMARY APPLICATIONS



- 1 Br3 Receives Input
- 2 Br3 Relay 1 Releases Maglock
- 3 Br3 Relay 2 Activates Door



DESCRIPTION

BEA's Br3 family of logic modules provides both simple and advanced logic controls.

Functions include: timer, ratchet/latching, inhibitor, 2 relay sequencer + inhibitor, 2 relay sequencer + door position deactivation timer, 3 relay sequencer + "1-shot", 3 relay sequencer with "independent relay", interlock timer, interlock ratchet / latching, 2 way 2 relay sequence, normally locked restroom, normally unlocked restroom, 3 relay sequencer + "day / night mode".

Common uses for the Br3 family include automatic pedestrian doors, access control, industrial automation and single-occupancy restrooms.

FEATURES & BENEFITS


- Versatility with 12 programmable logic functions for the Br3; 13 for the Br3-X
- Two-button programming combined with dual seven-segment display provides simple setup
- Two 3-AMP relays and one 1-AMP relay, all with built-in surge suppression, eliminates the need for external components when installing some electric locking devices
- WET output with AC / DC voltage for powering an electric locking device directly from the module



BEA, Inc.
RIDC Park West
100 Enterprise Drive
Pittsburgh, PA 15275-1213

Customer Service: 800.523.2462
Technical Support: 800.407.4545
www.BEAinc.com

APPLICATIONS



FUNCTION DETAILS

BR3 FUNCTION	DESCRIPTION
10	Timer
11	Ratchet / Latching
21	Inhibitor with Door Position Input
22	2 Relay Sequence + Inhibitor
25	2 Relay Sequence
28	2 Relay Sequence + Door Position
29	Deactivation Timer
35	3 Relay Sequence
50	Interlock Timer
55	Interlock Ratchet / Latching
65	2-Way, 2 Relay Sequence
75	2 Relay Sequence

Br3-X FUNCTION	DESCRIPTION
10	Timer
11	Ratchet / Latching
22	2 Relay Sequence + Inhibitor
28	2 Relay Sequence + Door Position
29	Deactivation Timer
36	3-Relay Sequencer + '1-shot'
37	3-Relay Sequence with 'Independent Relay'
50	Interlock Timer
55	Interlock Ratchet / Latching
65	2-Way, 2 Relay Sequence
nL	Normally Locked Restroom
nU	Normally Unlocked Restroom
dn	3-Relay Sequencer + 'Day / Night mode'
00	Disable

TECHNICAL SPECIFICATIONS

Supply Voltage	12 – 24 VAC / VDC $\pm 10\%$
Power Consumption	30 – 130 mA; DRY Output
Temperature Range	Br3 Br3-X –15 °F – 150 °F –15 °F – 150 °F* *If powered by AC voltage and using WET output to convert to DC voltage and current draw of device is greater than 0.9 A, the upper temperature range is 130 °F
Dimensions	5.2 in (W) x 1.0 in (H) x 2.2 in (D)
Relay Hold Time	Up to 60 seconds per relay
Delay Between Relays	Up to 60 seconds per relay with ¼, ½ and ¾ second options
Housing Material	ABS Plastic
Input Specification	Inputs 1, 2, 3, 4 WET Input DRY contact 5 – 24 VAC / VDC $\pm 10\%$
Contact Rating	Relay 1 (DRY) Relay 1 (WET) Relay 2 Relay 3 3 A @ 24 VAC / 30 VDC 1 A 3 A @ 24 VAC / 30 VDC 1 A @ 24 VAC / 30 VDC

RELATED PRODUCTS



www.BEAinc.com

© 2017 BEA, Inc. All rights reserved.

BR3 FAMILY PROGRAMMABLE 3-RELAY LOGIC MODULES

BEA, Inc.
RIDC Park West
100 Enterprise Drive
Pittsburgh, PA 15275-1213

Customer Service: 800.523.2462
Technical Support: 800.407.4545

