

## Configuration - Included Items

Item	Part Number - Description	Qty	List Per Unit	Unit Price	Extended Price
1	<p>- SonoSite Edge II Ultrasound System</p> <p>The SonoSite EDGE II is a high-resolution, all-digital, 9.0-pound (4.1 kg) ultrasound system with a 12.1in. LED full-bleed glass display. The Edge II boosts improvements in cardiac and abdominal image quality through DirectClear Technology and a new wide-angle display, as well as alignment with the SonoSite pillars. The Edge II features Armored Cable Technology on select transducers, a keypad sealed to the Edge for protection against infection, and persistent knobs for more precise actions. As with our past products, the Edge II is designed with SonoSite's proprietary Chip Fusion Technology that integrates digital signal processing and multiple system functions into a custom application-specific integrated circuit (ASIC) microchip.</p> <p>The purchase of the SonoSite EDGE II system includes the following software technologies:</p> <ul style="list-style-type: none"><li>- 2D grayscale with SonoMB Multi Beam Technology</li><li>- Auto Gain with SonoADAPT Tissue Optimization Technology</li><li>- M-Mode</li><li>- Application specific calculation packages</li></ul> <p>SonoSite EDGE II's reliability and durability are backed by a five-year standard warranty, which is included in the price of the system. Software upgrades to the main system and transducer databases are accomplished through one of two USB ports on the system. Also includes battery, ultrasound gel, and user guide on a CD (Printed user guides also available as a purchasable option).</p> <p>Included with the purchase of your SonoSite EDGE II, you will receive four consecutive hours of installation provided by a SonoSite Clinical Specialist. The installation includes an overview of the product and accessories purchased, training on the features, functions, and user interface, and system care/maintenance. Available for US locations only. Additional clinical installation support can be purchased separately as needed.</p>	1			
2	<p>- ACO Technology</p> <p>Automated Cardiac Output enables the clinician to rapidly assess quantitative cardiac output information and eliminate the need to manually navigate through complex measurement packages. Note: PW and/or CW is required when purchasing this option.</p>	1			

Item	Part Number - Description	Qty	List Per Unit	Unit Price	Extended Price
3	<p>- Steep Needle Profiling Technology (SNP)</p> <p>Proprietary software that enhances the system's ability to aid needle visualization. Ultrasound waves are periodically directed towards the needle to enhance visualization, without compromising image quality of the 2D image.</p>	1			-
4	<p>- Color Application Package, SonoSite EDGE II</p> <p>This package provides the following capabilities for the transducers that support these features:</p> <ul style="list-style-type: none"> <li>- Tissue Harmonic Imaging (THI): Capability in which the system transmits at one frequency and receives at a higher harmonic frequency to reduce noise and clutter and improve resolution.</li> <li>- SonoHD Imaging Technology: Significantly reduces speckle noise while enhancing tissue margins, thereby dramatically improving contrast and structural resolution.</li> <li>- Velocity color flow imaging provides the clinician with the color sensitivity to perform color Doppler examinations with all transducers during a clinical procedure.</li> <li>- PW Doppler is available on all transducers.</li> <li>- CW Doppler is a quantitative assessment of blood flow with Duplex imaging for higher flow velocities.</li> </ul>	1			
5	<p>- DICOM (Print, Store, Worklist, MPPS, Storage Commit)</p> <p>The DICOM package includes the capability to interface with your PACS network with the complete offering of DICOM capabilities: print, store, worklist, storage commit, and modality perform procedure step.</p>	1			
6	<p>- rC60xi / 5-2 MHz transducer Biopsy Compatible</p> <p>rC60xi / 5-2 MHz multi-frequency, broadband, 60 mm curved array transducer featuring DirectClear technology, (patent-pending transducer design that increases resolution and penetration without compromising SonoSite's renowned durability).</p> <p>Note: Please refer to the most recent version of the corresponding system specification sheet or transducer specification sheet for available exams supported by each system.</p>	1			
7	<p>- L38xi / 10-5 MHz transducer Biopsy Compatible</p> <p>L38xi / 10-5 MHz multi-frequency, broadband, 38 mm linear array transducer. This transducer is biopsy compatible.</p> <p>Note: Please refer to the most recent version of the corresponding system specification sheet or transducer specification sheet for available exams supported by each system.</p>	1			
8	<p>- rP19x / 5-1 MHz Transducer</p> <p>rP19x / 5-1 MHz multi-frequency, broadband, 19 mm phased array transducer featuring DirectClear technology (patent-pending transducer</p>	1			

Item	Part Number - Description	Qty	List Per Unit	Unit Price	Extended Price
	design that increases resolution and penetration without compromising SonoSite's renowned durability).				
	Note: Please refer to the most recent version of the corresponding system specification sheet or transducer specification sheet for available exams supported by each system.				
9	- C8 / 8-5 MHZ Broadband Intracavity Array Transducer C8x/ 8-5 MHz broadband intracavitary array transducer. Compatible with any S-Series system that has been upgraded with the Premier Transducer Package. Rohs-compliant.	1			
	Note: Please refer to the most recent version of the corresponding system specification sheet or transducer specification sheet for available exams supported by each system.				
10	- Powerpark System PowerPark docking station for the Universal stand. This stand module and docking station allows the ultrasound systems to charge without plugging in the power cord.	1			
11	- EDGE Stand Ergonomic stand and mobile work platform for the EDGE, SonoSite EDGE II system and transducers. Complete with power supply, mini-dock and accessory basket. OEM peripherals include: B/W or color printer. Unable to use together	1			
12	- Triple Transducer Connect (TTC) w/ quick disconnect Three-transducer module for mobile docking system that allows connection of up to three transducers simultaneously while the system is docked in the Stand	1			
13	- SonoSite EDGE II Ultrasound System User Guide English	1			
14	- SonoSite EDGE II Ultrasound System Service Manual	1			
15	- SonoSite EDGE II Ultrasound System Service Manual	1			
16	- Reusable Endocavity Needle Guide Kit For The C8 Transducer The C8 ICT transducer biopsy guide is recommended for prostate biopsy procedures. The guide is secured to the transducer by repositioning and tightening the thumbscrew into the closed position. This guide will accept 16-22GA sizes.	1			
17	5-YR-WARRANTY - 60 MONTHS - STANDARD COVERAGE WARRANTY 60 MONTHS - STANDARD COVERAGE WARRANTY	1			

Item	Part Number - Description	Qty	List Per Unit	Unit Price	Extended Price
------	---------------------------	-----	---------------	------------	----------------

Serial No: ultrasound system, performance applications software and all  
standard transducers.  
Please refer to Warranty Schedule.

18	1-YR-WARRANTY - 12 MONTHS - STANDARD COVERAGE WARRANTY 12 MONTHS - STANDARD COVERAGE WARRANTY (For Designated Products)	1			
----	--	---	--	--	--

Serial No: C8x Intracavitary Transducer  
Please refer to Warranty Schedule.