





Share:



SYBT4

Average Customer Review





★★★★★



5

1 of 1 (100%) reviewers would recommend this product to a friend.

[Read all reviews](#)

[Write a review](#)

Share this Product: 



Product Overview	Technical Specifications	Documentation	Ratings & Reviews																																											
<div><div>Input</div><div>Print Technical Specification</div></div> <table><tr><td>Number of Power Cords</td><td>1</td></tr></table> <div><div>Batteries & Runtime</div><table><tr><td>Battery type</td><td>Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof</td></tr><tr><td>Battery mounting</td><td>Enclosed battery cartridge</td></tr><tr><td>Battery Placement</td><td>Internal Battery</td></tr><tr><td>Battery blocks per string</td><td>4</td></tr><tr><td>Battery Design Life</td><td>5 - 8</td></tr><tr><td>Battery Service Life</td><td>3 - 5</td></tr></table><div><div>Physical</div><table><tr><td>Maximum Height</td><td>5.2inches (132mm , 13.2CM)</td></tr><tr><td>Maximum Width</td><td>17.0inches (432mm , 43.2CM)</td></tr><tr><td>Maximum Depth</td><td>28.0inches (711mm , 71.1CM)</td></tr><tr><td>Net Weight</td><td>200.0lbs. (90.91KG)</td></tr><tr><td>Shipping weight</td><td>224.0lbs. (101.82KG)</td></tr><tr><td>Shipping Height</td><td>18.0inches (457mm , 45.7CM)</td></tr><tr><td>Shipping Width</td><td>24.0inches (610mm , 61.0CM)</td></tr><tr><td>Shipping Depth</td><td>33.0inches (838mm , 83.8CM)</td></tr><tr><td>Color</td><td>Black</td></tr><tr><td>Units per Pallet</td><td>7.0</td></tr></table><div><div>Environmental</div><table><tr><td>Operating Temperature</td><td>32 - 104 °F (0 - 40 °C)</td></tr><tr><td>Operating Relative Humidity</td><td>0 - 95 %</td></tr><tr><td>Operating Elevation</td><td>0-3333ft (0-999.9meters)</td></tr><tr><td>Storage Temperature</td><td>-15 - 40 °C</td></tr><tr><td>Storage Relative Humidity</td><td>0 - 95 %</td></tr><tr><td>Storage Elevation</td><td>0-50000ft (0-15000meters)</td></tr></table><div><div>Conformance</div></div></div></div></div>	Number of Power Cords	1	Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	Battery mounting	Enclosed battery cartridge	Battery Placement	Internal Battery	Battery blocks per string	4	Battery Design Life	5 - 8	Battery Service Life	3 - 5	Maximum Height	5.2inches (132mm , 13.2CM)	Maximum Width	17.0inches (432mm , 43.2CM)	Maximum Depth	28.0inches (711mm , 71.1CM)	Net Weight	200.0lbs. (90.91KG)	Shipping weight	224.0lbs. (101.82KG)	Shipping Height	18.0inches (457mm , 45.7CM)	Shipping Width	24.0inches (610mm , 61.0CM)	Shipping Depth	33.0inches (838mm , 83.8CM)	Color	Black	Units per Pallet	7.0	Operating Temperature	32 - 104 °F (0 - 40 °C)	Operating Relative Humidity	0 - 95 %	Operating Elevation	0-3333ft (0-999.9meters)	Storage Temperature	-15 - 40 °C	Storage Relative Humidity	0 - 95 %	Storage Elevation	0-50000ft (0-15000meters)
Number of Power Cords	1																																													
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof																																													
Battery mounting	Enclosed battery cartridge																																													
Battery Placement	Internal Battery																																													
Battery blocks per string	4																																													
Battery Design Life	5 - 8																																													
Battery Service Life	3 - 5																																													
Maximum Height	5.2inches (132mm , 13.2CM)																																													
Maximum Width	17.0inches (432mm , 43.2CM)																																													
Maximum Depth	28.0inches (711mm , 71.1CM)																																													
Net Weight	200.0lbs. (90.91KG)																																													
Shipping weight	224.0lbs. (101.82KG)																																													
Shipping Height	18.0inches (457mm , 45.7CM)																																													
Shipping Width	24.0inches (610mm , 61.0CM)																																													
Shipping Depth	33.0inches (838mm , 83.8CM)																																													
Color	Black																																													
Units per Pallet	7.0																																													
Operating Temperature	32 - 104 °F (0 - 40 °C)																																													
Operating Relative Humidity	0 - 95 %																																													
Operating Elevation	0-3333ft (0-999.9meters)																																													
Storage Temperature	-15 - 40 °C																																													
Storage Relative Humidity	0 - 95 %																																													
Storage Elevation	0-50000ft (0-15000meters)																																													

PEP	Available in Documentation tab
EOLI	Available in Documentation tab



Sign up to stay up to date with best practices, new solutions and special offers.

Email

I am a... ▼

OK

- WHO WE ARE
- CONNECT WITH US
- FIND A RESELLER

Zip/Postal Code FIND

CATALOG KEYCODE
Enter Key Code GO



- TERMS & CONDITIONS >
- PRIVACY STATEMENT >

© 2018, APC by Schneider Electric