SECTION B -- SALIENT CHARACTERISTICS

This is a Brand Name or Equal solicitation. Salient characteristics and brand name manufacturers with associated part numbers are listed below. Line item numbers on quote(s) shall correlate with the line item numbers in the matrix below, or quote(s) may be determined nonresponsive. All furniture shall conform to the fit, form, and function of the design(s) of the VANCHCS facility where it will be installed, as described below, and all items shall be designed for use in an industrial environment.

| | | | Brand Name |
|--------|-----|--|------------------------------|
| | | | Manufacturer and |
| Line # | Qty | Description | Part Number |
| | | Chair, Bench, Locker | Global Industrial |
| 1 | 2 | | Hardwood top with |
| | | Salient Characteristics: To include minimum of the following specifications: | Steel Trapezoid Pedestals |
| | | Dimensions and Features • Overall dimensions: 48 inches (") width (w) x 10" depth (d) x 19" height (h) (+/- 3") so that it may fit into the | 1 odobiaio |
| | | space and design of the area | OR EQUAL |
| | | Freestanding, shall not require bolting to the ground for stability for safe use | |
| | | Hardwood top Metal legs | |
| | | Factory applied finish electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal | |
| | | corrosion, stain, abrasion, and scratch resistance | |
| | | Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | • Finishes: | |
| | | - Top: Clear maple or equivalent | |
| | | - Base: Brushed stainless or silver/grey powdercoat | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | CH01 |
| | | | |
| | | | |
| | | Chair, Conference | Highmark, HB |
| 2 | 15 | , | |
| | | Salient Characteristics: To include minimum of the following specifications: | OR EQUAL |
| | | Dimensions and Features | |
| | | Overall dimensions: 25"w x 25"d x 37-40"h (+/- 3") so that it may fit into the space and design of the area Standard height range piston | |
| | | Five (5) star base with castors for hard floors | |
| | | Upholstered seat with mesh back | |
| | | Fixed height arms, integral with frame Adjustable seat height. | |
| | | Adjustable seat height Greenquard indoor air quality certified | |
| | | • Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable | |
| | | of being wiped clean with ordinary household cleaning solutions | |
| | | All fabrics shall be bleach cleanable with a ten to one (10:1) water to bleach solution | |
| | | • Finishes: | |
| | | - Arm plastic: standard black | |
| | | - Base: standard black powder coat paint | |
| | | - Mesh back: tan - Upholstery: graded in, three (3) grades above base grade for a coated fabric) | |
| | | - Caster: black | |
| | | Style and finishes shall match with other conference room furniture | |
| | | All finishes must be selected and approved by the VA interior designer | |
| | | | |
| | | | |

36C26118Q0532

| Line # | Qty | Di | escription | Brand Name Manufacturer and Part Number |
|--------|-----|---|------------|---|
| | | Image is representational of general design intent. | | CH02 |

| | | | Brand Name Manufacturer and |
|--------|-----|--|----------------------------------|
| Line # | Qty | Description | Part Number |
| 3 | 40 | Chair, Dining | Loewenstein, Caprice |
| | | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features | OR EQUAL |
| | | Overall Dimensions: 24" depth; 24" width; and 33" height (+/- 1.5"); 29 lbs so that it may fit into the space and design of the area Rated up to 250 lbs load, minimum. Nylon Plastic Shell | |
| | | Polished Chrome 4-leg base Perforated seat design aesthetic and bucket seat shape Stacks at least five (5) chairs high Floor saver glides Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable | |
| | | of being wiped clean with ordinary household cleaning solutions | |
| | | Finishes: Plastic frame: grey Base frame: polished chrome | |
| | | Style and finishes shall coordinate with dining table and outdoor furniture | |
| | | Image is representational of general design intent. | |
| | | | CH03 |
| 4 | 4 | Chair, Dining, Barstool | Peter Pepper Products, STACKR |
| | | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 17" depth; 20" width; and 30" height (+/- 1.5"); 1/2" thick (+/25") so that it may fit into the space and design of the area | 30"h Stool OR EQUAL |
| | | Rated up to two hundred and twenty-five (225) pound (lb) load, minimum. Chrome tubular steel Molded veneer seat | |
| | | Stacks at least four (4) stools high Floor saver glides | |
| | | Cantilevered design and sled style base shall allow for stool to be hung from a bar height table to keep floors clear for cleaning Waterfall edge on seat | |
| | | Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions All finishes shall be bleach cleanable with a ten to one (10:1) water to bleach solution | |
| | | Finishes: - Upholstery: natural ash - Base frame: chrome | |
| | | Image is representational of general design intent. | |
| | | | CH04 |
| | | | |

| | | | Brand Name |
|--------|-----|--|---------------------------------|
| Line # | Qty | Description | Manufacturer and Part Number |
| _ | • | Chair, Patient, Bariatric | Carolina, Silver Ion Metal |
| 5 | 9 | Salient Characteristics: To include minimum of the following specifications: | |
| | | Dimensions and Features Overall Dimensions: 26" depth; 34.5" width; and 33" height (+/- 0.5"), weight seventy-two (72) lbs so that it | OR EQUAL |
| | | may fit into the space and design of the area • Seat depth 18.5"; seat height 19"; arm height 25"; (+/- 0.5") | |
| | | Rated for five hundred (500) lbs | |
| | | Three hundred and sixty (360) degrees clean-thru design Upholstered seat and back | |
| | | Wallsaver design Non-marring adjustable glides | |
| | | Durable metal frame with polyurethane armcaps, which feature antimicrobial properties Greenguard indoor air quality certified | |
| | | Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | • Finishes: | |
| | | - Arms: black polyurethane - Frame: warm grey | |
| | | - Upholstery: Graded in, three (3) grades above base grade for a coated fabric • Style and finishes shall match with "chair, patient, mid-back" | |
| | | Style dila inilatica di dii matan man shan, panan, ma bash | |
| | | Image is representational of general design intent. | |
| | | | |
| | | | CH05 |
| | | | |
| 6 | 51 | Chair, Patient, Mid-back | Carolina, Silver Ion Metal |
| | | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features | OR EQUAL |
| | | • Overall Dimensions: 26" depth; 25" width; and 33" height (+/- 0.5"), weight sixty (60) lbs so that it may fit into | |
| | | the space and design of the area • Seat depth 18.5"; seat height 19"; arm height 25"; (+/- 0.5") | |
| | | Rated up to four hundred (400) lbs load, minimum three hundred and sixty (360) degrees clean-thru design | |
| | | Upholstered Seat and Back Field replaceable components | |
| | | Wallsaver design | |
| | | Non-marring adjustable glides Durable metal frame with polyurethane armcaps, which feature antimicrobial properties | |
| | | Greenguard indoor air quality certified Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, | |
| | | stain, abrasion and scratch resistance • Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable | |
| | | of being wiped clean with ordinary household cleaning solutions • All fabrics shall be bleach cleanable with a ten to one (10:1) water to bleach solution | |
| | | • Finishes: | |
| | | - Arms: black polyurethane - Frame: warm grey | |
| | | - Upholstery: Graded in, three (3) grades above base grade for a coated fabric - Style and finishes shall match with "chair, patient, bariatric" | |
| | | | |
| | | | |
| | | • | • |

| Line # | Qty | Description | Brand Name Manufacturer and Part Number |
|---------|-----|--|---|
| Lille # | Qty | Image is representational of general design intent. | Part Number |
| | | image is representational or general design intent. | CH06 |
| | | Chair, Task | Steelcase, Leap |
| 7 | 50 | | (462 Series) |
| | | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 21.75"-24.5" depth; 27" width; and 38.5"-43.5" height, (+/- 1") so that it may fit into the space and design of the area Seat Depth 15.75"-18.75"; Seat Height 15.5"-20.5"; Seat Width 19.25", (+/5") so that it may fit into the space and design of the area Arm shall have height (4" range), depth (3" range), width (4.5" range), and pivot (30° range) adjustability; (+/5") so that it may fit into the space and design of the area Weight capacity of four hundred (400) lbs Upholistered seat and 3D knit back over plastic outer back and outer seat Recline angle of ninety-five (95) degrees to one hundred and twenty (120) (+/-5") for comfort Seat shall have waterfall edge to reduce pressure on user's thighs when sitting for prolonged periods Seat depth adjstability, standard, with minimum three (3)" range Flexible back construction designed to move with the user's spine Adjustable lumbar support, standard, with five (5)" range Adjustable limmess of lower back support Upper back force adjustability Five back recline step positions Five-arm base with two and one-half (2 1/2)" soft casters for use on hard floors ANSI/BIFMA furniture sustainability standard level three (3) certified Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions All fabrics shall be bleach cleanable with a ten to one (10:1) water to bleach solution Finishes: Back Upholstery: graded in, standard knit mesh Seat Upholstery: Graded in, three (3) grades above base grade for a coated fabric Frame: champagne metallic powder coat | OR EQUAL |
| | | Image is representational of general design intent. | CH07 |
| | | Clock | Peter Pepper |
| 8 | 13 | Salient Characteristics: To include minimum of the following specifications: | Products (Clock - 343) |

| " | | | Brand Name Manufacturer and |
|--------|-----|--|--------------------------------|
| Line # | Qty | Description | Part Number |
| | | Dimensions and Features Overall Dimensions: twelve (12) diameter (+/- 1") and 1.5" depth (+/- 0.25") so that it may fit into the space and design of the area Lightweight modern design Thin edge Bezel finish: Aluminum Clock face: White with black graphics, large simple to read hour numbers with minute tick-marks Face cover: Glass Face: Large numbers, twelve (12) hour Movement: Quartz battery movement Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Finishes: Frame: Brushed aluminum | OR EQUAL |
| | | Image is representational of general design intent. | |
| | | 3 3 4 4 4 5 6 3 3 4 5 | CL01 |

| | | | Brand Name |
|--------|-----|--|-------------------|
| | | | Manufacturer and |
| Line # | Qty | Description | Part Number |
| | | Computer Mount, CPU | Humanscale |
| 9 | 50 | | CPU600 |
| | | Salient Characteristics: To include minimum of the following specifications: | OR EQUAL |
| | | Dimensions and Features Overall Dimensions: fits computers that are 12"-20"h x 3.6"-9"w | ON EQUAL |
| | | Accomodates CPUs weighing up to 50 lbs | |
| | | Maintain convenient access to ports and drives | |
| | | Allow for quick hardware upgrades and repairs Under desk mount with 360-degree swivel mount | |
| | | Adjustable mounting plate to ensure CPU is centered and balanced | |
| | | Tool free installation | |
| | | Durable, easy-to-clean exterior composed of aluminum, high-grade plastic | |
| | | Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | • Finishes: | |
| | | - Frame: white/silver | |
| | | All selected finishes must be approved by VA Interior Designer | |
| | | Image is representational of general design intent. | |
| | | | |
| | | | |
| | | | CM01 |
| | | | |
| | | | |
| | | Computer Mount, Monitor, Double | Steelcase Eyesite |
| 10 | 17 | | Double Display |
| | | Salient Characteristics: To include minimum of the following specifications: | OR EQUAL |
| | | Dimensions and Features • Overall Dimensions: 35"w x 8.5"d x 15.5"h (+/- 4"), 18.5 lbs so that it may fit into the space and design of the | ON EQUAL |
| | | area | |
| | | Support for dual monitors, up to 24" and up to 25 lbs each | |
| | | Clamp mount to worksurface Provide handle below monitor to adjust monitor without grabbing screen | |
| | | Quick and easy connection or disconnection of monitors to the device | |
| | | Height Adjustable | |
| | | Depth Adjustable Pivot Adjustable | |
| | | • Angle Adjustable: Tilt: +10°/-90° for easy access to cable connections, Pan: 175° | |
| | | Rotation Adjustable: 360° portrait to landscape | |
| | | Integrated cable management Shall match style of double monitor arm | |
| | | Durable, easy-to-clean exterior composed of aluminum, high-grade plastic | |
| | | • Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable | |
| | | of being wiped clean with ordinary household cleaning solutions | |
| | | Frame: Silver | |
| | | | |
| | | Image is representational of general design intent. | |
| | | 17 19 | |
| | | | CM02 |
| | | | 0.1102 |
| | | | |
| | | | |

| | | | Brand Name Manufacturer and |
|--------|-----|---|---|
| Line # | Qty | Description | Part Number |
| 11 | 33 | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 10"w x 8.5"d x 15.5"h (+/- 4") Support for a single monitor, up to 30" Claimp mount to worksurface Configuration shall prevent monitor arm from extending beyond back surface of desk (e.g. abutting sit-stand table shall not hit an overlapping monitor arm while it is being raised) Provide handle below monitor to adjust monitor without grabbing screen Quick and easy connection or disconnection of monitors to the device Height Adjustable Depth Adjustable Privot Adjustable: Tilt: +10°/-90° for easy access to cable connections, Pan: 175° Rotation Adjustable: 360° portrait to landscape Integrated cable management Shall match style of double monitor arm Manufacturer must offer a minimum 5 year warranty that product is free from defects in materials and workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) Durable, easy-to-clean exterior composed of aluminum, high-grade plastic Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Finishes: Frame: Silver All selected finishes must be approved by VA Interior Designer | Steelcase Eyesite Single Display OR EQUAL |
| | | | CM03 |

| | | | Brand Name |
|------|-----|--|--------------------------------------|
| | ۵. | 5 | Manufacturer a |
| ine# | Qty | | Part Number |
| 40 | 40 | Desk, Office | Carolina Pulse, Kimball Priority, |
| 12 | 12 | Salient Characteristics: To include minimum of the following specifications: | Steelcase, Hawo |
| | | Dimensions and Features | Herman Miller |
| | | • Overall Dimensions: 72"d x 66"w x no greater than 64" h (+/-2") so that it may fit into the space and design of | |
| | | the area | Task Light: Reed |
| | | • Desk layout shall be per attached supplementary drawings so that hand of desk and electrical stub-ups are in adequate locations; verify all dimensions in field prior to order, manufacture, and installation | Premier, Linear I |
| | | Desk shall be comprised of a system of coordinating parts and panels for a complete look | OR EQUAL |
| | | Desk shall have provide power at worksurface height and shall provide cable management | |
| | | Power shall be provided to the desk at adjacent walls with standard outlets | |
| | | Service parts must be available Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is | |
| | | capable of being wiped clean with ordinary household cleaning solutions | |
| | | Bullet Shaped Table Worksurface | |
| | | • Overall Dimensions: 30"d x 66"w x 29" h (+/- 3") so that it may fit into the space and design of the area | |
| | | Bullet shape with square edges so that it may fit into the space and design of the area | |
| | | • Features T-shaped support on return side, curved end with post support on other to provide knee clearance from both sides of worksurface | |
| | | Space under the work surface shall be completely free of obstruction and support for the fixed height | |
| | | worksurface shall be accomplished with perimeter edges of the desk or storage units | |
| | | Worksurface shall have grommets for cable access and wire management Worksurface shall have actinizes high factures modeled into the deak components using either in a capital state. | |
| | | Worksurface shall have antimicrobial features molded into the desk components using silver ion or similar technology | |
| | | | |
| | | • 3/4 Box/File Return | |
| | | Overall Dimensions: 15"w x 18"d x 21"h (+/- 2") so that it may fit into the space and design of the area Rectangular return with square edges, attach to Bullet worksurface for L shaped desk configuration | |
| | | • One larger "file" drawer, one smaller "box" drawer configuration, attached to the underside of the desk return; | |
| | | leaves a clear space below drawers for easy cleaning | |
| | | • Include Box drawer divider and pencil tray | |
| | | One lock shall lock all drawers, and shall be front-removable to simplify field changes All pulls shall comply with current ABA codes | |
| | | Drawers must feature heavy-duty steel drawer suspensions which allow drawers to open their full depth | |
| | | Highback Organizer | |
| | | • Overall Dimensions: 14.63"d; 56.63"w; 37.13"h, (+/- 3"); worksurface clearance 19 3/4"h | |
| | | Designed to be installed on top of desk components; include mounting brackets or other hardware for stable and safe installation | |
| | | Back of unit at worksurface shall be enclosed and shall feature a tackboard and tool rail | |
| | | Storage shall be lockable with hinged, sliding, or flipper doors (which can be leveled) | |
| | | • Fully finished on all sides | |
| | | Highback organizer unit shall be lockable and key core shall be front-removable to simplify field changes Wherever door or drawer pulls occur directly next to each other, provide ample clearance for fingers at all | |
| | | times | |
| | | Where occurs, flipper door shall recess into the outer shell of the flipper unit to allow top most surface of the | |
| | | unit to remain undisturbed. • Highback organizer storage shall have a back panel to prevent items from falling behind the desk unit | |
| | | riigiibaan organizer storage shall have a back paller to prevent items from falling behind the desk unit | |
| | | Tackboard/Tool Rail | |
| | | • Shall feature a slat-style (or other type) tool rail to accommodate organizational accessories, to include pencil | |
| | | cup, file sorter and paper tray at minimum • Item shall coordinate with and install seamlessly with furniture upon which this is to be placed | |
| | | Task Light | |
| | | Shall provide a dimmable LED task Light under flipper storage unit Under cabinet light shall be affixed magnetically or otherwise to provide flexibility in depth placement by the user | |
| | | • LED, UL Listed | |
| | | Switch: single touch on/off; Dimmable, touch-and-hold, 15%-100% continuous with last state memory | |
| | | • At least 50,000 hours lifespan | |
| | | Color temperature: 3500K Screw and Magnetic Mounting kit included | |
| | | • 12' with 60-watt power supply | |
| | | Daisy chain capable up to 6 fixtures | |

| | | | Brand Name |
|-------|-----|---|------------------------------|
| Line# | Otv | Description | Manufacturer and Part Number |
| Line# | Qty | Technical Specification and Code Requirements • Table units meet or exceed ANSI/BIFMA X 5.5-1998 Desk/Table Product Tests. • Meets or exceeds UL 1286 and is designed in compliance with NFPA 70 National Electric Code • Product shall be tested and compliant with UL 723 Test for Surface Burning Characteristics of Building Materials using ASTM E 84 Standard Test Method • Work surface edge profile, on edges designed to come into contact with users' wrists, comply with ISO 9241-5 (1998) Section 5.4.4, ANSI/HFES-100 (2008) section 8.3.1.4, BIFMA G1 (2002) Section 9, and CSA-Z412 (2000) section 7.5.12. • Standard high-pressure laminates meet or exceed NEMA LD3-2005 High-Pressure Decorative Laminate standards. • Product must meet ANSI/SOHO S6.50 Racking Resistance Test • Product shall be tested to National Motor Freight standards to ensure packaging and shipment methods will prevent transit damage • MDF shall comply with ANSI 208.1 and ASTM D 1037, and shall comply with ANSI 208.2 Environmental Features • Paint is VOC-free powder coat type. Powder coat paint overspray is to be collected, reprocessed, and used on interior components • Contains recycled content, and shall be recyclable at end of life • Must have SCS IndoorAdvantage™ Gold Certification for indoor air quality. • Must be level 1 certified to ANSI/BIFMA e3 Furniture Sustainability Standard • Product shall be manufactured in a FSC Chain of Custody Certified plant to assure that wood is harvested from environmentally-managed forests • Shipping packing materials shall be reusable and/or recyclable | Part Number |
| | | Miscellaneous Service parts must be available Locks shall be keyed alike within each office All necessary brackets and fasteners shall be provided for a stable and secure installation High-pressure laminate finish; Edge band and bullnose edges must have finishes which compliment or match work surfaces Painted surfaces have the following qualities: Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Finishes: Laminate: Wilsonart Laminate, Kensington Maple 10776-60 Tackable Panel Upholstery: Graded in, TBD (3 grades above base grade) Tool Rail: Champagne Metallic (Steelcase); or match Style and finishes shall match workstations, other desks, and office furniture All selected finishes must be approved by VA Interior Designer Image is representational of general design intent. | |
| | | | DE01 |

| | | Brand Name |
|-------|--|-------------------|
| | | Manufacturer a |
| # Qty | Description | Part Number |
| | Desk, Office, Sit-Stand | Kimball, Steelcas |
| 9 | | Haworth, Herman |
| _ | | Miller |
| | Dimensions and Features | |
| | Overall Dimensions: 72" x 78" so that it may fit into the space and design of the area | OR EQUAL |
| | • Desk layout shall be per attached supplementary drawings so that hand of desk and electrical stub-ups are in | |
| | adequate locations; verify all dimensions in field prior to order, manufacture, and installation | |
| | Desk shall be comprised of a system of coordinating parts and panels for a complete look | |
| | Desk shall have provide power at worksurface height and shall provide cable management | |
| | Power shall be provided to the desk at adjacent walls with standard outlets | |
| | • Service parts must be available | |
| | • Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is | |
| | capable of being wiped clean with ordinary household cleaning solutions | |
| | Worksurfaces | |
| | • Overall Dimensions: Stationary worksurface: 30"d x 72"w x 29" h; Sit-stand table: 48"w x 24"d x 25.5"-49"h (+/- | |
| | 3") | |
| | Rectangular with square edges | |
| | Space under the work surface shall be completely free of obstruction and support for the fixed height | |
| 1 1 | worksurface shall be accomplished with perimeter edges of the desk or storage units | |
| | • Sit-stand shall feature a powered base with simple, infinite up/down adjustability and programmable up/down | |
| | control buttons with at least 3 pre-sets • Sit-stand mechanism shall be controlled by central box to ensure synchronization | |
| | Worksurface shall have antimicrobial features molded into the desk components using silver ion or similar | |
| | technology | |
| | | |
| | Mobile B/B/F | |
| | • Overall Dimensions: 15"w x 18"d x 27"h (+/- 2") so that it may fit into the space and design of the area | |
| | One larger "file" drawer, two smaller "box" drawers configuration In advada Bay drawer divides and grantification. | |
| | Include Box drawer divider and pencil tray 3" diameter, large, front-locking, soft casters for hard floors | |
| | Counterweight | |
| | One lock shall lock all drawers, and shall be front-removable to simplify field changes | |
| | • All pulls shall comply with current ABA codes | |
| | Drawers must feature heavy-duty steel drawer suspensions which allow drawers to open their full depth | |
| | Technical Specification and Code Requirements | |
| | Table units meet or exceed ANSI/BIFMA X 5.5-1998 Desk/Table Product Tests. | |
| | Meets or exceeds UL 1286 and is designed in compliance with NFPA 70 National Electric Code | |
| | Product shall be tested and compliant with UL 723 Test for Surface Burning Characteristics of Building Metarials using A STM F 84 Standard Test Method | |
| | Materials using ASTM E 84 Standard Test Method • Work surface edge profile, on edges designed to come into contact with users' wrists, comply with ISO 9241-5 | |
| 1 1 | (1998) Section 5.4.4, ANSI/HFES-100 (2008) section 8.3.1.4, BIFMA G1 (2002) Section 9, and CSA-Z412 | |
| | (2000) section 7.5.12. | |
| 1 1 | Standard high-pressure laminates meet or exceed NEMA LD3-2005 High-Pressure Decorative Laminate | |
| | standards. | |
| 1 1 | Product must meet ANSI/SOHO S6.50 Racking Resistance Test | |
| | Product shall be tested to National Motor Freight standards to ensure packaging and shipment methods will | |
| I I | prevent transit damage | |
| | MDF shall comply with ANSI 208.1 and ASTM D 1037, and shall comply with ANSI 208.2 | |
| | Environmental Features | |
| | Paint is VOC-free powder coat type. Powder coat paint overspray is to be collected, reprocessed, and used | |
| 1 1 | on interior components | |
| 1 1 | | |
| 1 1 | • | |
| 1 1 | · · · · · · · · · · · · · · · · · · · | |
| | | |
| | Contains recycled content, and shall be recyclable at end of life Must have SCS IndoorAdvantage™ Gold Certification or equal certification for indoor air quality. Must be level 1 certified to ANSI/BIFMA e3 Furniture Sustainability Standard Product shall be manufactured in a FSC Chain of Custody Certified plant to assure that wood is harvested from environmentally-managed forests | |

| | | | Brand Name |
|-------|-----|--|------------------------------|
| Line# | Qty | Description | Manufacturer and Part Number |
| | | • Miscellaneous Service parts must be available Locks shall be keyed alike within each desk All necessary brackets and fasteners shall be provided for a stable and secure installation High-pressure laminate finish; Edge band and bullnose edges must have finishes which compliment or match work surfaces Painted surfaces have the following qualities: Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Manufacturer must offer a lifetime warranty that product is free from defects in materials and workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) Exceptions to this warranty may apply to certain components, as listed on manufacturer literature. Finishes: Laminate worksurface: Wilsonart Laminate, Kensington Maple 10776-60 Metal/Trim: Champagne Metallic (Steelcase); or match Storage: Champagne Metallic (Steelcase); or match Style and finishes shall match workstations, other desks, and office furniture All selected finishes must be approved by VA Interior Designer | |
| | | Image is representational of general design intent. | DE02 |

| | | | Brand Name Manufacturer and |
|--------|-----|---|--|
| Line # | Qty | Description | Part Number |
| 14 | 2 | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 48"w x 24"d x 25.5"-49"h (+/- 3") Top available in different shapes and sizes; top shall be rectangle with square edge Powered base with simple, infinite up/down adjustability Programmable up/down control buttons with at least 3 pre-sets Worksurface shall have antimicrobial features molded into the desk components using silver ion or similar technology Integrated cable management Include Modesty Panel Shall provide leveling glides Greenguard Indoor Air Quality Certified High-pressure laminate finish; Edge band and bullnose edges must have finishes which compliment or match work surfaces Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Manufacturer must offer a minimum 10 year warranty that product is free from defects in materials and workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) Finishes: Laminate: Wilsonart Laminate, Kensington Maple 10776-60 Base: Champagne Metallic (Steelcase); or match Style and finishes shall match workstations, other desks, and office furniture All finishes must be selected and approved by the VA Interior Designer | Steelcase Ology, Kimball Priority, or HAT Contract OR EQUAL |
| | | Image is representational of general design intent. | DE03 |

| | | | Brand Name |
|--------|-----|---|---|
| | | | Manufacturer and |
| Line # | Qty | Description | Part Number |
| 15 | 3 | Dimensions and Features Overall Dimensions: 66"w x 24"d x 25.5"-49"h (+/- 3") Top available in different shapes and sizes; top shall be rectangle with square edge Powered base with simple, infinite up/down adjustability Programmable up/down control buttons with at least 3 pre-sets Worksurface shall have antimicrobial features molded into the desk components using silver ion or similar technology Integrated cable management Include Modesty Panel Shall provide leveling glides Greenguard Indoor Air Quality Certified High-pressure laminate finish; Edge band and bullnose edges must have finishes which compliment or match work surfaces Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Manufacturer must offer a minimum 10 year warranty that product is free from defects in materials and workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) Finishes: Laminate: Wilsonart Laminate, Kensington Maple 10776-60 Base: Champagne Metallic (Steelcase); or match Style and finishes shall match workstations, other desks, and office furniture All finishes must be selected and approved by the VA Interior Designer | Steelcase Ology, Kimball Priority, or HAT Contract OR EQUAL |
| | | Image is representational of general design intent. | DE04 |

| | | | Brand Name |
|--------|-----|---|--|
| _ | _ | | Manufacturer and |
| Line # | Qty | Description | Part Number |
| 16 | 4 | Desk, Sit-stand 30x66 | Steelcase Ology, Kimball Priority, or |
| | | Salient Characteristics: To include minimum of the following specifications: | HAT Contract |
| | | Dimensions and Features Overall Dimensions: 66"w x 30"d x 25.5"-49"h (+/- 3") Top available in different shapes and sizes; top shall be rectangle with square edge Powered base with simple, infinite up/down adjustability Programmable up/down control buttons with at least 3 pre-sets Worksurface shall have antimicrobial features molded into the desk components using silver ion or similar technology Integrated cable management Include Modesty Panel Shall provide leveling glides Greenguard Indoor Air Quality Certified High-pressure laminate finish; Edge band and bullnose edges must have finishes which compliment or match work surfaces Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Manufacturer must offer a minimum 10 year warranty that product is free from defects in materials and | OR EQUAL |
| | | workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) • Finishes: - Laminate: Wilsonart Laminate, Kensington Maple 10776-60 - Base: Champagne Metallic (Steelcase); or match • Style and finishes shall match workstations, other desks, and office furniture • All finishes must be selected and approved by the VA Interior Designer Image is representational of general design intent. | DE05 |

| | | | Brand Name |
|--------|-----|--|--------------------|
| | | | Manufacturer and |
| Line # | Qty | Description | Part Number |
| | | Lamp, Desk | SystemsLight: ESI |
| 17 | 16 | | Ergonomic |
| | | Salient Characteristics: To include minimum of the following specifications: | Solutions, Lustre, |
| | | Dimensions and Features | Lustre-SLV |
| | | • Overall Dimensions: 15"-19"w x 7.5"d x 13"-17"h (+/-1") | OD FOLIAL |
| | | Color Temperature: 3500K | OR EQUAL |
| | | • Lumens: 350 | |
| | | • CRI: 83 | |
| | | • "Touch & Hold" Built-in Dimmer with 3 brightness settings | |
| | | • UL Listed | |
| | | • Lamp Life: 50,000 hours | |
| | | 8 hr. shut-off feature | |
| | | 180-degree rotation at light source & lamp arm | |
| | | 360-degree rotation on base Cond Leagth 13 feet. | |
| | | Cord Length: 12 feet Telescoping arm and head | |
| | | Integrated occupancy sensor | |
| | | Light turns off after 15 minutes of detecting no motion | |
| | | USB charging port | |
| | | Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable | |
| | | of being wiped clean with ordinary household cleaning solutions | |
| | | Manufacturer must offer a warranty that product is free from defects in materials and workmanship (includes). | |
| | | shipping, parts and labor for the repair or replacement of defective item.) | |
| | | • Finishes: | |
| | | - Metal: Silver tone | |
| | | Style and finishes shall match Nursing Station and Office Furniture | |
| | | All finishes must be selected and approved by the VA Interior Designer | |
| | | - | |
| | | | |
| | | Image is representational of general design intent. | |
| | | 1500 yygo | |
| | | | |
| | | | LA01 |
| | | | |
| | | | |
| | | | |

| | | | Brand Name |
|--------|-----|---|--|
| 1: # | O+ | Description | Manufacturer and Part Number |
| Line # | Qty | Description | Carolina Y60.G2, |
| 18 | 43 | Lounge, Chair Salient Characteristics: To include minimum of the following specifications: | Kimball Villa Health, or Nemschoff Riva |
| | | Dimensions and Features Overall Dimensions: 35"w x 35.25"d x 29"h; (+/- 3") 19"h, 18.75"d seat (+/-1") Fully Upholstered | OR EQUAL |
| | | Crumb clean-out Upholstered arms with solid surface arm caps Tethered cushions Contrasting fabric on seat and back cushion, upholstered outer arms Non-skid, adjustable glides | |
| | | Power/USB Grommet in Arm (Location TBD) Greenguard Indoor Air Quality Certified Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions All fabrics shall be bleach cleanable with a 10:1 water to bleach solution Manufacturer must offer a minimum 10 year warranty that product is free from defects in materials and | |
| | | workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) • Finishes: - Arm Caps: Corian, Savannah - Legs: Square Silvertone metallic - Back and Seat Upholstery: Graded in, TBD (3 grades above base grade for a coated fabric) | |
| | | - Arm, Base, and Back Upholstery: Graded in, TBD (3 grades above base grade for a coated fabric) • Style and finishes shall match Lobby Furniture • All selected finishes must be approved by VA Interior Designer | |
| | | Image is representational of general design intent. | LO01 |
| | | | |
| 19 | 6 | Lounge, Loveseat Salient Characteristics: To include minimum of the following specifications: | Carolina Y60.G2, Kimball Villa Health, or Nemschoff Riva |
| | | Dimensions and Features Overall Dimensions: 51"w x 35.25"d x 29"h; (+/- 3") 19"h, 18.75"d seat (+/-1") so that it may fit into the space and design of the area | OR EQUAL |
| | | Fully Upholstered Crumb clean-out Upholstered arms with solid surface arm caps | |
| | | Tethered cushions Contrasting fabric on seat and back cushion, upholstered outer arms Non-skid, adjustable glides Power/USB Grommet in Arm (Location TBD) | |
| | | Greenguard Indoor Air Quality Certified Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | All fabrics shall be bleach cleanable with a 10:1 water to bleach solution Manufacturer must offer a minimum 10 year warranty that product is free from defects in materials and workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) Finishes: | |
| | | - Arm Caps: Corian, Savannah - Legs: Square Silvertone metallic - Back and Seat Upholstery: Graded in, three (3) grades above base grade for a coated fabric - Arm, Base, and Back Upholstery: Graded in, three (3) grades above base grade for a coated fabric | |
| | | • Style and finishes shall match Lobby Furniture | |

| | | | Brand Name |
|--------|------------|---|---|
| Line# | Qty | Description | Manufacturer and Part Number |
| Line # | <u>Qiy</u> | Image is representational of general design intent. | LO02 |
| 20 | 7 | Lounge, Table, Coffee Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 30"dia x 14.75"h (+/- 3"); 34 lbs so that it may fit into the space and design of the area Round, drum style table with square metal legs and 1/2" thick solid surface top Soft radius vertical edge on table top Durable High Pressure Laminate drum Shall provide non-marring leveling glides SCS Indoor Advantage and BIFMA Certified Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Manufacturer must offer a lifetime warranty that product is free from defects in materials and workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) Finishes: Solid Surface Top: Corian Clam Shell or approved equivalent (Savannah) Base: Clear Maple HPL (Hardrock) Legs: Square Silvertone metallic Style and finishes shall match with other Lobby Furniture | Krug Zola Freestanding Table, Round OR EQUAL |
| | | Image is representational of general design intent. Lounge, Table, End | LO03 Krug Zola |
| 21 | 11 | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 24"w x 24"d x 14.75"h (+/- 3"); 34 lbs so that it may fit into the space and design of the area Square, block style table with square metal legs and 1/2" thick solid surface top Soft radius vertical edge on table top Durable High Pressure Laminate block Shall provide non-marring leveling glides SCS Indoor Advantage and BIFMA Certified Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Finishes: Solid Surface Top: Corian Clam Shell or approved equivalent (Savannah) Base: Clear Maple (Hardrock) Legs: Square Silvertone metallic Style and finishes shall match with other Lobby Furniture | Freestanding Table, Round OR EQUAL |
| | | Image is representational of general design intent. | LO04 |

| | | | Brand Name |
|--------|-----|---|---|
| Line # | Qty | Description | Manufacturer and Part Number |
| 22 | 11 | Markerboard 3'x4' Salient Characteristics: To include minimum of the following specifications: Dimensions and Features | Peter Pepper Products, Tactics Plus |
| | | Overall Dimensions: 48" width, 36" height and 0.75" depth (+/- 0.25") so that it may fit into the space and design of the area Frame Finish: Natural Anodized Aluminum Includes at minimum a 12" Aluminum pen rail, 4 dry erase markers and eraser White porcelain enamel writing surface fused to steel Accepts magnetic accessories Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | OR EQUAL |
| | | Image is representational of general design intent. | MB01 |
| 23 | 2 | Markerboard 4'x5' Salient Characteristics: To include minimum of the following specifications: | Peter Pepper Products, Tactics Plus |
| | | Dimensions and Features Overall Dimensions: 60" width, 48" height and 0.75" depth (+/- 0.25") so that it may fit into the space and design of the area Frame Finish: Natural Anodized Aluminum Includes at minimum a 24" Aluminum pen rail, 4 dry erase markers and eraser White porcelain enamel writing surface fused to steel Accepts magnetic accessories Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | OR EQUAL |
| | | Image is representational of general design intent. | |
| | | | MB02 |

| | | | Brand Name |
|--------|-----|--|--------------------------------|
| | | | Manufacturer and |
| Line # | Qty | Description | Part Number |
| 24 | 26 | Outdoor, Chair, Dining | Coalesse, EMU Round Seating |
| 24 | 20 | Salient Characteristics: To include minimum of the following specifications: | rtouria dealing |
| | | Dimensions and Features | OR EQUAL |
| | | • Overall Dimensions: 24 3/4"w; 23 1/4"d; 32" h (+/- 1.5") | |
| | | Rated up to 250 lbs load, minimum Frame: Metal mesh seat welded to a tubular steel frame | |
| | | Outdoor grade powder coat paint | |
| | | Chair Stacks 8 high | |
| | | Optional outdoor cushion available (but not included) Shall provide nylon leveling glides | |
| | | Shall contain recycled content and be recyclable at end of life | |
| | | SCS Indoor Advantage and BIFMA Certified | |
| | | Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | Manufacturer must offer a lifetime warranty that product is free from defects in materials and workmanship | |
| | | (includes shipping, parts and labor for the repair or replacement of defective item.) | |
| | | Finishes: Powdercoat Paint: Antique Iron | |
| | | Style and finishes shall match with other Outdoor Furniture | |
| | | All selected finishes must be approved by VA Interior Designer | |
| | | | |
| | | | |
| | | Image is representational of general design intent. | |
| | | | |
| | | | OT01 |
| | | | |
| | | | |
| | | Outdoor, Table, Dining 32x32 | Coalesse, EMU |
| 25 | 3 | | Round Tables |
| | | Salient Characteristics: To include minimum of the following specifications: | OR EQUAL |
| | | Dimensions and Features • Overall Dimensions: 31 1/2"w; 31 1/2"d; 29 1/2" h (+/- 1.5") so that it may fit into the space and design of the | OK EQUAL |
| | | area | |
| | | Table top and base are sheet metal with tubular steel mountings | |
| | | Outdoor grade powder coat paint Shall provide nylon leveling glides | |
| | | Shall contain recycled content and be recyclable at end of life | |
| | | SCS Indoor Advantage and BIFMA Certified | |
| | | • Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | or being whee clean with ordinary household cleaning solutions | |
| | | • Finishes: | |
| | | Powdercoat Paint: Antique Iron Style and finishes shall match with other Outdoor Furniture | |
| | | Style and inherite entail material enter entails entails | |
| | | | |
| | | Image is representational of general design intent. | |
| | | | |
| | | | OT02 |
| | | | |
| | | | |
| | | | |

| | | | Brand Name |
|-------|-----|---|---------------------------------|
| Line# | Qty | Description | Manufacturer and Part Number |
| | | Outdoor, Table, Dining 47x31 | Coalesse, EMU |
| 26 | 5 | Salient Characteristics: To include minimum of the following specifications: | Round Tables |
| | | Dimensions and Features | OR EQUAL |
| | | • Overall Dimensions: 47 1/2"w; 31 1/2"d; 29 1/2" h (+/- 1.5") so that it may fit into the space and design of the area | |
| | | Table top and base are sheet metal with tubular steel mountings Outdoor grade powder coat paint | |
| | | Shall provide nylon leveling glides Shall contain recycled content and be recyclable at end of life | |
| | | SCS Indoor Advantage and BIFMA Certified | |
| | | Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | • Finishes: | |
| | | Powdercoat Paint: Antique Iron Style and finishes shall match with other Outdoor Furniture | |
| | | | |
| | | Image is representational of general design intent. | |
| | | | |
| | | | OT03 |
| | | | |
| | | Storage, Bookcase 2H | Steelcase Universal |
| 27 | 22 | | |
| | | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features | OR EQUAL |
| | | • Overall Dimensions: 15" depth; 36" width; and 28" height (+/- 1.5") with integral 1.5" high integral base so that it may fit into the space and design of the area | |
| | | Configuration shall include 1 adjustable shelf; adjust in 3/4" vertical increments with a reversible bracket Straight Front | |
| | | Leveling glides on each corner shall have 3/4" range Back must be finished to allow file to be used in the open plan | |
| | | • Ganging and tethering hardware must be offered to ensure alignment with adjacent cabinets and add stability; | |
| | | shall be tethered to adjacent wall for seismic stability Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, | |
| | | stain, abrasion and scratch resistance • Service parts must be available | |
| | | Powdercoated Metal Finish | |
| | | Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | Must meet or exceed all ANSI/BIFMA X5.9-2004 Storage Unit Tests Has documented proof that packaged product underwent shipping vibration and shock testing to ensure | |
| | | product received at customer site is undamaged | |
| | | • Finishes: | |
| | | -Powder Coated Metal: Champagne Metallic (Steelcase); or match - Style and finishes shall match workstations, desks, and office furniture | |
| | | | |
| | | Image is representational of general design intent. | |
| | | | |
| | | | ST01 |
| | | | |
| | | | |

| | | | Brand Name |
|--------|-----|--|---------------------|
| | | | Manufacturer and |
| Line # | Qty | Description | Part Number |
| | | Storage, Bookcase 5H | Steelcase Universal |
| 28 | 2 | | 00.501111 |
| | | Salient Characteristics: To include minimum of the following specifications: | OR EQUAL |
| | | Dimensions and Features | |
| | | • Overall Dimensions: 15" depth; 36" width; and 84" height (+/- 1.5") with integral 1.5" high integral base so that it may fit into the space and design of the area | |
| | | Configuration shall include 5 adjustable shelves; adjust in 3/4" vertical increments with a reversible bracket | |
| | | Straight Front | |
| | | • Leveling glides on each corner shall have 3/4" range | |
| | | Back must be finished to allow file to be used in the open plan | |
| | | Ganging and tethering hardware must be offered to ensure alignment with adjacent cabinets and add stability; | |
| | | shall be tethered to adjacent wall for seismic stability | |
| | | • Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, | |
| | | stain, abrasion and scratch resistance • Service parts must be available | |
| | | Powdercoated Metal Finish | |
| | | Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is | |
| | | capable of being wiped clean with ordinary household cleaning solutions | |
| | | Must meet or exceed all ANSI/BIFMA X5.9-2004 Storage Unit Tests | |
| | | Has documented proof that packaged product underwent shipping vibration and shock testing to ensure | |
| | | product received at customer site is undamaged | |
| | | • Finishes: | |
| | | -Powder Coated Metal: Champagne Metallic (Steelcase); or match | |
| | | Style and finishes shall match workstations, desks, and office furniture | |
| | | | |
| | | | |
| | | Image is representational of general design intent. | |
| | | | |
| | | | |
| | | | ST02 |
| | | | |
| | | | |
| | | | |
| | | | |

| Line # | Qty | Description | Brand Name Manufacturer and Part Number |
|--------|------|--|---|
| | - ', | Storage, Combination Cabinet | Steelcase Universal |
| 29 | 3 | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 24" depth; 36" width; and 66" height (+/- 1.5") with integral 3" high base so that it may fit into the space and design of the area Configuration shall include 3 lateral file drawers below a cabinet with one adjustable shelf Cabinet shall feature doors with european hinges Leveling glides on each corner shall have 3/4" range Back must be finished to allow file to be used in the open plan Ganging and tethering hardware must be offered to ensure alignment with adjacent cabinets and add stability One lock shall lock all drawers, a second lock shall lock cabinet doors, and both shall be keyed separately and be front-removable to simplify field changes. Lock mechanism shall engage both sides of case All pulls shall comply with current ABA codes Drawers must feature heavy-duty steel drawer suspensions which allow drawers to open their full depth Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Service parts must be available Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Must meet or exceed all ANSI/BIFMA X5.9-2004 Storage Unit Tests 36" wide lateral drawers shall be tested for 150 lbs for 75,000 cycles Has documented proof that packaged product underwent shipping vibration and shock testing to ensure product received at customer site is undamaged Finishes: -Powder Coated Metal: Champagne Metallic (Steelcase); or match Style and finishes shall match workstations, other desks, and office furniture | OR EQUAL |
| | | Image is representational of general design intent. | ST03 |

| | | | Brand Name |
|--------|-----|--|--|
| | | | Manufacturer and |
| Line # | Qty | Description | Part Number |
| 30 | 2 | Storage, Conference Credenza | Kimball Priority, Steelcase Universal |
| 30 | 2 | Salient Characteristics: To include minimum of the following specifications: | Oteeloase Oniversal |
| | | | OR EQUAL |
| | | • Overall Dimensions: 24" depth; 30" width; and 29" height, (+/- 2") so that it may fit into the space and design | |
| | | of the area | |
| | | Wood construction | |
| | | Finished back panel with wire access cut outs | |
| | | Locks: keyed random | |
| | | Square ribbed edge top | |
| | | Flush mount surface with softened wood edge | |
| | | One adjustable shelf behind each door | |
| | | • High-pressure laminate finish; Edge band and bullnose edges must have finishes which compliment or match | |
| | | work surfaces | |
| | | • Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable | |
| | | of being wiped clean with ordinary household cleaning solutions | |
| | | • Finishes: | |
| | | - Laminate chassis, back, and doors: Wilsonart Laminate, Kensington Maple | |
| | | - Laminate Chassis, back, and doors. Wilsonart Laminate, Kensington Maple | |
| | | - Pull: Brushed Stainless Arc | |
| | | Finishes shall coordinate and match directly with Conference Furniture | |
| | | · · · · · · · · · · · · · · · · · · · | |
| | | | |
| | | Image is representational of general design intent | |
| | | Image is representational of general design intent. | |
| | | | |
| | | | |
| | | | ST04 |
| | | | |
| | | | |
| | | | |

| | | | Brand Name |
|--------|-----|---|---------------------------------|
| Line # | Qty | Description | Manufacturer and Part Number |
| Line # | Ųίγ | · | |
| 31 | 3 | Storage, Lateral, 3H | Steelcase Universal |
| 0. | 3 | Salient Characteristics: To include minimum of the following specifications: | OR EQUAL |
| | | Dimensions and Features | |
| | | • Overall Dimensions: 36"w x 24"d x 40"h (+/- 2") so that it may fit into the space and design of the area | |
| | | Configuration shall include 3 lateral file drawers Leveling glides on each corner shall have 3/4" range | |
| | | Back must be finished to allow file to be used in the open plan | |
| | | Ganging and tethering hardware must be offered to ensure alignment with adjacent cabinets and add stability | |
| | | One lock shall lock all drawers, keyed random and be front-removable to simplify field changes. Lock mechanism shall engage both sides of case | |
| | | All pulls shall comply with current ABA codes | |
| | | Drawers must feature heavy-duty steel drawer suspensions which allow drawers to open their full depth | |
| | | Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance | |
| | | Service parts must be available | |
| | | Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is | |
| | | capable of being wiped clean with ordinary household cleaning solutions Must meet or exceed all ANSI/BIFMA X5.9-2004 Storage Unit Tests | |
| | | 36" wide lateral drawers shall be tested for 150 lbs for 75,000 cycles | |
| | | Has documented proof that packaged product underwent shipping vibration and shock testing to ensure | |
| | | product received at customer site is undamaged | |
| | | • Finishes: | |
| | | - Powder Coated Metal: Champagne Metallic (Steelcase); or match | |
| | | - Pull: Brushed Stainless Arc - Style and finishes shall match workstations, other desks, and office furniture | |
| | | * Style and finishes shall match workstations, other desks, and office furniture | |
| | | | |
| | | | |
| | | Image is representational of general design intent. | |
| | | 3 | |
| | | | |
| | | | ST05 |
| | | | |
| | | | |
| | | | |

| Line # | Qty | Description | Brand Name Manufacturer and Part Number |
|--------|-----|---|---|
| 32 | 24 | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 18" W, 24" D, 76" H (+/- 1") (per single tower component; ganged units comprised of multiple towers or starter units with add-on units of the same dimension are acceptable) so that it may fit into the space and design of the area Single tier openings Shall provide locker door number plates attached with rivets Available in at least 8 powder coated metal colors Hanging Garment Rod Two storage shelves with grommets for adding electric power Louvered locking pull out drawer (interior dimensions 18"w x 18"d x 18"h Weapons panel with J hook Louvered single hinged door with padlock hasp (18 gauge) Sloped top Leveling glides Environmentally friendly powder coat paint finish inside and out Easy to set-up and install Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Finishes: - Powder Coated Metal: Gray Mist | StoreMoreStore, Police Gear Storage Locker (#SMS-20- PLOC1) OR EQUAL |
| | | Image is representational of general design intent. | ST06 |

| Line # | Qty | Description | Brand Name Manufacturer and Part Number |
|--------|-----|---|---|
| | ٩٠١ | Storage, Mobile B/B/F | Steelcase Univers |
| 33 | 7 | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 15"w x 18"d x 27"h (+/- 2") One larger "file" drawer, two smaller "box" drawers configuration Include Box drawer divider and pencil tray 3" diameter, large, front-locking, soft casters for hard floors Counterweight One lock shall lock all drawers, and shall be front-removable to simplify field changes; keyed randomly All pulls shall comply with current ABA codes Drawers must feature heavy-duty steel drawer suspensions which allow drawers to open their full depth Service parts must be available Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Must meet or exceed all ANSI/BIFMA X5.9-2004 Storage Unit Tests Has documented proof that packaged product underwent shipping vibration and shock testing to ensure product received at customer site is undamaged Finishes: Powder Coated Metal: Champagne Metallic (Steelcase); or match Pull: Brushed Stainless Arc Style and finishes shall match workstations, other desks, and office furniture | OR EQUAL |
| | | Image is representational of general design intent. Table, 24x60 | ST07 Kimball Dock, First |
| 34 | 2 | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 60"w x 24"l x 28"h (+/- 3"): 27.5" AFF clear minimum so that it may fit into the space and design of the area Rectangular shaped top with soft square edges Folding T-Leg Base with non-marring levelling glides Top: High-pressure laminate finish; Edge band and bullnose edges must have finishes which compliment or match work surfaces Base: Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Finishes: Laminate: Kensington Maple Metal: Champagne Metallic (Steelcase); or match Style and finishes shall match workstations, other desks, and office furniture | Office Applause OR EQUAL |
| 35 | 2 | Image is representational of general design intent. Table, Charging Station Salient Characteristics: To include minimum of the following specifications: | TA01 Peter Pepper Products, Go-To Wall Mounted |

| | | Brand Name |
|----------|---|--|
| | | Manufacturer and |
| Line # Q | ' | Part Number |
| | Dimensions and Features Overall Dimensions: 60"w x 13 3/8"d x 40"h (+/- 3") so that it may fit into the space and design of the area Standing height, wall mounted work station with foot rail and wall panel Steel frame, 1/4" Aluminum Top, and 1/4" MDF with Velcro Attachment wall panel Includes (2) Aluminum hooks moiunted to frame for hanging bags, purses and backpacks Includes (2) Aluminum hooks moiunted to frame for hanging bags, purses and backpacks Includes Electrical Module: (2) 120v, 15 amp receptacles and (2) USB charging ports, 2100mA 5V/DV; Includes 8 foot wire drop, 14/3 gauge with grounded plug Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Finishes: Frame: Aluminum Metallic Top: Taupe Metallic Wall Panel: Taupe Metallic Finishes shall coordinate with Dining Cafe and Lobby Furniture | Worktable with Footrest and Wall Panel (60") OR EQUAL |
| | Image is representational of general design intent. Table, Dining 30x30 | TA02 Loewenstein, self- |
| 36 | | edge top with |
| | Salient Characteristics: To include minimum of the following specifications: | tubular steel X base |
| | Overall Dimensions: 30" square x 29"h (+/- 1.5") so that it may fit into the space and design of the area 1 3/16" thick (+/- 0.25") top with central style chrome metal base Laminate top with Urethane knife edge Leveling glides on each corner shall have 7/8" range Greenguard Indoor Air Quality Certified Anti-microbial finish on all exposed wood surfaces Service parts must be available High-pressure laminate finish Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Finishes: HPL Top: Pecan Table Edge: Urethane Knife Edge Metal Base: Chrome Finishes shall coordinate and match directly with Dining Cafe Furniture Image is representational of general design intent. | OR EQUAL |

| | | | Brand Name |
|--------|-----|--|---|
| 1: | 04 | Description | Manufacturer and |
| Line # | Qty | Description | Part Number |
| 37 | 8 | Table, Dining 42x42 Salient Characteristics: To include minimum of the following specifications: | Loewenstein, self- edge top with tubular steel X base |
| | | Dimensions and Features Overall Dimensions: 42" square x 29"h (+/- 1.5") so that it may fit into the space and design of the area 1 3/16" thick (+/- 0.25") top with central style chrome metal base Laminate top with Urethane knife edge Leveling glides on each corner shall have 7/8" range Greenguard Indoor Air Quality Certified Anti-microbial finish on all exposed wood surfaces Service parts must be available High-pressure laminate finish Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Finishes: HPL Top: Pecan Table Edge: Urethane Knife Edge Metal Base: Chrome Finishes shall coordinate and match directly with Dining Cafe Furniture | OR EQUAL |
| | | Image is representational of general design intent. | TA04 |
| 38 | 6 | Table, Training 24x60 | Kimball Dock, First Office Applause |
| | | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features Overall Dimensions: 60"w x 24"l x 28"h (+/- 3"): 27.5" AFF clear minimum so that it may fit into the space and design of the area Rectangular shaped top with soft square edges Flip/Nest Blade C-Leg Base with lockable casters Includes Power center with two USB and two AC power outlets; capable of being daisy chained Include Ganging bracket, leg cord manager, and wire management Top: High-pressure laminate finish; Edge band and bullnose edges must have finishes which compliment or match work surfaces Base: Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance Surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions Finishes: Laminate: Kensington Maple Metal: Champagne Metallic (Steelcase); or match Finishes shall coordinate and match directly with Conference Furniture | OR EQUAL |
| | | Image is representational of general design intent. | TA05 |

| | | | Brand Name |
|--------|-----|--|--|
| | | | Manufacturer and |
| Line # | Qty | Description | Part Number |
| 39 | 20 | Workstation, Typical 6x6 | Kimball, Steelcase, Haworth, Herman Miller |
| | | Salient Characteristics: To include minimum of the following specifications: Dimensions and Features | Willie |
| | | • Overall Dimensions: 72" x 72" x no greater than 64" h (+/-2") so that it may fit into the space and design of the area | Task Light: Reed- Premier, Linear LED |
| | | Workstation layout shall be per attached supplementary drawings so that electrical stub-ups are in adequate locations; verify all dimensions in field prior to order, manufacture, and installation Workstations shall be comprised of a system of coordinating parts and panels for a complete look Workstation shall have integral power and data and shall provide cable management Power shall be provided to the workstations through whip connections at adjacent walls | OR EQUAL |
| | | Service parts must be available Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | Panels: Overall Dimensions: 24" and 48"w x 4" thick x 64"h and 36"h Panel height shall remain low enough to maintain reasonably comfortable sightlines to daylight and views, while still providing privacy from adjacent employee desks Panels against walls or between workstations shall be solid, fabric wrapped, full-height panels; Panels against windows shall be fabric wrapped, low (36"h) panels; Panels along shared walkways shall be fabric wrapped for the lower portion, and glass panel for the top most 18" (+/-6") of the full panel height; see supplementary drawings for layout Shall include minimum 1.25" adjustable leveling glides to accommodate uneven floors Shall feature 1" increment slots within the panel frame to support worksurface brackets and/or accessories Base frame shall be steel with stacked fabric wrapped or glass panel face components and coordinating trim peices for a complete look | |
| | | Worksurfaces Overall Dimensions: Stationary worksurface: 24"d x 72"w x 29" h; Sit-stand table: 48"w x 24"d x 25.5"-49"h (+/-3") Rectangular with square edges Space under the work surface shall be completely free of obstruction and support for the fixed height worksurface shall be accomplished with perimeter edges of the desk or storage units Worksurface shall have a 1" gap between rear and panel face for clearance and cable access with wire management Sit-stand shall feature a powered base with simple, infinite up/down adjustability and programmable up/down control buttons with at least 3 pre-sets Sit-stand mechanism shall be controlled by central box to ensure synchronization Worksurface shall have antimicrobial features molded into the desk components using silver ion or similar technology | |
| | | Overhead Storage Overall Dimensions: Flipper door unit: 48"w x 14"d x 14"h (+/- 2"); Shelf unit: 24"w x 14"d x 6"h (+/- 2") so that it may fit into the space and design of the area Units shall be supported using the 1" increment slots within the panel frame for a clear worksurface area underneath Flipper storage unit shall be lockable and key core shall be front-removable to simplify field changes Wherever door or drawer pulls occur directly next to each other, provide ample clearance for fingers Where occurs, flipper door shall recess into the outer shell of the flipper unit to allow top most surface of the unit to remain undisturbed. Where occurs, flipper door storage shall have a back panel to prevent items from falling behind the desk unit | |

| Line # | Qty | Description | Brand Name Manufacturer and Part Number |
|--------|-----|--|---|
| | ٦٠, | Tackboard/Tool Rail | |
| | | Shall feature a slat-style (or other type) tool rail to accommodate organizational accessories, to include pencil | |
| | | cup, file sorter and paper tray at minimum | |
| | | • Item shall coordinate with and install seamlessly with furniture upon which this is to be placed | |
| | | Task Light | |
| | | Shall provide a dimmable LED task Light under flipper storage unit | |
| | | • Under cabinet light shall be affixed magnetically or otherwise to provide flexibility in depth placement by the | |
| | | user | |
| | | • LED, UL Listed | |
| | | • Switch: single touch on/off; Dimmable, touch-and-hold, 15%-100% continuous with last state memory • 50,000 hours lifespan | |
| | | • Color temperature: 3500K | |
| | | Screw and Magnetic Mounting kit included | |
| | | • 12' with 60-watt power supply | |
| | | Daisy chain capable up to 6 fixtures | |
| | | | |
| | | Mobile B/B/F | |
| | | Overall Dimensions: 15"w x 18"d x 27"h (+/- 2") | |
| | | One larger "file" drawer, two smaller "box" drawers configuration | |
| | | Include Box drawer divider and pencil tray | |
| | | • 3" diameter, large, front-locking, soft casters for hard floors | |
| | | Counterweight One leak shall leak all drawers and shall be front removable to simplify field shanges. | |
| | | One lock shall lock all drawers, and shall be front-removable to simplify field changes All pulls shall comply with current ABA codes | |
| | | Drawers must feature heavy-duty steel drawer suspensions which allow drawers to open their full depth | |
| | | Branco macroatare nearly daty elect drainer eacpendent miles allow drainer to open their tall depth | |
| | | Technical Specification and Code Requirements | |
| | | Table units meet or exceed ANSI/BIFMA X 5.5-1998 Desk/Table Product Tests. | |
| | | • Meets or exceeds UL 1286 and is designed in compliance with NFPA 70 National Electric Code | |
| | | Product shall be tested and compliant with UL 723 Test for Surface Burning Characteristics of Building Meterials using A STM F 84 Standard Test Method | |
| | | Materials using ASTM E 84 Standard Test Method • Work surface edge profile, on edges designed to come into contact with users' wrists, comply with ISO 9241-5 | |
| | | (1998) Section 5.4.4, ANSI/HFES-100 (2008) section 8.3.1.4, BIFMA G1 (2002) Section 9, and CSA-Z412 | |
| | | (2000) section 7.5.12. | |
| | | • Standard high-pressure laminates meet or exceed NEMA LD3-2005 High-Pressure Decorative Laminate | |
| | | standards. | |
| | | Product must meet ANSI/SOHO S6.50 Racking Resistance Test | |
| | | Product shall be tested to National Motor Freight standards to ensure packaging and shipment methods will | |
| | | prevent transit damage | |
| | | • MDF shall comply with ANSI 208.1 and ASTM D 1037, and shall comply with ANSI 208.2 | |
| | | | |
| | | Environmental Features | |
| | | • Paint is VOC-free powder coat type. Powder coat paint overspray is to be collected, reprocessed, and used on | |
| | | interior components | |
| | | Contains recycled content, and shall be recyclable at end of life | |
| | | • Must have SCS IndoorAdvantage™ Gold Certification for indoor air quality. | |
| | | Must be level 1 certified to ANSI/BIFMA e3 Furniture Sustainability Standard | |
| | | • Product shall be manufactured in a FSC Chain of Custody Certified plant to assure that wood is harvested | |
| | | from environmentally-managed forests | |
| | | Shipping packing materials shall be reusable and/or recyclable | |

| | | | Brand Name |
|-------|-----|--|------------------------------|
| Line# | Qty | Description | Manufacturer and Part Number |
| | ~-, | • Miscellaneous | |
| | | Service parts must be available | |
| | | Locks shall be keyed alike within each workstation | |
| | | All necessary brackets and fasteners shall be provided for a stable and secure installation | |
| | | High-pressure laminate finish; Edge band and bullnose edges must have finishes which compliment or match work surfaces | |
| | | Painted surfaces have the following qualities: Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance | |
| | | Manufacturer must offer a lifetime warranty that product is free from defects in materials and workmanship | |
| | | (includes shipping, parts and labor for the repair or replacement of defective item.) Exceptions to this warranty | |
| | | may apply to certain components, as listed on manufacturer literature. | |
| | | • Finishes: | |
| | | - Panel Fabric: Graded in, TBD (3 grades above base grade) | |
| | | - Tackable Panel Upholstery: Graded in, TBD (3 grades above base grade) | |
| | | - Laminate worksurface: Wilsonart Laminate, Kensington Maple 10776-60 - Metal/Trim: Champagne Metallic (Steelcase); or match | |
| | | - Tool Rail: Champagne Metallic (Steelcase); or match | |
| | | Style and finishes shall match workstations, other desks, and office furniture | |
| | | All selected finishes must be approved by VA Interior Designer | |
| | | | |
| | | Image is representational of general design intent. | |
| | | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | WK01 |

| | | Brand Name |
|------------------|---|--|
| | | Manufacturer and |
| e# Qty | Description | Part Number |
| 0 5 | | Kimball, Steelcase, Haworth, Herman |
| | Salient Characteristics: To include minimum of the following specifications: | Miller |
| | Dimensions and Features Overall Dimensions: 30"w x 4"th x 64"h (+/-2") | OR EQUAL |
| • F | Panel layout shall be per attached supplementary drawings; verify all dimensions in field prior to order, | OIT EQUITE |
| | nanufacture, and installation Service parts must be available | |
| ٠ ١ | Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is | |
| • F | capable of being wiped clean with ordinary household cleaning solutions Panel height shall remain low enough to maintain reasonably comfortable sightlines to daylight and views, while still providing privacy from edicable and love dealers. | |
| • F wi the | while still providing privacy from adjacent employee desks Panels against walls or between workstations shall be solid, fabric wrapped, full-height panels; Panels against windows shall be fabric wrapped, low (36"h) panels; Panels along shared walkways shall be fabric wrapped for he lower portion, and glass panel for the top most 18" (+/-6") of the full panel height; see supplementary drawings for layout | |
| | Shall include minimum 1.25" adjustable leveling glides to accomodate uneven floors | |
| • E | Shall feature 1" increment slots within the panel frame to support worksurface brackets and/or accessories Base frame shall be steel with stacked fabric wrapped or glass panel face components and coordinating trim beices for a complete look | |
| • F | Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance | |
| sh | Manufacturer must offer a warranty that product is free from defects in materials and workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) | |
| - | Finishes: - Panel Fabric: Graded in, TBD (3 grades above base grade) | |
| | - Metal/Trim: Champagne Metallic (Steelcase); or match Style and finishes shall match workstations, other desks, and office furniture | |
| | All selected finishes must be approved by VA Interior Designer | |
| | | |
| Im | mage is representational of general design intent. | |
| | | WK02 |
| | | |

| | | | Brand Name |
|-------|-----|---|--|
| | | | Manufacturer and |
| Line# | Qty | Description | Part Number |
| 41 | 3 | | Kimball, Steelcase, Haworth, Herman |
| | | Salient Characteristics: To include minimum of the following specifications: | Miller |
| | | Dimensions and Features Overall Dimensions: 42"w x 4"th x 64"h (+/-2") | OR EQUAL |
| | | Panel layout shall be per attached supplementary drawings; verify all dimensions in field prior to order, manufacture, and installation | 011 2 4 0 / 12 |
| | | Service parts must be available | |
| | | Work surfaces shall not be affected by ordinary household solvents, acids, alcohols, or salt solutions and is capable of being wiped clean with ordinary household cleaning solutions | |
| | | Panel height shall remain low enough to maintain reasonably comfortable sightlines to daylight and views, while still providing privacy from adjacent employee desks | |
| | | Panels against walls or between workstations shall be solid, fabric wrapped, full-height panels; Panels against windows shall be fabric wrapped, low (36"h) panels; Panels along shared walkways shall be fabric wrapped for the lower portion, and glass panel for the top most 18" (+/-6") of the full panel height; see supplementary | |
| | | drawings for layout | |
| | | Shall include minimum 1.25" adjustable leveling glides to accomodate uneven floors Shall feature 1" increment slots within the panel frame to support worksurface brackets and/or accessories | |
| | | Base frame shall be steel with stacked fabric wrapped or glass panel face components and coordinating trim peices for a complete look | |
| | | • Factory applied finish - electrostatic, baked-on epoxy-polyester hybrid powder coat paint for optimal corrosion, stain, abrasion and scratch resistance | |
| | | Manufacturer must offer a warranty that product is free from defects in materials and workmanship (includes shipping, parts and labor for the repair or replacement of defective item.) | |
| | | Finishes: Panel Fabric: Graded in, TBD (3 grades above base grade) Add Time Of the Management of the Manag | |
| | | Metal/Trim: Champagne Metallic (Steelcase); or match Style and finishes shall match workstations, other desks, and office furniture | |
| | | All selected finishes must be approved by VA Interior Designer | |
| | | | |
| | | Image is representational of general design intent. | |
| | | | WK03 |
| | | | |