

REQUESTING SERVICE: GERIATRICS & EXTENDED CARE
SHIP TO: CHIEF, A & MM
V.A. Medical Center
800 ZORN AVE
LOUISVILLE, KY 40206
REQUISITION: 603-B83007

Qty	Product Description
1	OEC 9900 Elite™ with 12 inch image intensifier, PMCare Platform, and Standard C-arm
1	Sony UP-991AD hybrid graphic printer
1	12 Inch Laser Aimer with English Language Manual
1	WSP Wireless DICOM Software Option, 5.0 GHz
1	12" Twelve Month Extended Warranty, 9900
1	Oakworks CFPM401 Four Movement Imaging Table with Integrated Headrest

Qty	Description
1	<p>OEC 9900 Elite™ with 12 inch image intensifier, PMCare Platform, and Standard C-arm</p> <p>High performance mobile C-arm for use in pain management procedures. Provides flexible mechanical features, rotating anode x-ray tube, user-friendly touch screen user interface, and superb image quality.</p> <p>The physical dimensions and the open design of the C-arm allow the system to be easily transported throughout the hospital and provide unobstructed imaging access around the patient and procedural table.</p> <p>Digital Image Processing and Workstation</p> <ul style="list-style-type: none"> - Dynamic Range Management (DRM) controls for image management - Four pre-set imaging profiles for optimized anatomical capture - Dual articulating, high resolution flat screen black & white monitors - Integrated keyboard touchpad - cursor/tap controls - DICOM 3.0 interface with send and query/retrieve - CD/DVD on-board media storage, read/write compatible - USB 2.0 mass storage device, write only, .jpg/.bmp/.avi file formats <p>X-ray Generator</p> <ul style="list-style-type: none"> - 60 kHz high frequency - 15kW power

Part Number	Qty	Description	List Price	Net Price
		<ul style="list-style-type: none"> - Up to 120 kVp - Up to 75mA for radiographic film exposure - Continuous high level fluoro (HLF) up to 20mA - Digital spot up to 75 mA - Full power from standard wall outlet - Patented battery buffered design 		
		X-ray Tube <ul style="list-style-type: none"> - Rotating anode x-ray tube - 0.3mm and 0.6mm focal spots - Anode heat capacity: 300,000 HU (per IEC 60613) - Anode cooling rate: 85,000 HU/min. - Housing heat capacity: 1,600,000 HU - Standard housing cooling 22,500 HU/min. 		
		Digital Image Rotation <ul style="list-style-type: none"> - Digitally adjusts image display - Automatic image update <ul style="list-style-type: none"> - Image rotation - Image reversal (side-to-side) - Image invert (top-to-bottom) - Image positioning without additional exposure 		
		PreView™ Collimator <ul style="list-style-type: none"> - On-screen collimator position indication - PreView™ iris collimator - PreView™ Tungsten rotatable double leaf collimator - Adjusts collimator without X-ray exposure 		
		Fluoro Mode <ul style="list-style-type: none"> - kVp range: 40 -120 - mA range: 0.2 - 10 <ul style="list-style-type: none"> 1.0 - 20 HLF (high level fluoro) - Auto and manual fluoro modes - AutoTrak™ ABS varies mA, kVp camera gain 		
		Pulsed Fluoro Mode <ul style="list-style-type: none"> - kVp range: 40 - 120 - mA range: 0.2 - 10 - Pulse rate: 1,2,4,8 - Pulse width: 25 or 50ms - AutoTrak™ ABS, mA, kVp, camera gain - Reduces X-ray dose to patient and operator 		
		High Level Pulsed Fluoro <ul style="list-style-type: none"> - kVp range : 40 - 120 - mA range: 1 - 40 - Pulse rate: 1,2,4,8 - Pulse width: 25 or 50ms 		

Part Number	Qty	Description	List Price	Net Price
		<ul style="list-style-type: none"> - AutoTrak™ ABS, mA, kVp, and camera gain 		
		Digital Spot Mode <ul style="list-style-type: none"> - kVp range: 40 - 120 - mA range: Up to 75 - Automatic exposure termination and automatic image save 		
		Radiographic Mode <ul style="list-style-type: none"> - mA range: up to 75 - mAs range: up to 300 - Computer controlled exposure time 		
		12" Image Intensifier <ul style="list-style-type: none"> - Tri-Mode 12"/9"/6" (31cm/23cm/15cm) image intensifier - Minimum central resolution (at the monitor) <ul style="list-style-type: none"> - 12" (31cm): 1.6 lp/mm - 9" (23cm): 2.2 lp/mm - 6" (15cm): 2.6 lp/mm - DQE: 65% (typical) 		
		Precision imaging with Dynamic Range Management (DRM) enhances features of interest while attenuating background noise. <ul style="list-style-type: none"> - Preset Imaging Profiles <ul style="list-style-type: none"> - 9800 - General - Orthopedic - Spine 		
		AutoTrak™ <ul style="list-style-type: none"> - Automatic Brightness Stabilization (ABS) - Automatically seeks the subject anatomy anywhere within the imaging field and selects the optimum imaging technique - Automatically adjusts to anatomical size and location - Provides uniform image quality throughout entire image - Simplifies operation 		
		Image Quality <ul style="list-style-type: none"> - Smart Window: <ul style="list-style-type: none"> - Dynamically senses the collimator position and automatically adjusts brightness and contrast to produce high image quality. - Smart Metal: <ul style="list-style-type: none"> - Allow user to adjust automatic brightness and contrast sensitivity levels to metal 		

<i>Part Number</i>	<i>Qty</i>	<i>Description</i>	<i>List Price</i>	<i>Net Price</i>
		<ul style="list-style-type: none"> - Provides optimum image quality even when metal is introduced to the field - Tungsten Collimator: <ul style="list-style-type: none"> - Denser collimator limits X-ray exposure area - Reduces scatter radiation - Improves image detail 		
		<p>Video Camera</p> <ul style="list-style-type: none"> - High resolution 1k x 1k CCD camera - Full frame capture - Motorized rotation - On-screen orientation indicator (real-time feedback without fluoro) - Left-right image reversal - Top-bottom image invert 		
		<p>Video Display</p> <ul style="list-style-type: none"> - Dual display anti-glare, LCD flat panel monitors mounted on an articulating arm: <ul style="list-style-type: none"> - Left hand Black & White monitor, Right hand Color monitor - 22" horizontal travel - 7° up/10° down - Monitors viewable from all four sides of workstation - Horizontal and vertical viewing angle 170° - 1200 CD/M2 maximum brightness - Touch screen system control - 1280 x 1024 high resolution monitors - OEC 9900 TechView Reference Monitor: <ul style="list-style-type: none"> - 9" LCD Display mounted at C-arm mainframe - Reference quality real-time video of left live-image C-arm - 270° rotation, +30/-5° tilt 		
		<p>PMCare Platform</p> <ul style="list-style-type: none"> - 1k x 1k x 16 bit image processing - Preset Imaging Profiles: <ul style="list-style-type: none"> - 9800 - General - Orthopedic - Spine - Noise filter with on-screen indicator - Minimal difference spatiotemporal noise filter (MDST) <ul style="list-style-type: none"> - Real-time dynamic range management (DRM) - Automatic digital brightness and contrast control - Manual digital brightness and contrast control - Negate mode - Save and auto-save feature 		

Part Number	Qty	Description	List Price	Net Price
		<ul style="list-style-type: none"> - Swap and auto-swap feature - Patient information <ul style="list-style-type: none"> - Examination list - Customized patient information - Customize functions <ul style="list-style-type: none"> - Workstation set-up - Mainframe set up - Patient information set up - Date/time set up - DICOM interface set-up - Last image hold - 1000 image storage - CD/DVD burner with DICOM viewer for displaying images on PC platforms 512 x 512 or 1k x 1k <ul style="list-style-type: none"> - Integrated DICOM interface (store, print, worklist, and query/retrieve) - HIPAA SecureView <ul style="list-style-type: none"> - Password protection - Blank screen function - Delete all - Zoom and roam function - Image annotation - Measurement software - 8fps Dynamic digital disk <ul style="list-style-type: none"> - Recording /playback rate: 1,2,4,8fps - Recording time: 5 minutes @ 8fps - Automatic image playback - Frame-by-frame review - Re-registration - Real-time digital subtraction (DSA) 		
		<p>User Interface</p> <ul style="list-style-type: none"> - Entire system is computer controlled and software upgradeable - Touchscreen control simplifies operation - Automated system operation requires minimum operator interface - Multi-functional controls <ul style="list-style-type: none"> - Footswitch - Hand-held control - Simplified keyboard with integrated touchpad - Multi-purpose image directory <ul style="list-style-type: none"> - Retrieve and review images - Compose hardcopy films - Copy images - X-ray dose summary 		
		<p>C-arm Mechanics</p> <ul style="list-style-type: none"> - Counterbalanced, manual adjustment of orbital rotation, cranial-caudal rotation, wig-wag and 		

<i>Part Number</i>	<i>Qty</i>	<i>Description</i>	<i>List Price</i>	<i>Net Price</i>
		horizontal motion <ul style="list-style-type: none"> - Patented flip-flop C-arm reversal (SmartView) - 31" free space, 28" depth in arc, 115° orbital rotation - Dual, illuminated C-arm operator control panels 		
		OEC Clinical Excellence Onsite Training <ul style="list-style-type: none"> - Pre-training package with interactive CD-ROM - Up to two days* of in-service by our ARRT certified Clinical Imaging Specialists (CIS) during the one-year warranty period. - Post-training skills assessment & test - Participants may be eligible for Continuing Education (CE) credits from the American Society of Radiologic Technologists** 		
		Notes: WSP - Wireless Service Platform <ul style="list-style-type: none"> - The OEC 9900 comes with a device called the WSP which facilitates these capabilities: <ul style="list-style-type: none"> - USB 2.0 mass storage: The USB functionality is write only, and saves images in .jpg/.bmp/.avi file formats. USB storage devices must be unencrypted and unprotected. 		
		Warranty <ul style="list-style-type: none"> - One Year Warranty 		
		Notes: OEC Clinical Excellence Onsite Training <p>* Onsite training provided from 8am to 5pm, Monday through Friday. Includes all CIS travel and living expenses. ** Training produces the best results when a dedicated core group of technologists complete the session. Those who complete the entire OEC Clinical Excellence curriculum should be competent to perform the tasks required for basic operation of the system. Competency will be measured through a skills assessment completed while the CIS is on-site.</p>		
	1	Sony UP-991AD hybrid graphic printer		
	1	12 Inch Laser Aimer with English Language Manual		
	1	WSP Wireless DICOM Software Option, 5.0 GHz Dual band (2.4GHz/5.0GHz) WSP Wireless DICOM – sftw only; installation and setup		
	1	12" Twelve Month Extended Warranty, 9900		
	1	Oakworks CFP401 Four Movement Imaging Table with Integrated Headrest Four Motions <ul style="list-style-type: none"> - Motion 1: height range 26" - 44" (66cm - 112cm) 		

<i>Part Number</i>	<i>Qty</i>	<i>Description</i>	<i>List Price</i>	<i>Net Price</i>
		<ul style="list-style-type: none"> - Motion 2: Trendelenburg tilt +15°/-11° - Motion 3: 10" (25cm) longitudinal travel - Motion 4: lateral travel ±4" <p>Specifications:</p> <ul style="list-style-type: none"> - Patient Weight Capacity: 500 lbs - Table top dimensions: 22" x 84" carbon fiber with integrated headrest - Metal free imaging area: 56" <p>Included Accessories:</p> <ul style="list-style-type: none"> - 1 hand control - 1 foot control - Table top pad- 1" thick - 1 Patient Safety strap - 1 crescent face rest cushion <p>Certification, Power Requirements and Warranty:</p> <ul style="list-style-type: none"> - Power required – 110V/120V, 15 amps, standard US wall outlet - FDA listed - ETL approved - CE marked - 36 month limited warranty, provided by Oakworks: <p>3 years parts / 2 years labor</p>		