



NEW WORK PLAN
SCALE: 1/8"=1'-0"

GENERAL NOTES

- A. PITCH CONCRETE TO DRAINS.
- B. PROVIDE CONTINUOUS EXPANSION JOINTS AROUND ENTIRE PERIMETER OF NEW CONCRETE.
- C. TOTAL PARKING AREA EQUALS APPROXIMATELY 4000 SQ. FT. NEW CONCRETE SHALL VARY FROM 6" THICK AT THE PERIMETER TO 3" MIN. AT THE DRAINS.
- D. CLEAN AND FLUSH THE 3 EXISTING DRAINS.
- E. FLOOD THE MEMBRANE FOR 24 HOURS TO PROVE IT IS WATERPROOF PRIOR TO POURING CONCRETE.
- F. REPAINT PARKING LINES TO MATCH EXISTING SPACES.
- G. BROOM FINISH CONCRETE SURFACE TO PROVIDE A NON-SLIP SURFACE.
- H. BRIDGE OVER AREAWAY IS NOT NEEDED FOR TRUCK TRAFFIC CONCRETE WILL NOT BE PUMPED OVER AREAWAY.

- ① PROVIDE NEW SLOPED CONCRETE WITH MEMBRANE AND PROTECTION BOARD ON EXISTING CONCRETE STRUCTURAL SLAB.
- ② PROVIDE NEW CONCRETE CURBING.
- ③ PROVIDE NEW CONCRETE RAMP AND ASSOCIATED CURBING AND RAILINGS (TO MATCH EXISTING).
- ④ REPLACE EXISTING DRAIN PIPING IN BASEMENT CEILING BACK TO MAIN STACK - APPROX. 90'.

7/16/2018 12:56:54 PM