

Salient Characteristics

**Imaging Workstation #1**

**ROOM 1D159**

Dimension: (78"x78") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T5 Table Base. Under fixed work surface, 65" High sound absorptive panel system. Drawer Pedestal 24"W with (6",6",12") drawers and open shelf storage Anchor panel system to wall 6 outlet power bar under return surface Swivel Cup Holder (2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height Data Dock - Keyboard surface cable organizer (2) Dimmable Lux task lights with a flexible mounting arm, mounted to keyboard surface Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power-only USB ports Control with filtered air flow and (2) 250w Forced Air Heaters Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (2) 24" portrait scissor mount, (2) 24" Barco, (1) 16" portrait scissor mount flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors (6) DISPLAY PORTS (6) DVI-D

**Imaging Workstation #2**

**ROOM C306D**

(78"x78") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T5 Table Base. Under fixed work surface, Drawer Pedestal 24"W with (6",6",12") drawers and open shelf storage 6 outlet power bar under return surface " Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (3) 16", (2) 16" portrait flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors Control with filtered air flow and (2) 250w Forced Air Heaters Data Dock - Keyboard surface cable organizer (2) Dimmable Lux task lights with a flexible mounting arm, mounted to keyboard surface Swivel Cup Holder Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power-only USB ports (2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height (5) DVI-D

**Imaging Workstation #3**

**Broward ROOM**

(72"x44") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T4 Table Base. Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (2) 13" portrait, (2) 15" portrait flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors Control with filtered air flow and (2) 250w Forced Air Heaters Data Dock - Keyboard surface cable organizer (2) Dimmable Lux task lights with a flexible mounting arm, mounted to keyboard surface Swivel Cup Holder Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power-only USB ports true sit to stand adjustment range of 22"-48" (2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height

**Imaging Workstation #4**

**ROOM A208E**

(78"x78") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T5 Table Base. Under fixed work surface, Drawer Pedestal 36"W with (6",6",12") drawers and open shelf storage 6 outlet power bar under return surface Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (1) 22", (1) 14" portrait, (4) 16" Barco portrait flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors Control with filtered air flow and (2) 250w Forced Air Heaters Data Dock - Keyboard surface cable organizer (2) Dimmable Lux task lights with a flexible mounting arm, mounted to keyboard surface Swivel Cup Holder Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power-only USB ports. (2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height

**Imaging Workstation #5**

**ROOM D300G**

(72"x72") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T5S Table Base. Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (1) 12" portrait, (2) 16" portrait, (1) 16" flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors Control with filtered air flow and (2) 250w Forced Air Heaters Data Dock - Keyboard surface cable organizer (2) Dimmable Lux task lights with a flexible mounting arm, mounted to keyboard surface Swivel Cup Holder Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power-only USB ports (2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height

**Imaging Workstation #6**

**ROOM D302**

(84"x84") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T5 Table Base. Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (2) 16", (2) 12" portrait, (2) 16" portrait flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors Control with filtered air flow and (2) 250w Forced Air Heaters Data Dock - Keyboard surface cable organizer (2) Dimmable Lux task lights with a flexible mounting arm, mounted to keyboard surface Swivel Cup Holder Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power-only USB ports. (2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height 6 outlet power bar under return surface Under fixed work surface, Drawer Pedestals 30"W with (6",6",12") drawers and open shelf storage

**Imaging Workstation #7**

**ROOM PET CT**

(78"x44") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T4 Table Base. Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (2) 16" Barco Portrait, (2) 19" portrait, (1) 16" portrait flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors Control with filtered air flow and (2) 250w Forced Air Heaters Data Dock - Keyboard surface cable organizer Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power-only USB ports 2) Dimmable Lux task lights with a flexible mounting arm, mounted to keyboard surface Swivel Cup Holder 2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height 2) DISPLAY PORT TAG:

**Imaging Workstation #8**

**ROOM D300E**

78"x78") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T5 Table Base Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (2) 24" scissor mount, (1) 24" portrait scissor mount, (2) 24" Barco portrait flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors Control with filtered air flow and (2) 250w Forced Air Heaters Data Dock - Keyboard surface Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power Swivel Cup Holder 2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height (2) DISPLAY PORT (3) DVI-D

**Imaging Workstation #9**

**ROOM D300H**

(78"x78") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T5 Table Base Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (2) 24" scissor mount, (1) 24" portrait scissor mount, (2) 24" Barco portrait flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors Control with filtered air flow and (2) 250w Forced Air Heaters Data Dock - Keyboard surface cable organizer Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power-only USB ports Swivel Cup Holder (2) Dimmable Lux task lights with a flexible mounting arm, mounted to keyboard surface 2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height (2) DISPLAY PORT (3) DVI-D

**Imaging Workstation #10**

**ROOM D300**

(84"x84") Dual Surface Console with true sit to stand adjustment range of 22"-48" AFF, with T5 Table Base. Fixed Monitor Mount. Accommodates up to (2) 24" portrait, (1) 21" Flat Panel Monitors on a single level Optional: Additional mounts can be added to stack a second tier of monitors NOTE: Placement of mounting system will be determined by customer on site during installation Control with filtered air flow and (2) 250w Forced Air Heaters Swivel Cup Holder

Data Dock - Keyboard surface cable organizer Single shelf with grommet, under monitor surface 19"W x 5 1/4"H x 9"D with power-only USB ports 2) Dimmable Lux task lights with a flexible mounting arm, mounted to keyboard surface (2) Fixed CPU Hangers mounted under monitor surface. 18.75" Maximum CPU Height Monitor Mounting system capable of 10" of focal depth adjustment. Accommodates up to (1) 21" scissor mount, (1) 21" portrait scissor mount, (1) 24" portrait scissor mount, (2) 38" Barco flat panel monitors on a single level. Optional: Additional mounts can be added to stack a second tier of monitors Under fixed work surface, Drawer Pedestals 36"W with (6",6",12") drawers and open shelf storage 6 outlet power bar under return surface (7) DISPLAY PORT (3) DVI-D