

**SECTION 10 21 13  
TOILET COMPARTMENTS**

**PART 1 - GENERAL**

**1.1 DESCRIPTION**

This section specifies solid phenolic toilet partitions, and urinal screens. Support structure from the toilet compartment to the structure above shall be designed and engineered entirely by the compartment manufacturer.

**1.2 RELATED WORK**

- A. Overhead structural steel supports for ceiling hung pilasters: Section 05 50 00, METAL FABRICATIONS. Support structure from the toilet compartment to the structure above shall be designed and engineered entirely by the compartment manufacturer.
- B. Color of baked enamel finish: Section 09 06 00, SCHEDULE FOR FINISHES.
- C. Grab bars and toilet tissue holders: Section 10 28 00, TOILET, BATH, AND LAUNDRY ACCESSORIES.

**1.3 SUBMITTALS**

- A. Submit in accordance with Section 01 33 23, SHOP DRAWINGS, PRODUCT DATA, AND SAMPLES.
- B. Samples: Prime coat of paint on 150 mm (six-inch) square of metal panel with baked enamel finish coat over half of panel.
- C. Manufacturer's Literature and Data: Specified items indicating all hardware and fittings, material, finish, and latching.
- D. Shop Drawings: Construction details at 1/2 scale, showing installation details, anchoring and leveling devices.
- E. Manufacturer's certificate, attesting that zinc-coatings conform to specified requirements.

**1.4 APPLICABLE PUBLICATIONS**

- A. Publications listed below form a part of this specification to the extent referenced. Publications are referenced in the text by the basic designation only.
- B. Federal Specifications (Fed. Spec.):  
FF-B-575C.....Bolt, Hexagon and Square
- C. Code of Federal Regulations (CFR):  
40 CFR 247.....Comprehensive Procurement Guidelines for  
Products Containing Recovered Materials

- D. Commercial Item Descriptions (CID):  
 A-A-1925.....Shield, Expansion (Nail Anchors)  
 A-A-60003.....Partitions, Toilet, Complete

## **PART 2 - PRODUCTS**

### **2.1 TOILET PARTITIONS:**

- A. Solid phenolic: water resistant; graffiti resistant; non-absorbent; contain a minimum 30 percent post consumer recycled plastic; Class C flame spread rating.
- B. Conform to Fed. CID A-A-60003, except as modified herein.
- C. Fabricate to dimensions shown or specified.
- D. Toilet Enclosures:
1. Type 1, Style B (Ceiling hung).
  2. Reinforce panels shown to receive toilet tissue holders or grab bars.
  3. Upper pivots and lower hinges adjustable to hold doors open 30 degrees.
  4. Latching devices and hinges for handicap compartments shall comply with ADA requirements.
  5. Keeper:
    - a. U-slot to engage bar of throw latch.
    - b. Combined with rubber bumper stop.
  6. Wheelchair Toilets:
    - a. Upper pivots and lower hinges to hold out swinging doors in closed position.
    - b. Provide U-type doors pulls, approximately 100 mm (four inches) long on pull side.
  7. Finish:
    - a. Finish: Solid Phenolic, Color to be selected from manufactures standard.
- E. Urinal Screens:
1. Type III, Style E (wall hung), finish 2 or 3.
    - a. With integral flanges and continuous, full height wall anchor plate.
    - b. Option: Full height U-Type bracket.
    - c. Wall anchor plate drilled for 4 anchors on both sides of screen.
  2. Screen 600 mm (24 inches) wide and 1060 mm (42 inches high).

### **2.2 FASTENERS**

- A. Partition Fasteners: CID A-A-60003.
- B. Use expansion bolts, CID A-A-60003, for anchoring to solid masonry or concrete.

- C. Use toggle bolts, CID A-A-60003, for anchoring to hollow masonry or stud framed walls.
- D. Use steel bolts FS-B-575, for anchoring pilasters to overhead steel supports.

### **PART 3 - EXECUTION**

#### **3.1 INSTALLATION**

##### A. General:

1. Install in rigid manner, straight, plumb and with all horizontal lines level.
2. Conceal evidence of drilling, cutting and fitting in finish work.
3. Use hex-bolts for through-bolting.
4. Adjust hardware and leave in freely working order.
5. Clean finished surfaces and leave free of imperfections.

##### B. Panels and Pilasters:

1. Support panels, except urinal screens, and pilaster abutting building walls near top and bottom by stirrup supports secured to partitions with through-bolts.
2. Secure stirrups to walls with two suitable anchoring devices for each stirrup.
3. Secure panels to faces of pilaster near top and bottom with stirrup supports, through-bolted to panels and machine screwed to each pilaster.
4. Secure edges of panels to edges of pilasters near top and bottom with "U" shaped brackets.
5. Where overhead braced, secure pilasters to building walls by headrails clamped on or set into top of each pilaster.
  - a. Secure clamps to pilasters with two through-bolts to each clamp.
  - b. When headrails are set into pilasters, through-bolt them to the pilasters.
  - c. Support headrails on wall flange fittings secured to building walls with minimum of two anchor bolts to each flange fitting.

##### C. Urinal Screens:

1. Anchor urinal screen flange to walls with minimum of four bolts both side of panel.
2. Space anchors at top and bottom and equally in between.

- - - E N D - - -