

SHIP TO :
BLOG. 126 , RECEIVG B80009
V.A. Medical Center
WAREHOUSE , BLOG. 126
4100 WEST THIRD ST.
DAYTON, OH 45428

P .O.# 552- B80009

Item No.	Qty	Description
1	1	<p>OPTIMA XR240AMX, US</p> <p>Optima XR240amx Digital Mobile Radiographic system</p> <p>*THIS IS A ZERO DETECTOR SYSTEM*</p> <p>The Optima XR240amx is a self-contained battery operated mobile radiographic digital X-ray imaging system designed for performing radiographic exams at the point of care</p> <p>Key features</p> <ul style="list-style-type: none">-30KW generator-Compatible with FlashPad HD2530 and FlashPad HD3543 digital wireless detectors-Dose Area Product Meter (DAP)-Capable of 100 - 240V nominal, 50/60Hz operation-Stand-by mode eliminates boot up cycles and allows the start of the imaging exam within 20 seconds. <p>Exposures can be taken and processed while the unit is charging</p> <ul style="list-style-type: none">-FlashPad HD detector batteries charge automatically while the detector(s) are in the bin when the system is on, or in standby mode-Tether cord-Optimized GUI - Technique, image acquisition and display tools in a single integrated user interface-FlashPad HD detectors can be shared across compatible systems within the healthcare facility by all

Item No.	Qty	Description
		<p>users.</p> <p>Please refer to the current literature for system compatibility.</p> <ul style="list-style-type: none"> -Drive inhibit keypad access -Password protected access to patient -Information for compliance with confidentiality regulations -Automatic safety brake: Operator must hold drive handles to allow system to move -Integrated front bumper stops unit and activates brakes when activated <p>Productivity:</p> <ul style="list-style-type: none"> -Less than 4.5 hours to go from 20% to 100% for system battery charge -System can be driven within 4 seconds of activation -Pre-programmed techniques per anatomy, view, and patient size -System can be used without the detector. Designed for use with films or CR Cassettes
2	1	<p>DETECTOR BATTERY 14X17IN</p> <p>DETECTOR BATTERY 14X17IN</p>
3	1	<p>GRID 6:1 14X17IN</p> <p>6:1 Grid for FlashPad HD3543</p>
4	1	<p>BATTERY CHARGER 14X17IN</p> <p>Battery charger for FlashPad HD3543 (14" x 17" Wireless digital detector):</p> <p>The external desktop charger is intended to charge up to two Flashpad HD3543 rechargeable</p>

Item No.	Qty	Description
		<p>lithium#ion batteries simultaneously.</p> <p>The external desktop charger:</p> <ul style="list-style-type: none"> - Displays the status of the battery packs - Contains two charging bays. Status lights on the charger indicate the status of each battery pack - Will charge the battery in up to three hours, depending on the initial state of charge - Is keyed to accept the battery in one orientation
5	1	<p>Auto Protocol Assist</p> <p>Auto Protocol Assist for Optima XR200amx, Optima XR220amx, and Optima XR240amx; this APA is for the existing customer license from Optima XR220amx to Optima XR240amx.</p>
6	1	<p>Repeat/Reject Analysis</p> <p>Repeat/Reject Analysis for Optima XR220amx/Upgraded Optima XR200amx, and Optima XR240amx</p>
7	1	<p>GE Grip Flashpad HD 14x17</p> <p>FlashPad HD 3543 (14"x17") detector non-slip grips are designed to be applied to the detector for the benefit of helping the user get a better hold of the detector during handling and patient positioning.</p>
8	1	<p>Int Flashpad HD 14x17</p> <p>FlashPad HD3543 (14" x 17" Wireless integrated digital detector):</p> <ul style="list-style-type: none"> - Detector battery can take up to 60

Item No.	Qty	Description
		<p>exposures per hour and provide enough power for 5 hours of use on a single charge</p> <ul style="list-style-type: none"> - Single panel (non-tiled) amorphous silicon detector with a directly deposited cesium iodide scintillator - Pixel pitch 100 microns - Pixel matrix: 3524 x 4288 pixels - Typical DQE @ 0lp/mm: 75% - Include QAP (Quality Assurance Procedure) - Available with 6:1 or 8:1 removable grids - Image area: (13.8 in x 16.6 in) - Weight: 3.2kb (7.1 lbs) - 802.11n 5GHz link between system and detector - Supports automatic channel switching to improve image transfer and avoid wireless interference with hospital network
9	1	<p>Sterile Protective Drapes - Tube Drape</p> <p>Sterile Protective Drapes - Tube Drape</p>
10	1	<p>Optima XR240amx Expert 1 Package New to GE Digital Portable System</p> <p>Optima XR240amx Expert 1 Package New to GE Digital Portable System</p> <p>Optima XR240amx Expert 1 Package New to GE Recommended for training 4-5 users on All System Features.</p> <p>Four full days (1 day = 8 hours)</p>

Item No.	Qty	Description
		<p>Includes one 3-day on-site visit to coincide with system go-live and one 1-day on-site follow-up visit to be scheduled Monday through Friday. Training cannot be scheduled as single day events. Training expires 12 months from the date of go-live of equipment or purchase, whichever is the latest.</p> <p>Configuration List Price: Configuration List Price:</p> <p>Shimadzu MobileArt Evolution EE51426</p>

Options

Item No.	Qty	Description
11	1	<p>Mobile XR Systems Svc Trng</p> <p>Optima XR240amx, XR220amx, and XR200amx Full Service Training (Class/Lab) (4 Days)</p> <p>This service training class covers all three mobile X-ray systems Optima XR240amx, XR220amx, and XR200amx. Engineer must have have completed DGS Fundamentals training R0211RY & R0212RY or equivalent experience before attending this course.</p>

Item No.	Qty	Description
12	1	<p>This course must be taken within 2 years from the purchase date.</p> <p>Optima XR240amx Service Training</p> <p>Optima XR240amx Service Training This online course provides the knowledge and skills necessary to perform service tasks on the X-ray Mobile Digital Optima XR240amx. This course is intended for those individuals who have already attended and completed the instructor led course on the X-ray Mobile Digital Optima XR 220amx and talks to the differences between these two systems.</p> <p>Please visit our webpage to register: http://www3.gehealthcare.com/en/education/product_education_-_technical/ or contact us at: edservices@ge.com</p>