

SHIP TO: WEST ROXBURY VA  
V.A. Medical Center  
Warehouse Bldg 7  
1400 VFW Parkway  
West Roxbury, MA

REQUISITION: 523-B91014

	Payment terms are Net thirty (30) days from receipt of invoice. Equ shipped FOB Origin, freight pre-paid and ad
<b>Qty</b>	<b>Product</b>
2	<b>IntraSight 7</b> <i>IntraSight interventional applications platform. Includes IntraSight CPU, on (1) CPU Base, Operator's Manual, Power Transformer, Cable Pre-Install Kit, Power Supply, Connection Box, Mouse, Keyboard, 19"Monitor Kit, DICOM Network Connection and Windows10 OS.</i>
2	<b>iFR &amp; IVUS co-registration</b> <i>Includes: SyncVision Workstation CPU, Power Supply, Isolation Transformer Medical Grade, Joystick Controller, Optical USB Mouse and Keyboard, LCD Monitor 19"Philips, Cable Kit, SyncVision System Operator's Guide.</i>
1	<b>IntraSight 5</b> <i>IntraSight interventional applications platform. Includes IntraSight CPU, on (1) CPU Base, Operator's Manual, Power Transformer, Cable Pre-Install Kit, Power Supply, Connection Box, Mouse, Keyboard, 19"Monitor Kit, DICOM Network Connection and Windows10 OS.</i>
2	<b>End User License Agreement</b>
3	<b>Imaging (IVUS) License</b> <i>Includes: Digital, Rotational and ChromaFlo, IVUS</i>
3	<b>Touch Screen Module (TSM)</b>
3	<b>iFR® Hyperemia Free Lesion Assessment Modality</b>
3	<b>FFR® Modality</b>
3	<b>Philips Remote Services</b>
3	<b>One (1) Year Warranty</b>

TRADE IN -MFG VOLCANO CORP; 1 EA  
MODEL CORE; SN 103000596001; ACQ  
DT 1/6/16

# Specifications

		IntraSight (for configurations 5 and 7)	SyncVision (with IntraSight 7)
<b>Power requirements</b>	System input	100, 120v, 220, 240VAC, 50/60Hz, 1000VA	100V-120V, 50/60Hz, 220-240V, 50/60Hz, 600 VA
	Workstation	100 – 240V, 50/60Hz, 825VA	100-240V, 50/60Hz, 250 VA
	Monitor	100V – 240V 50/60Hz, 39W	100-240V, 50/60Hz, 93 VA
<b>Dimensions</b>	Workstation	H= 17", W= 10", D= 16.5", 46 lbs.	H= 16.5", W= 6.75", D= 21.25", 35 lbs.
	Touch screen module (TSM) with articulating tableside mount	H= 7", W= 11.9", D= 9", 8 lbs. (Articulating arm extends to a max depth of 16.5" and/or 20" above the top of the bedrail)	n/a
	Monitor	H= 15"-19" (adjustable stand), W= 15.8", D= 9.7", 13 lbs.	H= 15"-19" (adjustable stand), W= 15.8", D= 9.7", 13 lbs.
	Joystick	n/a	H= 1.5", W= 4.2", D= 3", 2 lbs.
	Connection box	H= 9.85", W=2.95", D= 7.75", 6 lbs.	n/a
<b>Processing and data storage</b>	Processor	1 CPU with 2.3GHz (maximum turbo frequency of 3.2GHz). 12 core total. 2400 MHz BUS.	1 GPU P5000 1 CPU Intel E5-1600/E5-2600 Series Processor
	Memory	32GB SD RAM	16GB SD RAM
	Hard drive capacity	1TB SSD SATA	120GB SSD SATA + 480GB SSD SATA
	Digital archiving capacity	Local, DVD, DICOM Network (includes Worklist management, DICOM Store)	n/a
<b>Compatible disposables</b>	Catheters	Eagle Eye Platinum Eagle Eye Platinum ST PV Visions .014P PV Visions .018 PV Visions .035 Refinity ST Pioneer Plus	Eagle Eye Platinum Eagle Eye Platinum ST
	Pressure wires	Verrata Plus	Verrata Plus