

PURCHASE ORDER: 652-B90054
 REQUESTING SERVICE: MEDICAL
 SHIP TO: CHF, ACQ & MAT MGT
 V.A. Medical Center
 REC. WHSE. BLDG 500
 1201 BROAD ROCK BLVD.
 RICHMOND, VA 23249

Configuration - Included Items

Item	Part Number - Description	Qty
1	L22406 - SonoSite S I Ultrasound System	1

The SonoSite Sli is a high-resolution, all-digital, 126 pound (5.70 kg) ultrasound system with a 121 in. LED full-bleed glass display. The system is portable, and can be used across multiple hospital environments, including a zero footprint option for space-constrained rooms. The Sli features a new touchscreen user interface with a clinician-driven menu logic that adaptively adjusts to the use case - "what you need, is what you see". An embedded dual transducer connector also allows seamless switching between transducers with two simple taps of the screen, ensuring that the right transducer is always readily available. DirectClear technology, a novel, patent-pending process that elevates transducer performance by increasing penetration and contrast resolution, is available on select transducers.

The purchase of the SonoSite Sli system includes the following software technologies:

2D grayscale with SonoMB Multi Beam Technology

Auto Gain with SonoADAPT Tissue Optimization technology

M-Mode

- SonoHD Imaging Technology, technology which significantly reduces speckle noise while enhancing image margins, thereby dramatically improving contrast and structural resolution. - Tissue Harmonic Imaging (THI), a capability in which the system transmits at one frequency and receives at a higher harmonic frequency to reduce noise and clutter and improve resolution. - Velocity color flow imaging provides the clinician with the color sensitivity to perform color Doppler examinations with all transducers during a clinical procedure

The system uses a Video Electronics Standards Association (VESA) Flat Display Mounting Interface (FDMI) MIS-D 75 (75mm x 75mm) and MIS-D 100 (100mm x 100mm.), allowing direct mounting to many commercially available options.

Item	Part Number - Description	Qty
	<p>The reliability and durability of the SonoSite Sli are backed by a five-year standard warranty, which is included in the price of the system. Software upgrades to the main system and transducer databases are both accomplished through one of the three USB ports on the system.</p> <p>You will receive four consecutive hours of installation provided by a SonoSite Clinical Specialist, as part of the SonoSite Sli purchase. The installation includes an overview of the product and accessories purchased, training on the features, functions, and user interface, and system care/maintenance. (Available for US locations only.)</p> <p>Additional clinical installation support can be purchased separately as needed.</p>	
2	<p>P22162 - DICOM (Print, Store, Worklist, MPPS, Storage Commit)</p> <p>The DICOM package includes the capability to interface with your PACS network with the complete offering of DICOM capabilities: print, store, worklist, storage commit, and modality perform procedure step.</p>	1
3	<p>P19626 - L38xi / 10-5 MHz Transducer - Armored Cable Biopsy Compatible</p> <p>L38xi / 10-5 MHz multi-frequency, broadband, 38 mm linear array transducer. This transducer is biopsy compatible.</p> <p>Armored Cable Technology provides further protection against trampling, crushing and twisting using a stainless-steel jacket inside the cable.</p>	1
4	<p>P20679 - HSL25x / 13-6 MHz Transducer Biopsy Compatible</p> <p>HSL25x / 13-6 MHz multi-frequency, broadband, 25 mm linear array transducer.</p>	1
5	<p>L13559- Power Pack</p> <p>The PowerPack is an external battery pack that mounts quickly and easily to the universal stand. The PowerPack extends the system battery life for performing more exams on a single charge.</p>	1
6	<p>L21432 - Sli Stand</p> <p>To further accelerate end-to-end workflow, the Sli comes with a new stand, offering additional capabilities, all while minimizing footprint. The stand features:</p> <ul style="list-style-type: none"> - Larger storage basket for items like medication, syringes, gloves etc. - Elevated transducer holder to prevent transducer cables from hitting the ground - Lockable drawer with a tray located on the back of system, to allow the clinician to bring the image as close to the patient as possible - AC Cord retainer to prevent accidental removal of AC cord - Dedicated gel bottle holder - New casters for increased portability - Auxiliary cord management solution 	1
7	<p>P21701 - Wireless Data Management</p> <p>This kit includes the USB dongle that is used to transmit images and information wirelessly and installation instructions.</p>	1
8	<p>P22358 - Sli Ultrasound Service Manual</p>	1
9	<p>P20536 - Sli Ultrasound System User Guide English</p>	1
10	<p>P22358- Sli Ultrasound Service Manual</p>	1

Item	Part Number - Description	Qty
11	5-YR-WARRANTY - 60 MONTHS - STANDARD COVERAGE WARRANTY Please refer to Warranty Schedule. 60 MONTHS - STANDARD COVERAGE WARRANTY	1