



A. ALL NEW INTERIOR PARTITIONS SHALL BE WALL TYPE 'U' UNLESS OTHERWISE INDICATED. NO RATED WALLS BEYOND EXISTING DUCTWOOL SHALL BE TYPE '0' (PROVIDE ACOUSTICAL BATT INSULATION ABOVE CEILING; REFER TO PRIME FOR WALL TYPES.

B. CONSTRUCTION AND INSTALLATIONS SHALL CONFORM TO ALL FEDERAL, STATE AND LOCAL ORDINANCES, CODES, ETC.

C. DIMENSION PLANS ARE INTENDED TO SHOW DIMENSIONS AND WALL TYPES. WALL RATINGS, WALL SECTIONS, BUILDING SECTION INDICATORS, EXTERIOR ELEVATION INDICATORS, PLAN OR SECTION INDICATORS, ETC. REFER TO THE PLAN KEY NOTES, REFER TO THE A4 SERIES ARCHITECTURAL PLANS FOR ADDITIONAL PLAN KEY NOTES, INTERIOR ELEVATION MARKS AND INFORMATION RELATED TO OTHER ASPECTS OF THE PROJECT.

D. ALL DIMENSIONS ARE TAKEN FROM COLUMN CENTERLINES TO THE FACE OF FINISH FACE OF MASONRY, CONCRETE, OR EXISTING FINISHES, UNLESS NOTED OTHERWISE.

E. CONTRACTOR SHALL VERIFY ALL CRITICAL DIMENSIONS WITHIN AND/OR RELATED TO THE SITE AND/OR EXISTING BUILDINGS, DIMENSIONS AND CONDITIONS IDENTIFIED WERE CORROBORATED BY VISUAL MEANS. THE CONTRACTOR SHALL OBTAIN AND VERIFY ALL DIMENSIONS AND CONDITIONS AT JOB SITE AND BE FULLY RESPONSIBLE FOR THE SAME. IF DISCREPANCY IS FOUND, THE CONTRACTOR SHALL CONTACT THE ARCHITECT AND THE ARCHITECT SHALL DETERMINE THE CORRECT DIMENSIONS TO BE HELD. THE CONTRACTOR SHALL SUBMIT TO THE ARCHITECT FOR REVIEW A DIMENSIONED INTERIOR WALL LAYOUT PRIOR TO ANY INTERIOR WALL CONSTRUCTION.

F. DIMENSIONS ARE TAKEN TO THE 4'-0" PLANE ABOVE FINISHED FLOOR.

G. ALL FIRE RATED ASSEMBLIES WITH RECESSED WALL ACCESSORIES AND/OR PENETRATIONS, I.E. RECESSES, CONCEALED DUCTS, PIPING, FIRE EXTINGUISHER CABINETS, RECESSED FILL VIEWERS, PAPER TOWEL DISPENSER, ETC. SHALL BE CONSTRUCTED TO MAINTAIN THE DESIGNATED RATED ASSEMBLY.

H. VERIFY ALL EXISTING FLOOR ELEVATIONS, GRADES AND DIMENSIONS OF EXISTING BUILDING AS IT RELATES TO THE NEW CONSTRUCTION. NOTIFY THE ARCHITECT OF ANY DISCREPANCIES PRIOR TO CONSTRUCTION.

I. FINISHED FLOOR ELEVATIONS ARE FROM THE FACE OF THE FINISHED SUBSTRATE, I.E. CONCRETE DECK, CONCRETE SLAB, ETC.

J. VARIATION IN THE EXISTING FLOOR SLAB ELEVATIONS MAY PRODUCE DIFFERENT CLEARANCES BETWEEN DOOR FRAME HEAD AND CEILING HEIGHTS. FIELD VERIFY EXISTING CONDITIONS PRIOR TO THE INSTALLATION OF EXIST' LIGHTS, VENT' WALL COVERING, DOOR LIGHTS, TRIM, ETC. NOTIFY THE ARCHITECT OF ANY DISCREPANCIES OR REVISIONS PRIOR TO CONSTRUCTION.

K. VERIFY LOCATION AND SIZE OF ALL RECESSES, PLUMBING CHASES AND MECHANICAL SHAFTS PRIOR TO CONSTRUCTION.

L. ALL EXTERIOR WALLS SHALL BE FRAMED OUT OF 6 GAUGE .6" METAL STUD AT 16" ON CENTER UNLESS NOTED OTHERWISE. REFER TO THE STRUCTURAL DRAWINGS.

M. INSTALL MINERAL WOOL INSULATION IN ALL EXPANSION JOINTS THROUGH THE FLOOR AND ROOF SLABS, CONTINUOUS. PROVIDE FIRE RATED EXPANSION JOINTS WITH MINERAL WOOL INSULATION BLANKET AT ALL RATED ASSEMBLIES.

N. ALL PENETRATIONS THROUGH FLOORS, CHASES, SHAFTS AND FIRE RATED ASSEMBLIES SHALL BE SLEEVED PER THE REQUIRED TEST AND FIRE STOPPED.

O. ALL PENETRATIONS THROUGH FLOOR SLABS, I.E. CONDUITS, DUCTS, PIPING, PNEUMATIC CABLES, ETC. SHALL BE FIRE STOPPED AND SEALED AS REQUIRED TO PROVIDE THE ASSEMBLY RATED DESIGNATED AND SHALL BE WATERTIGHT.

P. PROVIDE FULL HEIGHT METAL STUDS (20 GAUGE MINIMUM) TO THE FLOOR OR ROOF DECK ABOVE AT ALL CORNERS, DOOR FRAMES, BORROWED LIGHTS FRAME, BEHIND WALL MOUNTED EQUIPMENT AND BEHIND WALL MOUNTED CASEWORK.

Q. ALL TRACES ARE REQUIRED TO VISIT THE SITE AND DETERMINE THAT ALL WORK CAN BE ACHIEVED IN A COMPLETE MANNER UNDER THEIR BID.

R. PACK MINERAL WOOL INSULATION IN VOID SPACE BETWEEN STRUCTURAL DECK AND TOP OF ALL FIRE-RATED ASSEMBLIES. PROVIDE FIRE- RATED SEALANT AT ALL FIRE-RATED ASSEMBLIES.

S. ALL INTERIOR WALLS INCLUDING THE METAL STUD FRAMING, ACOUSTICAL INSULATION AND GYPSUM WALLBOARD SHALL EXTEND UP TO THE FLOOR OR ROOF DECK ABOVE.

T. ALL VERTICAL OR HORIZONTAL DUCTS, PIPING, CONDUIT, ETC. (SHOWN OR NOT) WHERE REQUIRED SHALL BE BOXED OUT TO MATCH ADJACENT WALL CONSTRUCTION.

U. RATED WALL DESIGNATIONS ARE SHOWN THROUGH OPENINGS TO INDICATE THAT THE WALL CONSTRUCTION ABOVE THE OPENING HAS THE SAME RATING AS THE CONSTRUCTION ON EITHER SIDE OF OPENING.

V. PROVIDE ACCESS PANELS IN WALLS WHERE SERVICE TO MECHANICAL, PLUMBING, ELECTRICAL, ETC. ELEMENTS ARE REQUIRED. PANELS SHALL BE CLEAN OUT VALVES, DAMPPERS, ETC. ACCESS PANELS SHALL BE OF THE SAME RATING AS THE ADJACENT WALL CONSTRUCTION.

W. PROVIDE BLOCKING BEHIND ALL WALL MOUNTED HANDRAILS, BUMPER RAILS, TOILET ACCESSORIES, SCONCES, ETC.

X. ALL CORRIDORS, HALLWAYS, PASSAGeways, ETC. WALLS SHALL BE CONSTRUCTED TO BE SPOKE TIGHT AND SPOKE RESISTANT UNLESS NOTED OTHERWISE.

Y. REFER TO FR1 SHEET FOR PLAN SYMBOLS & LEGEND.

Z. REFER TO FR2 SHEET FOR WALL RATING ASSEMBLY DETAILS.

AA. REFER TO THE A1 SERIES SHEETS FOR PROJECT LIMITS, PHASING OF WORK, CONSTRUCTION POLLUTING, STAGING, ETC. COORDINATE ALL WORK WITH OTHER PHASES AND SEQUENCE AS REQUIRED FOR THE COMPLETION OF THE PROJECT.

AB. REFER TO THE A5 SERIES SHEETS FOR REFLECTED CEILING PLANS FOR DIMENSIONS TO LOCATE GULCH CURB/GRANT TRACKS, IV, TRACKS, ETC.

AC. REFER TO A11 SERIES FOR ENLARGED TOILET PLANS AND TOILET ACCESSORY SCHEDULE FOR TYPICAL INSTALLATION.

AD. REFER TO THE A11 SERIES SHEETS FOR INTERIOR ELEVATIONS.

AE. REFER TO A14 SERIES SHEETS FOR THE OPENING SCHEDULE FOR THE OPENING SIZE.

AF. REFER TO A16 SERIES SHEETS FOR EQUIPMENT PLANS, EQUIPMENT NUMBERS AND SCHEDULE.

NOTES:

A. RATED WALL DESIGNATIONS ARE DRAIN THROUGH OPENINGS TO INDICATE THAT THE WALL CONSTRUCTION ABOVE THE OPENING HAS THE SAME RATINGS AS THE CONSTRUCTION ON EITHER SIDE OF OPENING.

B. THE CONTRACTOR MUST SUBMIT DOCUMENTATION WHEN RATED WALL ASSEMBLY HAS BEEN TESTED AND APPROVED BY AGENCY OTHER THAN ILL.

C. THE CONTRACTOR SHALL VERIFY THE RATED WALLS IF DIFFERENCES ARE FOUND. THE CONTRACTOR SHALL UPGRADE WALL RATINGS AS ON LIFE SAFETY PLAN A1A AND A1E.

**NON RATED SMOKE PARTITION**  
DOOR AND FRAME - NOT RATED  
DAMPERS - NOT REQUIRED  
PENETRATIONS/PERFETER - SEALED

EXTEND AT LEAST ONE LAYER OF GYPSUM WALL BOARD TO DECK ABOVE OR ENTIRE WALL CONSTRUCTION TO GROUND RESISTANT CONSTRUCTION.

**ONE HOUR FIRE BARRIER**  
DOOR AND FRAME - 45 MIN RATING  
DAMPERS - SEE TECH CODE  
PENETRATIONS/PERFETER - FIRE CALLED

EXTEND ENTIRE WALL CONSTRUCTION TO DECK ABOVE.

**TWO HOUR FIRE BARRIER**  
DOOR AND FRAME - 90 MIN RATING  
DAMPERS - SEE TECH CODE  
PENETRATIONS/PERFETER - SEALED

EXTEND ENTIRE WALL CONSTRUCTION TO DECK ABOVE.

**FIRE SMOKE BARRIER**  
DOOR AND FRAME - 30 MIN RATING  
DAMPERS - SEE TECH CODE  
PENETRATIONS/PERFETER - SEALED

EXTEND ENTIRE WALL CONSTRUCTION TO DECK ABOVE.

**ONE HOUR FIRE SMOKE BARRIER**  
DOOR AND FRAME - 30 MIN RATING  
DAMPERS - FIRE AND SMOKE - SEE TECH CODE  
PENETRATIONS/PERFETER - FIRE CALLED

EXTEND ENTIRE WALL CONSTRUCTION TO DECK ABOVE.

**TWO HOUR FIRE SMOKE BARRIER**  
DOOR AND FRAME - 30 MIN RATING  
DAMPERS - FIRE AND SMOKE - SEE TECH CODE  
PENETRATIONS/PERFETER - FIRE CALLED

EXTEND ENTIRE WALL CONSTRUCTION TO DECK ABOVE.

1. OFFSET SINK DRAIN LINE TO AVOID EXISTING STRUCTURE AND/OR BUILT-IN FREEZER BELT. REFER TO PLUMBING DRAWINGS.
2. FLOOR MOUNTED WATER CLOSET WITH BACK DISCHARGE TO AVOID EXISTING STRUCTURE AND/OR BUILT-IN FREEZER BELT. REFER TO PLUMBING DRAWINGS.
3. EXISTING BUILDING TO REMAIN, PROTECT DURING NEW CONSTRUCTION.
4. ALIGN CORNERS OF NEW CONSTRUCTION WITH EXISTING CONSTRUCTION.
5. NEW WINDOW AND FRAME (OPERABLE FROM EXTERIOR FOR EMERGENCY?) REFER TO OPENING SCHEDULE.
6. PROVIDE BLINDS AT CLOSED POSITION PRIOR TO INSTALLATION OF WALL INFFIL. REFER TO DETAIL SHEET A504.
7. NEW WINDOW AND FRAME (SUICIDE RESISTANT?). REFER TO OPENING SCHEDULE.
8. HALF WALL REFER TO PRUJ AND ID SHEETS
9. NEW WALL AND FRAME (DUCTWORK ACCESS?) REFER TO OPENING SCHEDULE.
10. PATCH/INFFIL WINDOW SILL (TYPICAL FOR ALL EXISTING SILL BEING DISTURBED).
11. NEW WINDOW AND FRAME FOR LOUVER. REFER TO NEW OPENING SCHEDULE.
12. REPLACE EXISTING GYPSUM WALLBOARD WITH CATEGORY 4-EXTREME DUTY GYPSUM.
13. COORDINATE DRAIN LINES TO AVOID EXISTING CONCRETE BEAM / JOIST BELOW. REFER TO PLUMBING DRAWINGS.
14. ROUND CORNER OF HALF WALL TO PREVENT INJURIES. TOP OF WALL + TOP OF WINDOW SILL.

ale: AS NOTED

		CONSULTANTS:		PROJECT MANAGERS AND ENGINEERS:		Drawing Title		Project Title		Project Number		Office of Construction and Facilities Management	
		 <b>TEGE</b> <b>The Estopinal Group</b> <small>ARCHITECTS ENGINEERS INTERIORS</small> 820 Jordan Street, Suite 507 tel. 318.424.3700 Shreveport, LA 71310 fax 318.424.3744		 <b>TNF</b> <b>A VETERAN OWNED COMPANY</b> 3 EXECUTIVE COURT, UNIT 4 SOUTH BARRINGTON, IL 60010		<b>DIMENSION PLAN - I NORTH</b>		<b>RENOVATE ED # PRIMARY CARE</b> Phase I		667-10-100 Building Number 1 N			
Revisions:		Date				Approved: Project Director		Location		Drawing Number		 <b>Department of Veterans Affairs</b>	
								SHREVEPORT VAMC 510 EAST STONER AVE		<b>A3.N1</b> Dwg. <b>14</b> of <b>112</b>			
								Date 01/09/13		Checked JAH		Drawn CSH	