MASTER KEYNOTE SCHEDULE

DIVISION 01 : GENERAL REQUIREMENTS

1.000 KEYNOTES TYPICALLY ARE NOT DUPLICATED WITHIN A GIVEN DETAIL. CONTRACTOR IS TO ASSUME THAT AN UN-KEYED ITEM IS TO BE THE SAME AS THE KEYNOTED ITEM WITHIN THE SAME DETAIL.
1.101 OWNER-PROVIDED ITEM (N.I.C.): OFFICE EQUIPMENT; SMALL PHOTOCOPY MACHINE.
1.104 OWNER-PROVIDED ITEM (N.I.C.): OFFICE FURNITURE; CUBICLE. CONTRACTOR TO MAKE FINAL ELECTRICAL AND DATA CONNECTIONS TO OWNER FURNITURE. TYPICAL.
1.105 OWNER-PROVIDED ITEM (N.I.C.): OFFICE FURNITURE; LATERAL FILE CABINETS.
1.106 OWNER-PROVIDED ITEM (N.I.C.): OFFICE FURNITURE; DESK CARREL.
1.108 OWNER-PROVIDED ITEM (N.I.C.): OFFICE EQUIPMENT; COFFEE MAKER.
1.110 OWNER-PROVIDED ITEM (N.I.C.): WORKSHOP FURNITURE; WORK BENCH.
1.111 OWNER-PROVIDED ITEM (N.I.C.): WORKSHOP FURNISHING; TOOLBOX ON CASTERS.
1.115 OWNER-PROVIDED ITEM (N.I.C.): WORKSHOP EQUIPMENT; LATHE.
1.116 OWNER-PROVIDED ITEM (N.I.C.): WORKSHOP EQUIPMENT; BAND SAW.
1.117 OWNER-PROVIDED ITEM (N.I.C.): WORKSHOP EQUIPMENT; DRILL PRESS.
1.118 OWNER-PROVIDED ITEM (N.I.C.): WORKSHOP EQUIPMENT; GRINDER.
1.119 OWNER-PROVIDED ITEM (N.I.C.): WORKSHOP EQUIPMENT; BUFFER.
1.121 OWNER-PROVIDED ITEM (N.I.C.): RESIDENTIAL EQUIPMENT; MICROWAVE OVEN.
1.125 OWNER-PROVIDED ITEM (N.I.C.): STORAGE FURNISHING; PALETTE SHELVING.
1.126 OWNER-PROVIDED ITEM (N.I.C.): STORAGE FURNISHING; METAL SHELVING.
1.127 OWNER-PROVIDED ITEM (N.I.C.): STORAGE FURNISHING; SMALL PARTS BINS.
1.166 OWNER-FURNISHED ITEM TO BE INSTALLED BY CONTRACTORS: FLAT SCREEN TV.
1.171 OWNER-FURNISHED ITEM TO BE INSTALLED BY CONTRACTORS: RESIDENTIAL EQUIPMENT; REFERIGERATOR.
1.411 60" DIA. CLEAR TURNING SPACE FOR WHEELCHAIR.
1.553 CONTRACTOR MATERIAL STAGING AREA.
1.555 DUMPSTER STAGING AREA.

DIVISION 02 : SITE WORK AND DEMOLITION

2.212 DEMOLISH EXISTING SUBSTRUCTURE: CONCRETE SLAB-ON-GRADE; SAW CUT SLAB AT LIMITS OF DEMOLISHED AREA.
2.221 DEMOLISH EXISTING EXTERIOR DOOR.
2.231 CONTRACTOR TO SAWCUT AND REMOVE PORTION OF EXISTING PRECAST CONCRETE DECK PLANK AS REQUIRED FOR NEW OPENING. CONTRACTOR TO INSTALL NEW SUPPLEMENTAL STEEL PRIOR TO SAWCUTTING.
2.233 CONTRACTOR TO SAWCUT AND REMOVE PORTION OF EXISTING PRECAST CONCRETE DECK PLANK (BETWEEN RIBS) TO ACCOMMODATE NEW OPENING. DO NOT CUT EXISTING PLANK RIBS. OPENING LOCATION AND SIZE TO BE COORDINATED IN FIELD. PROVIDE ROUND HOLES IN CORNERS TO PREVENT OVER-RUN OF SAW BLADE.
2.235 DEMOLISH EXISTING CONSTRUCTION: SAWCUT AND REMOVE PORTION OF EXISTING PRECAST CONCRETE DECKING PLANK(S) AND ASSOCIATED ROOFING ASSEMBLY AS REQUIRED FOR NEW MECHANICAL EQUIPMENT OPENING, ROOF CURB AND CURB FLASHING; SEE PARTIAL ROOF FRAMING PLAN, DETAIL #3 ON SHEET A301; REFER TO MECHANICAL DRAWINGS FOR ADDITIONAL INFORMATION.
2.251 DEMOLISH EXISTING INTERIOR WALL CONSTRUCTION: MASONRY PARTITION.
2.258 DEMOLISH EXISTING INTERIOR DOOR AND FRAME.
2.260 REMOVE AND RELOCATE EXISTING INTERIOR COILING OVERHEAD DOOR, HOOD, TRACKS, DOOR CONTACTS AND OPERATOR; PROTECT COILING OVERHEAD DOOR ASSEMBLY FROM DAMAGE DURING REMOVAL AND RELOCATE IN ITS ENTIRITY IN THE LOCATION AS INDICATED IN THE DRAWINGS.
2.264 DEMOLITION BY OWNER: OWNER TO DEMOLISH EXISTING INTERIOR SPECIALTY; GUARDRAIL; CONTRACTOR TO GRIND BOLTS FLUSH TO FLOOR SLAB AND PATCH CONCRETE.
2.269 DEMOLISH EXISTING INTERIOR CONSTRUCTION: CHAIN-LINK FENCE STORAGE PARTITION AND GATES; AS INDICATED; GRIND BOLTS FLUSH TO FLOOR SLAB AND PATCH CONCRETE.
2.270 DEMOLISH EXISTING INTERIOR CONSTRUCTION: PORTABLE OFFICE CONSTRUCTION IN ITS ENTIRITY; ITEMS TO BE DEMOLISHED IN ADDITION TO THE DEMOUNTABLE PARTITIONS AND THEIR ASSOCIATED DOORS, WINDOWS AND A/C UNITS ARE THE METAL DECK AT THE TOP OF THE DEMOUNTABLE PARTITIONS AND ONLY THE STRUCTURAL STEEL RELATED TO SUPPORTING THE METAL DECK, CARPET/CARPET TILE, SUSPENDED CEILING SYSTEM: COORDINATE WITH OWNER ITEMS TO BE SALVAGED: PROTECT EXISTING CONSTRUCTION TO REMAIN FROM DAMAGE: ITEMS TO REMAIN ARE EXISTING CONCRETE SLAB, STEEL SUPERSTRUCTURE (STEEL COLUMNS AND BEAMS SUPPORTING ROOF ASSEMBLY) , PRECAST CONCRETE DECK, EXTERIOR MASONRY WALL AND WINDOWS: REFER TO MECHANICAL, ELECTRICAL AND FIRE PROTECTION DRAWINGS FOR ADDITIONAL INFORMATION.

DIVISION 03 : CONCRETE

3.001 EXISTING CONCRETE FOUNDATION WALL.
3.003 EXISTING CONCRETE SLAB.
3.004 EXISTING CONCRETE DECK.
3.007 EXISTING PRECAST PLANK DECK.
3.025 CONCRETE REINFORCEMENT: #4 DOWEL x 2'-0" AT 1'-0" O.C. U.N.O. ANCHOR INTO EXISTING SLAB/WALL/FOOTING USING HILTI HY-150 INJECTION ADHESIVE. EMBEDMENT TO BE 6" U.N.O..
3.030 CAST-IN-PLACE CONCRETE: MATCH EXISTING CONCRETE SLAB THICKNESS. REINFORCE WITH WWF-6x6 W2.0 x W2.0.

DIVISION 04 : MASONRY

4.001 EXISTING MASONRY WALL.
4.170 MASONRY GROUT: CONTINUOUS GROUTED SOLID MASONRY COURSES. REFER TO SPECIFICATIONS.
4.171 MASONRY GROUT: GROUT DOOR FRAME SOLID.
4.175 MASONRY GROUT: FILL EXISTING RECESS IN CONCRETE SLAB TO BRING NEW DOOR THRESHHOLD UP TO FLOOR LEVEL.
4.180 MASONRY ANCHORAGE AND REINFORCEMENT: CONTINUOUS JOINT REINFORCEMENT; SINGLE WYTHE; 16" O.C. VERTICAL SPACING.
4.306 CONCRETE UNIT MASONRY: 6" (NOM.) THK.; MATCH COURSING, BOND AND TYPE.
4.808 MASONRY ASSEMBLY: TOOTH NEW MASONRY INTO EXISTING.

DIVISION 05 : METALS

5.001 EXISTING STRUCTURAL STEEL FRAMING MEMBER.
5.002 EXISTING STEEL LINTEL.
5.005 EXISTING PIPE TRENCH COVER; STEEL PLATE.
5.006 EXISTING STRUCTURAL STEEL COLUMN TO REMAIN. PROTECT FROM DAMAGE DURING DEMOLITION.
5.007 EXISTING OVERHEAD DOOR JAMB SUPPORT STEEL TO REMAIN.
5.030 METAL OR CONCRETE ROOF DECKING: EXISTING.
5.056 METAL FABRICATION: STEEL LINTEL: (2) - L3 1/2" x 2 1/2" x 7/16" (LLV) WITH 4" BEARING AT EA. END TYPICAL.
5.092 METAL FABRICATION: OVERHEAD DOOR HEADER SUPPORT POST AND JAMB PROTECTION ASSEMBLY; STEEL TUBE POST CONTINUOUS TO EXISTING STEEL BEAM AND BRACED WITH ATTACHED STEEL PLATES; STEEL BASE PLATE WELDED TO POST AND ANCHOR BOLTED TO EXISTING SLAB; STEEL TUBE HEADER WELDED TO STEEL TUBE JAMB POSTS; REFER TO DETAILS 1, 5 AND 9, SHEET A1001; EXPOSED STEEL TO BE PAINTED.
5.093 METAL FABRICATION: OVERHEAD DOOR HEADER; STEEL TUBE HEADER WELDED TO STEEL TUBE JAMB POSTS; REFER TO DETAILS 1, 5 AND 9, SHEET A1001; EXPOSED STEEL TO BE PAINTED.
5.101 STRUCTURAL STEEL: STEEL COLUMN AS NOTED.
5.515 METAL FABRICATION: INSTALL BEAM TIGHT TO UNDERSIDE OF EXISTING CONCRETE DECK. PROVIDE STEEL SHIMS AS REQUIRED. PROVIDE 3/8"x 4" STEEL TAB CONNECTION OF NEW BEAM TO EXISTING STEEL BEAM WITH 1/4" FILLET WELDS EACH SIDE OF TAB. NEW BEAM TO BE COPED AT CONNECTION TO EXISTING BEAM.
5.535 METAL FABRICATION: L5x3x1/4x0'-6" LONG (L.L.V.) AT 4'-0" O.C. N.S. AND F.S. ATTACH INTO DECK WITH (2)-#12-14x1/2" LONG SELF DRILLING SCREWS.
5.565 METAL FABRICATION: MISCELLANEOUS STEEL ELEMENTS AS NOTED; CONNECT TO SUPPORTING ELEMENTS AS DEPICTED.

DIVISION 06 : WOOD AND PLASTIC

6.001 WOOD BLOCKING: DIMENSIONAL LUMBER; SIZE AS INDICATED; REFER TO SCHEDULE FOR TREATMENT.
6.002 WOOD BLOCKING: DIMENSIONAL LUMBER; SIZE AS REQUIRED; REFER TO SCHEDULE FOR TREATMENT.
6.007 PLYWOOD: 3/4" THICK; REFER TO SPECIFICATIONS FOR TREATMENT.
6.009 WOOD SHIM.
6.420 LAMINATE CLAD WOOD CASEWORK: BASE CABINETS; COLOR-PLA.
6.430 LAMINATE CLAD WOOD CASEWORK: WALL CABINETS; COLOR-PLA
6.431 LAMINATE CLAD WOOD CASEWORK: WALL CABINETS; MICROWAVE SHELF WITH 18 INCH DEEP EXTENDED LOWER SHELF; COLOR-PLA.
6.440 LAMINATE CLAD WOOD CASEWORK: FILLER PANEL, SIZE AS REQUIRED; COLOR-PLA.
6.453 LAMINATE CLAD WOOD CASEWORK: COLUMN ENCLOSURES; REFER TO ENLARGED DETAILS AND ELEVATIONS. TYPICAL OF ALL FREE-STANDING COLUMNS; COLOR-PLA.
6.454 LAMINATE CLAD WOOD CASEWORK: COLUMN ENCLOSURES; 2 x 3 WOOD FRAMING.
6.455 LAMINATE CLAD WOOD CASEWORK: COLUMN ENCLOSURES; 3/4" PARTICLE BOARD.
6.461 SOLID SURFACING COUNTERTOP/CASEWORK ACCESSORY: COUNTERTOP SUPPORT BRACKET.
6.501 SOLID SURFACING COUNTERTOP: 3/4" THICK WITH 3/4" PLYWOOD BACKING - FRONT EDGE 1-1/2" THICK PROFILE; WITH 4" HIGH X 3/4" THICK BACKSPLASH/SIDE SPLASHES; 1/4" RADIUSED EDGE DETAIL TO TOP EDGE OF COUNTERTOP. TYPICAL. EASED EDGE FOR BACK AND SIDE SPLASHES. TYPICAL. COLOR - SSA.
6.502 SOLID SURFACING COUNTERTOP: 1/2" THICK WITH 3/4' PLYWOOD BACKING; WITH 4" HIGH BACKSPLASH/ SIDESPLASHES; 4" HIGH FRONT EDGE; 22" COUNTER DEPTH; COUNTER SURFACE AT 34" A.F.F.. UNLESS NOTED OTHERWISE.

DIVISION 07 : THERMAL AND MOISTURE PROTECTION

7.001 EXISTING ROOF CONSTRUCTION.
7.203 INSULATION: THERMAL BATT; THICKNESS AS INDICATED.
7.260 VAPOR BARRIER.
7.520 MODIFIED BITUMINOUS ROOF MEMBRANE ASSEMBLY PATCHING; MATCH EXISTING ROOF INSULATION THICKNESS TO ALLOW FOR NEW ROOF CURB ASSEMBLY INSTALLATION; FLASH CURB WATERTIGHT INTO EXISTING MODIFIED BITUMEN ROOF MEMBRANE IN ACCORDANCE WITH NRCA DETAIL #MB-12, WITH ROOFING MANUFACTURER'S INSTRUCTIONS AND SO AS NOT TO VOID ROOFING SYSTEM WARRANTY; REFER TO MECHANICAL DRAWINGS FOR ADDITIONAL INFORMATION.
7.840 FIRESTOPPING: PACKING MATERIAL; REFER TO SPECIFICATIONS
7.841 FIRESTOPPING: SEALANT; REFER TO SPECIFICATIONS.
7.900 JOINT SEALANT: REFER TO SCHEDULE; PROVIDE BACKER ROD OR BOND BREAKER.

DIVISION 08 : DOORS AND WINDOWS

8.003 EXISTING WINDOW.
8.004 EXISTING WINDOW FRAME.
8.005 EXISTING INSULATED METAL PANEL.
8.006 EXISTING STEEL DOOR FRAME.
8.007 RELOCATED EXISTING COILING OVERHEAD DOOR, TRACK, HOOD, DOOR CONTACTS AND OPERATOR.
8.110 STEEL DOOR FRAME: REFER TO DOOR, FRAME AND BORROWED LIGHT SCHEDULE.
8.114 WOOD DOOR ACCESSORY: VISION PROOF DOOR LOUVER, FACTORY PRIMED AND FIELD PAINTED WITH THREE COATS OF ENAMEL PAINT EACH SIDE OF DOOR. SIZE AS SHOWN.
8.115 STEEL FRAME ACCESSORY: DOOR FRAME ANCHORS (PROVIDE AT JAMBS ONLY).
8.116 DOOR ACCESSORY: METAL FRAMED VISION LIGHT IN DOOR. PRIMED AND FIELD PAINTED WITH THREE COATS OF ENAMEL PAINT EACH SIDE OF DOOR. TYPICAL.
8.117 STEEL FRAME ACCESSORY: GLAZING STOP.
8.118 DOOR: REFER TO DOOR AND FRAME SCHEDULE.
8.720 DOOR THRESHOLD: ALUMINUM, REFER TO SPECIFICATIONS.
8.800 GLAZING: REFER TO DOOR/FRAME/WINDOW SCHEDULES FOR TYPE.
8.830 MIRROR: LENGTH MATCHES LENGTH OF COUNTERTOP; TOP OF MIRROR AT TOP OF NEW TILE WAINSCOT; BOTTOM OF MIRROR AT TOP OF COUNTERTOP BACKSPLASH.

DIVISION 09 : FINISHES

9.001 EXISTING DRYWALL CONSTRUCTION.
9.002 EXISTING GYPSUM BOARD.
9.003 EXISTING METAL STUD FRAMING.
9.004 EXISTING ACOUSTICAL CEILING PANELS AND GRID.
9.101 METAL STUD FRAMING: 1-5/8" STUD; 16" O.C. SPACING; 20 GAUGE UNLESS NOTED OTHERWISE; ANCHORAGE TO SUIT APPLICATION.
9.103 METAL STUD FRAMING: 3-5/8" STUD; 16" O.C. SPACING; 20 GAUGE UNLESS NOTED OTHERWISE; ANCHORAGE TO SUIT APPLICATION.
9.105 METAL STUD FRAMING: SEE FLOOR PLAN AND PARTITION TYPES FOR METAL STUD SIZE.
9.106 METAL STUD FRAMING: 6" STUD; 16" O.C. SPACING; 20 GAUGE UNLESS NOTED OTHERWISE; ANCHORAGE TO SUIT APPLICATION.
9.120 METAL STUD FRAMING: STUD RUNNER: SIZE TO MATCH METAL STUDS.
9.121 METAL STUD FRAMING: DOUBLE STUD RUNNER: FOR DEFLECTION RELIEF.
9.131 METAL STUD FRAMING: CLIP ANGLE.
9.143 METAL STUD FRAMING: LATERAL BRACING STRAP; 14 GA. GALVANIZED; 6" WIDE AT 24" O.C..
9.250 GYPSUM BOARD: 5/8" THICK; TYPE "X".
9.251 GYPSUM BOARD: 5/8" THICK; MOISTURE RESISTANT.
9.252 CEMENT BOARD: 5/8" THICK.
9.257 GYPSUM BOARD/METAL STUD PARTITION.
9.260 GYPSUM BOARD ACCESSORY: ACOUSTICAL SEALANT.
9.261 GYPSUM BOARD ACCESSORY: ACOUSTICAL INSULATION: SOUND ATTENUATION BATTS; THICKNESS AS SPECIFIED.
9.262 GYPSUM BOARD ACCESSORY: CONTROL JOINT.
9.263 GYPSUM BOARD ACCESSORY: CORNER BEAD.
9.264 GYPSUM BOARD ACCESSORY: EDGE TRIM; "L" PROFILE.
9.265 GYPSUM BOARD ACCESSORY: EDGE TRIM; "J" PROFILE.
9.267 GYPSUM BOARD ACCESSORY: MINERAL WOOL INSULATION.
9.301 GLASS WALL TILE; 2X2. REFER TO INTERIOR ELEVATIONS DETAIL 9/A901 FOR TILE PATTERN AND ROOM FINISH SCHEDULE FOR COLOR AND TYPE.
9.310 CERAMIC WALL TILE.
9.311 CERAMIC FLOOR TILE.
9.312 STAINLESS STEEL EDGE PROTECTION TRIM.
9.315 STAINLESS STEEL FLOOR TRANSITION TRIM.
9.510 ACOUSTICAL CEILING PANELS AND GRID.
9.651 RESILIENT BASE: REFER TO FINISH SCHEDULE.
9.680 CARPET: REFER TO FINISH SCHEDULE.
9.681 WALK-OFF CARPET TILE: REFER TO FINISH SCHEDULE.

DIVISION 10 : SPECIALTIES

10.101 VISUAL DISPLAY BOARD: MARKER BOARD W/ INTEGRAL TRAY; 4'H X 8'L; MOUNT TOP AT 7'-0" A.F.F. UNLESS NOTED OTHERWISE.
10.211 METAL TOILET COMPARTMENT: CONFIGURATION AS INDICATED.
10.212 METAL URINAL SCREEN: 24" WIDE; CONFIGURATION AS INDICATED.
10.520 SEMI-RECESSED FIRE EXTINGUISHER AND CABINET.
10.521 FIRE EXTINGUISHER AND BRACKET.

DIVISION 11 : EQUIPMENT

NOT USED

DIVISION 12 : FURNISHINGS

12.240 WINDOW SHADES: ROLLING TYPE; CLOTH.
12.362 SOLID SURFACE WINDOW SILL; 3/4" THICK WITH 3/4" PLYWOOD BACKING.

DIVISION 13 : SPECIAL CONSTRUCTION

NOT USED

DIVISION 14 : CONVEYING SYSTEMS

NOT USED

DIVISION 21 : FIRE SUPPRESSION

21.100 REMOVE EXISTING SPRINKLER HEAD. PROVIDE NEW SPRINKLER HEAD AND ALL MATERIALS REQUIRED TO LOCATE SPRINKLER HEAD IN NEW CEILING CONFIGURATION. REFER TO DRAWING F301.
21.101 PROVIDE EXTENSION OF EXISTING OVERHEAD SPRINKLER SYSTEM FOR FIRE PROTECTION BELOW NEW LAY IN CEILING IN OUTLINED AREA.
21.102 PROVIDE ALL MATERIAL AND LABOR AS REQUIRED TO ROUTE BRANCH SPRINKLER PIPE AND HEADS TO ACCOMMODATE NEW WALL LOCATION.

DIVISION 22 : PLUMBING

22.011 PLUMBING ACCESSORY; WATER VALVE BOX; REFER TO PLUMBING DRAWINGS.
22.014 EXISTING ROOF DRAIN DOWNCOMER: REFER TO PLUMBING DRAWINGS.
22.040 PLUMBING FIXTURE: REFER TO PLUMBING DRAWINGS.
22.050 SANITARY EJECTOR PIT: REFER TO PLUMBING DRAWINGS.
22.100 PROVIDE SANITARY PIPE TO 4-INCH SANITARY LOCATED NEAR LAUNDRY AT COLUMN G-15, APPROXIMATELY 120'.

DIVISION 23 : HEATING, VENTILATING AND AIR CONDITIONING

23.002 EXISTING CONDENSATE PIPING.
23.010 EXISTING CONDENSATE PIPING AND ASSOCIATED VENT PIPING.
23.100 REMOVE FLARED OPENING ON SUPPLY AND RETURN AIR DUCTWORK FOR RT-5.
23.101 PROVIDE EXHAUST FAN ON ROOF. INCORPORATE FAN INTO RT-5 SEQUENCE OF OPERATIONS. WHEN RT-5 IS IN ECONOMIZER MODE, EF-2 SHALL BE ENABLED BY THE EF VFD IN RT-5 AND MODULATE AS REQUIRED TO MAINTAIN A SPACE PRESSURE OF 0.05 IN. WG.
23.102 PROVIDE ROOF MOUNTED TOILET EXHAUST FAN.

DIVISION 26 : ELECTRICAL

26.001 LIGHT FIXTURE: REFER TO ELECTRICAL DRAWINGS.
26.002 SWITCH: REFER TO ELECTRICAL DRAWINGS.
26.003 POWER, DATA, PHONE ELECTRICAL RACEWAY; REFER TO ELECTRICAL DRAWINGS.
26.005 POWER RECEPTACLE: REFER TO ELECTRICAL DRAWINGS.
26.006 JUNCTION BOX: REFER TO ELECTRICAL DRAWINGS.
26.007 EXISTING ELECTRICAL PANELBOARD.
26.008 ELECTRICAL PANELBOARD.
26.010 COMMUNICATIONS RECEPTACLE: REFER TO ELECTRICAL DRAWINGS.
26.201 LIMITS OF ELECTRICAL RENOVATION.
26.202 REMOVE EXISTING LOW VOLTAGE CABINET. COORDINATE REMOVAL WITH OWNER.
26.203 REMOVE CONDUIT FEEDS TO OFFICE PARTITIONS. COORDINATE REMOVAL WITH OWNER.
26.204 REMOVE EXISTING SURFACE MOUNTED RACEWAY RUNNING ALONG FLOOR.
26.205 REMOVE EXISTING DATA CABINET. COORDINATE REMOVAL WITH OWNER.
26.206 REMOVE EXISTING PULL BOX.
26.301 PROVIDE SINGLE CHANNEL LARGE CAPACITY RACEWAY - MINIMUM 3-1/2" DEEP X 4-3/4" HIGH.
26.302 PROVIDE 2 CHANNEL SURFACE RACEWAY ABOVE COUNTER FOR RECEPTACLES AND VOICE/DATA JACKS.
26.309 PROVIDE RECEPTACLE FOR UPPER CABINET MICROWAVE. COORDINATE EXACT MOUNTING HEIGHT AND LOCATION WITH CABINETS PRIOR TO INSTALLATION.
26.310 PROVIDE FLOOR BOX. COORDINATE EXACT LOCATION OF FLOOR BOX WITH CONFERENCE TABLE LEGS PRIOR TO INSTALLATION.
26.312 PROVIDE JUNCTION BOX, FLEXIBLE WHIP, CABLING AND FINAL CONNECTION TO FURNITURE FOR VOICE DATA WIRING. PROVIDE CABING AND PHONE/DATA JACKS WITHIN FURNITURE SYSTEMS. COORDINATE EXACT CONNECTION AND JUNCTION BOX LOCATIONS IN FIELD WITH FURNITURE MANUFACTURER PRIOR TO INSTALLATION.
26.313 PROVIDE JUNCTION BOX, FLEXIBLE WHIP, CABLING AND FINAL CONNECTION TO FURNITURE FOR RECEPTACLE WIRING. PROVIDE WIRING AS REQUIRED IN FURNITURE SYSTEM TO CONNECT TO RECEPTACLES. COORDINATE EXACT CONNECTION AND JUNCTION BOX LOCATIONS IN FIELD WITH FURNITURE MANUFACTURER PRIOR TO INSTALLATION.
26.318 PROVIDE JUNCTION BOX AND FINAL CONNECTION TO CARD READER INTERFACE UNIT.
26.324 JUNCTION BOX FOR FUTURE FLAT SCREEN.
26.325 JUNCTION BOX FOR FUTURE A/V CONNECTIONS.
26.326 PROVIDE SPECIAL RECEPTACLE. COORDINATE EXACT LOCATION AND NEMA CONFIGURATION OF RECEPTACLE IN FIELD WITH OWNER. PROVIDE 2@10,1@10G.,3/4"C. TO PANELBOARD.
26.327 LADDER RACK PROVIDED BY OWNER. PROVIDE NEW CABLING AND UTILIZE OWNER PROVIDED LADDER RACK TO ROUTE CABLING BACK TO EXISTING RACK IN IDF ROOM.
26.328 PROVIDE FINAL CONNECTION TO EXHAUST FAN, LOCATED ON ROOF.
26.329 EXISTING COLUMN.
26.401 PROVIDE LOCKABLE, THERMOPLASTIC, VENTED ENCLOSURE FOR (3) DIMMER SWITCHES.
26.403 MANUAL OVERRIDE SWITCH FOR CONTROL OF LIGHTING. LABEL "MASTER LIGHTING CONTROL". SEE LIGHTING CONTROL SCHEDULE FOR ADDITIONAL INFORMATION.
26.421 PROVIDE ENGRAVED THREE-LAYER LAMINATE PLASTIC, BLACK LETTERS ON BACKGROUND (BACKGROUND COLOR TO MATCH COLOR OF FACEPLATE).
26.612 PROVIDE SINGLE CHANNEL LARGE CAPACITY RACEWAY - MINIMUM 3-1/2" DEEP X 4-3/4" WIDE.
26.613 PROVIDE DATA CABLING CONNECTION TO NEW PATCH PANELS IN EXISTING RACK.
26.614 PROVIDE (2) 4" CONDUIT SLEEVES.
26.616 PROVIDE CONDUIT GROUNDING BUSHINGS IN PANELBOARD FOR TRANSITION TO RACEWAY.
26.617 PROVIDE 2" CONDUIT FROM PANELBOARD TO RACEWAY ON WEST WALL OF WORKSHOP.
26.618 PROVIDE PANELBOARD.
26.619 PROVIDE NEW FEEDER FROM DISTRIBUTION PANEL TO VFD IN ROOF TOP UNIT RT-5 (LOCATED AT COLUMN B,4) AND FROM VFD IN RT-5 TO EXHAUST FAN.
26.620 REMOVE EXISTING CIRCUIT BREAKER.
26.630 PROVIDE NEW CIRCUIT BREAKER.
26.631 PROVIDE NEW FEEDER.
26.632 PROVIDE NEW TRANSFORMER. MOUNT ON WALL, +10'-0" A.F.F.
26.633 PROVIDE NEW PANELBOARD.
26.634 PROVIDE NEW TRANSFORMER. MOUNT ON COLUMN, +10'-0" A.F.F.
26.635 PROVIDE NEW CIRCUIT BREAKER. CIRCUIT BREAKER SHALL BE LOCKABLE IN THE "OPEN" POSITION.
26.640 PROVIDE (1) CAT 3 CABLE FOR EACH PHONE LINE FROM COMBINATION 110 BLOCK/CAT 6 JACK PANEL. SEE TERMINATION SCHEDULE FOR EXACT QUANTITIES.
26.641 PROVIDE (1) CAT 6 CABLE FOR EACH PHONE LINE FROM PHONE JACK TO COMBINATION 110 BLOCK/CAT 6 JACK PANEL. SEE TERMINATION SCHEDULE FOR EXACT QUANTITIES.
26.642 PROVIDE COMBINATION 110 BLOCK/CAT 6 JACK PANEL. PROVIDE RACK MOUNTED BRACKET AND CABLE MANAGEMENT. SEE DETAIL ON THIS SHEET. SEE TERMINATION SCHEDULE FOR EXACT QUANTITIES.
26.643 PATCH CORDS PROVIDED BY OWNER.
26.644 PROVIDE CABLE MANAGEMENT.

DIVISION 27 : COMMUNICATIONS

NOT USED

DIVISION 28 : ELECTRONIC SAFETY AND SECURITY

NOT USED

DIVISION 32 : EXTERIOR IMPROVEMENTS

NOT USED

GENERAL NOTES

1. THE LIST OF KEYNOTES ON G003 IS A STANDARDIZED LIST; NOT ALL KEYNOTES APPEARING ON THIS DRAWING MAY BE USED ON THIS PROJECT. REFER TO INDIVIDUAL DRAWINGS FOR KEYNOTES USED.
2. THE KEYNOTE SYSTEM IS USED FOR CONVENIENCE, GENERAL INFORMATION AND AS AN EXPRESSION OF GENERAL INTENT ONLY. THE ARCHITECT SPECIFICALLY DOES NOT WARRANT ALL MATERIALS, COMPONENTS OR ASSEMBLIES THAT ARE SIMILARLY IDENTIFIED.
3. THE INTENT OF THE CONTRACT DOCUMENTS IS TO INCLUDE ALL ITEMS NECESSARY FOR THE PROPER EXECUTION AND COMPLETION OF THE WORK BY THE CONTRACTOR, WHETHER OR NOT THE KEYNOTE SYSTEM IS USED, OR WHETHER OR NOT THE IDENTIFICATION IS COMPLETE, CONSISTENT OR COGENT TO THE APPROPRIATE SPECIFICATION DIVISION.

Revisions:	Date
100% CONSTRUCTION DOCUMENTS FOR BID	04-12-13
95% CONSTRUCTION DOCUMENTS SUBMITTAL	03-12-13
50% CONSTRUCTION DOCUMENTS SUBMITTAL	02-08-13

CONSULTANTS:

ARCHITECT/ENGINEERS:

Kluber, Inc.
10 South Shumway
Batavia, Illinois 60510
tel. 630.406.1213
fax 630.406.9472
www.kluberinc.com

Kluber Architects + Engineers

Drawing Title: BUILDING 37 - MASTER KEYNOTE SCHEDULE

Approved Project Director:

Project Title: HINES BUILDING 37
O.I. AND T. FIELD OFFICES - PHASE 3
OFFICE AND RESTROOM RENOVATIONS

Location: VA OFFICE OF ACQUISITION AND LOGISTICS HINES, ILLINOIS

Date: 04-12-13 | Checked: CJH | Drawn: DLT

Project Number: 796-13-004
Building Number: 37
Drawing Number: 37 - G003
Dwg. 3 of 32

Office of Construction and Facilities Management
Department of Veterans Affairs

VA FORM 08-6231