

CHILLER AND DOG SYSTEM - SEQUENCE OF OPERATION

(CONTINUED FROM PREVIOUS PAGE)

The system will start up automatically as follows:

After power is supplied to the system, the chiller will start up.

The chiller will draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.

The chiller will then draw in air from the outside and cool it down.

The chiller will then pump the cooled water through the system.

The chiller will then cool the system down.

The chiller will then stop operating.



ARCHITECTS H A W A I I 	CHILLER SEQUENCE OF OPERATION 
1. DOGS 2. CHILLER 3. DOMESTIC HOT WATER 4. REFRIGERATION	5. DOGS 6. CHILLER 7. DOMESTIC HOT WATER 8. REFRIGERATION
9. DOGS 10. CHILLER 11. DOMESTIC HOT WATER 12. REFRIGERATION	13. DOGS 14. CHILLER 15. DOMESTIC HOT WATER 16. REFRIGERATION
17. DOGS 18. CHILLER 19. DOMESTIC HOT WATER 20. REFRIGERATION	21. DOGS 22. CHILLER 23. DOMESTIC HOT WATER 24. REFRIGERATION
25. DOGS 26. CHILLER 27. DOMESTIC HOT WATER 28. REFRIGERATION	29. DOGS 30. CHILLER 31. DOMESTIC HOT WATER 32. REFRIGERATION
HEAT PUMP/DOMESTIC HOT WATER SYSTEM SEQUENCE OF OPERATION	
HEAT PUMP	
DOMESTIC HOT WATER	
REFRIGERATION	